Page 1 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

(B) (RL)

3-IN-ONE® White Lithium Grease

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited
252 Upper Third Street
Milton Keynes, MK9 1DZ, United Kingdom

WD-40 Company Limited PO Box 440 GB-Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom

Tel.: +44 (0) 1908 555400 Fax: +44 (0) 1908 266900 E-Mail: Compliance@wd40.co.uk Homepage: www.wd40.co.uk

WD-40 Company Limited Noorderpoort 93E NL- 5916PJ Venlo

Tel.: +31 85 487 46 91

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+44 20 3807 3798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementSTOT SE3H336-May cause dataAquatic Chronic2H411-Toxic to aqua

Hazard statement H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. Aerosol Aerosol

(GB) (RL)

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



1

1

H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking. EUH208-Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

EINECS, ELINCS, NLP, REACH-IT List-No.

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol 3.1 Substances n.a 3.2 Mixtures Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics **Registration number (REACH)** 01-2119463258-33-XXXX Index EINECS, ELINCS, NLP, REACH-IT List-No. 919-857-5 CAS content % 30 - < 50Classification according to Regulation (EC) 1272/2008 (CLP), M-EUH066 factors Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Zinc oxide 01-2119463881-32-XXXX **Registration number (REACH)** 030-013-00-7 Index

215-222-5

CAS	1314-13-2
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Aquatic Acute 1, H400 (M=1)
factors	Aquatic Chronic 1, H410 (M=1)

(R)-p-mentha-1,8-diene	
Registration number (REACH)	
Index	601-096-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	227-813-5
CAS	5989-27-5
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 3, H226
factors	Skin Irrit. 2, H315
	Skin Sens. 1B, H317
	Asp. Tox. 1, H304
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the respiratory tract Coughing Headaches Dizziness Effects/damages the central nervous system Coordination disorders Product removes fat. Drying of the skin. Dermatitis (skin inflammation) Allergic reaction possible. Page 4 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Nausea

Vomiting Danger of aspiration. Oedema of the lungs Other dangerous properties cannot be ruled out. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2 Extinction powder Water jet spray Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases Danger of bursting (explosion) when heated Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping. 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

Page 5 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

7.1.1 General recommendations

Ensure good ventilation. Avoid inhalation of the vapours. Avoid contact with eyes or skin. Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Do not use on hot surfaces. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Observe special regulations for aerosols!

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Store cool.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons C9-C	11 n-alkanos	isoalkanes o	clics, <2% aromatics	
WEL-TWA: 800 mg/m3		VEL-STEL:			
Monitoring procedures:	-		arbons 0,1%/c	(81 03 571)	
Monitoring procedures.			arbons 2/a (81		
			87 S (551 174)	03 301)	
BMGV:	- 001	ipui - KITA-T	57 5 (551 174)	Other information:	
Bivigv					
				method, paragraphs	04-07, EH40)
Chemical Name	Hydrocarbons, C9-C	11, n-alkanes	, isoalkanes, cy	clics, <2% aromatics	
OELV-8h: 100 ppm (573 mg/m3) ("Stoddard C	ELV-15min:			
solvent", [White spirit])					
Monitoring procedures:	- Drae	eger - Hydroc	arbons 0,1%/c	(81 03 571)	
	- Drae	eger - Hydroc	arbons 2/a (81	03 581)	
	- Com	npur - KÍTA-1	87 S (551 174)	,	
BLV:		-		Other information:	
Chemical Name	Petroleum gases, liq	uofiod			
WEL-TWA: 1000 ppm (1750 mg			1250 ppm (219	0 mg/m3) (Liquefied	
petroleum gas (LPG))		etroleum gas		o mg/ms) (Liquelleu	
Monitoring procedures:	l h	ell'oleuni yas	(LFG))		
BMGV:				Other information:	
Bivigv					
Chemical Name	Petroleum gases, liq	uefied			
OELV-8h:	0	ELV-15min:	1000 ppm (Bu	itane)	
Monitoring procedures:					
BLV:				Other information:	
œ					

Page 6 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

GB (RL)

Chemical Name	Oil mist, mineral				
WEL-TWA: 5 mg/m3 (Mineral of	oil, excluding	WEL-STEL:			
metal working fluids, ACGIH)	-				
Monitoring procedures:	- [Draeger - Oil Mis	t 1/a (67 33 031)	
BMGV:				Other information:	
Chemical Name	Oil mist, mineral				
Chemical Name OELV-8h: 5 mg/m3 (Mineral oil	,	OELV-15min:			
	,	OELV-15min:			
OELV-8h: 5 mg/m3 (Mineral oil	, pure, highly and	OELV-15min: Draeger - Oil Mis)	

Area of application	Exposure route / Environmental compartment	tal r		nvironmental r		Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	46	mg/kg bw/day			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3			
Consumer	Human - oral	Long term, systemic effects	DNEL	46	mg/kg bw/day			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	77	mg/kg bw/day			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3			

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	20,6	µg/l	
	Environment - marine		PNEC	6,1	µg/l	
	Environment - sewage treatment plant		PNEC	100	µg/I	
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dw	
	Environment - sediment, marine		PNEC	56,5	mg/kg dw	
	Environment - soil		PNEC	35,6	mg/kg dw	
Consumer	Human - inhalation	Short term, local effects	DNEL	3,1	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,5	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, local effects	DNEL	6223	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, local effects	DNEL	83	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,5	mg/m3	
Workers / employees	Human - oral	Short term, local effects	DNEL	62,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,2	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3	

GB (RL)

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	14	µg/l	
	Environment - marine		PNEC	1,4	µg/l	
	Environment - sewage treatment plant		PNEC	1,8	mg/l	
	Environment - sediment, freshwater		PNEC	3,85	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,3851	mg/kg dry weight	
	Environment - soil		PNEC	0,763	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	133	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	66,7	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,5	mg/kg body weight/day	

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. (EL) = Directive $\frac{91}{22}$ /EEC $\frac{200}{20}$ /20/EC $\frac{200}{20}$ /20/E

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL))

| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A,

Page 8 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

8.2 Exposure controls

GB (RL)

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN ISO 374). If applicable Protective Neoprene® / polychloroprene gloves (EN ISO 374). Minimum layer thickness in mm:

Permeation time (penetration time) in minutes: >= 480

Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes: >= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Page 9 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

GB (RL)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: White Odour: Characteristic Melting point/freezing point: There is no information available on this parameter. Boiling point or initial boiling point and boiling range: There is no information available on this parameter. Does not apply to aerosols. Flammability: Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: Does not apply to aerosols. Auto-ignition temperature: Does not apply to aerosols. There is no information available on this parameter. Decomposition temperature: pH: Mixture is non-soluble (in water). Kinematic viscosity: >20,5 mm2/s (40°C) Solubility: Not miscible Partition coefficient n-octanol/water (log value): Does not apply to mixtures. Vapour pressure: There is no information available on this parameter. Density and/or relative density: Does not apply to aerosols. Relative vapour density: Does not apply to aerosols. Particle characteristics: Does not apply to aerosols. 9.2 Other information Explosives:

Oxidising liquids:

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. 10.3 Possibility of hazardous reactions No dangerous reactions are known. 10.4 Conditions to avoid See also section 7. Heating, open flame, ignition sources Pressure increase will result in danger of bursting. **10.5** Incompatible materials Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification). 3-IN-ONE® White Lithium G

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.

Aerosol. Active substance: liquid.

When using: development of explosive vapour/air mixture possible. No

(B) (RL) Page 10 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease Skin corrosion/irritation: Repeated exposure may cause skin dryness or cracking. Serious eye n.d.a. damage/irritation: Respiratory or skin n.d.a. sensitisation: Germ cell mutagenicity: n.d.a. Carcinogenicity: Reproductive to: n.d.a.

Reproductive toxicity:			n.d.a.
Specific target organ toxicity -			n.d.a.
single exposure (STOT-SE):			
Specific target organ toxicity -			n.d.a.
repeated exposure (STOT-			
RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Rat	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion Chinese hamster
Carcinogenicity:	NOAEC	1100	mg/m3	Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Female
Carcinogenicity:	NOAEC	>= 2200	mg/m3	Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Male

(B) (RL) Page 11 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Volid from: 26 11 2024 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Reproductive toxicity:					OECD 414 (Prenatal	Negative,
					Developmental	Analogous
					Toxicity Study)	conclusion
Reproductive toxicity (Effects on fertility):	NOAEL	>= 3000	mg/kg bw/d	Rat	OECD 415 (One- Generation	Male
.,					Reproduction Toxicity Study)	
Reproductive toxicity (Effects	NOAEL	>= 1500	mg/kg	Rat	OECD 415 (One-	Female
on fertility):			bw/d		Generation	
					Reproduction Toxicity Study)	
Specific target organ toxicity -					••••	May cause
single exposure (STOT-SE):						drowsiness or
						dizziness.,
						STOT SE 3,
Openifie townet owner towicity	NOAEL	3000		Det		H336
Specific target organ toxicity - repeated exposure (STOT-	NOAEL	3000	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral	Analogous conclusion
RE), oral:					Toxicity Study in	CONCIUSION
					Rodents)	
Specific target organ toxicity -	NOAEC	1444	ppm	Rat	OECD 413	Analogous
repeated exposure (STOT-					(Subchronic Inhalation	conclusion
RE), inhalat.:					Toxicity - 90-Day	
					Study)	
Aspiration hazard:						Yes
Symptoms:						unconsciousne
						s, headaches,
						dizziness,
						discoloration of
						the skin,
						vomiting,
						diarrhoea

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute	
					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by dermal	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,7	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	-
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
					Mammalian	Chinese
					Chromosome	hamster
					Aberration Test)	
Germ cell mutagenicity:				Mouse	OECD 474	Negative
					(Mammalian	
					Erythrocyte	
					Micronucleus Test)	
Reproductive toxicity:				Rat	OECD 416 (Two-	Negative,
					generation	Analogous
					Reproduction Toxicity	conclusion
					Study)	

Page 12 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Symptoms:			breathing
			difficulties,
			chest pain
			(thorax pain),
			diarrhoea,
			fever, joint
			pain, coughing,
			headaches,
			circulatory
			disorders,
			metal fume
			fever, muscle
			pains, mucous
			membrane
			irritation,
			nausea and
			vomiting.
			vonnung.

(R)-p-mentha-1,8-diene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 2000	mg/kg	Rat	OECD 423 (Acute	Female
					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit		Skin Irrit. 2
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
-					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	Skin Sens. 1B
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Respiratory or skin				Mouse	OECD 429 (Skin	Skin Sens. 1
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
5 ,					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 479 (Genetic	Negative
0 ,					Toxicology - In Vitro	Chinese
					Sister Chromatid	hamster
					Exchange assay in	
					Mammalian Cells)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
3 ,					Mammalian	Chinese
					Chromosome	hamster
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
				51	Test)	
Symptoms:					/	diarrhoea,
						rash, itching,
						gastrointestinal
						disturbances,
						mucous
						membrane
						irritation,
						nausea and
						vomiting.
						vornung.

Page 13 of 20	
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)	
Revision date / version: 26.11.2024 / 0010	
Replacing version dated / version: 26.09.2022 / 0009	
Valid from: 26.11.2024	
PDF print date: 02.12.2024	
3-IN-ONE® White Lithium Grease	

Symptoms:		diarrhoea,
		rash, itching,
		gastrointestinal
		disturbances,
		mucous
		membrane
		irritation,
		nausea and
		vomiting.

Petroleum gases, liquefied								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by inhalation:	LC50	>5	mg/l					
Skin corrosion/irritation:						Not irritant		
Serious eye						Not irritant		
damage/irritation:								
Respiratory or skin						No (skin		
sensitisation:						contact)		
Aspiration hazard:						No		

11.2. Information on other hazards

GB (RL)-

3-IN-ONE® White Lithium Grease								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Endocrine disrupting						Does not apply		
properties:						to mixtures.		
Other information:						No other		
						relevant		
						information		
						available on		
						adverse effects		
						on health.		
	·		·					

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	-						n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as
degradability:							much as
0							possible with
							an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							According to
							the recipe,
							contains no
							AOX.

Page 14 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Other information:		DOC-
		elimination
		degree(complex
		ing organic
		substance)>=
		80%/28d; n.a.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus	QSAR	
					mykiss		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
, ,				Ũ	lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis	OECD 201	
					subcapitata	(Alga, Growth	
					ouboupitata	Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchnerie	OECD 201	
12.11. Toxicity to algue.	NOLEN.		U		lla subcapitata	(Alga, Growth	
					na Subcapitata	Inhibition Test)	
12.2. Persistence and		28d	80	%		OECD 301 F	Readily
degradability:		200		/0		(Ready	biodegradable
degradability.						Biodegradability -	biodegradable
						Manometric	
						Respirometry	
						• •	
12.3. Bioaccumulative			5-6,7			Test)	High
potential:			5-6,7				піgn
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substanc
Toxicity to bacteria:	EL50	48h	0,95	mg/l			QSAR

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,1-2,5	ppm	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,413- 0,83	mg/l	Ceriodaphnia spec.	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,04	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	0,136	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,017	mg/l	Pseudokirchnerie Ila subcapitata		

(B) (B) Page 15 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

12.1. Toxicity to algae:	EC50	72h	0,136	mg/l	Scenedesmus quadricauda	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:			158,5	L/kg			
12.4. Mobility in soil:	Log Koc		2,2				
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,70	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,307- 0,42	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	0,214- 0,32	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	4	mg/l		, ,	
12.2. Persistence and degradability:		28d	80-92	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	71	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		4,38			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	37 °C, pH = 7.2
12.4. Mobility in soil:							Adsorption in ground.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	209	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Page 16 of 20 Safety data sheet accor Revision date / version: Replacing version dated Valid from: 26.11.2024 PDF print date: 02.12.20 3-IN-ONE® White Lithiu	26.11.2024 / 0010 I / version: 26.09.202 024	, Annex II (la	st amended by Reg	ulation (EU) 2020/87	8)
Other information:					Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Petroleum gases, liquefied							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	147,54	mg/l		QSAR	
12.3. Bioaccumulative							Not to be
potential:							expected
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

6B (RL)

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU) 07 06 99 wastes not otherwise specified

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations. Recommendation: Do not perforate, cut up or weld uncleaned container. Recycling 15 01 04 metallic packaging

SECTION 14: Transport information

4000

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	AV.
14.5. Environmental hazards:	environmentally hazardous	
Tunnel restriction code:	D	\sim
Classification code:	5F	
LQ:	1 L	
Transport category:	2	
Transport by sea (IMDG-code)		
14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	AK
14.5. Environmental hazards:	environmentally hazardous	
Marine Pollutant:	Yes	\checkmark
EmS:	F-D, S-U	

Page 17 of 20			
Safety data sheet according to Regulation (EC) No 1907/2006, An Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease	nex II (last amended by Regulation (EU) 2020/878)		
Transport by air (IATA)			
14.1. UN number or ID number:	1950		
14.2. UN proper shipping name:			
UN 1950 Aerosols, flammable			
14.3. Transport hazard class(es):	2.1		
14.4. Packing group:	· ·		
14.5. Environmental hazards:	Not applicable		
14.6. Special precautions for user			
Persons employed in transporting dangerous goods must be trained.			
All persons involved in transporting must observe safety regulation	S.		
Precautions must be taken to prevent damage.			
14.7. Maritime transport in bulk according to IMO instruments			
Freighted as packaged goods rather than in bulk, therefore not applicable.			
Minimum amount regulations have not been taken into account.			
Danger code and packing code on request.			
Comply with special provisions.			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

രത

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of	
		dangerous substances as dangerous substances as		
		referred to in Article 3(10) for	referred to in Article 3(10) for	
		the application of - Lower-tier	the application of - Upper-tier	
		requirements	requirements	
E2		200	500	
P3a	11.1	150 (netto)	500 (netto)	
The Notes to Apply 1 of Directive 2012/18/ELL in particular these named in the tables here and notes 1.6, must be taken into				

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 83 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

EUF0007 Revised sections:

6, 14

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H336	Classification according to calculation procedure.

Page 18 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

 ${\it Aerosol-Aerosols}$

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard

Aquatic Acute - Hazardous to the aquatic environment - acute

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approximately approx. Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community

-@ R
Page 19 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009
Valid from: 26.11.2024
PDF print date: 02.12.2024
3-IN-ONE® White Lithium Grease
EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient IARC International Agency for Research on Cancer
IARC International Agency for Research on Cancer IARC International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLIDInternational Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships mg/kg bw mg/kg body weight
mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
mg/kg dw mg/kg dry weight
mg/kg wwt mg/kg wet weight
n.a. not applicable
n.av. not available n.c. not checked
n.d.a. no data available
NIOSHNational Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development org. organic
org. organic OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning
the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other
numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a
submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the
International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds vPvB very persistent and very bioaccumulative
The statements made here should describe the product with regard to the necessary safety precautions - they are
not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.
These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinbeim, Tel : ±49,5233,94,17,0, Fax:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document

Page 20 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 26.11.2024 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 26.11.2024 PDF print date: 02.12.2024 3-IN-ONE® White Lithium Grease

is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.