

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

WD-40® Specialist® Fast Acting Degreaser WD-40® Specialist® Degreaser

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Degreaser

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

WD-40 Company Limited
252 Upper Third Street
Milton Keynes, MK9 1DZ, United Kingdom

WD-40 Company Limited
PO Box 440
GB-Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom

Tel.: +44 (0) 1908 555400
Fax: +44 (0) 1908 266900
E-Mail: Compliance@wd40.co.uk
Homepage: www.wd40.co.uk

WD-40 Company Limited
Noorderpoort 93E
NL- 5916PJ Venlo

Tel.: +31 85 487 46 91

M

Danka Import Export
548 St Joseph High Road
SVR 1018 St Venera

Tel.: +356 21233649
Fax: +356 21233501
E-Mail: Danka@maltanet.net

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

M

Medicines & Poisons Info Office - Mater Dei Hospital, Msida MSD 2090, Malta - Tel.: +356 2545 6508
Emergency Ambulance - Tel.: 112

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:

+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+44 20 3807 3798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

1-methoxy-2-propanol

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2-methoxy-1-methylethyl acetate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	919-857-5
CAS	---
content %	50-60
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304

1-methoxy-2-propanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119457435-35-XXXX
Index	603-064-00-3
EINECS, ELINCS, NLP, REACH-IT List-No.	203-539-1
CAS	107-98-2
content %	15-25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 STOT SE 3, H336

2-methoxy-1-methylethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475791-29-XXXX
Index	607-195-00-7
EINECS, ELINCS, NLP, REACH-IT List-No.	203-603-9
CAS	108-65-6
content %	15-25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 STOT SE 3, H336

Carbon dioxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	204-696-9
CAS	124-38-9
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	---

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 03.03.2026 / 0014

Replacing version dated / version: 09.10.2025 / 0013

Valid from: 03.03.2026

PDF print date: 04.03.2026

WD-40® Specialist® Fast Acting Degreaser WD-40® Specialist® Degreaser

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation of the eyes

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Unconsciousness

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

chemical pneumonitis (condition similar to pneumonia)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

Pulmonary oedema prophylaxis

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Extinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 03.03.2026 / 0014

Replacing version dated / version: 09.10.2025 / 0013

Valid from: 03.03.2026

PDF print date: 04.03.2026

WD-40® Specialist® Fast Acting Degreaser WD-40® Specialist® Degreaser

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Observe special regulations for aerosols!

Observe special storage conditions.

Store cool.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m³

Chemical Name		Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
WEL-TWA: 800 mg/m ³	WEL-STEL: ---		
Monitoring procedures:		<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 	
BMGV: ---		Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name		Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
OELV-8h: 100 ppm (573 mg/m ³) ("Stoddard solvent", [White spirit])	OELV-15min: ---		
Monitoring procedures:		<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 	
BLV: ---		Other information: ---	

Chemical Name		1-methoxy-2-propanol	
WEL-TWA: 100 ppm (375 mg/m ³) (WEL-TWA, EU)	WEL-STEL: 150 ppm (560 mg/m ³) (WEL-STEL), 150 ppm (568 mg/m ³) (EU)		
Monitoring procedures:		<ul style="list-style-type: none"> INSHT MTA/MA-017/A89 (Determination of glycol ethers (1-methoxy-2-propanol, 2-ethoxyethanol) in air - Charcoal tube method / Gas chromatography) - 1989 - EU project BC/CEN/ENTR/000/2002-16 card 12-1 (2004) NIOSH 2554 (GLYCOL ETHERS) - 2003 OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993 	
BMGV: ---		Other information: Sk (WEL)	

Chemical Name		1-methoxy-2-propanol	
OELV-8h: 100 ppm (375 mg/m ³) (Propylene glycol monomethyl ether) (OELV-8h, EU)	OELV-15min: 150 ppm (568 mg/m ³) (Propylene glycol monomethyl ether) (OELV-15min, EU)		
Monitoring procedures:		<ul style="list-style-type: none"> INSHT MTA/MA-017/A89 (Determination of glycol ethers (1-methoxy-2-propanol, 2-ethoxyethanol) in air - Charcoal tube method / Gas chromatography) - 1989 - EU project BC/CEN/ENTR/000/2002-16 card 12-1 (2004) NIOSH 2554 (GLYCOL ETHERS) - 2003 OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993 	
BLV: ---		Other information: IOELV	

Chemical Name		1-methoxy-2-propanol	
OELV-8h: 100 ppm (375 mg/m ³) (OELV-8h, EU)	OELV-ST: 150 ppm (568 mg/m ³) (OELV-ST, EU)		
Monitoring procedures:		<ul style="list-style-type: none"> INSHT MTA/MA-017/A89 (Determination of glycol ethers (1-methoxy-2-propanol, 2-ethoxyethanol) in air - Charcoal tube method / Gas chromatography) - 1989 - EU project BC/CEN/ENTR/000/2002-16 card 12-1 (2004) NIOSH 2554 (GLYCOL ETHERS) - 2003 OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993 	
BMGV: ---		Other information: Skin	

Chemical Name		2-methoxy-1-methylethyl acetate	
WEL-TWA: 50 ppm (274 mg/m ³) (WEL-TWA), 50 ppm (275 mg/m ³) (EU)	WEL-STEL: 100 ppm (548 mg/m ³) (WEL-STEL), 100 ppm (550 mg/m ³) (EU)		
Monitoring procedures:		<ul style="list-style-type: none"> INSHT MTA/MA-024/A92 (Determination of esters II (1-methoxy-2-propyl acetate, 2-ethoxyethyl acetate) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 15-1 (2004) NIOSH 2554 (GLYCOL ETHERS) - 2003 OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993 	
BMGV: ---		Other information: Sk (WEL)	

Chemical Name		2-methoxy-1-methylethyl acetate	
OELV-8h: 50 ppm (275 mg/m ³) (OELV-8h, EU)	OELV-15min: 100 ppm (550 mg/m ³) (OELV-15min, EU)		
Monitoring procedures:		<ul style="list-style-type: none"> INSHT MTA/MA-024/A92 (Determination of esters II (1-methoxy-2-propyl acetate, 2-ethoxyethyl acetate) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 15-1 (2004) NIOSH 2554 (GLYCOL ETHERS) - 2003 	

- OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993	
BLV: ---	Other information: Skin, IOELV

M Chemical Name		2-methoxy-1-methylethyl acetate	
OELV-8h: 50 ppm (275 mg/m3) (OELV-8h, EU)	OELV-ST: 100 ppm (550 mg/m3) (OELV-ST, EU)	---	
Monitoring procedures:		INSHT MTA/MA-024/A92 (Determination of esters II (1-methoxy-2-propyl acetate, 2-ethoxyethyl acetate) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 15-1 (2004) - NIOSH 2554 (GLYCOL ETHERS) - 2003 - OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993	
BMGV: ---	Other information: Skin		

GB Chemical Name		Carbon dioxide	
WEL-TWA: 5000 ppm (9150 mg/m3) (WEL-TWA), 5000 ppm (9000 mg/m3) (EU)	WEL-STEL: 15000 ppm (27400 mg/m3) (WEL-STEL)	---	
Monitoring procedures:		- Draeger - Carbon Dioxide 0,1%/a (CH 23 501) - Draeger - Carbon Dioxide 0,5%/a (CH 31 401) - Draeger - Carbon Dioxide 1%/a (CH 25 101) - Draeger - Carbon Dioxide 100/a (81 01 811) - Draeger - Carbon Dioxide 5%/A (CH 20 301) - Compur - KITA-126 B (549 475) - Compur - KITA-126 SA (549 467) - Compur - KITA-126 SB (548 816) - Compur - KITA-126 SF (549 491) - Compur - KITA-126 SG (550 210) - Compur - KITA-126 SH (549 509) - Compur - KITA-126 UH (549 517) - NIOSH 6603 (Carbon dioxide) - 1994 - OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990	
BMGV: ---	Other information: ---		

IRL Chemical Name		Carbon dioxide	
OELV-8h: 5000 ppm (9000 mg/m3) (OELV-8h, EU)	OELV-15min: ---	---	
Monitoring procedures:		- Draeger - Carbon Dioxide 0,1%/a (CH 23 501) - Draeger - Carbon Dioxide 0,5%/a (CH 31 401) - Draeger - Carbon Dioxide 1%/a (CH 25 101) - Draeger - Carbon Dioxide 100/a (81 01 811) - Draeger - Carbon Dioxide 5%/A (CH 20 301) - Compur - KITA-126 B (549 475) - Compur - KITA-126 SA (549 467) - Compur - KITA-126 SB (548 816) - Compur - KITA-126 SF (549 491) - Compur - KITA-126 SG (550 210) - Compur - KITA-126 SH (549 509) - Compur - KITA-126 UH (549 517) - NIOSH 6603 (Carbon dioxide) - 1994 - OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990	
BLV: ---	Other information: IOELV		

M Chemical Name		Carbon dioxide	
OELV-8h: 5000 ppm (9000 mg/m3) (OELV-8h, EU)	OELV-ST: ---	---	
Monitoring procedures:		- Draeger - Carbon Dioxide 0,1%/a (CH 23 501) - Draeger - Carbon Dioxide 0,5%/a (CH 31 401) - Draeger - Carbon Dioxide 1%/a (CH 25 101) - Draeger - Carbon Dioxide 100/a (81 01 811) - Draeger - Carbon Dioxide 5%/A (CH 20 301) - Compur - KITA-126 B (549 475) - Compur - KITA-126 SA (549 467) - Compur - KITA-126 SB (548 816) - Compur - KITA-126 SF (549 491) - Compur - KITA-126 SG (550 210) - Compur - KITA-126 SH (549 509) - Compur - KITA-126 UH (549 517) - NIOSH 6603 (Carbon dioxide) - 1994 - OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990	
BMGV: ---	Other information: ---		

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	46	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	46	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	77	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	

1-methoxy-2-propanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - periodic release		PNEC	100	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	52,3	mg/kg dw	
	Environment - sediment, marine		PNEC	5,2	mg/kg dw	
	Environment - soil		PNEC	4,59	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	33	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	78	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	553,5	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,9	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	183	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	369	mg/m3	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	3,3	mg/kg	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	183	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	553,5	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	553,5	mg/m3	

2-methoxy-1-methylethyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,635	mg/l	
	Environment - marine		PNEC	0,0635	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	3,29	mg/kg dw	
	Environment - sediment, marine		PNEC	0,329	mg/kg dw	

	Environment - soil		PNEC	0,29	mg/kg dw	
	Environment - oral (animal feed)		PNEC	6,35	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	6,35	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	500	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	33	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	320	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	36	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	33	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	796	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	275	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	550	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

IRL - Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2024, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2024, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2024, HSA (Health and Safety Authority)): Carc1A,

Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Skin = Can be absorbed through skin. Asphx = asphyxiant. Sens = The substance can cause sensitisation. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

M - Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.646.16, last amended by L.N. 356 of 2021 and Act XXXIII of 2024]: [9] = Inhalable fraction, [10] = Respirable fraction. (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.646.16, last amended by L.N. 356 of 2021 and Act XXXIII of 2024]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction. (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom) / BBLV = Binding Biological Limit Value (S.L.646.16, last amended by L.N. 356 of 2021 and Act XXXIII of 2024). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) | | Other information [S.L.646.16, last amended by L.N. 356 of 2021 and Act XXXIII of 2024]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU: (EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE), (EU15) = Substantial contribution to the total body burden via dermal exposure possible. |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN ISO 16321-1).

Skin protection - Hand protection:

Normally not necessary.

with long-term contact:

If applicable

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If the workplace limit value is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Solvent
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	n.a.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	0,8 Vol-%
Upper explosion limit:	9 Vol-%
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	n.a.
Kinematic viscosity:	<30 cSt (25°C)
Solubility:	partially
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	6,7569 bar
Density and/or relative density:	0,843 g/ml
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

Explosives:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 03.03.2026 / 0014

Replacing version dated / version: 09.10.2025 / 0013

Valid from: 03.03.2026

PDF print date: 04.03.2026

WD-40® Specialist® Fast Acting Degreaser WD-40® Specialist® Degreaser

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

WD-40® Specialist® Fast Acting Degreaser WD-40® Specialist® Degreaser						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion

Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Rat	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion Chinese hamster
Carcinogenicity:	NOAEC	1100	mg/m3	Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Female
Carcinogenicity:	NOAEC	>= 2200	mg/m3	Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Male
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):	NOAEL	>= 3000	mg/kg bw/d	Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Male
Reproductive toxicity (Effects on fertility):	NOAEL	>= 1500	mg/kg bw/d	Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Female
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3000	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	1444	ppm	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, discoloration of the skin, vomiting, diarrhoea

1-methoxy-2-propanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	Regulation (EC) 440/2008 B.3 (ACUTE TOXICITY (DERMAL))	
Acute toxicity, by inhalation:	LC0	>7000	ppmV/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Not irritant

Serious eye damage/irritation:				Rabbit	Regulation (EC) 440/2008 B.5 (ACUTE EYE IRRITATION/CORROSION)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	Regulation (EC) 440/2008 B.6 (SKIN SENSITISATION)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Symptoms:						drowsiness, unconsciousness, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

2-methoxy-1-methylethyl acetate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,5	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative Chinese hamster
Germ cell mutagenicity:				Rat	OECD 482 (Gen. Tox. - DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Carcinogenicity:	NOAEL	~ 3690	mg/m3	Rat		Analogous conclusion vapour
Reproductive toxicity:	NOAEL	300-1000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Analogous conclusion vapour

12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:			5-6,7				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	0,95	mg/l			QSAR

1-methoxy-2-propanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	6812	mg/l	Leuciscus idus	DIN 38412 T.15	
12.1. Toxicity to fish:	LC50	96h	20800	mg/l	Pimephales promelas		ASTM

12.1. Toxicity to fish:	LC50	96h	>=1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC50	7d	>1000	mg/l	Pseudokirchnerie lla subcapitata		
12.1. Toxicity to algae:	IC50	72h	>1000	mg/l	Pseudokirchnerie lla subcapitata		
12.2. Persistence and degradability:		28d	90	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		~-0,49				Not to be expected
12.3. Bioaccumulative potential:	BCF		<100				Low
12.3. Bioaccumulative potential:	Log Pow		0,37				Slight
12.4. Mobility in soil:	Koc		0,2-1				High estimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

2-methoxy-1-methylethyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	100-180	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	14d	47,5	mg/l	Oryzias latipes	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	373	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	

12.2. Persistence and degradability:		28d	83-90	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		1,2			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	A notable biological accumulation potential is not to be expected (LogPow 1-3).20 °C, pH 6.8
12.4. Mobility in soil:	Koc		1,7-3,998				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	30min	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Carbon dioxide

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	35	mg/l	Salmo gairdneri		
12.3. Bioaccumulative potential:	Log Kow		0,83				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.7. Other adverse effects:							Greenhouse effect
Global warming potential (GWP):			1				

SECTION 13: Disposal considerations**13.1 Waste treatment methods****For the substance / mixture / residual amounts**

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

11 01 13 degreasing wastes containing hazardous substances

14 06 03 other solvents and solvent mixtures

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.


E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.
For contaminated packing material
 Pay attention to local and national official regulations.
 Recommendation:
 Do not perforate, cut up or weld uncleaned container.
 Recycling
 15 01 04 metallic packaging


SECTION 14: Transport information

General statements


Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
Classification code:	5F	
LQ:	1 L	
Transport category:	2	

Transport by sea (IMDG-code)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-D, S-U	

Transport by air (IATA)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 Aerosols, flammable		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements

P3b	11.1, 11.2	5000 (netto)	50000 (netto)
-----	------------	--------------	---------------

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 97 %

REGULATION (EC) No 648/2004

30 % and more

aliphatic hydrocarbons

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

EU F0059

Revised sections: 8

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw mg/kg body weight
mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
mg/kg dw mg/kg dry weight
mg/kg wwt mg/kg wet weight
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT Persistent, bioaccumulative and toxic
PE Polyethylene
PMT Persistent, mobile and toxic
PNEC Predicted No Effect Concentration

Page 22 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 03.03.2026 / 0014

Replacing version dated / version: 09.10.2025 / 0013

Valid from: 03.03.2026

PDF print date: 04.03.2026

WD-40® Specialist® Fast Acting Degreaser WD-40® Specialist® Degreaser

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB Very persistent and very bioaccumulative

vPvM Very persistent and very mobile

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.