

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

megol Motorenoel Super LL DIMO Premium SAE 10W-40

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Motor oil

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Meguin GmbH & Co. KG Mineraloelwerke

Rodener Strasse 25

66740 Saarlouis

Tel.: 06831/89 09-0

Fax: 06831/89 09-62

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.06.2022 / 0018
Replacing version dated / version: 24.02.2022 / 0017
Valid from: 30.06.2022
PDF print date: 30.06.2022
megol Motorenoel Super LL DIMO Premium SAE 10W-40

3.1 Substances

n.a.

3.2 Mixtures

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	265-157-1
CAS	64742-54-7
content %	20-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Highly refined mineral oil (C15 - C50) *	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	---
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	
Registration number (REACH)	01-2119657973-23-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	272-238-5
CAS	68784-31-6
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Dam. 1, H318 Aquatic Chronic 2, H411

Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	953-650-0
CAS	---
content %	0,1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1B, H317 Repr. 2, H361d
Specific Concentration Limits and ATE	Repr. 2, H361d: >=17,15 %

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	682-816-2
CAS	722503-68-6
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1B, H317

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP, REACH-IT List-No.	Registration number (REACH)	Chemical name
265-090-8	--	Baseoil - unspecified
265-091-3	--	Distillates (petroleum), solvent-refined light paraffinic
265-097-6	--	Distillates (petroleum), solvent-refined heavy naphthenic
265-098-1	--	Distillates (petroleum), solvent-refined light naphthenic

265-101-6	--	Baseoil - unspecified
265-156-6	--	Distillates (petroleum), hydrotreated light naphthenic
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	--	Distillates (petroleum), solvent-dewaxed light paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
276-737-9	--	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
276-738-4	--	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
278-012-2	--	Baseoil - unspecified
265-155-0	--	Baseoil - unspecified
276-735-8	--	Lubricating oils (petroleum), C>25, hydrotreated bright stock-based
276-736-3	--	Baseoil - unspecified
265-096-0	--	Residual oils (petroleum), solvent deasphalted
265-160-8	--	Residual oils (petroleum), hydrotreated
265-161-3	--	Lubricating oils (petroleum), hydrotreated spent
265-166-0	--	Residual oils (petroleum), solvent-dewaxed
265-176-5	--	Paraffin oils (petroleum), catalytic dewaxed light

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

Drying of the skin.

Dermatitis (skin inflammation)

Sensitive individuals:

Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Foam

Page 4 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.06.2022 / 0018
Replacing version dated / version: 24.02.2022 / 0017
Valid from: 30.06.2022
PDF print date: 30.06.2022
megol Motorenoel Super LL DIMO Premium SAE 10W-40

Dry extinguisher
Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Aldehydes
Oxides of sulphur
Boron oxide
Oxides of nitrogen
Oxides of phosphorus
Zinc oxide
Calcium oxide
Hydrogen sulphide
Acrylates

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Avoid formation of oil mist.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.
Oil binder
Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.
Ensure good ventilation.
Avoid contact with eyes or skin.
Do not carry cleaning cloths soaked in product in trouser pockets.
Do not heat to temperatures close to flash point.

Page 5 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.06.2022 / 0018
 Replacing version dated / version: 24.02.2022 / 0017
 Valid from: 30.06.2022
 PDF print date: 30.06.2022
 megol Motorenoel Super LL DIMO Premium SAE 10W-40

Take measures against electrostatic charging, if appropriate.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Protect against moisture and store closed.
 Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral		
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---		

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3	

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - water		PNEC	4	µg/l	
	Environment - marine		PNEC	4,6	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	4,4	µg/l	
	Environment - sediment, marine		PNEC	0,00701	mg/kg	
	Environment - soil		PNEC	0,0548	mg/kg	
	Environment - oral (animal feed)		PNEC	8,33	mg/kg	
	Environment - sewage treatment plant		PNEC	3,8	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	4,8	mg/kg	

Page 6 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.06.2022 / 0018
 Replacing version dated / version: 24.02.2022 / 0017
 Valid from: 30.06.2022
 PDF print date: 30.06.2022
 megol Motorenoel Super LL DIMO Premium SAE 10W-40

Consumer	Human - oral	Long term, systemic effects	DNEL	0,19	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,67	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,6	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,6	mg/kg	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:
 Protective gloves, oil resistant (EN ISO 374).
 If applicable
 Protective nitrile gloves (EN ISO 374).
 Protective gloves made of polyvinyl alcohol (EN ISO 374).
 Protective Viton® / fluoroelastomer gloves (EN ISO 374).
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 > 480
 Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Melting point/freezing point:	- 36 °C
Boiling point or initial boiling point and boiling range:	Not determined
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	230 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	n.d.a.
Kinematic viscosity:	97,0 mm ² /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,865 g/cm ³
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Protect from humidity.

Page 8 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.06.2022 / 0018
 Replacing version dated / version: 24.02.2022 / 0017
 Valid from: 30.06.2022
 PDF print date: 30.06.2022
 megol Motorenoel Super LL DIMO Premium SAE 10W-40

Open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

megol Motorenoel Super LL DIMO Premium SAE 10W-40						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						No (skin contact), Analogous conclusion
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), hydrotreated heavy paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster

Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion 78 weeks, dermal
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion dermal
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion oral
Aspiration hazard:						Asp. Tox. 1
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Symptoms:						gastrointestinal disturbances, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,22	mg/l	Rat		Dust, Mist, Analogous conclusion 4 weeks

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2900	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	Analogous conclusion

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	5,1	mg/l/4h	Rat		Aerosol
Acute toxicity, by inhalation:	LC50	20,1	mg/l/4h	Rat		Vapours

Page 10 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.06.2022 / 0018
 Replacing version dated / version: 24.02.2022 / 0017
 Valid from: 30.06.2022
 PDF print date: 30.06.2022
 megol Motorenoel Super LL DIMO Premium SAE 10W-40

Respiratory or skin sensitisation:						Yes (skin contact), Analogous conclusion
------------------------------------	--	--	--	--	--	--

11.2. Information on other hazards

megol Motorenoel Super LL DIMO Premium SAE 10W-40						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

megol Motorenoel Super LL DIMO Premium SAE 10W-40							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree (complexing organic substance) >= 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	Analogous conclusion

Page 11 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.06.2022 / 0018
 Replacing version dated / version: 24.02.2022 / 0017
 Valid from: 30.06.2022
 PDF print date: 30.06.2022
 megol Motorenoel Super LL DIMO Premium SAE 10W-40

12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	48h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,9-6				High
Other information:	AOX		0	%			

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	4,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	75	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	410	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		27d	<5	%		Regulation (EC) 440/2008 C.6 (DEGRADATION - CHEMICAL OXYGEN DEMAND)	Not biodegradable

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Not readily biodegradable

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 9, 11, 12, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361d Suspected of damaging the unborn child.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Skin Sens. — Skin sensitization

Repr. — Reproductive toxicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Page 14 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.06.2022 / 0018
 Replacing version dated / version: 24.02.2022 / 0017
 Valid from: 30.06.2022
 PDF print date: 30.06.2022
 megol Motorenoel Super LL DIMO Premium SAE 10W-40

Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 TOC Total organic carbon
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.