

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GB

PAG 46 yf 8887200041 / 8887200042

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Refrigeration Lubrificant, A/C Lubricant, Compressor Lubricant, Lubricant **Uses advised against:**

No information available at present.

1.3 Details of the supplier of the safety data sheet

Dometic WAECO International GmbH, Hollefeldstr. 63, 48282 Emsdetten, Germany Phone:+49 (0) 2572 879 0, Fax:+49 (0) 2572 879 300

Dometic UK Ltd Dometic House, The Brewery, DT11 9LS Blandford St Mary, Dorset, United Kingdom Phone:+44 (0) 0844 626 0133, Fax:+44 (0) 0844 626 0143 www.waeco.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (CCWA)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementSkin Sens.1H317-May cause an allergic skin reaction.Aquatic Chronic3H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 13

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042



Warning

H317-May cause an allergic skin reaction. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P280-Wear protective gloves. P333+P313-If skin irritation or rash occurs: Get medical advice / attention. P501-Dispose of contents / container to special waste collection point.

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3 2 Mixturo

3.2 WIXture	
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	221-453-2
CAS	3101-60-8
content %	1-2
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317
	Aquatic Chronic 2, H411

2,6-di-tert-butyl-p-cresol	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	204-881-4
CAS	128-37-0
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16. The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.



Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Never pour anything into the mouth of an unconscious person!

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

irritation of the eyes

Skin irritation possible with prolonged contact.

4.3 Indication of any immediate medical attention and special treatment needed n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing media
Water jet spray / alcohol resistant foam / CO2 / dry extinguisher
Unsuitable extinguishing media
None known
5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Toxic gases
5.3 Advice for firefighters
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up. Resolve leaks if this possible without risk. Prevent from entering drainage system.



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

Ensure sufficient supply of air.

Avoid contact with eyes.

GB

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.1 General recommendations

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Store in a well-ventilated place.

Store in a well-

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	2,6-di-tert-butyl-p-cresol		Content %:0,1- <1
WEL-TWA: 10 mg/m3	WEL-STEL:		
Monitoring procedures:			
BMGV:		Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

2,6-di-tert-butyl-p-cresol									
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note			
	Environmental		r						
	compartment								
	Environment - soil		PNEC	1,04	mg/kg wwt				
	Environment - sewage		PNEC	100	mg/l				
	treatment plant								
	Environment - sediment		PNEC	1,29	mg/kg wwt				



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

	Environment - marine		PNEC	0,4	µg/l	
	Environment - periodic release		PNEC	4	µg/l	
	Environment - freshwater		PNEC	4	µg/l	
	Environment - oral (animal feed)		PNEC	16,7	mg/kg	
	Environment - soil		PNEC	1,23	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,74	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5,8	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/day	

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

GB

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. In case of emergency: Protective respirator with independent air supply.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.



Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

GB

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties: Oxidising properties: 9.2 Other information Miscibility: Fat solubility / solvent: Conductivity:

Liquid Yellow Characteristic Not determined n.a. <-25 °C Not determined >230 °C Not determined Not determined Not determined Not determined Not determined Not determined 0,9895 g/cm3 (20°C) n.a. Not determined Insoluble Not determined Not determined Not determined 44.6 mm2/s Product is not explosive. No Not determined Not determined

Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Surface tension:

Solvents content:

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Heating, open flame, ignition sources **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. Avoid contact with strong acids. **10.6 Hazardous decomposition products** No decomposition when used as directed.

SECTION 11: Toxicological information



Page 7 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

11.1 Information on toxicological effects Possibly more information on health effects, see Section 2.1 (classification). PAG 46 vf

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						Sensitising
sensitisation:						(skin contact)
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 425 (Acute			
					Oral Toxicity - Up-and-			
					Down Procedure)			
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute			
route:					Dermal Toxicity)			

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>2930	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:						Slightly irritant
Serious eye				Rabbit	(Draize-Test)	Slightly irritant
damage/irritation:						
Respiratory or skin				Human being		Not sensitizising
sensitisation:						
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Mammalian		Negative
Reproductive toxicity:	NOAEL	100	mg/kg	Rat		
Specific target organ toxicity - repeated exposure (STOT- RE):	NOEL	25	mg/kg	Rat		(28 d)
Symptoms:						mucous
						membrane
						irritation



_ (B)	
Page 8 of 13	
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II	
Revision date / version: 16.08.2016 / 0003	
Replacing version dated / version: 13.07.2015 / 0002	
Valid from: 16.08.2016	
PDF print date: 08.03.2017	
PAG 46 yf	
8887200041 / 8887200042	_

Specific target organ toxicity -	NOAEL	25	mg/kg	Rat	
repeated exposure (STOT-					
RE), oral:					

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

8887200041 / 88872000	042						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and	BOD		28	%			Not readily
degradability:							biodegradable
12.2. Persistence and	ThOD		16	%			Not readily
degradability:							biodegradable
12.3. Bioaccumulative							Not to be
potential:							expected
12.4. Mobility in soil:							The product is
							water-soluble
							and can be
							dispersed in
							aqueous
							systems.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse effects:							n.d.a.
Other information:							Aquatic
							Chronic 3

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	7,5	mg/l	Oncorhynchus	OECD 203		
					mykiss	(Fish, Acute		
						Toxicity Test)		
12.1. Toxicity to	EC50	48h	67,9	mg/l	Daphnia magna	OECD 202		
daphnia:						(Daphnia sp.		
						Acute		
						Immobilisation		
						Test)		
12.1. Toxicity to algae:	EC50	72h	9	mg/l	Pseudokirchnerie	OECD 201		
					lla subcapitata	(Alga, Growth		
						Inhibition Test)		

2,6-di-tert-butyl-p-cresol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>0,57	mg/l		QSAR	
12.1. Toxicity to fish:	NOEC/NOEL	42d	0,053	mg/l	Oryzias latipes	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	0,61	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

œ

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,07	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,5	mg/l	Desmodesmus subspicatus	OEĆD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	1	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	4,5	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		4,17-5,1				
12.3. Bioaccumulative potential:	Log Pow		5,1				
12.3. Bioaccumulative	BCF		330-				
potential:			1800				
12.3. Bioaccumulative potential:			230- 2500		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	56d
12.5. Results of PBT and vPvB assessment							No PBT substance
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge		
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Water solubility:			0,00076	g/l			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 06 synthetic engine, gear and lubricating oils

Recommendation:



- (B)					
Page 10 of 13					
Safety data sheet according to Regulation (EC) No 1907/2006, A	Annex II				
Revision date / version: 16.08.2016 / 0003					
Replacing version dated / version: 13.07.2015 / 0002					
Valid from: 16.08.2016					
PDF print date: 08.03.2017					
PAG 46 vf					
8887200041 / 8887200042					
Sewage disposal shall be discouraged.					
Pay attention to local and national official regulations.					
E.g. suitable incineration plant.					
For contaminated packing material					
Pay attention to local and national official regulations.					
Empty container completely.					
Uncontaminated packaging can be recycled.					
Dispose of packaging that cannot be cleaned in the same manne	er as the substance.				
SECTION 14: Tra	ansport information				
General statements					
14.1. UN number:	n.a.				
Transport by road/by rail (ADR/RID)	••				
14.2. UN proper shipping name:					
14.2. On proper snipping name. 14.3. Transport hazard class(es):	n.a.				
14.4. Packing group:	n.a.				
Classification code:	n.a.				
LQ:	n.a.				
14.5. Environmental hazards:	Not applicable				
Tunnel restriction code:					
Transport by sea (IMDG-code)					
14.2. UN proper shipping name:					
14.3. Transport hazard class(es):	n.a.				
14.4. Packing group:	n.a.				
Marine Pollutant:	n.a				
14.5. Environmental hazards:	Not applicable				
Transport by air (IATA)	···· • • • • • • • • • • • • • • • • •				
14.2. UN proper shipping name:					
14.2. On proper simpling name. 14.3. Transport hazard class(es):	n.a.				
14.4. Packing group:	n.a.				
14.5. Environmental hazards:	Not applicable				
14.6. Special precautions for user					
	must be followed				
Unless specified otherwise, general measures for safe transport					
14.7. Transport in bulk according to Annex II of	MARPOL and the IBC Code				
Non-dangerous material according to Transport Regulations.					
SECTION 15: Red	gulatory information				
	J				
45.4 Cofety, health and environmental regulation	nollowialation analitic for the autotance or minture				
•	ns/legislation specific for the substance or mixture				
Observe restrictions:					
Comply with trade association/occupational health regulations.					
Directive $2010/75/EU(1)/00$	0 %				
Directive 2010/75/EU (VOC):	0 78				
15.2 Chemical safety assessment					
A chemical safety assessment is not provided for mixtures.					
SECTION 16: 0	Other information				
Revised sections:	2, 3, 8, 11, 12, 15				
These details refer to the product as it is delivered.					

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):



Page 11 of 13

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H317 May cause an allergic skin reaction. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

Skin Sens. — Skin sensitization Aquatic Chronic — Hazardous to the aquatic environment - chronic Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

AC **Article Categories** acc., acc, to according, according to ACGIHAmerican Conference of Governmental Industrial Hygienists ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approximately approx. Art., Art. no. Article number ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum body weight bw **Chemical Abstracts Service** CAS CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques **CIPAC Collaborative International Pesticides Analytical Council** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEA European Economic Area European Economic Community EEC



Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 vf 8887200041 / 8887200042 European Inventory of Existing Commercial Chemical Substances **EINECS ELINCS** European List of Notified Chemical Substances **European Norms** EN EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** Exposure scenario ES et cetera etc. EU **European Union** EWC European Waste Catalogue Fax number Fax. gen. general Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC Intermediate Bulk Container International Bulk Chemical (Code) IBC (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLIDInternational Uniform ChemicaL Information Database lethal concentration LC LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level 10 Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. not checked n.c. n.d.a. no data available NIOSHNational Institute of Occupational Safety and Health (United States of America) NOAEC No Observed Adverse Effective Concentration No Observed Adverse Effect Level NOAEL NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic Chemical product category PC PE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential ppm parts per million **PROC Process category** PTFE Polytetrafluorethylene Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning REACH the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical REACH-IT List-No. identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

GB



Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.08.2016 / 0003 Replacing version dated / version: 13.07.2015 / 0002 Valid from: 16.08.2016 PDF print date: 08.03.2017 PAG 46 yf 8887200041 / 8887200042

GB

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the RID International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.