

Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

ആ

# **Touring High Tech Special 20W-50**

**1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Grease Uses advised against: No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

(B) LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number Emergency information services / official advisory body:

Landspitali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland) **Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

Dangerous vapours heavier than air. Product floats on the water surface. Product can re-ignite itself.

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

#### n.a. 3.2 Mixtures

ആ

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP, REACH-IT List-No.	265-158-7
CAS	64742-55-8
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic	
Registration number (REACH)	01-2119471299-27-XXXX
Index	649-474-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	265-169-7
CAS	64742-65-0
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

# 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### **4.3 Indication of any immediate medical attention and special treatment needed** Symptomatic treatment.

**SECTION 5: Firefighting measures** 



Page 3 of 14

അ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

#### 5.1 Extinguishing media Suitable extinguishing media

CO2 Foam Dry extinguisher Water jet spray

Unsuitable extinguishing media High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Fume

# Toxic gases **5.3 Advice for firefighters**

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

# 7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Do not heat to temperatures close to flash point.



Page 4 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

#### Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Under all circumstances prevent penetration into the soil. Store at room temperature. Store in a dry place.

#### 7.3 Specific end use(s)

œ

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Chemical Name Oil mist, mineral		
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:	
working fluids, ACGIH)		
Monitoring procedures: - I	Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	

Distillates (petroleum), hydro	otreated light paraffinic					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3	

Distillates (petroleum), solvent-dewaxed heavy paraffinic								
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note		
	Environmental compartment							
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed			
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3			
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/d			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/d			

Distillates (petroleum), hydrotreated heavy paraffinic



Page 5 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

ആ

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

# 8.2 Exposure controls

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: >= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded.



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	230 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	n.d.a.
Kinematic viscosity:	170,0 mm2/s (40°C)
Kinematic viscosity:	19,20 mm2/s (100°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,875 g/cm3
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
9.2 Other information	

#### 9.2 Other information

No information available at present.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
Open flame, ignition sources
10.5 Incompatible materials
Avoid contact with strong oxidizing agents.
10.6 Hazardous decomposition products
No decomposition when used as directed.

**SECTION 11: Toxicological information** 



B Page 7 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Touring High Tech Special 20V	V-50					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), hydrotreated light paraffinic								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion		
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion		
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion		
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion		
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusionChine e hamster		
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusionderm		
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Analogous conclusionderm		
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion		
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion		



Safety data sheet according to Re Revision date / version: 06.06.202 Replacing version dated / version Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-5	24 / 0004 1: 17.01.2022					
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	<30	mg/kg bw/d	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,05	mg/l	Rat	OECD 412 (Subacute Inhalation Toxicity - 28- Day Study)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,15	mg/l	Rat		Aerosol, Analogous conclusion13 weeks
Aspiration hazard:						Yes
Distillates (petroleum), solvent-	dewaxed her	avy paraffinic				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50 LD50	>5000	mg/kg mg/l/4h	Rabbit	OECD 402 (Acute Dermal Toxicity) OECD 403 (Acute	Aerosol
Skin corrosion/irritation:	2030	-0,00		Rabbit	Inhalation Toxicity) OECD 404 (Acute	Not irritant,
					Dermal Irritation/Corrosion)	Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamste
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse		Female, Negativ
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion 78 weeks, dermal
Reproductive toxicity:				Rat		Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion dermal
Reproductive toxicity (Effects on fertility):				Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative, Analogous conclusion oral, dermal
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	30	mg/kg/d	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Analogous conclusion

- (GB)-



Page 9 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

œ)

Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	~1000	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,22	mg/l	Rat		Aerosol, Analogous conclusion 4 weeks
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,15	mg/l	Rat		Aerosol, Analogous conclusion 13 weeks
Aspiration hazard:						Yes
Symptoms:						mucous membrane irritation, dizziness, nausea

#### 11.2. Information on other hazards

Touring High Tech Special 20W-50							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Endocrine disrupting properties:						Does not apply to mixtures.	
Other information:						No other relevant information available on adverse effects on health.	

# **SECTION 12: Ecological information**

Touring High Tech Special 20W-50							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-elimination
							degree(complexi
							ng organic
							substance)>=
							80%/28d: No
Other information:	AOX		0	%			According to the
							recipe, contains
							no ÁOX.



Page 10 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

œ

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	> 10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>6			· · · · · · · · · · · · · · · · · · ·	@20°C
12.3. Bioaccumulative potential:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:							The product can be extensively eliminated from water via abiotic processes (e.g. adsorption on activated sludge

Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>5000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	96h	>1000	mg/l	Scenedesmus subspicatus		



Page 11 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50

12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable (Analogous conclusion)
12.3. Bioaccumulative potential:	Log Pow		>3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC20	6h	>1000	mg/l	Pseudomonas fluorescens		

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.

EC disposal code no.:

œ

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

# For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely. Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

**SECTION 14: Transport information** 

## **General statements**

Transport by road/by rail (ADR/RID)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable
Transport by sea (IMDG-code)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable



Page 12 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024

Touring High Tech Special 20W-50 Marine Pollutant: EmS:

അ

# Transport by air (IATA)

14.1. UN number or ID number: 14.2. UN proper shipping name: Not applicable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards:

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable. Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC):

National requirements/regulations on safety and health protection must be applied when using work equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

1.3 %

Revised sections:

2, 3, 4, 8, 9, 11, 12, 15, 16

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

# Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

# Any abbreviations and acronyms used in this document:

Not applicable

Not applicable Not applicable

Not applicable Not applicable Not applicable



ആ Page 13 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50 acc., acc. to according, according to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATF Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. **European Union** EU EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. **IUCLID** International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships mg/kg bw mg/kg body weight mg/kg bw/d, mg/kg bw/day mg/kg body weight/day mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight not applicable n.a. not available n.av. n.c. not checked n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NI P No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development



ആ Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 06.06.2024 / 0004 Replacing version dated / version: 17.01.2022 / 0003 Valid from: 06.06.2024 PDF print date: 06.06.2024 Touring High Tech Special 20W-50 org. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PF Polyethylene PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride PVC REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

#### These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.