

Page 1 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ആ

2-Takt-Motoroil

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0, 1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients



Page 2 of 11

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

3.1 Substances

n.a. 3.2 Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119456620-43-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	926-141-6
CAS	
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately. Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. The following may occur: Drying of the skin.

Irritation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Foam Dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon



Page 3 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

Oxides of nitrogen Oxides of sulphur Flammable vapour/air mixtures

ആ

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist. Ensure good ventilation.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Do not carry cleaning cloths soaked in product in trouser pockets.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Protect against moisture and store closed.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection



Page 4 of 11

അ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Hydrocarbons, C11	1-C14, n-alkanes, isoalkanes, cycli	cs, <2% aromatics		Content %:10- <20
WEL-TWA: 1200 mg/m3 (>=C7 no	rmal and branched	WEL-STEL:			
chain alkanes)					
Monitoring procedures:	- [Draeger - Hydrocarbons 0,1%/c (81	l 03 571)		
	- [Draeger - Hydrocarbons 2/a (81 03	581)		
	- (Compur - KITA-187 S (551 174)			
BMGV:			Other information:		
Chemical Name	Oil mist, mineral				Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL:			
working fluids, ACGIH)					
Monitoring procedures:	- [Draeger - Oil Mist 1/a (67 33 031)			
BMGV:			Other information:	•	

Distillates (petroleum), hydr	otreated heavy paraffinic					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - oral (animal		PNEC	9,33	mg/kg feed	
	feed)					

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). (WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 5 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Protective Neoprene® / polychloroprene gloves (EN ISO 374). Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: > 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	110 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	59,5 mm2/s (40°C)
Kinematic viscosity:	9,1 mm2/s (100°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,865 g/cm3
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
9.2 Other information	
Explosives:	There is no information available on this parameter.
Oxidising liquids:	There is no information available on this parameter.



Page 6 of 11

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Protect from humidity. Open flame, ignition sources **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification). 2-Takt-Motoroil Toxicity / effect Endpoint Value Unit Organism Notes Test method Acute toxicity, by oral route: n.d.a. Acute toxicity, by dermal route: n.d.a. Acute toxicity, by inhalation: n.d.a. Skin corrosion/irritation: n.d.a. Serious eye damage/irritation: n.d.a. Respiratory or skin n.d.a. sensitisation: Germ cell mutagenicity: n.d.a. Carcinogenicity: n.d.a. Reproductive toxicity: n.d.a. Specific target organ toxicity n.d.a. single exposure (STOT-SE): Specific target organ toxicity n.d.a. repeated exposure (STOT-RE): n.d.a. Aspiration hazard: Symptoms: n.d.a.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Organism Endpoint Value Test method Notes Toxicity / effect Unit Acute toxicity, by oral route: LD50 >5000 Rat OECD 401 (Acute Oral mg/kg Toxicity) LD50 Acute toxicity, by dermal route: >5000 Rabbit OECD 402 (Acute mg/kg Dermal Toxicity) LC50 Acute toxicity, by inhalation: >5000 mg/m3/8h Rat OECD 403 (Acute Vapours Inhalation Toxicity) Skin corrosion/irritation: OECD 404 (Acute Analogous conclusion, Dermal Irritation/Corrosion) Drying of the skin., Dermatitis (skin inflammation) Serious eye damage/irritation: OECD 405 (Acute Eye Analogous Irritation/Corrosion) conclusion, Slightly irritant



Page 7 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

œ)

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity: Germ cell mutagenicity:				Mouse Salmonella typhimurium	in vivo OECD 471 (Bacterial Reverse Mutation Test)	Negative Negative, Analogous
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome	Conclusion Negative
Germ cell mutagenicity:				Mouse	Aberration Test) OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

11.2. Information on other hazards

2-Takt-Motoroil						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							



Page 8 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

œ

12.3. Bioaccumulative potential:	n.d.a.
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Endocrine	Does not apply
disrupting properties:	to mixtures.
12.7. Other adverse	No information
effects:	available on
	other adverse
	effects on the
	environment.
Other information:	DOC-elimination
	degree(complexi
	ng organic
	substance)>=
	80%/28d: No

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:							Insoluble
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSÁR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		6-8				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substanc

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

13 02 06 synthetic engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.



Page 9 of 11

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

For contaminated packing material

Pay attention to local and national official regulations. 15 01 01 paper and cardboard packaging 15 01 02 plastic packaging 15 01 04 metallic packaging Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements	
14.1. UN number or ID number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for safe	transport must be followed
14.7. Maritime transport in bulk accor	•
Non-dangerous material according to Transport Regula	ations.
SECTIO	ON 15: Regulatory information
15.1 Safety health and environmental	l regulations/legislation specific for the substance or mixture
rorr barciy, nearrinana crivitorinienta	
Observe restrictions: General hygiene measures for the handling of chemica	Is are applicable.
Directive 2010/75/EU (VOC):	17.79 %
Directive 2010/13/LO(VOC).	11,13 /0

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

1-16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable



Page 10 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard

ആ

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., a ADR Interna AOX	cc. to according, according to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the tional Carriage of Dangerous Goods by Road) Adsorbable organic halogen compounds
	. approximately
Art., A	
ASTM	ASTM International (American Society for Testing and Materials)
ATE	Acute Toxicity Estimate
BAM	Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA	Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF	Bioconcentration factor
BSEF	
bw	body weight
CAS	Chemical Abstracts Service
CLP and mi	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances
CMR	carcinogenic, mutagenic, reproductive toxic
	Derived Minimum Effect Level
	Derived No Effect Level
DOC	Dissolved organic carbon
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
	EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC	European Community
ECHA	European Chemicals Agency
	Lx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
	European Economic Community
EINEC	
ELINC	
EN	
EPA	United States Environmental Protection Agency (United States of America)
	EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera
etc. EU	European Union
EVAL	
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
Koc	Adsorption coefficient of organic carbon in the soil



ആ Page 11 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0013 Replacing version dated / version: 14.10.2021 / 0012 Valid from: 01.11.2021 PDF print date: 01.11.2021 2-Takt-Motoroil Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. n.c. not checked no data available n.d.a. NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer No Observed Effect Concentration/Level NOEC, NOEL OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) persistent, bioaccumulative and toxic PBT Polyethylene PF PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride PVC REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.