

Page 1 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GEAR PROTECT 80 mL

Art.: 1007

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Skin Irrit. 2 H315-Causes skin irritation.

Skin Sens. 1 H317-May cause an allergic skin reaction.

Aquatic Chronic 4 H413-May cause long lasting harmful effects to aquatic

life.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Warning

H315-Causes skin irritation. H317-May cause an allergic skin reaction. H413-May cause long lasting harmful effects to aquatic life.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

P302+P352-IF ON SKIN: Wash with plenty of water / soap. P333+P313-If skin irritation or rash occurs: Get medical advice / attention.

P501-Dispose of contents / container to an approved waste disposal facility.

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogene dithiophosphate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3.2 Mixture**

OLE MIXEGIO	
Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)]	
hydrogene dithiophosphate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	947-946-9 (REACH-IT List-No.)
CAS	
content %	20-<30
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Skin Sens. 1B, H317
	Aquatic Chronic 4, H413

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid	Substance with specific conc. limit(s) acc. to REACh-
with phosphorus oxide, propylene oxide and amines, C12-14-alkyl	registration
(branched)	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	931-384-6 (REACH-IT List-No.)
CAS	
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Skin Sens. 1, H317
	Eye Dam. 1, H318
	Aquatic Chronic 2, H411

C16-18-(even numbered, saturated and unsaturated)-alkylamines	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	627-034-4 (REACH-IT List-No.)
CAS	1213789-63-9
content %	0,1-<0,25



Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Asp. Tox. 1, H304
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
	STOT SE 3, H335
	Aguatic Acute 1, H400 (M=10)
	Aguatic Chronic 1, H410 (M=10)
	STOT RE 2, H373 (gastrointestinal tract, liver, immune
	system) (oral)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Not required.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Product removes fat.

Dermatitis (skin inflammation)

Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Extinction powder

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur Hydrocarbons

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.



Œ

Page 4 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary. Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Under all circumstances prevent penetration into the soil.

Protect from direct sunlight and warming.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters



Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

WEL-TWA: 10 mg/m3 (as Mo) (Molybdenum	WEL-STEL: 20 mg/m3 (as Mo) (Molybdenum	
compounds, insoluble)	compounds, insoluble)	
Monitoring procedures:		
BMGV:	Other information:	
Chemical Name Oil mist, mine	eral	Content %:
Si chica ranic	Ciai	Ooritorit 70.

©B Chemical Name Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal WEL-STEL:		
working fluids, ACGIH)		
Monitoring procedures: - Draeger - Oil 10/a-P (67 28 371)		
- Draeger - Oil Mist 1/a (67 33 031)		
BMGV: Ot	ther information:	

Molybdenum trioxide, reaction products with bis[0,0-bis(2-ethylhexyl)] hydrogene dithiophosphate								
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note		
Consumer	Human - oral	Long term, systemic effects	DNEL	0,5	mg/kg bw/day			
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,5	mg/kg bw/day			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,87	mg/m3			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,4	mg/kg bw/day			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,93	mg/m3			

C16-18-(even numbered, saturated and unsaturated)-alkylamines							
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note	
	Environment - freshwater		PNEC	0,26	μg/l		
Consumer	Human - oral	Long term, systemic effects	DNEL	0,04	mg/kg		
Workers / employees	Human - dermal		DNEL	0,09	mg/kg		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 6 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374)

If applicable

Protective nitrile gloves (EN 374). Protective PVC gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

240

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

n.a.

9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

Liquid

Brown

Characteristic

Not determined

pH-value: n.a.

Melting point/freezing point: Not determined
Initial boiling point and boiling range: 270 °C

Initial boiling point and boiling range:

Flash point:

Evaporation rate:

Flammability (solid, gas):

270 °C

>180 °C

Not determined

n.a.

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Density:

Not determined

Not determined

Not determined

Not determined

O,941 g/ml (15°C)

Bulk density:



Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Solubility(ies):
Water solubility:
Insoluble
Partition coefficient (n-octanol/water):
Not determined
Auto-ignition temperature:
Not determined
Decomposition temperature:
Viscosity:
Not determined
Not determined
Viscosity:
80 mm2/s (40°C)

Explosive properties: Product is not explosive.

Oxidising properties:

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Strong heat

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

GEAR PROTECT 80 mL		,	,			
Art.: 1007						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.



Page 8 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL Art.: 1007

Other information:			Classification
			according to
			calculation
			procedure.

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogene dithiophosphate							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	6810	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	10000	mg/kg	Rabbit			
Skin corrosion/irritation:				Human being	OECD 439 (In Vitro Skin	Skin Irrit. 2	
					Irritation -		
					Reconstructed Human		
					Epidermis Test Method)		
Respiratory or skin				Mouse	OECD 429 (Skin	Skin Sens. 1B	
sensitisation:					Sensitisation - Local		
					Lymph Node Assay)		

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral		
					Toxicity)		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant	
					Dermal		
					Irritation/Corrosion)		
Serious eye damage/irritation:				Rabbit	·	Corrosive	
Respiratory or skin				Mouse	OECD 429 (Skin	Sensitising	
sensitisation:					Sensitisation - Local		
					Lymph Node Assay)		

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1689	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LD50	>0,099	ppmV/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Effects on fertility):	NOAEL	12,5	mg/kg	Ŕat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3,25	mg/kg/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	Target organ(s): gastrointestinal tract, liver, immune system

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification). GEAR PROTECT 80 mL

-	Taviaitu / affaat	Fradmaint
	Art.: 1007	
- 1	0	

Art.: 1007							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.



Page 9 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL Art.: 1007

12.1. Toxicity to daphnia:	n.d.a.
12.1. Toxicity to algae:	n.d.a.
12.2. Persistence and	n.d.a.
degradability:	
12.3. Bioaccumulative	n.d.a.
potential:	
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Other adverse	n.d.a.
effects:	
Other information:	According to the
	recipe, contains
	no AOX.
Other information:	Aquatic Chronic
	4 Classification
	based on test
	data.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and		28d	11	%		OECD 301 B	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EL50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EL50	72h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
Toxicity to bacteria:	EC50	3h	1000	mg/l	activated sludge	OECD 209	
						(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	3,2	mg/l	Oncorhynchus	OECD 203 (Fish,	
-					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	91,4	mg/l	Daphnia magna	OECD 202	
•						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	96h	6,4	mg/l	Selenastrum	OEĆD 201 (Alga,	
					capricornutum	Growth Inhibition	
					'	Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	1,7	mg/l	Selenastrum	OECD 201 (Alga,	
					capricornutum	Growth Inhibition	
						Test)	



(B)

Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

12.2. Persistence and degradability:		28d	7,4	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)
Toxicity to bacteria:	EC50	3h	~2433	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,06	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	0,011	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,46	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to daphnia:	EC50		0,011	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	66	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
Toxicity to bacteria:	EL50	3h	222,5	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.



Page 11 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:
n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): < 0,1 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: These details refer to the product as it is delivered. 2, 3, 7, 8, 11, 12, 16

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.



Page 12 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

Aquatic Chronic 4, H413

Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - oral

Eye Dam. — Serious eye damage

Asp. Tox. — Aspiration hazard Skin Corr. — Skin corrosion

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Aquatic Acute — Hazardous to the aquatic environment - acute

STOT RE — Specific target organ toxicity - repeated exposure

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Article number Art., Art. no.

ASTM ASTM International (American Society for Testing and Materials)

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

Chemical Abstracts Service CAS

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

carcinogenic, mutagenic, reproductive toxic CMR

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

ΕČ **European Community** ECHA European Chemicals Agency **European Economic Community** EEC

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

ΕN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU **European Union**

EVAL Ethylene-vinyl alcohol copolymer

Fax number Fax.



Page 13 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.08.2019 / 0017

Replacing version dated / version: 21.08.2015 / 0016

Valid from: 14.08.2019 PDF print date: 14.08.2019 GEAR PROTECT 80 mL

Art.: 1007

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.