

Page 1 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Top Tec 6400 0W-20

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

അ

Sector of use [SU]: SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites Chemical product category [PC]: PC17 - Hydraulic fluids PC24 - Lubricants, greases, release products Process category [PROC]: PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC20 - Use of functional fluids in small devices PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 7 - Use of functional fluid at industrial site ERC 9a - Widespread use of functional fluid (indoor) ERC 9b - Widespread use of functional fluid (outdoor) Life cycle stages (LCS): LCS C - Consumer use LCS F - Formulation or re-packing LCS IS - Use at industrial sites LCS PW - Widespread use by professional workers Technical functions (TF): Lubricating agent Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:



Page 2 of 19

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains C14-16-18 Alkylphenol. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

3.2 Mixtures	
Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP	265-157-1
CAS	64742-54-7
content %	60-<80
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
1-Decene, homopolymer, hydrogenated	
Registration number (REACH)	01-2119486452-34-XXXX
Index	
EINECS, ELINCS, NLP	500-183-1 (NLP)
CAS	68037-01-4
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5
EINECS, ELINCS, NLP	276-738-4
CAS	72623-87-1
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474878-16-XXXX
Index	649-482-00-X
EINECS, ELINCS, NLP	276-737-9
CAS	72623-86-0



Page 3 of 19

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

content %	1-<10			
	Asp. Tox. 1, H304			
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. 10x. 1, H304			
Bis(nonylphenyl)amine				
Registration number (REACH)	01-2119488911-28-XXXX			
Index	01-2119400911-20-7777			
EINECS, ELINCS, NLP	253-249-4			
CAS	36878-20-3			
CAS	<2.5			
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413			
Distillation (noticely with a short the same set 11)				
Distillates (petroleum), solvent-dewaxed heavy paraffinic				
Registration number (REACH)	01-2119471299-27-XXXX			
Index	649-474-00-6			
EINECS, ELINCS, NLP	265-169-7			
CAS	64742-65-0			
content %	<2,5			
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304			
Distillates (petroleum), solvent-dewaxed light paraffinic				
Registration number (REACH)	01-2119480132-48-XXXX			
Index	649-469-00-9			
EINECS, ELINCS, NLP	265-159-2			
CAS	64742-56-9			
content %	<2,5			
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304			
Paraffin oils (petroleum), catalytic dewaxed heavy				
Registration number (REACH)	01-2119487080-42-XXXX			
Index	649-477-00-2			
EINECS, ELINCS, NLP	265-174-4			
CAS	64742-70-7			
content %	<2,5			
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304			

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Sensitive individuals:



Page 4 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

Allergic reaction possible.

ആ

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Foam Dry extinguisher Water mist

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Oxides of sulphur Oxides of phosphorus Hydrogen sulphide

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up. Resolve leaks if this possible without risk. Prevent from entering drainage system. Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist. Avoid contact with eyes or skin. Do not carry cleaning cloths soaked in product in trouser pockets. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.



Page 5 of 19

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

 $\label{eq:keep} \ensuremath{\mathsf{Keep}}\xspace \ensuremath{\mathsf{avay}}\xspace \ensuremath{\mathsf{from}}\xspace \ensuremath{$

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Under all circumstances prevent penetration into the soil. Store at room temperature. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name Oil mist, mineral		Content	%:			
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:					
working fluids, ACGIH)						
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)						
BMGV:	Other information:					

Distillates (petroleum), hydrotreated heavy paraffinic									
Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note			
	compartment								
	Environment - oral (animal		PNEC	9,33	mg/kg				
	feed)								
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	8h			

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based									
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note			
	Environmental								
	compartment								
	Human - oral		PNEC	9,33	mg/kg feed				
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h			

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based								
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note		
	Environmental							
	compartment							
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h		
Consumer	Human - dermal	Long term, systemic	DNEL	0,74	mg/kg			
		effects			bw/day			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h		
Workers / employees	Human - dermal	Long term, systemic	DNEL	0,97	mg/kg			
		effects			bw/day			
Workers / employees	Human - inhalation	Long term, systemic	DNEL	2,73	mg/m3			
		effects						

Bis(nonylphenyl)amine



Page 6 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

ആ

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	132000	mg/kg dw	
	Environment - sediment, marine		PNEC	13200	mg/kg dw	
	Environment - soil		DNEL	263000	mg/kg dw	
	Environment - periodic release		PNEC	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,09	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,62	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,37	mg/m3	

Distillates (petroleum), solvent-dewaxed heavy paraffinic									
Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note			
	compartment								
	Environment - oral (animal		PNEC	9,33	mg/kg feed				
	feed)								
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3				

B WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".



Page 7 of 19

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). If applicable Protective gloves made of fluorocarbon rubber (EN 374). Protective Neoprene® / polychloroprene gloves (EN 374). Protective nitrile gloves (EN 374). Minimum layer thickness in mm: >= 0,5 Permeation time (penetration time) in minutes: >= 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time. Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	-48 °C
Initial boiling point and boiling range:	Not determined
Flash point:	230 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined



Page 8 of 19

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: Not determined Not determined 0,845 g/cm3 Not determined Insoluble Not determined Not determined 39,0 mm2/s (40°C) 8,0 mm2/s (100°C) Not determined Not determined

Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Strong heat **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Top Tec 6400 0W-20							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:						n.d.a.	
Acute toxicity, by dermal route:						n.d.a.	
Acute toxicity, by inhalation:						n.d.a.	
Skin corrosion/irritation:						n.d.a.	
Serious eye damage/irritation:						n.d.a.	
Respiratory or skin						n.d.a.	
sensitisation:							
Germ cell mutagenicity:						n.d.a.	
Carcinogenicity:						n.d.a.	
Reproductive toxicity:						n.d.a.	
Specific target organ toxicity -						n.d.a.	
single exposure (STOT-SE):							
Specific target organ toxicity -						n.d.a.	
repeated exposure (STOT-RE):							
Aspiration hazard:						n.d.a.	
Symptoms:						n.d.a.	
Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	



Page 9 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

œ.

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,22	mg/l	Rat		Dust, Mist, Analogous conclusion

1-Decene, homopolymer, hydrogenated								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Aspiration hazard:						Asp. Tox. 1		

Lubricating oils (petroleum), C	20-50, hydrotr	eated neutral	oil-based			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
					,	cause skin
						dryness or
						cracking.



Page 10 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

GB

Serious eye damage/irritation:	Rabbit	OECD 405 (Acute Eye	Not irritant
		Irritation/Corrosion)	
Respiratory or skin	Guinea pig	OECD 406 (Skin	No (skin contac
sensitisation:		Sensitisation)	
Germ cell mutagenicity:		OECD 471 (Bacterial	Negative
		Reverse Mutation Test)	
Germ cell mutagenicity:		OECD 473 (In Vitro	Negative
		Mammalian	
		Chromosome	
		Aberration Test)	
Germ cell mutagenicity:		OECD 474 (Mammalian	Negative
		Erythrocyte	
		Micronucleus Test)	
Germ cell mutagenicity:		OECD 476 (In Vitro	Negative
		Mammalian Cell Gene	
		Mutation Test)	
Carcinogenicity:		OECD 451	Negative
		(Carcinogenicity Studies)	
Carcinogenicity:		OECD 453 (Combined	Negative
		Chronic	
		Toxicity/Carcinogenicity	
		Studies)	
Reproductive toxicity:		OECD 414 (Prenatal	Negative
		Developmental Toxicity	
		Study)	
Reproductive toxicity:		OECD 421	Negative
		(Reproduction/Developm	-
		ental Toxicity Screening	
		Test)	
Specific target organ toxicity -		OECD 408 (Repeated	Negative
repeated exposure (STOT-RE):		Dose 90-Day Oral	
		Toxicity Study in	
		Rodents)	
Specific target organ toxicity -		OECD 410 (Repeated	Negative
repeated exposure (STOT-RE):		Dose Dermal Toxicity -	
		90-Day)	
Specific target organ toxicity -		OECD 411 (Subchronic	Negative
repeated exposure (STOT-RE):		Dermal Toxicity - 90-day	-
		Study)	
Specific target organ toxicity -		OECD 412 (Subacute	Negative
repeated exposure (STOT-RE):		Inhalation Toxicity - 28-	-
		Day Study)	
Aspiration hazard:			Asp. Tox. 1

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based Notes Value Organism Test method Toxicity / effect Endpoint Unit Acute toxicity, by oral route: LD50 >5000 Rat OECD 401 (Acute Oral mg/kg Toxicity) OECD 402 (Acute Acute toxicity, by dermal route: LD50 >2000 mg/kg Rabbit Dermal Toxicity) LC50 Acute toxicity, by inhalation: >5,53 mg/m3/4h Rat OECD 403 (Acute Aerosol Inhalation Toxicity) OECD 404 (Acute Rabbit Skin corrosion/irritation: Not irritant, Dermal Analogous Irritation/Corrosion) conclusion OECD 405 (Acute Eye Serious eye damage/irritation: Rabbit Not irritant, Irritation/Corrosion) Analogous conclusion Respiratory or skin Guinea pig OECD 406 (Skin No (skin sensitisation: contact), Sensitisation) Analogous conclusion



B Page 11 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Reproductive toxicity:	NOAEL	>=1000	mg/kg/d	Rat	OECD 421	Negative
					(Reproduction/Developm	
					ental Toxicity Screening	
					Test)	
Aspiration hazard:						Yes
Symptoms:						nausea and
						vomiting.
Specific target organ toxicity -	NOAEL	125	mg/kg	Rat	OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose 90-Day Oral	conclusion
oral:					Toxicity Study in	
					Rodents)	
Specific target organ toxicity -	NOAEL	30	mg/kg	Rat	OECD 411 (Subchronic	Analogous
repeated exposure (STOT-RE),					Dermal Toxicity - 90-day	conclusion
dermal:					Study)	
Specific target organ toxicity -	NOAEL	~1000	mg/kg	Rabbit	OECD 410 (Repeated	Analogous
repeated exposure (STOT-RE),			bw/d		Dose Dermal Toxicity -	conclusion
dermal:					90-Day)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
					,	Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
					,	conclusion
Germ cell mutagenicity:				Mouse	OECD 478 (Genetic	Negative,
					Toxicology - Rodent	Analogous
					dominant Lethal Test)	conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Reproductive toxicity	NOAEL	150	mg/kg	Rat	OECD 414 (Prenatal	Negative
(Developmental toxicity):			bw/d		Developmental Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	<100	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	
oral:					Toxicity Study in	
					Rodents)	

Distillates (petroleum), solvent-dewaxed heavy paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	



Page 12 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

œ.

Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
Acute toxicity, by initialation.	LDSU	20,00	iiig///4ii		Inhalation Toxicity)	Ae10301
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
, ,					Irritation/Corrosion)	Analogous
					,	conclusion
Respiratory or skin				Mammalian	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian	Negative
-					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Carcinogenicity:				Mouse	OECD 451	Negative,
					(Carcinogenicity Studies)	Analogous
						conclusion
Carcinogenicity:				Mouse		Female, Negativ
Reproductive toxicity:				Rat		Negative
Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative,
(Developmental toxicity):					Developmental Toxicity	Analogous
				_	Study)	conclusion
Reproductive toxicity (Effects				Rat	OECD 421	Negative,
on fertility):					(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusion
Appiration hazard					Test)	Vee
Aspiration hazard:						Yes
Symptoms:						mucous
						membrane
						irritation,
						dizziness,
Specific target organ toxicity -	NOAEL	~1000	ma/ka	Dabbit	OECD 410 (Repeated	nausea
	NUAEL	~1000	mg/kg	Rabbit		Analogous
repeated exposure (STOT-RE),			bw/d		Dose Dermal Toxicity -	conclusion
dermal:					90-Day)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l	Rat	OECD 403 (Acute	Mist
			_		Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin				Guinea pig		No (skin contact)
sensitisation:						
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	



Page 13 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

œ

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Mouse		Female, Negative
Reproductive toxicity:	NOAEL	>2000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Reproductive toxicity:	NOAEL	>1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., vomiting, nausea

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	•						n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							
Other information:							DOC-elimination
							degree(complexi
							ng organic
							substance)>=
							80%/28d: No

Distillates (petroleum), h	ydrotreated hea	vy paraffin	-				
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:	·	28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric	Readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		3,9-6			Respirometry Test)	High
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	Analogous conclusion



B Page 14 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	Analogous
				-		(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	6	%		OECD 301 B	
degradability:						(Ready	
						Biodegradability -	
						Co2 Evolution	
						Test)	
Other information:	AOX		0	%			

I	
I	1-Decene, homopolymer, hydrogenated
I	1-Decene homonolymer hydrodenated
I	i-becche, nonopolymer, nyalogenatea

r-Decene, nomopolymer	, inyurogenateu						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative	Log Kow		>6,5				measured
potential:							
12.1. Toxicity to algae:	LC50	72h	>1000	mg/l	Scenedesmus		
				_	quadricauda		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	125	mg/l	Daphnia magna		
12.2. Persistence and		28d	2	%		OECD 301 D	
degradability:						(Ready	
						Biodegradability -	
						Closed Bottle Test)	

	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>=100	mg/l	Pimephales	OECD 203 (Fish,	
					promelas	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales	OECD 203 (Fish,	
					promelas	Acute Toxicity	
	E 1 = 0	4.01	10000			Test)	
2.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211	
	NOEC/NOEL	210	10	iiig/i	Daprina magna	(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
12.11. Toxicity to digue.	NOLO/NOLL	1211	2-100	iiig/i	a subcapitata	Growth Inhibition	
					a ouooupnata	Test)	
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
,		-		5	a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	46	%		OECD 301 B	
degradability:						(Ready	
						Biodegradability -	
						Co2 Evolution	
						Test)	
2.3. Bioaccumulative	Log Kow		>6				A notable
potential:							biological
							accumulation
							potential has to
							be expected
2.5. Results of PBT							(LogPow > 3). No PBT
and vPvB assessment							substance. No
							vPvB substance



Page 15 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

œ

 Toxicity to bacteria:
 NOEC/NOEL
 10min
 >1,93
 mg/l
 DIN 38412 T.8

Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	>=1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Inherent, Analogous conclusion
Other information:	Log Pow		6,1			. , , ,	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	>10	mg/l	Desmodesmus		Analogous
					subspicatus		conclusion
12.2. Persistence and		28d	24	%		OECD 301 C	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Modified MITI	
						Test (I))	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish,	Analogous
						Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	600	mg/l	Pseudokirchneriell	OECD 201 (Alga,	Analogous
					a subcapitata	Growth Inhibition	conclusion
						Test)	
12.2. Persistence and		28d	1	%	activated sludge	OECD 301 B	Not readily
degradability:						(Ready	biodegradable,
						Biodegradability -	Analogous
						Co2 Evolution	conclusion
						Test)	
12.3. Bioaccumulative	Log Pow		>7,6				Concentration in
potential:							organisms
							possible.
12.3. Bioaccumulative potential:	BCF		1730				High
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance



Page 16 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

œ.

Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and	Analogous conclusion
						Ammonium	
						Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>5000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	96h	>1000	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable (Analogous conclusion)
12.3. Bioaccumulative potential:	Log Pow		>3				Low
Toxicity to bacteria:	EC20	6h	>1000	mg/l	Pseudomonas fluorescens		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	LL50	48h	>1000	mg/l	Gammarus sp.	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 17 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Inherent
12.3. Bioaccumulative potential:	Log Pow		>3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

ആ

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Observe regulations for disposal of old oil/waste. E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements 14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for safe transport must b	e followed.
14.7. Transport in bulk according to Annex II of M	IARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.



Page 18 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 16.10.2020 / 0001 Replacing version dated / version: 16.10.2020 / 0001 Valid from: 16.10.2020 PDF print date: 20.10.2020 Top Tec 6400 0W-20

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

0 %

15.2 Chemical safety assessment A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

അ

n.a.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) The International Bromine Council BSEF body weight bw CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw drv weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. ΕČ European Community ECHA European Chemicals Agency European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms United States Environmental Protection Agency (United States of America) EPA etc. et cetera FU **European Union**



г (®)
Page 19 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.10.2020 / 0001
Replacing version dated / version: 16.10.2020 / 0001
Valid from: 16.10.2020
PDF print date: 20.10.2020
Top Tec 6400 0W-20
EVAL Ethylene vind algebal equalymer
EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number
gen. general CHS Clabelly Hermonized System of Classification and Labelling of Chamicela
GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential
IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available OFOD Organization for Economic Organization and Development
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,
Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List
Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International
Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.