

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Motorbike Kettenspray

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Lubricant

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.  
 P312-Call a POISON CENTRE / doctor if you feel unwell.  
 P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH208-Contains Methyl salicylate. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.  
 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
 Pentane

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substances

n.a.

### 3.2 Mixtures

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	---
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Pentane	
Registration number (REACH)	01-2119459286-30-XXXX
Index	601-006-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-692-4
CAS	109-66-0
content %	10-<20

Page 3 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH066 Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
---	---

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene</b>	
<b>Registration number (REACH)</b>	01-2119491299-23-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	270-128-1
<b>CAS</b>	68411-46-1
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Repr. 2, H361f Aquatic Chronic 3, H412

<b>Methyl salicylate</b>	
<b>Registration number (REACH)</b>	01-2119515671-44-XXXX
<b>Index</b>	607-749-00-8
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	204-317-7
<b>CAS</b>	119-36-8
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 2, H361d Aquatic Chronic 3, H412
<b>Specific Concentration Limits and ATE</b>	ATE (oral): 890 mg/kg

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.  
 Rinse the mouth thoroughly with water.  
 Do not induce vomiting. Consult doctor immediately.  
 Danger of aspiration.  
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.  
 headaches

Page 4 of 22  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.11.2023 / 0022  
Replacing version dated / version: 06.02.2023 / 0021  
Valid from: 22.11.2023  
PDF print date: 22.11.2023  
Motorbike Kettenspray

dizziness  
mental confusion  
Coordination disorders  
reddening of the skin  
Dermatitis (skin inflammation)  
Allergic reaction  
Ingestion:  
nausea  
vomiting  
Danger of aspiration.  
oedema of the lungs  
Chemical pneumonitis (condition similar to pneumonia)

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

Water jet spray/foam/CO2/dry extinguisher

##### **Unsuitable extinguishing media**

High volume water jet

#### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Toxic gases

Danger of bursting (explosion) when heated

Possible build up of explosive/highly flammable vapour/air mixture.

#### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

##### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid inhalation, and contact with eyes or skin.

##### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

#### **6.2 Environmental precautions**

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

#### **6.3 Methods and material for containment and cleaning up**

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Avoid breathing vapours or spray.  
 Avoid contact with eyes or skin.  
 Keep away from sources of ignition - Do not smoke.  
 Take measures against electrostatic charging, if appropriate.  
 Do not use on hot surfaces.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Observe special regulations for aerosols!  
 Observe special storage conditions.  
 Do not store with flammable or self-igniting materials.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Store cool.

### 7.3 Specific end use(s)

No information available at present.  
 Observe the instructions for good working practice and the recommendations for risk assessment.  
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 600 mg/m<sup>3</sup>

(GB) Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
WEL-TWA: 600 mg/m <sup>3</sup>	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

(GB) Chemical Name	Pentane	
WEL-TWA: 1800 mg/m <sup>3</sup> (600 ppm) (WEL), 3000 mg/m <sup>3</sup> (1000 ppm) (EU)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Pentane 100/a (67 24 701) - Compur - KITA-113 SB(C) (549 368) - DFG (D) (Loesungsmittelgemische Meth. Nr. 1), DFG (E) (Solvent mixtures 1) - 1998, 2002 - NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996	
BMGV: ---	Other information: ---	

(GB) Chemical Name	Butane
--------------------	--------

GB

Page 6 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

WEL-TWA: 600 ppm (1450 mg/m <sup>3</sup> )	WEL-STEL: 750 ppm (1810 mg/m <sup>3</sup> )	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
	- OSHA PV2010 (n-Butane) - 1993	
BMGV: ---	Other information: ---	

<b>Chemical Name</b>	Propane	
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
	- OSHA PV2077 (Propane) - 1990	
BMGV: ---	Other information: ---	

<b>Chemical Name</b>	Isobutane	
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV: ---	Other information: ---	

<b>Chemical Name</b>	Oil mist, mineral	
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Oil Mist 1/a (67 33 031)	
BMGV: ---	Other information: ---	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m <sup>3</sup>	

Pentane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	0,55	mg/kg	
	Environment - sewage treatment plant		DNEL	3,6	mg/l	
	Environment - periodic release		PNEC	0,88	mg/l	
	Environment - freshwater		PNEC	0,23	mg/l	
	Environment - marine		PNEC	0,23	mg/l	
	Environment - sediment, freshwater		PNEC	1,2	mg/kg	
	Environment - sediment, marine		PNEC	1,2	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	214	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	643	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	214	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	432	mg/kg bw/day	

Page 7 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3000	mg/m <sup>3</sup>	
---------------------	--------------------	-----------------------------	------	------	-------------------	--

**Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,51	mg/l	
	Environment - sediment, freshwater		PNEC	0,0246	mg/kg	
	Environment - sediment, marine		PNEC	0,00246	mg/kg	
	Environment - soil		PNEC	0,0193	mg/kg	
	Environment - sewage treatment plant		PNEC	0,187	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,22	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,1	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,05	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,07	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,31	mg/m <sup>3</sup>	

**Methyl salicylate**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	20	µg/l	
	Environment - marine		PNEC	2	µg/l	
	Environment - sewage treatment plant		PNEC	140	mg/l	
	Environment - soil		PNEC	0,35	mg/kg dw	
	Environment - sediment, freshwater		PNEC	0,52	mg/kg dw	
	Environment - sediment, marine		PNEC	0,052	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	4	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	213	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	3	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Consumer	Human - oral	Short term, local effects	DNEL	5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	17,5	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	285	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	6	mg/kg bw/day	

**Propene**



Page 8 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1,38	mg/l	
	Environment - marine		PNEC	1,38	mg/l	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	860	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	860	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN ISO 374).  
 If applicable  
 Protective nitrile gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 >= 0,3  
 Permeation time (penetration time) in minutes:  
 < 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 If OES or MEL is exceeded.  
 Filter A P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.



Page 9 of 22  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.11.2023 / 0022  
Replacing version dated / version: 06.02.2023 / 0021  
Valid from: 22.11.2023  
PDF print date: 22.11.2023  
Motorbike Kettenspray

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Yellow
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	-60 °C (The flash-point of the mixture was not tested, but complies with the ingredient with the lowest value. )
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	2100 hPa (20°C)
Density and/or relative density:	-0,69 g/cm <sup>3</sup> (estimated )
Density and/or relative density:	0,78 g/ml (Active substance )
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

### 9.2 Other information

No information available at present.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources  
Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.11.2023 / 0022

Replacing version dated / version: 06.02.2023 / 0021

Valid from: 22.11.2023

PDF print date: 22.11.2023

Motorbike Kettenspray

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

<b>Motorbike Kettenspray</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800-3100	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Aspiration hazard:						Yes

Page 11 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Symptoms:						drowsiness, unconsciousness , heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Pentane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>25,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	No (inhalation and skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative
Aspiration hazard:						Yes
Symptoms:						drying of the skin., respiratory distress, coughing, fever, drowsiness, dizziness, nausea, headaches, unconsciousness , burning of the membranes of the nose and throat

GB

Page 12 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract).
---	--	--	--	--	--	-----------------------------------

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Mild irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 487 (In Vitro Mammalian Cell Micronucleus Test)	Negative
Reproductive toxicity:				Rat	OECD 443 (Extended One-Generation Reproductive Toxicity Study)	Possible risk of impaired fertility.
Specific target organ toxicity - single exposure (STOT-SE):						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):				Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Target organ(s): Thyroid, Target organ(s): liver

Methyl salicylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	890	mg/kg			
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 491 (Short-time Exposure ... Chemicals Causing Eye Dam., Chem. Not Requir. Eye Dam. or Irrit.)	Eye Dam. 1
Symptoms:						acidosis, respiratory distress, annoyance, blisters, heart/circulatory disorders, coughing, cramps, stomach pain, intoxication, mucous membrane irritation, pain in chest, sweats, dizziness, visual disturbances, nausea and vomiting.

Page 13 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No

Page 14 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

## 11.2. Information on other hazards

Motorbike Kettenspray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						No

## SECTION 12: Ecological information

Page 15 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Possibly more information on environmental effects, see Section 2.1 (classification).

Motorbike Kettenspray							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	30-100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:							Concentration in organisms possible.
12.3. Bioaccumulative potential:	BCF		242-253				



Page 16 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

12.4. Mobility in soil:							Adsorption in ground., Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			

Pentane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,26	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	2,7	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	10,7	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	72h	7,51	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	87	%			
12.2. Persistence and degradability:							Readily biodegradable, Photochemical decomposition in the atmosphere.
12.3. Bioaccumulative potential:	Log Pow		3,39				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	51	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC10	21d	1,69	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	Log Koc		3,8				calculated value
12.3. Bioaccumulative potential:	BCF	42d	1730		Cyprinus caprio		Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Endocrine disrupting properties:							No
Toxicity to bacteria:	EC20	3h	~100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Page 17 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Toxicity to annelids:	EC10	56d	259	mg/kg	Eisenia foetida	OECD 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei))	
-----------------------	------	-----	-----	-------	-----------------	--	--

Methyl salicylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	19,8	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	870	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	28	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	27	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,79	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:	DOC	28d	98,4	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,5				
12.4. Mobility in soil:	Log Koc		2,346				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	16h	380	mg/l	Pseudomonas putida		

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 18 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

## SECTION 14: Transport information

### General statements

#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:	UN 1950 AEROSOLS	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	environmentally hazardous	
Tunnel restriction code:	D	
Classification code:	5F	
LQ:	1 L	
Transport category:	2	

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.11.2023 / 0022



Replacing version dated / version: 06.02.2023 / 0021

Valid from: 22.11.2023

PDF print date: 22.11.2023

Motorbike Kettenspray

### Transport by sea (IMDG-code)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS (HYDROCARBONS, C6-C7, PENTANES)		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	environmentally hazardous	
Marine Pollutant:	Yes	
EmS:	F-D, S-U	

### Transport by air (IATA)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 Aerosols, flammable		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	

### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### 14.7. Maritime transport in bulk according to IMO instruments

Freight as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane

Comply with trade association/occupational health regulations.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Page 20 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Directive 2010/75/EU (VOC): 71,1 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 3  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H224 Extremely flammable liquid and vapour.  
 H361d Suspected of damaging the unborn child.  
 H361f Suspected of damaging fertility.  
 H225 Highly flammable liquid and vapour.  
 H317 May cause an allergic skin reaction.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

Skin Irrit. — Skin irritation  
 Asp. Tox. — Aspiration hazard  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Aerosol — Aerosols  
 Flam. Liq. — Flammable liquid  
 Repr. — Reproductive toxicity  
 Acute Tox. — Acute toxicity - oral  
 Eye Dam. — Serious eye damage  
 Skin Sens. — Skin sensitization

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
 Guidelines for the preparation of safety data sheets as amended (ECHA).

Page 21 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.11.2023 / 0022  
 Replacing version dated / version: 06.02.2023 / 0021  
 Valid from: 22.11.2023  
 PDF print date: 22.11.2023  
 Motorbike Kettenspray

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
 Safety data sheets for the constituent substances.  
 ECHA Homepage - Information about chemicals.  
 GESTIS Substance Database (Germany).  
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
 National Lists of Occupational Exposure Limits for each country as amended.  
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, EBLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Page 22 of 22  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.11.2023 / 0022  
Replacing version dated / version: 06.02.2023 / 0021  
Valid from: 22.11.2023  
PDF print date: 22.11.2023  
Motorbike Kettenspray

Log Kow, Log Pow      Logarithm of octanol-water partition coefficient  
LQ      Limited Quantities  
MARPOL      International Convention for the Prevention of Marine Pollution from Ships  
n.a.      not applicable  
n.av.      not available  
n.c.      not checked  
n.d.a.      no data available  
NIOSH      National Institute for Occupational Safety and Health (USA)  
NLP      No-longer-Polymer  
NOEC, NOEL      No Observed Effect Concentration/Level  
OECD      Organisation for Economic Co-operation and Development  
org.      organic  
OSHA      Occupational Safety and Health Administration (USA)  
PBT      persistent, bioaccumulative and toxic  
PE      Polyethylene  
PNEC      Predicted No Effect Concentration  
ppm      parts per million  
PVC      Polyvinylchloride  
REACH      Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No.      9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID      Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC      Substances of Very High Concern  
Tel.      Telephone  
TOC      Total organic carbon  
UN RTDG      United Nations Recommendations on the Transport of Dangerous Goods  
VOC      Volatile organic compounds  
vPvB      very persistent and very bioaccumulative  
wwt      wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.