

Page 1 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Zinkspray **Zinc Spray**

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Corrosion protection

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT RE	2	H373-May cause damage to organs through prolonged
		or repeated exposure.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements



Page 2 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H373-May cause damage to organs through prolonged or repeated exposure. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Acetone

Hydrocarbons, C9, aromatics

Xylene

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	200-662-2
CAS	67-64-1
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Eye Irrit. 2, H319
	STOT SE 3. H336

Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-022-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	215-535-7
CAS	1330-20-7
content %	10-20



(B)

Page 3 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	Acute Tox. 4, H312
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Acute Tox. 4, H332
	STOT SE 3, H335
	STOT RE 2, H373
	Aquatic Chronic 3, H412

Zinc powder - zinc dust (stabilized)	
Registration number (REACH)	
Index	030-001-01-9
EINECS, ELINCS, NLP, REACH-IT List-No.	231-175-3
CAS	7440-66-6
content %	5-15
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Hydrocarbons, C9, aromatics	
Registration number (REACH)	01-2119455851-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-668-5
CAS	64742-95-6
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H335
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.



(B)

Page 4 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032 Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.



Page 5 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 500 mg/m3

Chemical Name	Acetone		Content %:10-20
WEL-TWA: 500 ppm (1210 mg/m3	3) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m3) (WEL)	
Monitoring procedures:	-	Draeger - Acetone 100/b (CH 22 901)	
	-	Draeger - Acetone 40/a (5) (81 03 381)	
	-	Compur - KITA-102 SA (548 534)	
	-	Compur - KITA-102 SC (548 550)	
	-	Compur - KITA-102 SD (551 109)	
		INSHT MTA/MA-031/A96 (Determination of ketones (acetone	e, methyl ethyl ketone,
		methyl isobutyl ketone) in air - Charcoal tube method / Gas o	chromatography) - 1996 -
	-	EU project BC/CEN/ENTR/000/2002-16 card 67-1 (2004)	
		MDHS 72 (Volatile organic compounds in air - Laboratory m	ethod using pumped solid
	-	sorbent tubes, thermal desorption and gas chromatography)	- 1993
	-	NIOSH 1300 (KETONES I) - 1994	
	-	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREE	ENING)) - 1996
	-	NIOSH 2555 (KETONES I) - 2003	
		NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXT	RACTIVE FTIR
	-	SPECTROMETRY) - 2016	
	-	OSHA 69 (Acetone) - 1988	
BMGV:	·	Other information:	
(R) Chemical Name	Yylene		Content %:10-20

© Chemical Name Xylene		Content %:10-20
WEL-TWA: 220 mg/m3 (50 ppm) (WEL), 50 pp	om WEL-STEL: 100 ppm (441 mg/m3 (WEL), 100 ppm	
(221 mg/m3) (EU)	(442 mg/m3) (EU)	
Monitoring procedures:	- Draeger - Xylene 10/a (67 33 161)	
	- Compur - KITA-143 SA (550 325)	
	 Compur - KITA-143 SB (505 998) 	
	INSHT MTA/MA-030/A92 (Determination of aromatic hydroc	carbons (benzene, toluene,
	ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Cha	rcoal tube method / Gas
	- chromatography) - 1992 - EU project BC/CEN/ENTR/000/20)02-16 card 47-1 (2004)
	- NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003	, ,
	 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREIG) 	ENING)) - 1996
	- OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 19	999 ′′
BMGV: 650 mmol methyl hippuric acid/mol cre	eatinine in urine, post shift (Xylene, o-, m- Other information: Sk	
, p- or mixed isomers) (BMGV)	., , , , ,	` ,

© Chemical Name	Hydrocarbons, C9, aromatics	Content %:5-<10
WEL-TWA: 500 mg/m3 (Aromatics) WEL-STEL:	
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 	
	 Draeger - Hydrocarbons 2/a (81 03 581) 	
	- Compur - KITA-187 S (551 174)	



Page 6 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021 PDF print date: 23.07.2021

BMGV:			Other information:	
DIVIGV			Other information	
Chemical Name	Butane			Content %:
WEL-TWA: 600 ppm (1450 mg/m3	3)	WEL-STEL: 750 ppm (1810 m	ng/m3)	
Monitoring procedures:	-	Compur - KITA-221 SA (549 459)		
	-	OSHA PV2010 (n-Butane) - 1993		
BMGV:			Other information:	
® Chemical Name	Propane			Content %:
WEL-TWA: 1000 ppm (ACGIH)		WEL-STEL:		
Monitoring procedures:	-	Compur - KITA-125 SA (549 954)		
	-	OSHA PV2077 (Propane) - 1990		
BMGV:			Other information:	
Chemical Name	Barium sulphate			Content %:
WEL-TWA: 4 mg/m3 (respirable d	ust), 10 mg/m3	WEL-STEL:		
(total inhalable dust)	,			
Monitoring procedures:				
BMGV:			Other information:	
Chemical Name	Isobutane			Content %:
WEL-TWA: 1000 ppm (EX) (ACGI	H)	WEL-STEL:		
Monitoring procedures:	-	Compur - KITA-113 SB(C) (549 36	8)	
BMGV:			Other information:	

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assesment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assesment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/kg dw	
	Environment - sediment, marine		PNEC	3,04	mg/kg dw	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assesment factor 100
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m3	Overall assesment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m3	

Area of application Exposure route / Environmental Environmental	Xylene						
compartment	Area of application	· ·	Effect on health	Descriptor	Value	Unit	Note



Page 7 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021

PDF print date: 23.07.2021

	Environment - periodic release		PNEC	0,327	mg/l
	Environment - sewage treatment plant		PNEC	6,58	mg/l
	Environment - freshwater		PNEC	0,327	mg/l
	Environment - marine		PNEC	0,327	mg/l
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw
	Environment - sediment, marine		PNEC	12,46	mg/kg dw
	Environment - soil		PNEC	2,31	mg/kg dw
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment					
	Environment - freshwater		PNEC	20,6	μg/l	
	Environment - marine		PNEC	6,1	μg/l	
	Environment - sewage treatment plant		PNEC	52	μg/l	
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dw	
	Environment - sediment, marine		PNEC	56,5	mg/kg	
	Environment - soil		PNEC	35,6	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg	

Hydrocarbons, C9, aromatics									
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3				



(B)

Page 8 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/dav	
Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m3	

Barium sulphate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,115	mg/l	
	Environment - sediment, freshwater		PNEC	600,4	mg/kg dw	
	Environment - sewage treatment plant		PNEC	62,2	mg/l	
	Environment - soil		PNEC	207,7	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	13000	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).



Page 9 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Skin protection - Hand protection:

Protective gloves in butyl rubber (EN 374).

Minimum layer thickness in mm:

>= 0.7 mm

Permeation time (penetration time) in minutes:

>= 60

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Grev

Odour: Characteristic

Odour threshold: Not determined pH-value: n.a.

Melting point/freezing point: Not determined

Initial boiling point and boiling range: <0 °C Flash point: Not determined

Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined

Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined 0,92671 g/cm3 (20°C) Density:

Bulk density: n.a.

Solubility(ies): Not determined Water solubility: Not miscible Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: >200 °C (Ignition temperature)

Decomposition temperature: Not determined Viscosity: Not determined

Explosive properties: Possible build up of explosive/highly flammable vapour/air mixture. Oxidising properties:

Not determined

9.2 Other information



Page 10 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Possible build up of explosive/highly flammable vapour/air mixture.

10.4 Conditions to avoid

See also section 7.

Pressure increase will result in danger of bursting.

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Zinkspray	,	,				
Zinc Spray Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	•					n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						No indications of
sensitisation:						such an effect.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Acetone						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		



Page 11 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021

PDF print date: 23.07.2021

Skin corrosion/irritation:				Guinea pig		Repeated
						exposure may
						cause skin
						dryness or
						cracking., Not
						irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Eye Irrit. 2
-					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative
(Developmental toxicity):					Developmental Toxicity	
					Study)	
Symptoms:						unconsciousness
						, vomiting,
						headaches,
						gastrointestinal
						disturbances,
						fatigue, mucous
						membrane
						irritation,
						dizziness,
						nausea,
						drowsiness
Specific target organ toxicity -	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	
oral:					Toxicity Study in	
					Rodents)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat		Does not conform with EU classification.
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	27	mg/l/4h	Rat		Vapours, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Irritant
Serious eye damage/irritation:				Rabbit		Irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:					·	Yes



Page 12 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021

PDF print date: 23.07.2021

Symptoms:		breathing
, ,		difficulties,
		drying of the
		skin.,
		drowsiness,
		unconsciousness
		, burning of the
		membranes of
		the nose and
		throat, vomiting,
		skin afflictions,
		heart/circulatory
		disorders,
		coughing,
		headaches,
		drowsiness,
		dizziness,
		nausea
Specific target organ toxicity -		Irritation of the
single exposure (STOT-SE),		respiratory tract
inhalative:		1 2 7 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
iiiiaiaii o.		

Zinc powder - zinc dust (stabi	lized)					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>5410	mg/m3/4h	Rat		
Symptoms:						respiratory distress, chest pain (thorax pain), fever, joint pain, heart/circulatory disorders, coughing, metal fume fever, muscle pains, mucous membrane irritation, chills, nausea and vomiting.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4h	Rat	OECD 403 (Acute	Analogous
					Inhalation Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	> 6,193	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	



(B)

Page 13 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 $\,$ / 0031 Valid from: 22.04.2021

PDF print date: 23.07.2021

Respiratory or skin sensitisation:	Guinea pig OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Germ cell mutagenicity:	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:	OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Germ cell mutagenicity:	Salmonella OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:		Negative
Reproductive toxicity:	Rat OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):		STOT SE 3, H335, STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	OECD 452 (Chronic Toxicity Studies)	Negative
Aspiration hazard: Symptoms:		Yes
		respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousness, fever, ear noises, drying of

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	



Page 14 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021 PDF print date: 23.07.2021

Germ cell mutagenicity: Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test) OECD 473 (In Vitro	Negative Negative
					Mammalian Chromosome Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	_

Propane	Fundana inst	Value	I I mit	Overeniem	Toot moth od	Notes
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male,
						Analogous
						conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Reproductive toxicity	NOAEC	21,641	mg/l		OECD 422 (Combined	
(Developmental toxicity):					Repeated Dose Tox.	
•					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing
•						difficulties,
						unconsciousnes
						, frostbite,
						headaches,
						cramps, mucous
						membrane
						irritation.
						dizziness.
						nausea and
						vomiting.



B.

Page 15 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)

Barium sulphate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	IUCLID Chem. Data	
					Sheet (ESIS)	
Acute toxicity, by dermal route:	LD50	>2000		Rat		Analogous
						conclusion
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
, ,					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:					Sensitisation - Local	contact),
					Lymph Node Assay)	Analogous
					1	conclusion
Germ cell mutagenicity:						Negative

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	_
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Zinkspray							
Zinc Spray							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	•						n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							



Page 16 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021

PDF print date: 23.07.2021

12.3. Bioaccumulative				n.d.a.
potential:				
12.4. Mobility in soil:				n.d.a.
12.5. Results of PBT				n.d.a.
and vPvB assessment				
12.6. Other adverse				n.d.a.
effects:				

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other organisms:	EC5	72h	28	mg/l	Entosiphon sulcatum		
12.1. Toxicity to fish:	EC50	96h	8300	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	8300	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	6100- 12700	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	8800	mg/l	Daphnia pulex	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	8d	530	mg/l		DIN 38412 T.9	Test organism: M. aeruginosa
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriell a subcapitata		J
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	91	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.2. Persistence and degradability:		30d	81-92	%		Regulation (EC) 440/2008 C.4-E (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - CLOSED BOTTLE TEST)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,24			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	
12.3. Bioaccumulative potential:	BCF		0,19			,	Low
12.4. Mobility in soil:							No adsorption i soil.



Page 17 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021

PDF print date: 23.07.2021

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	Pseudomonas putida		
Other information:	BOD5		1760- 1900	mg/g			
Other information:	AOX		0	%			
Other information:	COD		2070	mg/g			

Xylene									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.2. Persistence and			>60	%		OECD 301 F	Readily		
degradability:						(Ready	biodegradable		
						Biodegradability -			
						Manometric			
						Respirometry Test)			
12.3. Bioaccumulative	Log Pow		3				A notable		
potential:							biological		
							accumulation		
							potential is not to		
							be expected (LogPow 1-3).		
12.3. Bioaccumulative	BCF		25,9						
potential:									
12.1. Toxicity to fish:	LC50	96h	2,6	mg/l	Oncorhynchus				
					mykiss				
12.1. Toxicity to daphnia:	EC50	48h	1	mg/l	Daphnia magna				
12.1. Toxicity to algae:	EC50	72h	2,2	mg/l					
12.1. Toxicity to algae:	NOEC/NOEL		0,44	mg/l					

Zinc powder - zinc dust (stabilized)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,238- 0.56	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	2,8	mg/l	Daphnia magna		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,2	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	3,2	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	54-56	%		OECD 301 B	
degradability:						(Ready	
						Biodegradability -	
						Co2 Evolution	
						Test)	



Page 18 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031 Valid from: 22.04.2021

PDF print date: 23.07.2021

12.2. Persistence and		28d	78	%	OECD 301 E Readily
degradability:					(Ready biodegradable
					Biodegradability -
					Modified OECD
					Screening Test)
12.2. Persistence and		28d	78	%	OECD 301 F
degradability:					(Ready
					Biodegradability -
					Manometric
					Respirometry Test)
12.3. Bioaccumulative	Log Pow		3,7 - 4,5		
potential:					
12.5. Results of PBT					No PBT
and vPvB assessment					substance, No
					vPvB substanc

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Barium sulphate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>3,5	mg/l	Brachydanio rerio	OECD 203 (Fish,	Analogous
						Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to fish:	NOEC/NOEL	33d	>1,26	mg/l	Brachydanio rerio	OECD 210 (Fish,	Analogous
						Early-Life Stage	conclusion
						Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,9	mg/l	Daphnia magna	OECD 211	Analogous
						(Daphnia magna	conclusion
						Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	14,5	mg/l	Daphnia magna	OECD 202	Analogous
						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	ErC50	72h	>1,15	mg/l	Pseudokirchneriell	OECD 201 (Alga,	Analogous
					a subcapitata	Growth Inhibition	conclusion
						Test)	



Œ

Page 19 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

12.1. Toxicity to algae:	NOEC/NOEL	72h	>1,15	mg/l	Pseudokirchneriell	OECD 201 (Alga,	Analogous
				_	a subcapitata	Growth Inhibition	conclusion
					·	Test)	
12.2. Persistence and							Not
degradability:							biodegradable,
							Inorganic
							products cannot
							be eliminated
							from water
							through
							biological
							purification
							methods.
12.5. Results of PBT							n.a.
and vPvB assessment							

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:					_		A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 04 metallic packaging

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name: UN 1950 AEROSOLS

14.3. Transport hazard class(es):





Page 20 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

14.4. Packing group:

Classification code:

5F
LQ:

1 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name: AEROSOLS (ZINC POWDER) 14.3. Transport hazard class(es):

14.4. Packing group:

EmS:

F-D, S-U

Marine Pollutant:

Yes

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):
2.1
14.4. Packing group:

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

2.1

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148. Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements







Page 21 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

69,22 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
STOT RE 2, H373	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

STOT RE — Specific target organ toxicity - repeated exposure

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation



Page 22 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation

Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

Acute Toxicity Estimate ATE

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAHA

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

ΕĊ **European Community** ECHA European Chemicals Agency EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

ΕN **European Norms**

EPA United States Environmental Protection Agency (United States of America)

et cetera etc.

ΕU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax number Fax. general gen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

International Agency for Research on Cancer IARC International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ **Limited Quantities**

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available not checked n.c. n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

organic org.



Page 23 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.04.2021 / 0032

Replacing version dated / version: 04.02.2021 / 0031

Valid from: 22.04.2021 PDF print date: 23.07.2021

Zinkspray Zinc Spray

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.