

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalytic-System Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

Page 2 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting.
 P405-Store locked up.
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
 Hydrocarbons, C10, aromatics, >1% naphthalene
 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	---
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	919-284-0
CAS	(64742-94-5)
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	601-052-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	202-049-5
CAS	91-20-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

Page 3 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0030
Replacing version dated / version: 29.04.2020 / 0029
Valid from: 01.11.2021
PDF print date: 01.11.2021
Catalytic-System Cleaner

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.
Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."
Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.
Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.
Protective hand cream recommended.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.
Danger of aspiration.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes
Irritation of the respiratory tract
Headaches
Dizziness
Effects/damages the central nervous system
Coordination disorders
Unconsciousness
Liver and kidney damage
Blood count modifications
Nausea
Vomiting
Danger of aspiration.
Oedema of the lungs
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Ingestion:
Activated carbon
Gastric lavage (stomach washing) only under endotracheal intubation.
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Extinction powder
Foam
Water jet spray

Unsuitable extinguishing media

Page 4 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0030
Replacing version dated / version: 29.04.2020 / 0029
Valid from: 01.11.2021
PDF print date: 01.11.2021
Catalytic-System Cleaner

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Ensure sufficient ventilation.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

GB

Page 5 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Solvent resistant floor
 Do not store with oxidizing agents.
 Store in a well ventilated place.
 Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:80- <100
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Hydrocarbons, C10, aromatics, >1% naphthalene	Content %:1-<2,5
WEL-TWA: 500 mg/m ³ (Aromatics)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: ---	

Chemical Name	Naphthalene	Content %:0,1- <0,25
WEL-TWA: 500 mg/m ³ (Aromatics) (WEL), 10 ppm (50 mg/m ³) (EU)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-153 U(C) (551 182) - NIOSH 5506 (POLYNUCLEAR AROMATIC HYDROCARBONS by HPLC) - 1998 - NIOSH 5515 (POLYNUCLEAR AROMATIC HYDROCARBONS by GC) - 1994 - OSHA 35 (Naphthalene) - 1982 	
BMGV: ---	Other information: ---	

Chemical Name	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:
WEL-TWA: 1200 mg/m ³ (>=C7 normal and branched chain alkanes)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: ---	

Naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	2,4	µg/l	
	Environment - marine		PNEC	0,24	µg/l	
	Environment - sewage treatment plant		PNEC	2,9	mg/l	

Page 6 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

	Environment - sediment, freshwater		PNEC	0,0672	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,0672	mg/kg dry weight	
	Environment - soil		PNEC	0,0533	mg/kg dry weight	
	Environment - sporadic (intermittent) release		PNEC	0,02	mg/l	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Solvent resistant protective gloves (EN ISO 374).
 If applicable
 Protective Viton® / fluoroelastomer gloves (EN ISO 374).
 Permeation time (penetration time) in minutes:
 >480
 Minimum layer thickness in mm:
 0,4
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Page 7 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

Respiratory protection:
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light yellow
Colour:	Clear
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	145 °C
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	>61 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<7 mm ² /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,765 g/ml (20°C)
Relative vapour density:	Vapours heavier than air.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising liquids:	No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Catalytic-System Cleaner						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the real Naphthalene content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m ³ /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizing, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion

Page 9 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, mucous membrane irritation

Hydrocarbons, C10, aromatics, >1% naphthalene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	~7093	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising

Naphthalene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>110	mg/l/4h	Rat		Vapours
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)
Symptoms:						lack of appetite, ataxia, breathing difficulties, unconsciousness, diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting, sweating, Reddening, eyes, reddened

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours

Page 10 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	in vivo	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

11.2. Information on other hazards

Catalytic-System Cleaner						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

Page 11 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

Other information:							Repeated exposure may cause skin dryness or cracking.
--------------------	--	--	--	--	--	--	---

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Catalytic-System Cleaner							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Product floats on the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymena pyriformis		

Page 12 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

Hydrocarbons, C10, aromatics, >1% naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EL50	48h	10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>1-<3	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l	Oncorhynchus mykiss		
12.4. Mobility in soil:	Koc		240-1300				
12.1. Toxicity to fish:	LC50	96h	1,99	mg/l	Pimephales promelas		Does not conform with EU classification.
12.1. Toxicity to daphnia:	EC50	48h	1,6-24,1	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	>60d	0,6	mg/l	Daphnia pulex		
12.1. Toxicity to algae:	ErC50	72h	0,4	mg/l	Skeletonema costatum		
12.2. Persistence and degradability:		28d	2	%			Not readily biodegradable
12.3. Bioaccumulative potential:	BCF	28d	40-300				Lowfish
Other information:	BOD5		0	%			
Other information:	COD		22	%			
Other information:	Log Pow		3,3				

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:							Insoluble
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		6-8				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

~ 96 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

Page 14 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0030
 Replacing version dated / version: 29.04.2020 / 0029
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Catalytic-System Cleaner

SECTION 16: Other information

Revised sections: 1-16
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Acute Tox. — Acute toxicity - oral
 Carc. — Carcinogenicity
 Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor

BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

Page 16 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0030
Replacing version dated / version: 29.04.2020 / 0029
Valid from: 01.11.2021
PDF print date: 01.11.2021
Catalytic-System Cleaner

SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.