

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

അ

# mtx Vergaserreiniger **Carburetor and Valve Cleaner**

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives Uses advised against: No information available at present.

## 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets

**1.4 Emergency telephone number** Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) Hazard class Hazard category 1

Asp. Tox. Aquatic Chronic

3

Hazard statement

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

## 2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 18

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner



Danger

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10, aromatics, >1% naphthalene Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

#### <sup>n.a.</sup> 3.2 Mixtures

01-2119457273-39-XXXX
918-481-9
80-<100
EUH066
Asp. Tox. 1, H304
01-2119456620-43-XXXX
926-141-6
1-<2,5
EUH066
Asp. Tox. 1, H304
01-2119463588-24-XXXX



#### Page 3 of 18

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

EINECS, ELINCS, NLP, REACH-IT List-No.	919-284-0
CAS	(64742-94-5)
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Carc. 2, H351
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	202-049-5
CAS	91-20-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Carc. 2, H351
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here. A classification for the mixture with Carc. 2, H351 is not required as the naphthalene content in the product is < 1%. There are no other ingredients with this classification.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Protective hand cream recommended.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Irritation of the eyes

Irritation of the eyes Irritation of the respiratory tract Headaches Dizziness



Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

Effects/damages the central nervous system Coordination disorders Unconsciousness Liver and kidney damage Blood count modifications Nausea Vomiting Danger of aspiration. Oedema of the lungs In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Ingestion: Activated carbon

ആ

Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

## SECTION 5: Firefighting measures

# 5.1 Extinguishing media

Suitable extinguishing media

CO2 Extinction powder Foam Water jet spray

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Hydrocarbons Toxic pyrolysis products. Explosive vapour/air or gas/air mixtures.

## 5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

## 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition. Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary. Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

## 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

## 6.2 Environmental precautions

If leakage occurs, dam up. Resolve leaks if this possible without risk.



Page 5 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

Prevent surface and ground-water infiltration, as well as ground penetration. Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

#### If accidental entry into drainage system occurs, inform responsible authorities. 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Ensure sufficient ventilation.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

ആ

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point. Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells. Solvent resistant floor Do not store with oxidizing agents. Store in a well ventilated place. Protect from direct sunlight and warming.

## 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycli	cs, <2% aromatics	
WEL-TWA: 800 mg/m3	WEL-STEL:		
Monitoring procedures:	<ul> <li>Draeger - Hydrocarbons 0,1%/c (81</li> </ul>	03 571)	
	<ul> <li>Draeger - Hydrocarbons 2/a (81 03)</li> </ul>	581)	
	- Compur - KITA-187 S (551 174)		
BMGV:		Other information: (O	EL acc. to RCP-method,
		paragraphs 84-87, EH4	40)
Chemical Name	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycli	cs <2% aromatics	



	g to Regulation (EC) No 1907	/2006, Annex II				
Revision date / version: 10 Replacing version dated / v	.03.2023 / 0034 version: 02.03.2023 / 0033					
/alid from: 10.03.2023						
PDF print date: 13.03.2023	3					
ntx Vergaserreiniger Carburetor and Valve Clea	ner					
	(>=C7 normal and branched	WEL-STEL:				
hain alkanes) Monitoring procedures:	- 1	Draeger - Hydrocarbons 0,1%/c (	<u>91 03 571)</u>			
		Draeger - Hydrocarbons 2/a (81 0				
		Compur - KITA-187 S (551 174)	,			
BMGV:			Other inform	nation:	-	
Chemical Name		0, aromatics, >1% naphthalene			1	
VEL-TWA: 500 mg/m3 (/ Monitoring procedures:	Aromatics) - [	WEL-STEL: Draeger - Hydrocarbons 0,1%/c (	81 03 571)			
	- [	Draeger - Hydrocarbons 2/a (81 0	)3 581)			
	- (	Compur - KITA-187 S (551 174)	Other inform			
BMGV:			Other inform	nation:	-	
Chemical Name	Naphthalene Aromatics) (WEL), 10 ppm	WEL-STEL:			1	
(50 mg/m3) (EU)	Aromatics) (w⊏L), To ppm	WEL-SIEL				
Monitoring procedures:		Compur - KITA-153 U(C) (551 18				
		NIOSH 5506 (POLYNUCLEAR A				
		NIOSH 5515 (POLYNUCLEAR A OSHA 35 (Napthalene) - 1982		JKUCAKB	JNS by GC) -	1994
BMGV:			Other inforr	mation:	-	
Hydrocarbons, C10, arom	natice 1% nanhthalene					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
••	Environmental		•			
Consumor	Compartment			75	ma/ka	
Consumer	Compartment Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer Consumer		effects Long term, systemic	DNEL DNEL	7,5 32		
Consumer	Human - dermal Human - inhalation	effects Long term, systemic effects	DNEL	32	bw/day mg/m3	
	Human - dermal	effects Long term, systemic			bw/day	
Consumer Consumer	Human - dermal Human - inhalation	effects Long term, systemic effects Long term, systemic effects Long term, systemic	DNEL	32	bw/day mg/m3 mg/kg bw/day mg/kg	
Consumer Consumer Workers / employees	Human - dermal Human - inhalation Human - oral Human - dermal	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects	DNEL DNEL DNEL	32 7,5 12,5	bw/day mg/m3 mg/kg bw/day mg/kg bw/day	
Consumer Consumer	Human - dermal Human - inhalation Human - oral	effects Long term, systemic effects Long term, systemic effects Long term, systemic	DNEL	32 7,5	bw/day mg/m3 mg/kg bw/day mg/kg	
Consumer Consumer Workers / employees	Human - dermal Human - inhalation Human - oral Human - dermal	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic	DNEL DNEL DNEL	32 7,5 12,5	bw/day mg/m3 mg/kg bw/day mg/kg bw/day	
Consumer Consumer Workers / employees Workers / employees	Human - dermal Human - inhalation Human - oral Human - dermal	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic	DNEL DNEL DNEL	32 7,5 12,5	bw/day mg/m3 mg/kg bw/day mg/kg bw/day	
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal Human - inhalation Human - oral Human - dermal	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic	DNEL DNEL DNEL	32 7,5 12,5	bw/day mg/m3 mg/kg bw/day mg/kg bw/day	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - inhalation         Exposure route / Environmental	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects	DNEL DNEL DNEL DNEL	32 7,5 12,5 151	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal Human - inhalation Human - oral Human - dermal Human - inhalation Exposure route / Environmental compartment	effects         Long term, systemic         effects         Effect on health	DNEL DNEL DNEL DNEL DNEL	32 7,5 12,5 151 Value	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - inhalation         Exposure route / Environmental	effects         Long term, systemic         effects         Effect on health	DNEL DNEL DNEL DNEL	32 7,5 12,5 151	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage	effects         Long term, systemic         effects         Effect on health	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	32 7,5 12,5 151 Value 2,4	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Effect on health er	DNEL DNEL DNEL DNEL DNEL DNEL PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 Unit ug/l ug/l mg/l	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant         Environment - sediment	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Effect on health er	DNEL DNEL DNEL DNEL DNEL DNEL DNEL PNEC PNEC PNEC	32 7,5 12,5 151 Value 2,4 0,24	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 Unit ug/l ug/l ug/l mg/l mg/kg dry	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Effect on health er	DNEL DNEL DNEL DNEL DNEL DNEL PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 Unit ug/l ug/l ug/l mg/l mg/kg dry weight mg/kg dry	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - dermal         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant         Environment - sediment         freshwater         Environment - sediment	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Effect on health er	DNEL DNEL DNEL DNEL DNEL DNEL DNEC PNEC PNEC PNEC PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9 0,0672 0,0672	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 <b>Unit</b> µg/l µg/l µg/l mg/kg dry weight mg/kg dry weight	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant         Environment - sediment         freshwater         Environment - sediment	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Effect on health er	DNEL DNEL DNEL DNEL DNEL DNEL DNEL PNEC PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9 0,0672	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 <b>Unit</b> ug/l ug/l ug/l mg/l mg/kg dry weight mg/kg dry weight mg/kg dry	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - dermal         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant         Environment - sediment         freshwater         Environment - sediment	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Effect on health er	DNEL DNEL DNEL DNEL DNEL DNEL DNEC PNEC PNEC PNEC PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9 0,0672 0,0672	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 <b>Unit</b> µg/l µg/l µg/l mg/kg dry weight mg/kg dry weight	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene Area of application	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant         Environment - sediment         freshwater         Environment - sediment         marine         Environment - soil         Environment - soil	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Effect on health Effect on health	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEC PNEC PNEC PNEC PNEC PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9 0,0672 0,0672 0,0672 0,0672	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 Unit Unit Unit ug/l ug/l ug/l ug/l mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene Area of application	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sediment         freshwater         Environment - sediment         freshwater         Environment - sediment         marine         Environment - soil	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Eor  Feffect on health  Cor  Long term, systemic Effect on health Long term, systemic Effect on health	DNEL DNEL DNEL DNEL DNEL DNEL DNEC PNEC PNEC PNEC PNEC PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9 0,0672 0,0672 0,0533	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 Unit Unit Unit ug/l ug/l ug/l ug/l mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry	Note
Consumer Consumer Workers / employees Workers / employees Naphthalene Area of application Workers / employees	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Human - inhalation         Exposure route /         Environmental         compartment         Environment - freshwate         Environment - sewage         treatment plant         Environment - sediment         freshwater         Environment - sediment         marine         Environment - soil         Environment - soil	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Long term, systemic effects  Effect on health  Effect on health Long term, systemic effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEC PNEC PNEC PNEC PNEC PNEC PNEC PNEC	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9 0,0672 0,0672 0,0672 0,0672	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 Unit Unit ug/l ug/l ug/l ug/l mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight	Note
Consumer Consumer Workers / employees	Human - dermal         Human - inhalation         Human - oral         Human - dermal         Human - dermal         Human - inhalation         Human - inhalation         Exposure route / Environmental compartment         Environment - freshwate         Environment - sevage treatment plant         Environment - sediment freshwater         Environment - sediment marine         Environment - soil         Environment - soil         Environment - sporadic (intermittent) release         Human - dermal	effects Long term, systemic effects Long term, systemic effects Long term, systemic effects Eor  Feffect on health  Cor  Long term, systemic Effect on health Long term, systemic Effect on health	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEC PNEC PNEC PNEC PNEC PNEC DNEL DNEL	32 7,5 12,5 151 <b>Value</b> 2,4 0,24 2,9 0,0672 0,0672 0,0533 0,02 3,57	bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 Unit Unit Unit ug/l ug/l ug/l ug/l mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry weight mg/kg dry	Note

B WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).



Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

ആ

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN ISO 374). If applicable Protective Viton® / fluoroelastomer gloves (EN ISO 374). Permeation time (penetration time) in minutes: >480 Minimum layer thickness in mm: 0,4 Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.



Page 8 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

ആ

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Colour: Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

## 9.2 Other information

Explosives:

Oxidising liquids:

Liquid Light yellow Clear Characteristic There is no information available on this parameter. 145 °C Flammable There is no information available on this parameter. There is no information available on this parameter. >61 °C There is no information available on this parameter. There is no information available on this parameter. Mixture is non-soluble (in water). <7 mm2/s (40°C) Insoluble Does not apply to mixtures. There is no information available on this parameter. 0,765 g/ml (20°C) Vapours heavier than air. Does not apply to liquids.

Product is not explosive. When using: development of explosive vapour/air mixture possible.

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Heating, open flame, ignition sources **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** No decomposition when used as directed.

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

mtx vergaserreiniger						
Carburetor and Valve Cleaner						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Acute toxicity, by initialation.						11.u.a.



Safety data sheet according to Revision date / version: 10.03.20	23 / 0034					
Replacing version dated / versior	n: 02.03.2023 /	0033				
Valid from: 10.03.2023						
PDF print date: 13.03.2023 mtx Vergaserreiniger						
Carburetor and Valve Cleaner						
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the
						real Naphthalene content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE): Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE): Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
· · ·					1	
Hydrocarbons, C10-C13, n-alka Toxicity / effect	nes, isoalkan Endpoint	es, cyclics, <2º Value	% aromatics	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous
					Inhalation Toxicity)	conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,
					Dermal Irritation/Corrosion)	Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,
ochous cyc damage/imiation.					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin					OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome Aberration Test)	conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
com con matagomoty.					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
<u> </u>				typhimurium	Reverse Mutation Test)	
Carcinogenicity:					OECD 453 (Combined Chronic	Negative,
					Toxicity/Carcinogenicity	Analogous conclusion
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative,
-					Developmental Toxicity	Analogous
					Study)	conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral	Negative, Analogous
iopealeu exposure (STOT-RE).					Toxicity Study in Rodents)	conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousnes
						, headaches,
						dizziness,
						mucous
						membrane irritation

- (GB)-



Page 10 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

œ.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	in vivo	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Aspiration hazard:					,	Yes
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

Hydrocarbons, C10, aromatics, >1% naphthalene							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral		
					Toxicity)		



Page 11 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

œ.

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose	
					Procedure)	
Acute toxicity, by oral route:	LD50	6318	mg/kg	Rat	OECD 401 (Acute Oral	
ioato toxiolity, by oral routo.	2200	0010	ing/ing	- Tur	Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
,,					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute	
<i></i>			U U		Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic	Negative,
					Toxicology - In Vitro	Analogous
					Sister Chromatid	conclusion
					Exchange assay in	
					Mammalian Cells)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Reproductive toxicity	NOAEL	>450	mg/kg	Rat	OECD 415 (One-	Negative,
(Developmental toxicity):					Generation	Analogous
					Reproduction Toxicity	conclusion
				_	Study)	
Reproductive toxicity (Effects				Rat	OECD 415 (One-	Negative,
on fertility):					Generation	Analogous
					Reproduction Toxicity	conclusion
					Study)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative,
					Developmental Toxicity	Analogous
Design design for 1.11					Study)	conclusion
Reproductive toxicity:					OECD 416 (Two-	Negative,
					generation	Analogous
					Reproduction Toxicity	conclusion
Coopilia target argen tavisit					Study)	
Specific target organ toxicity -						Vapours may
single exposure (STOT-SE):						cause
						drowsiness and
						dizziness.,
						STOT SE 3,
Openifie towned arms to daily						H336
Specific target organ toxicity -					OECD 452 (Chronic	Negative,
repeated exposure (STOT-RE):					Toxicity Studies)	Analogous
						conclusion Yes
Aspiration hazard:				1		V OO



Page 12 of 18 Safety data sheet according to Re Revision date / version: 10.03.20 Replacing version dated / version Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner	23 / 0034		nnex II			
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	750	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Symptoms:						drowsiness, headaches, drowsiness, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	495	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	1000	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Negative, Analogous conclusion
Naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>110	mg/l/4h	Rat		Vapours
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)
Symptoms:						lack of appetite, ataxia, breathing difficulties, unconsciousness , diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting.,

## **11.2. Information on other hazards**

- @B-

mtx Vergaserreiniger Carburetor and Valve Cleaner						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Other information:						Repeated	
						exposure may	
						cause skin	
						dryness or	
						cracking.	



Page 13 of 18

œ)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification). mty Va roiniac

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
							an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							According to the
							recipe, contains
							no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Water solubility:							Product floats of
							the water
							surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
-				_	mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus		
					mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	80	%	activated sludge	OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen		
					pyriformis		
Hydrocarbons, C11-C14,	n-alkanes iso	alkanes cv	clics <2% a	romatics			
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:	•						Insoluble



B Page 14 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus	QSAR	
		200	0,		mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	69	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		6-8				High
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Hydrocarbons, C10, aromatics, >1% naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,48	mg/l	Daphnia magna		Analogous conclusion
12.3. Bioaccumulative potential:	BCF		99-5780				High
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	58	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		2,8-6,5				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l	Oncorhynchus mykiss		
12.4. Mobility in soil:	Koc		240- 1300				
12.1. Toxicity to fish:	LC50	96h	1,99	mg/l	Pimephales promelas		Does not conform with EU classification.
12.1. Toxicity to daphnia:	EC50	48h	1,6-24,1	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	>60d	0,6	mg/l	Daphnia pulex		
12.1. Toxicity to algae:	ErC50	72h	0,4	mg/l	Skeletonema costatum		



Page 15 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

12.2. Persistence and		28d	2	%		Not readily
degradability:						biodegradable
12.3. Bioaccumulative	BCF	28d	40-300			Lowfish
potential:						
Other information:	BOD5		0	%		
Other information:	COD		22	%		
Other information:	Log Pow		3,3			

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

ആ

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

#### E.g. suitable incineration plant. For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## **SECTION 14: Transport information**

## **General statements**

#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable
Transport by sea (IMDG-code)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	Not applicable
Transport by air (IATA)	
14.1. UN number or ID number:	Not applicable
	Not applicable
14.2. UN proper shipping name:	
Not applicable	Not oppligable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable



Page 16 of 18

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

94,8 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

Employee instruction/training in handling hazardous materials is required.

**SECTION 16: Other information** 

1

Revised sections: These details refer to the product as it is delivered.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic Carc. — Carcinogenicity STOT SE — Specific target organ toxicity - single exposure - narcotic effects Acute Tox. — Acute toxicity - oral Aquatic Acute — Hazardous to the aquatic environment - acute

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances.



Page 17 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

ആ

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon drv weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  $ErCx, E\mu Cx, ErLx (x = 10, 50)$ et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow International Agency for Research on Cancer IARC International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient



ആ Page 18 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.03.2023 / 0034 Replacing version dated / version: 02.03.2023 / 0033 Valid from: 10.03.2023 PDF print date: 13.03.2023 mtx Vergaserreiniger Carburetor and Valve Cleaner LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NI P No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.