

Page 1 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

അ

Motorbike Kettenspray weiss

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

(B) LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Landspitali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland) **Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

	of the substance or mix ording to Regulation (E	
Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 23

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss



H315-Causes skin irritation. H317-May cause an allergic skin reaction. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P273-Avoid release to the environment. P280-Wear protective gloves.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Methyl salicylate

Molybdenum trioxide, reaction products with bis[0,0-bis(2-ethylhexyl)] hydrogene dithiophosphate

Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %). Dangerous vapours heavier than air.

SECTION 3: Composition/information on ingredients

Aerosol 3.1 Substances

n.a. 3 2 Mixtures

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	
content %	25-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411
Mathed as Baudata	

Methyl Sancylate	
Registration number (REACH)	01-2119515671-44-XXXX
Index	607-749-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	204-317-7



Page 3 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

œ

CAS	119-36-8
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Skin Sens. 1B, H317
	Repr. 2. H361d
	STOT SE 3, H335
	Aquatic Chronic 3, H412
Specific Concentration Limits and ATE	ATE (oral): 890 mg/kg
•	
Molybdenum trioxide, reaction products with bis[0,0-bis(2-ethylhexyl)]	
hydrogene dithiophosphate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	947-946-9
CAS	
content %	0,5-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315
	Skin Sens. 1B, H317
	Aquatic Chronic 4, H413
Titanium dioxide (in powder form containing 1 % or more of particles	
with aerodynamic diameter <= 10 µm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	0.1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	
Registration number (REACH)	01-2119491299-23-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	270-128-1
CAS	68411-46-1
content %	0.1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361f
	Aquatic Chronic 3, H412
Benzene, mono-C10-14-alkyl derivs., fractionation bottoms,	
intermediate cut, sulfonated, sodium salts	
Registration number (REACH)	
	285-597-8
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	85117-47-1

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

<0,25

Skin Sens. 1B, H317

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

content %

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!



Page 4 of 23

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

Inhalation

Remove person from danger area. Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. reddening of the skin

Dermatitis (skin inflammation) Allergic reaction headaches dizziness Coordination disorders mental confusion Nausea vomiting Danger of aspiration. oedema of the lungs Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Toxic gases Danger of bursting (explosion) when heated Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



Page 5 of 23

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition. Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Without adequate ventilation, formation of explosive mixtures may be possible. Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Do not store with flammable or self-igniting materials.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place. Store cool.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 600 mg/m3



-08						
Page 6 of 23						
Safety data sheet according to Revision date / version: 18.04. Replacing version dated / vers Valid from: 18.04.2024 PDF print date: 19.04.2024	.2024 / 0028	06, Annex II				
Motorbike Kettenspray weiss						
Chemical Name	Hydrocarbons C6-C7	, n-alkanes, isoalkanes, cyclid	s <5% n-hexa	ne		
WEL-TWA: 600 mg/m3	V	VEL-STEL:				
Monitoring procedures:	- Con	npur - KITA-187 S (551 174)				
BMGV:			Other infor paragraphs	•	DEL acc. to R	CP-method,
				•	/	
GB Chemical Name	Molybdenum trioxide, dithiophosphate	reaction products with bis[O,0	O-bis(2-ethylhe	exyl)] hydro	gene	
WEL-TWA: 10 mg/m3 (as M		VEL-STEL: 20 mg/m3 (as N	lo) (Molybdenu	ım		
compounds, insoluble)		ompounds, insoluble)	, , , ,			
Monitoring procedures: BMGV:			Other infor	mation:		
	-				-	
Chemical Name	aerodynamic diameter	bwder form containing 1 % or $c = 10 \text{ µm}$	more of partic	les with		
WEL-TWA: 10 mg/m3 (total		VEL-STEL:				
(respirable dust)						
Monitoring procedures: BMGV:			Other infor	mation:		
			Other Infor			
Chemical Name WEL-TWA: 600 ppm (1450 r	Butane	VEL-STEL: 750 ppm (1810	ma/m3)			
Monitoring procedures:		npur - KITA-221 SA (549 459)				
	- OSł	A PV2010 (n-Butane) - 1993				
BMGV:			Other infor	mation:	-	
Chemical Name (A 0 0	Propane					
WEL-TWA: 1000 ppm (ACG Monitoring procedures:		VEL-STEL: npur - KITA-125 SA (549 954))			
		A PV2077 (Propane) - 1990	/			
BMGV:			Other infor	mation:	-	
Chemical Name	Isobutane					
WEL-TWA: 1000 ppm (EX) (Monitoring procedures:		VEL-STEL: npur - KITA-113 SB(C) (549 3	(68)			
BMGV:	- 001	ipui - KITA-115 5b(C) (549 5	Other infor	mation:	-	
Hydrocarbons, C6-C7, n-alka						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic	DNEL	699	mg/kg	
0	Liver en link eletter	effects	DNE	000	bw/day	
Consumer Consumer	Human - inhalation	Long term, systemic effects Long term, systemic	DNEL	608 699	mg/m3	
	Human - oral	effects			mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	
Molybdenum trioxide, reacti						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental compartment					
Consumer	Human - oral	Long term, systemic	DNEL	0,5	mg/kg	
	<u></u>	effects	DUE		bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,5	mg/kg bw/day	
L	1	0	1	1	, auy	



Page 7 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

œ.

Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,87	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,4	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,93	mg/m3	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental		••••			
	compartment					
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - water, sporadic (intermittent)		PNEC	0,51	mg/l	
	release					
	Environment - sediment, freshwater		PNEC	0,0246	mg/kg	
	Environment - sediment, marine		PNEC	0,00246	mg/kg	
	Environment - soil		PNEC	0,0193	mg/kg	
	Environment - sewage treatment plant		PNEC	0,187	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,22	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,1	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,05	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,07	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,31	mg/m3	

Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts								
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note		
	Environment - freshwater		PNEC	1	mg/l			



Page 8 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

ആ

	Environment - marine		PNEC	1	mg/m3
	Environment - sediment, freshwater		PNEC	7235000 00	mg/kg dw
	Environment - sediment, marine		PNEC	7235000 00	mg/kg dw
	Environment - soil		PNEC	8687000 00	mg/kg dw
	Environment - sewage treatment plant		PNEC	100	mg/l
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l
	Environment - oral (animal feed)		PNEC	16,667	mg/kg feed
Consumer	Human - oral	Long term, systemic effects	DNEL	0,833	mg/kg bw/d
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,667	mg/kg bw/d
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,33	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,33	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,66	mg/m3

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value

in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:



Page 9 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: >= 0,4 Permeation time (penetration time) in minutes: <= 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

	• • • • • • • • • • • •
Physical state:	Aerosol. Active substance: liquid.
Colour:	White
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<=20,5 mm2/s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,83 g/ml (Active substance)
Density and/or relative density:	$\sim 0.71 \text{ g/cm}3 \text{ (calculated)}$
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.
9.2 Other information	
No information available at present.	



Page 10 of 23

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral		
					Toxicity)		
Acute toxicity, by dermal route:	LD50	>2800-3100	mg/kg	Rat	OECD 402 (Acute		
					Dermal Toxicity)		
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute	Vapours	
					Inhalation Toxicity)		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Skin Irrit. 2	
					Dermal		
					Irritation/Corrosion)		
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Mild irritant	
					Irritation/Corrosion)	(Analogous	
						conclusion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)	
sensitisation:					Sensitisation)		
Germ cell mutagenicity:					OECD 471 (Bacterial	Analogous	
					Reverse Mutation Test)	conclusion,	
						Negative	
Carcinogenicity:						Negative	



B Page 11 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

Reproductive toxicity:	OECD 414 (Prenatal	Analogous
.,,	Developmental Toxicity	
	Study)	Negative
Specific target organ toxicity -		May cause
single exposure (STOT-SE):		drowsiness or
		dizziness.,
		STOT SE 3,
		H336
Aspiration hazard:		Yes
Symptoms:		drowsiness,
		unconsciousness
		,
		heart/circulatory
		disorders,
		headaches,
		cramps,
		drowsiness,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.

Molybdenum trioxide, reaction Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	6810	ml/kg	Rat		
Acute toxicity, by dermal route:	LD50	10000	ml/kg	Rabbit		
Skin corrosion/irritation:				Human being	OECD 439 (In Vitro Skin Irritation - Reconstructed Human Epidermis Test Method)	Skin Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Human being	OECD 487 (In Vitro Mammalian Cell Micronucleus Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 490 (In vitro Thymidine Kinase Mutation Test)	Negative

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral	
					Toxicity - Up-and-Down	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Mechanical
						irritation possible
Respiratory or skin				Mouse	OECD 429 (Skin	Not sensitizising
sensitisation:					Sensitisation - Local	_
					Lymph Node Assay)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	



Page 12 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

œ.

Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte	Negative
					Micronucleus Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	(Ames-Test)	Negative
				typhimurium		
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Reproductive toxicity				Rat	OECD 414 (Prenatal	No indications of
(Developmental toxicity):					Developmental Toxicity	such an effect.
					Study)	
Specific target organ toxicity -						Not irritant
single exposure (STOT-SE):						(respiratory tract).
Specific target organ toxicity -	NOAEL	3500	mg/kg/d	Rat		(90d)
repeated exposure (STOT-RE),						
oral:						
Specific target organ toxicity -	NOAEC	10	mg/m3	Rat		(90d)
repeated exposure (STOT-RE),						
inhalat.:						
Symptoms:						mucous
						membrane
						irritation,
						coughing,
						respiratory
						distress, drying
						of the skin.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Mild irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 487 (In Vitro	Negative
					Mammalian Cell	
					Micronucleus Test)	
Reproductive toxicity:				Rat	OECD 443 (Extended	Possible risk of
					One-Generation	impaired fertility.
					Reproductive Toxicity	
					Study)	
Specific target organ toxicity -						Negative
single exposure (STOT-SE):						
Specific target organ toxicity -				Rat	OECD 422 (Combined	Target organ(s):
repeated exposure (STOT-RE):					Repeated Dose Tox.	Thyroid, Target
					Study with the	organ(s): liver
					Reproduction/Developm.	
					Tox. Screening Test)	
Benzene, mono-C10-14-alkyl de	arive fraction	nation bottom	s intermediate	cut sulfonated	sodium salts	
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 13 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

œ.

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit		Not irritantEPA
						OPPTS 870.2500
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Yes (skin
sensitisation:					Sensitisation)	contact)

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Aspiration hazard:						No
Specific target organ toxicity -	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),					Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Symptoms:						ataxia, breathing
						difficulties,
						drowsiness,
						unconsciousnes
						, frostbite,
						disturbed heart
						rhythm,
						headaches,
						cramps,
						intoxication,
						dizziness,
						nausea and
						vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 14 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

œ)

Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness , frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Aspiration hazard:						No
Symptoms:						unconsciousness , frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

11.2. Information on other hazards

Motorbike Kettenspray weiss Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
,	Linupoint	Value	Unit	Organishi	restinethou	
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information



Page 15 of 23	Page	15 of	23
---------------	------	-------	----

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

Possibly more information on environmental effects, see Section 2.1 (classification).

Motorbike Kettenspray v	veiss						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-elimination
							degree(complexi
							ng organic
							substance)>=
							80%/28d: No
Other information:	AOX			%			Does not contain
							any organically
							bound halogens
							which can
							contribute to the
							AOX value in
							waste water.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	30-100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable



Page 16 of 23 Safety data sheet accordir Revision date / version: 18 Replacing version dated / Valid from: 18.04.2024	3.04.2024 / 0028		07/2006, Anr	nex II			
PDF print date: 19.04.202 Motorbike Kettenspray we							
	133	1		1		1	
12.3. Bioaccumulative potential:							Concentration ir organisms possible.
12.3. Bioaccumulative potential:	BCF		242-253				
12.4. Mobility in soil:							Adsorption in ground., Produc is slightly volatile
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			
Methyl salicylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,79	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:		28d	98,4	%		/	
Molybdenum trioxide, re	action products	with bis[C),O-bis(2-eth	vlhexyl)] h	vdrogene dithiophospl	nate	
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	11	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 μ m)										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)				
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)				
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriell a subcapitata	U.S. EPA-600/9- 78-018				



Page 17 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

œ.

12.2. Persistence and						Not relevant for
degradability:						inorganic
						substances.
12.3. Bioaccumulative	BCF	42d	9,6			Not to be
potential:						expected
12.3. Bioaccumulative	BCF	14d	19-352			Oncorhynchus
potential:						mykiss
12.4. Mobility in soil:						Negative
12.5. Results of PBT						No PBT
and vPvB assessment						substance, No
						vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli	
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas	
-				_	fluorescens	
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida	
Water solubility:						Insoluble20°C

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	51	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC10	21d	1,69	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	Log Koc		3,8				calculated value
12.3. Bioaccumulative potential:	BCF	42d	1730		Cyprinus caprio		Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Endocrine disrupting properties:							No
Toxicity to bacteria:	EC20	3h	~100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:	EC10	56d	259	mg/kg	Eisenia foetida	OECD 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei))	

Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish,					
				_	-	Acute Toxicity					
						Test)					
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Pimephales	OECD 203 (Fish,					
-					promelas	Acute Toxicity					
						Test)					



Image 18 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	8	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not biodegradable
12.3. Bioaccumulative potential:	Log Pow		6,75				A notable biological accumulation potential has to be expected (LogPow > 3).

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected
12.4. Mobility in soil:							(LogPow 1-3). Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and							Readily
degradability:							biodegradable
12.3. Bioaccumulative							A notable
potential:							biological
-							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

SECTION 13: Disposal considerations



Æ

Page 19 of 23

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations. Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)	
14.1. UN number or ID number:	1950
14.2. UN proper shipping name:	
UN 1950 AEROSOLS	
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
14.5. Environmental hazards:	environmentally hazardous
Tunnel restriction code:	D
Classification code:	5F
LQ:	1 L
Transport category:	2
Transport by sea (IMDG-code)	
14.1. UN number or ID number:	1950
14.2. UN proper shipping name:	
UN 1950 AEROSOLS	
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
14.5. Environmental hazards:	environmentally hazardous
Marine Pollutant:	Yes
EmS:	F-D, S-U
Transport by air (IATA)	
14.1. UN number or ID number:	1950
14.2. UN proper shipping name:	1950
14.2. UN proper shipping name: UN 1950 Aerosols, flammable	
14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es):	1950 2.1
14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group:	2.1
 14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards: 	
14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group:	2.1
 14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards: 	2.1
 14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards: 14.6. Special precautions for user 	2.1
 14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards: 14.6. Special precautions for user Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage. 	2.1 - environmentally hazardous
 14.2. UN proper shipping name: UN 1950 Aerosols, flammable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards: 14.6. Special precautions for user Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. 	2.1 - environmentally hazardous

Freighted as packaged goods rather than in bulk, therefore not applicate Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions.

SECTION 15: Regulatory information



Page 20 of 23

അ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Comply with trade association/occupational health regulations.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 71 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

2, 3, 4, 8, 11, 12, 14, 15, 16

Revised sections:

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.



Page 21 of 23

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H361d Suspected of damaging the unborn child. H361f Suspected of damaging fertility.

H225 Highly flammable liquid and vapour.

H351 Suspected of causing cancer by inhalation.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Skin Irrit. — Skin irritation Skin Sens. — Skin sensitization Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aquatic Chronic — Hazardous to the aquatic environment - chronic Aerosol — Aerosols Flam. Liq. — Flammable liquid Acute Tox. — Acute toxicity - oral Eye Irrit. — Eye irritation Repr. — Reproductive toxicity STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation Carc. — Carcinogenicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)



-@
Page 22 of 23
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.04.2024 / 0028
Replacing version dated / version: 04.03.2024 / 0027
Valid from: 18.04.2024
PDF print date: 19.04.2024
Motorbike Kettenspray weiss
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances
and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level DOC Dissolved organic carbon
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx ($x = 10, 50$) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms EPA United States Environmental Protection Agency (United States of America)
ErX = Office States Environmental Protection Agency (office States of America) ErCx, EµCx, EµCx, trLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw mg/kg body weight
mg/kg bw/d, mg/kg bw/day_mg/kg body weight/day
mg/kg dw mg/kg dry weight
mg/kg wwt mg/kg wet weight n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,
Evaluation, Authorisation and Restriction of Chemicals)



Page 23 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.04.2024 / 0028 Replacing version dated / version: 04.03.2024 / 0027 Valid from: 18.04.2024 PDF print date: 19.04.2024 Motorbike Kettenspray weiss

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

GB

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.