

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

അ

Cockpitpflege vanille

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Car care Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC35 - Washing and cleaning products Process category [PROC]: PROC 7 - Industrial spraying PROC10 - Roller application or brushing PROC11 - Non industrial spraying PROC19 - Manual activities involving hand contact Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAerosol1H222-Extremely flammable aerosol.



Page 2 of 18

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

1

1

Asp. Tox. Aerosol H304-May be fatal if swallowed and enters airways. H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a. 3.2 Mixtures

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
Registration number (REACH)	01-2119472146-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-167-1
CAS	
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	Aquatic Chronic 4, H413

registration.
01-2119457610-43-XXXX
603-002-00-5
200-578-6
64-17-5
1-10



Page 3 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors

Flam. Liq. 2, H225 Eye Irrit. 2, H319

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

അ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

Ingestion

Call doctor immediately - have Data Sheet available.

Do not induce vomiting. Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray CO2 Extinction powder Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. Take explosion-prevention measures if applicable.

6.2 Environmental precautions

അ

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke. Do not use on hot surfaces. Take precautions against electrostatic charges. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Chemical Name Hydrocarbons, C11-C12, isoalkanes, <2% aromatics							
WEL-TWA: 1200 mg/m3 (>=C7 nc	rmal and branched	WEL-STEL:						
chain alkanes)								
Monitoring procedures:	- [Draeger - Hydrocarbons 0,1%/c (81	03 571)					
	- [Draeger - Hydrocarbons 2/a (81 03	581)					
	- (Compur - KITA-187 S (551 174)						
BMGV:			Other information:					
Chemical Name	Ethanol				Content %:1-10			
WEL-TWA: 1000 ppm (1920 mg/m	13)	WEL-STEL:						



Page 5 of 18 Safety data sheet according Revision date / version: 22. Replacing version dated / v Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille		, Annex II				
Monitoring procedures:	- Comp DFG (- 2002 - DFG M - BC/CE DFG M	er - Alcohol 25/a Ethanol ur - KITA-104 SA (549 21 D) (Loesungsmittelgemis - EU project BC/CEN/ENT Meth. Nr. 2 (D) (Loesungs EN/ENTR/000/2002-16 ca Meth. Nr. 3 (D) (Loesungs EN/ENTR/000/2002-16 ca	0) che), Methode N R/000/2002-16 mittelgemische) rd 63-2 (2004) mittelgemische) rd 63-2 (2004)	card 63-2 (; - 2013 - EL - 2013 - EL	2004) J project	ıres) - 2013
BMGV:			Other infor	mation:	-	
Chemical Name	Propane					Content %:
WEL-TWA: 1000 ppm (A0 Monitoring procedures:	- Comp	EL-STEL: ur - KITA-125 SA (549 95				
BMGV:	- OSHA	NPV2077 (Propane) - 199	Other infor	mation:	_	
Chemical Name	Butane					Content %:
WEL-TWA: 600 ppm (145		EL-STEL: 750 ppm (181	0 mg/m3)			Jontent %
Monitoring procedures:	- Comp	ur - KITA-221 SA (549 45 VPV2010 (n-Butane) - 199	9)			
BMGV:			Other infor	mation:	-	
B Chemical Name	Isobutane				(Content %:
WEL-TWA: 1000 ppm (E)		EL-STEL: ur - KITA-113 SB(C) (549	269)			
Monitoring procedures: BMGV:	- Comp	ur - KITA-113 SB(C) (549	Other infor	mation:	_	
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine Environment - water,		PNEC PNEC	0,79 2,75	mg/l mg/l	
	sporadic (intermittent) release			2,10	ing,i	
	Environment - sewage treatment plant		PNEC	580	mg/l	
	Environment - sediment, freshwater		PNEC	3,6	mg/kg	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3	
NA/ 1 / ·	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d	
Workers / employees			D1::			
Workers / employees Workers / employees Workers / employees	Human - inhalation Human - inhalation	Long term, systemic effects Short term, local	DNEL DNEL	950 1900	mg/m3 mg/m3	

🐵 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW =



Page 6 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

"Arbeitsplatzgrenzwert" (workplace limit value, Germany).

ആ

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Protective hand cream recommended. Protective PVC gloves (EN 374). Or: PE If applicable Protective nitrile gloves (EN 374). Minimum layer thickness in mm: >= 0,4 Permeation time (penetration time) in minutes: >= 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Gas mask filter AX (EN 14387), code colour brown. Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.



Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

ആ

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	1,5 Vol-%
Upper explosive limit:	15 Vol-%
Vapour pressure:	2,1 hPa (20°C)
Vapour density (air = 1):	Not determined
Density:	0,625 g/ml (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	365 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	When using: development of explosive vapour/air mixture possible.
	Product is not explosive.
Oxidising properties:	Not determined
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity The product has not been tested. 10.2 Chemical stability Stable with proper storage and handling. 10.3 Possibility of hazardous reactions Hazardous reactions will not occur during storage and handling under normal conditions. 10.4 Conditions to avoid Pressure increase will result in danger of bursting. Heating, open flame, ignition sources Electrostatic charge 10.5 Incompatible materials None known 10.6 Hazardous decomposition products

No decomposition when used as directed.



Page 8 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

SECTION 11: Toxicological information

11.1 Information on toxicological effects

œ)

Possibly more information on hea	alth effects, see	e Section 2.1 (classification).					
Cockpitpflege vanille								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:						n.d.a.		
Acute toxicity, by dermal route:						n.d.a.		
Acute toxicity, by inhalation:						n.d.a.		
Skin corrosion/irritation:						n.d.a.		
Serious eye damage/irritation:						n.d.a.		
Respiratory or skin						n.d.a.		
sensitisation:								
Germ cell mutagenicity:						n.d.a.		
Carcinogenicity:						n.d.a.		
Reproductive toxicity:						n.d.a.		
Specific target organ toxicity -						n.d.a.		
single exposure (STOT-SE):								
Specific target organ toxicity -						n.d.a.		
repeated exposure (STOT-RE):								
Aspiration hazard:						n.d.a.		
Symptoms:						n.d.a.		

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	> 3160	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute	Vapours,
			-		Inhalation Toxicity)	Analogous
						conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
, ,					Irritation/Corrosion)	Analogous
					,	conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative,
0 2					Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative,
5 ,					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Germ cell mutagenicity:					OECD 478 (Genetic	Negative,
5 ,					Toxicology - Rodent	Analogous
					dominant Lethal Test)	conclusion



Page 9 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

œ.

				OECD 479 (Genetic	Negative,
					Analogous
					conclusion
				OECD 451	Negative,
					Analogous
					conclusion
				OECD 453 (Combined	Negative,
					Analogous
					conclusion
					Negative,
					Analogous
					conclusion
NOAEC	> 5,2	mg/l	Rat	OECD 414 (Prenatal	vapour
 				Study)	Newsti
					Negative,
					Analogous conclusion
<u> </u>					Negative,
					Analogous
				ental Toxicity Screening	conclusion
				Test)	
				OECD 422 (Combined	Negative,
					Analogous
					conclusion
				Reproduction/Developm.	
NOAEI	750	ma/ka	Rat	OFCD 415 (Ope-	
NOALL	750	iiig/kg	Rat		
				Study)	
NOAEL	> 1500	mg/kg	Rat		
					Negative,
					Analogous
					conclusion
†				OECD 453 (Combined	Negative,
				Chronic	Analogous
				Toxicity/Carcinogenicity	conclusion
	_				
					Negative,
					Analogous conclusion
+					Negative,
					Analogous
				Study with the	conclusion
				Reproduction/Developm.	
				Tox. Screening Test)	
					Negative,
					Analogous
					conclusion
+				Kodenis)	Asp. Tox. 1
I					
					drowsiness,
	NOAEL	NOAEL 750	NOAEL 750 mg/kg	NOAEL 750 mg/kg Rat	NOAEL 750 mg/kg Rat OECD 415 (One-Generation Toxicity Studies) NOAEL > 5,2 mg/l Rat OECD 414 (Prenatal Developmental Toxicity Studies) NOAEL > 5,2 mg/l Rat OECD 414 (Prenatal Developmental Toxicity Studies) NOAEL > 5,2 mg/l Rat OECD 414 (Prenatal Developmental Toxicity Studies) NOAEC > 5,2 mg/l Rat OECD 414 (Prenatal Developmental Toxicity Study) NOAEL > 5,2 mg/l Rat OECD 414 (Prenatal Developmental Toxicity Study) NOAEL > 5,2 mg/l Rat OECD 414 (Prenatal Developmental Toxicity Study) OECD 414 (Prenatal Developmental Toxicity Study) OECD 414 (Prenatal Developmental Toxicity Study) OECD 414 (Prenatal Developmental Toxicity Study) OECD 414 (Prenatal Developmental Toxicity Study) OECD 415 (One-Generation Reproduction/Developm. Tox. Screening Test) OECD 415 (One-Generation Reproduction Toxicity Study) NOAEL > 1500 mg/kg Rat OECD 415 (One-Generation Reproduction Toxicity Study) NOAEL > 1500 mg/kg Rat OECD 415 (One-Generation Reproduction Toxicity Study) OECD 415 (One-Generation Reproduction Toxicity Study) OECD 413 (



intoxication, drowsiness, mucous membrane irritation, dizziness, nausea

_	- (GB)					
	Page 10 of 18 Safety data sheet according to Re Revision date / version: 22.04.202 Replacing version dated / version Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille	21 / 0008		nnex II		
	Specific target organ toxicity - single exposure (STOT-SE), oral:	NOAEL	> 5000	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
	Specific target organ toxicity - single exposure (STOT-SE), oral:	NOAEL	> 1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)
	Specific target organ toxicity -	NOAEC	> 10,4	mg/l	Rat	OECD 413 (Subchronic

					Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	> 10,4	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Vapours
iiiidat					Day Sludy)	
Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	124,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Aspiration hazard:				Human being		No indications o such an effect.
Symptoms:						respiratory distress, drowsiness, unconsciousnes , drop in blood pressure, vomiting, coughing, headaches, intovication



B Page 11 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

	1	1 1	1	
Other information:				Excessive
				alcohol
				consumption
				during
				pregnancy
				induces the
				foetus alcohol
				syndrome
				(reduced weight
				at birth, physical
				and mental
				disorders).,
				There is no sign
				that this
				syndrome is also
				caused by
				dermal or
				inhalative
				absorption.,
				Experiences on
				persons.

Propane									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat					
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion			
Skin corrosion/irritation:						Not irritant			
Serious eye damage/irritation:						Not irritant			
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative			
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative			
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)				
Aspiration hazard:						No			
Symptoms:	NOAFI	7.044		Dat	OFOD 400 (Combined	breathing difficulties, unconsciousnes , frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.			
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)				
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)				



B Page 12 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

Butane

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Aspiration hazard:						No
Symptoms:						ataxia, breathing
						difficulties,
						drowsiness,
						unconsciousnes
						, frostbite,
						disturbed heart
						rhythm,
						headaches,
						cramps,
						intoxication,
						dizziness,
						nausea and
						vomiting.
Specific target organ toxicity -	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),					Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	-
Aspiration hazard:						No
Symptoms:						unconsciousness
						, frostbite,
						headaches,
						cramps,
						dizziness,
						nausea and
						vomiting.
Specific target organ toxicity -	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),					Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	

Possibly more information on environmental effects, see Section 2.1 (classification).									
Cockpitpflege vanille									



Page 13 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021

Cockpitpflege vanille

œ.

12.1. Toxicity to fish:		n.d.a.
12.1. Toxicity to daphnia:		n.d.a.
12.1. Toxicity to algae:		n.d.a.
12.2. Persistence and		n.d.a.
degradability:		
12.3. Bioaccumulative		n.d.a.
potential:		
12.4. Mobility in soil:		n.d.a.
12.5. Results of PBT		n.d.a.
and vPvB assessment		
12.6. Other adverse		n.d.a.
effects:		
and vPvB assessment 12.6. Other adverse		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	IC50		>100	mg/l			estimated
12.4. Mobility in soil:							Product floats or the water surface.
12.1. Toxicity to daphnia:	NOELR	21d	>1	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31,3	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short- term Toxicity Test on Embryo and Sac- fry Stages)	
12.1. Toxicity to daphnia:	EC50	48h	5414	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	



Page 14 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

œ.

12.2. Persistence and degradability:		28d	97	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,32				Bioaccumulation is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				
12.4. Mobility in soil:	H (Henry)		0,00013 8				
12.4. Mobility in soil:	Koc		1,0				Highestimated
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No vPvB substance
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected ((acposed 2))
12.5. Results of PBT and vPvB assessment							(LogPow 1-3). No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Endpoint	Time	Value	Unit	Organism	Test method	Notes
						A notable
						biological
						accumulation
						potential is not to
						be expected
						(LogPow 1-3).
LC50	96h	27,98	mg/l			
EC50	96h	7,71	mg/l			
	LC50	LC50 96h	LC50 96h 27,98	LC50 96h 27,98 mg/l	LC50 96h 27,98 mg/l	LC50 96h 27,98 mg/l



Page 15 of 18	
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II	
Revision date / version: 22.04.2021 / 0008	
Replacing version dated / version: 29.06.2018 / 0007	
Valid from: 22.04.2021	
PDF print date: 14.06.2021	
Cockpitpflege vanille	

12.2. Persistence and			Readily
degradability:			biodegradable
12.5. Results of PBT			No PBT
and vPvB assessment			substance, No
			vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

(GB)

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

Do not dispose of with household waste.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements 14.1. UN number: Transport by road/by rail (ADR/RID) 14.2. UN proper shipping name:	1950	
UN 1950 AEROSOLS 14.3. Transport hazard class(es): 14.4. Packing group: Classification code: LQ:	2.1 - 5F 1 L	*
14.5. Environmental hazards: Tunnel restriction code:	Not applicable D	
Transport by sea (IMDG-code) 14.2. UN proper shipping name: AEROSOLS		
14.3. Transport hazard class(es): 14.4. Packing group: EmS:	2.1 - F-D, S-U	•
Marine Pollutant: 14.5. Environmental hazards:	n.a Not applicable	
Transport by air (IATA) 14.2. UN proper shipping name: Aerosols, flammable		
14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards:	2.1 - Not applicable	-
14.6. Special precautions for user Persons employed in transporting dangerous goods must be All persons involved in transporting must observe safety reg Precautions must be taken to prevent damage.	e trained.	
14.7. Transport in bulk according to Anne Freighted as packaged goods rather than in bulk, therefore Minimum amount regulations have not been taken into acco	not applicable.	



Page 16 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

Danger code and packing code on request. Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

ആ

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
	dangerous substances as	dangerous substances as
	referred to in Article 3(10) for the	referred to in Article 3(10) for the
	application of - Lower-tier	application of - Upper-tier
	requirements	requirements
11.1	150 (netto)	500 (netto)
		dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
-			(tonnes) for the	(tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 99 %

50 - 100% III

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

15

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.



Page 17 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

ആ

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation. H413 May cause long lasting harmful effects to aquatic life.

Aerosol — Aerosols Asp. Tox. — Aspiration hazard Flam. Liq. — Flammable liquid Aquatic Chronic — Hazardous to the aquatic environment - chronic Eye Irrit. — Eye irritation

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council bw body weight CAS Chemical Abstracts Service CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency European Economic Community EEC European Inventory of Existing Commercial Chemical Substances EINECS European List of Notified Chemical Substances ELINCS EN European Norms EPA United States Environmental Protection Agency (United States of America) et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av.



ആ Page 18 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.04.2021 / 0008 Replacing version dated / version: 29.06.2018 / 0007 Valid from: 22.04.2021 PDF print date: 14.06.2021 Cockpitpflege vanille n.c. not checked n.d.a. no data available OECD Organisation for Economic Co-operation and Development organic org. PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride **PVC** REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.