

Page 1 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## **Bike Glanz-Spruehwachs**

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Polish

Chemical product category [PC]: PC31 - Polishes and wax blends

#### **Uses advised against:**

No information available at present.

## 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

## Emergency information services / official advisory body:

---

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Skin Sens. 1 H317-May cause an allergic skin reaction.

Aquatic Chronic 3 H412-Harmful to aquatic life with long lasting effects.

Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016 Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs





#### Danger

H317-May cause an allergic skin reaction. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

P333+P313-If skin irritation or rash occurs: Get medical advice / attention.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible. 2-methylisothiazol-3(2H)-one

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

#### Aerosol

#### 3.1 Substances

## n.a. **3.2 Mixtures**

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119480153-44-XXXX
Index	
EINECS, ELINCS, NLP	920-134-1 (REACH-IT List-No.)
CAS	
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	
EINECS, ELINCS, NLP	919-857-5 (REACH-IT List-No.)
CAS	
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H336



Page 3 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)	
Registration number (REACH)	01-2119951823-33-XXXX
Index	
EINECS, ELINCS, NLP	271-653-9
CAS	68603-38-3
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Aquatic Chronic 2, H411

2-methylisothiazol-3(2H)-one	
Registration number (REACH)	
Index	613-326-00-9
EINECS, ELINCS, NLP	220-239-6
CAS	2682-20-4
content %	0,0015-<0,01
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 3, H301
	Acute Tox. 3, H311
	Skin Corr. 1B, H314
	Skin Sens. 1A, H317
	Eye Dam. 1, H318
	Acute Tox. 2, H330
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

Irritation of the respiratory tract

Coughing

Headaches

Nausea



Page 4 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

Effects/damages the central nervous system

With long-term contact: Dermatitis (skin inflammation) Product removes fat. Allergic reaction

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Foam

### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

## 6.2 Environmental precautions

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

## 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.



(B)-

Page 5 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use. Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Observe special regulations for aerosols!

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Store cool.

#### 7.3 Specific end use(s)

No information available at present.

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% arc	matics	Content %:5-<10
WEL-TWA: 800 mg/m3	WEL-STEL:		
Monitoring procedures:	<ul> <li>Draeger - Hydrocarbons 0,1%/c (8</li> </ul>		
	- Draeger - Hydrocarbons 2/a (81 03	3 581)	
	- Compur - KITA-187 S (551 174)		
BMGV:			EL acc. to RCP-method,
		paragraphs 84-87, EH	10)
Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic	cs, <2% aromatics	Content %:5-<10
WEL-TWA: 800 mg/m3	WEL-STEL:		
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (8	1 03 571)	
	- Draeger - Hydrocarbons 2/a (81 03		
	<ul> <li>Compur - KITA-187 S (551 174)</li> </ul>		
BMGV:		Other information: (O	EL acc. to RCP-method,
		paragraphs 84-87, EH4	10)
Chemical Name	Butane		Content %:
WEL-TWA: 600 ppm (1450 mg/m3	7 101 7	ng/m3)	Content 76.
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	19/1113)	
Wormoning procedures.	- OSHA PV2010 (n-Butane) - 1993		
BMGV:	OCT 17 1 72010 (11 Buttane) 1000	Other information:	
		Guior information:	
© Chemical Name	Propane		Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL:		
Monitoring procedures:	- Compur - KITA-125 SA (549 954)		
	- OSHA PV2077 (Propane) - 1990		
BMGV:		Other information:	
Chemical Name	Isobutane		Content %:
WEL-TWA: 1000 ppm (EX) (ACGII			
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 36	58)	
BMGV:		Other information:	
© Chemical Name	Kaolin, calcined		Content %:
WEL-TWA: 2 mg/m3 (res. dust) (K			
5 - ( ) (			



Page 6 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

Monitoring procedures: --
BMGV: --
Other information: ---

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics									
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note			
Consumer	Human - inhalation	Long term	DNEL	185	mg/m3				
Consumer	Human - oral	Short term, local effects	DNEL	125	mg/kg				
Consumer	Human - dermal	Long term	DNEL	125	mg/kg				
Workers / employees	Human - inhalation	Long term	DNEL	871	mg/m3				
Workers / employees	Human - dermal	Long term	DNEL	208	mg/kg				

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects			mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1500	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	208	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.



Page 7 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents"

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

>= 0.7

Permeation time (penetration time) in minutes:

>= 240

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: White
Odour: Characteristic
Odour threshold: Not determined
pH-value: Not determined
Melting point/freezing point: Not determined

Initial boiling point and boiling range:

Flash point:

Evaporation rate:

Flammability (solid, gas):

n.a.

n.a.

Lower explosive limit: Not determined



Page 8 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

Upper explosive limit: Not determined Vapour pressure: Not determined

Vapour density (air = 1): Vapours heavier than air. Density: 0,988 g/cm3 (Active substance)

Density: 0,76933 g/cm3 (20°C) Bulk density: n.a.

Solubility(ies): Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: >200 °C (Ignition temperature)

Decomposition temperature: Not determined Viscosity: Not determined

Explosive properties: Product is not explosive. When using: development of explosive

vapour/air mixture possible.

Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined

Solvents content: 49,3 % (Organic solvents)

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

#### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

#### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.



Page 9 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rabbit		
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Aspiration hazard:						Yes
Symptoms:						unconsciousness , headaches, dizziness

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Aspiration hazard:						Yes



Page 10 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Symptoms:				unconsciousness , headaches, dizziness, discoloration of the skin, vomiting, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:			OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Not to be expected

Amides, C16-18 and C18-unsat Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>3000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	Regulation (ÉC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)	Negative
Reproductive toxicity:	NOAEL	>1000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	

2-methylisothiazol-3(2H)-one	2-methylisothiazol-3(2H)-one								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	183	mg/kg	Rat					
Acute toxicity, by dermal route:	LD50	242	mg/kg	Rat	OECD 402 (Acute				
					Dermal Toxicity)				
Acute toxicity, by inhalation:	LD50	0,11	mg/l/4h	Rat	OECD 403 (Acute	Aerosol			
					Inhalation Toxicity)				
Skin corrosion/irritation:						Corrosive			
Serious eye damage/irritation:						Risk of serious			
						damage to eyes.			
Respiratory or skin						Sensitising (skin			
sensitisation:						contact)			

Butane								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat				
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative		
				typhimurium	Reverse Mutation Test)			
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative		
					Mammalian			
					Chromosome			
					Aberration Test)			
Aspiration hazard:					,	No		



Page 11 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Symptoms:		ataxia, brea difficulties, drowsiness, unconscious , frostbite, disturbed he rhythm, headaches, cramps, intoxication,	sness
		intoxication, dizziness, nausea and vomiting.	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:					,	No
Symptoms:						breathing difficulties, unconsciousnes, frostbite, headaches, cramps, mucous membrane irritation
						irritation, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Aspiration hazard:						No
Symptoms:						unconsciousness
						, frostbite,
						headaches,
						cramps,
						dizziness,
						nausea and
						vomiting.

Kaolin, calcined						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat	U.S. EPA 81-2	Analogous conclusion



B.

Page 12 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

Skin corrosion/irritation:	Rabbit	OECD 404 (Acute	Not irritant,
		Dermal	Analogous
		Irritation/Corrosion)	conclusion
Serious eye damage/irritation:	Rabbit	OECD 405 (Acute Eye	Not irritant,
		Irritation/Corrosion)	Analogous
		,	conclusion
Respiratory or skin	Mouse	OECD 429 (Skin	Not sensitizising,
sensitisation:		Sensitisation - Local	Analogous
		Lymph Node Assay)	conclusion
Respiratory or skin	Mouse	OECD 429 (Skin	No (skin contact)
sensitisation:		Sensitisation - Local	
		Lymph Node Assay)	
Aspiration hazard:			No
Specific target organ toxicity -			Inhalation of
repeated exposure (STOT-RE),			alveolargenic
inhalat.:			quartz dust can
			lead to silico-
			arthrosis
			(nodular
			connective
			tissue changes
			in the lungs).,
			Analogous
			conclusion

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effectEndpointTimeValueUnitOrganismTest methodNotes12.1. Toxicity to fish:n.d.a.12.1. Toxicity to daphnia:n.d.a.12.1. Toxicity to algae:n.d.a.12.2. Persistence andThe surfactar	
12.1. Toxicity to daphnia: n.d.a. 12.1. Toxicity to algae: n.d.a.	
12.1. Toxicity to algae: n.d.a.	
12.2 Persistence and The surfactor	
1110 odridotal	nt(s)
degradability: contained in the containe	his
mixture	
complies(con	nply)
with the	
biodegradabi	
criteria as laic	Ė
down in	
Regulation (E	C)
No.648/2004	
detergents. D	ata
to support thi	
assertion are	
held at the	
disposal of th	е
competent	
authorities of	the
Member State	es
and will be m	ade
available to	
them, at their	
direct reques	
at the reques	
a detergent	
manufacturer	
12.3. Bioaccumulative n.d.a.	
potential:	
12.4. Mobility in soil: n.d.a.	
12.5. Results of PBT n.d.a.	
and vPvB assessment	



Page 13 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

12.6. Other adverse				n.d.a.
effects:				

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	3,6	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>22-<46	mg/l	Daphnia magna	OECD 202	
				_	STRAUS	(Daphnia sp.	
						Acute	
						Immobilisation	
10.1 Tayloity to algory	EL50	72h	>1000	m a/l	Doguđakirskosticil	Test)	
12.1. Toxicity to algae:	EL50	/2n	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition	
					a Subcapitata	Test)	
12.2. Persistence and		28d	53	%		OECD 301 F	Biodegradable
degradability:						(Ready	<b>.</b>
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Pow		4 - 6				A notable
potential:							biological accumulation
							potential has to
							be expected
							(LogPow > 3).
12.3. Bioaccumulative potential:							Yes
Water solubility:							Insoluble

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Dáphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.3. Bioaccumulative potential:			5-6,7				High



Page 14 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

12.5. Results of PBT				No PBT
and vPvB assessment				substance, No
				vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	60	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	
12.1. Toxicity to fish:	LC50	96h	1,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,32	mg/l	Oncorhynchus mykiss	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	Analogous conclusion
12.1. Toxicity to daphnia:	LOEC/LOEL	21d	0,24	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	0,9	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	EC50	72h	18,6	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
Toxicity to bacteria:	EC50	72h	6	mg/l	Pseudomonas putida	DIN 38412 T.8	Analogous conclusion

2-methylisothiazol-3(2H)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and		28d	0,32	%		OECD 301 B	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.3. Bioaccumulative	Log Kow		-0,32			OECD 117	
potential:	-					(Partition	
						Coefficient (n-	
						octanol/water) -	
						HPLC method)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,38	mg/l	Pimephales	OECD 210 (Fish,	
					promelas	Early-Life Stage	
						Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	4,77	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,359	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,0442	mg/l	Daphnia magna		
12.1. Toxicity to algae:	NOEC/NOEL	120h	0,05	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	



Page 15 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

12.1. Toxicity to algae:	EC50	72h	0,445	mg/l	Pseudokirchneriell	OECD 201 (Alga,
					a subcapitata	Growth Inhibition
					-	Test)

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative	Log Pow		2,98				A notable
potential:							biological
							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative							A notable
potential:							biological
							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and							Readily
degradability:							biodegradable
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Kaolin, calcined							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							Not to be expected
12.1. Toxicity to fish:	NOEC/NOEL	30d	100	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	



Page 16 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

12.2. Persistence and degradability:		Inorganic products cannot be eliminated from water through biological
		purification methods., Mechanical precipitation possible.

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

## **SECTION 14: Transport information**

#### **General statements**

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name: UN 1950 AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

14.4. Packing group:

Classification code:

5F
I O:

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):
2.1
14.4. Packing group:

EmS: F-D, S-U Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):
2.1
14.4. Packing group:

14.5. Environmental hazards:

Not applicable







Page 17 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage.

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

according to ctorago, riarraining oto	· /·		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3b	11.1, 11.2	5000 (netto)	50000 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

DITCOLIVE ZOTZ/TO/LO ( OCV	coom j, minox i, r art z min	product contains the substai	1000 Hoted Delevi.	
Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

379,4 g/l

#### REGULATION (EC) No 648/2004

30 % and more aliphatic hydrocarbons less than 5 % non-ionic surfactants

BENZISOTHIAZOLINONE LAURYLAMINE DIPROPYLENEDIAMINE METHYLISOTHIAZOLINONE

Observe incident regulations.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

Revised sections: 2, 3, 4, 8, 11, 12, 15, 16



Page 18 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H330 Fatal if inhaled.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Skin Irrit. — Skin irritation

Eye Irrit. — Eye irritation

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - dermal

Skin Corr. — Skin corrosion
Eye Dam. — Serious eye damage
Acute Tox. — Acute toxicity - inhalation

Aquatic Acute — Hazardous to the aquatic environment - acute

## Any abbreviations and acronyms used in this document:

according, according to

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM

Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA

The International Bromine Council



Page 19 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015

Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EC **European Community** ECHA European Chemicals Agency EEC **European Economic Community** 

**EINECS** European Inventory of Existing Commercial Chemical Substances

**ELINCS** European List of Notified Chemical Substances

ΕN European Norms

**EPA** United States Environmental Protection Agency (United States of America)

et cetera etc. EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number general gen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

**GWP** Global warming potential

International Agency for Research on Cancer IARC International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

**IUCLID International Uniform Chemical Information Database** IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ **Limited Quantities** 

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. n.c. not checked n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

organic ora.

**PBT** persistent, bioaccumulative and toxic

Polyethylene PΕ

PNEC Predicted No Effect Concentration

parts per million **PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No.

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Telephone Tel.

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90



~			
	$\sim$	-	
	ന്ദ	R١	

Page 20 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.02.2020 / 0016

Replacing version dated / version: 05.11.2019 / 0015 Valid from: 18.02.2020 PDF print date: 08.02.2021 Bike Glanz-Spruehwachs © by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.