

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Elektronikspray

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Grease

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

Page 2 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substances

n.a.

### 3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	(64742-48-9)
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	
Registration number (REACH)	01-2119491299-23-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	270-128-1
CAS	68411-46-1
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361f Aquatic Chronic 3, H412

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0015

Replacing version dated / version: 01.11.2021 / 0014

Valid from: 13.09.2023

PDF print date: 14.09.2023

Elektronikspray

## Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

## Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

## Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

## Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Effects/damages the central nervous system

With long-term contact:

Dermatitis (skin inflammation)

Product removes fat.

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

# SECTION 5: Firefighting measures

## 5.1 Extinguishing media

### Suitable extinguishing media

CO<sub>2</sub>

Foam

Extinction powder

Water jet spray

### Unsuitable extinguishing media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

# SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 13.09.2023 / 0015  
Replacing version dated / version: 01.11.2021 / 0014  
Valid from: 13.09.2023  
PDF print date: 14.09.2023  
Elektronikspray

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.  
Avoid inhalation, and contact with eyes or skin.  
If applicable, caution - risk of slipping.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Keep away from sources of ignition - Do not smoke.  
Take measures against electrostatic charging, if appropriate.  
Do not use on hot surfaces.  
Avoid contact with eyes or skin.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.  
Observe special regulations for aerosols!  
Do not store with oxidizing agents.  
Observe special storage conditions.  
Observe special storage conditions.  
Keep protected from direct sunlight and temperatures over 50°C.  
Store in a well ventilated place.

### 7.3 Specific end use(s)

No information available at present.  
Observe the instructions for good working practice and the recommendations for risk assessment.  
Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

GB

Page 5 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Chemical Name	Hydrocarbons, C3-4		
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: 1250 ppm (2180 mg/m <sup>3</sup> ) (Liquefied petroleum gas (LPG))	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		

Chemical Name	Oil mist, mineral		
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---		

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,51	mg/l	
	Environment - sediment, freshwater		PNEC	0,0246	mg/kg	
	Environment - sediment, marine		PNEC	0,00246	mg/kg	
	Environment - soil		PNEC	0,0193	mg/kg	
	Environment - sewage treatment plant		PNEC	0,187	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,22	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,1	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,05	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,07	mg/kg	

Ⓞ

Page 6 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,31	mg/m <sup>3</sup>	
---------------------	--------------------	-----------------------------	------	------	-------------------	--

Ⓞ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).  
 (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN ISO 374).  
 If applicable  
 Protective nitrile gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 0,3  
 Permeation time (penetration time) in minutes:  
 > 120  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.  
 If OES or MEL is exceeded.  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Page 7 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	There is no information available on this parameter.
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,71 g/ml
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

### 9.2 Other information

Explosives:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	No

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources  
 Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

#### Elektronikspray

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------



Page 8 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4,951	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Maximum achievable concentration., Vapours
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking., Product removes fat.
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion



Page 9 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

Reproductive toxicity:	NOAEC	>= 5220	mg/m <sup>3</sup>	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion inhalation
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, Dermatitis (skin inflammation), Reddening, drying of the skin., mucous membrane irritation, nausea and vomiting., diarrhoea, lower abdominal pain

#### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Mild irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 487 (In Vitro Mammalian Cell Micronucleus Test)	Negative
Reproductive toxicity:				Rat	OECD 443 (Extended One-Generation Reproductive Toxicity Study)	Possible risk of impaired fertility.
Specific target organ toxicity - single exposure (STOT-SE):						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):				Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Target organ(s): Thyroid, Target organ(s): liver

#### Hydrocarbons, C3-4

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	10000	ppm	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

Page 10 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

Symptoms:						malaise, nausea, dizziness, mucous membrane irritation, drowsiness, unconsciousness
-----------	--	--	--	--	--	---

## 11.2. Information on other hazards

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						No

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Elektronikspray							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,10	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna	QSAR	

Page 11 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				
12.4. Mobility in soil:	Log Koc		>3				Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.7. Other adverse effects:							Product floats on the water surface.
Water solubility:			~10	mg/l			Slight

**Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	51	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC10	21d	1,69	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	Log Koc		3,8				calculated value
12.3. Bioaccumulative potential:	BCF	42d	1730		Cyprinus caprio		Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Endocrine disrupting properties:							No
Toxicity to bacteria:	EC20	3h	~100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:	EC10	56d	259	mg/kg	Eisenia foetida	OECD 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei))	

**Hydrocarbons, C3-4**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 12 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

12.2. Persistence and degradability:							Biodegradable
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:


Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging


## SECTION 14: Transport information

### General statements

#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
Classification code:	5F	
LQ:	1 L	
Transport category:	2	

#### Transport by sea (IMDG-code)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-D, S-U	

#### Transport by air (IATA)

14.1. UN number or ID number:	1950
-------------------------------	------

Page 13 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

14.2. UN proper shipping name:  
 UN 1950 Aerosols, flammable  
 14.3. Transport hazard class(es): 2.1   
 14.4. Packing group: -  
 14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

**14.7. Maritime transport in bulk according to IMO instruments**

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:  
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with trade association/occupational health regulations.  
 Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 70,5 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**

Revised sections: 3, 8, 11, 12  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 13.09.2023 / 0015  
 Replacing version dated / version: 01.11.2021 / 0014  
 Valid from: 13.09.2023  
 PDF print date: 14.09.2023  
 Elektronikspray

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- H361f Suspected of damaging fertility.
- H304 May be fatal if swallowed and enters airways.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- Aerosol — Aerosols
- Asp. Tox. — Aspiration hazard
- Repr. — Reproductive toxicity
- Aquatic Chronic — Hazardous to the aquatic environment - chronic

**Key literature references and sources for data:**

- Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
- Guidelines for the preparation of safety data sheets as amended (ECHA).
- Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
- Safety data sheets for the constituent substances.
- ECHA Homepage - Information about chemicals.
- GESTIS Substance Database (Germany).
- German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
- EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
- National Lists of Occupational Exposure Limits for each country as amended.
- Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

**Any abbreviations and acronyms used in this document:**

- acc., acc. to according, according to
- ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
- AOX Adsorbable organic halogen compounds
- approx. approximately
- Art., Art. no. Article number
- ASTM ASTM International (American Society for Testing and Materials)
- ATE Acute Toxicity Estimate
- BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
- BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
- BCF Bioconcentration factor
- BSEF The International Bromine Council
- bw body weight
- CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
- CMR carcinogenic, mutagenic, reproductive toxic
- DMEL Derived Minimum Effect Level
- DNEL Derived No Effect Level
- DOC Dissolved organic carbon
- dw dry weight
- e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
- EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
- EC European Community
- ECHA European Chemicals Agency
- ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
- EEC European Economic Community
- EINECS European Inventory of Existing Commercial Chemical Substances
- ELINCS European List of Notified Chemical Substances
- EN European Norms
- EPA United States Environmental Protection Agency (United States of America)
- ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
- etc. et cetera

Page 15 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 13.09.2023 / 0015  
Replacing version dated / version: 01.11.2021 / 0014  
Valid from: 13.09.2023  
PDF print date: 14.09.2023  
Elektronikspray

EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
Koc Adsorption coefficient of organic carbon in the soil  
Kow octanol-water partition coefficient  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute for Occupational Safety and Health (USA)  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
OSHA Occupational Safety and Health Administration (USA)  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.