

Page 1 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Wartungsspray weiss Maintenance Spray, white

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Grease

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category **Hazard statement**

STOT SE 3 H336-May cause drowsiness or dizziness.

2 Aquatic Chronic H411-Toxic to aquatic life with long lasting effects.

Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



(B)

Page 2 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white



H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

Pentane

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a. **3.2 Mixtures**

Pentane	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-006-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-692-4
CAS	109-66-0
content %	30-40
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 2, H225
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aguatic Chronic 2, H411

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	



(B)

Page 3 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Dizinc pyrophosphate	
Registration number (REACH)	01-2120768152-56-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	231-203-4
CAS	7446-26-6
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Titanium dioxide (in powder form containing 1 % or more of particles	
with aerodynamic diameter <= 10 μm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	
Registration number (REACH)	01-2119491299-23-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	270-128-1
CAS	68411-46-1
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361f
	Aquatic Chronic 3, H412

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.



Page 4 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029 Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Effects/damages the central nervous system

With long-term contact:

Dermatitis (skin inflammation)

Product removes fat.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Water jet spray

CO2

Extinction powder

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of phosphorus

Oxides of sulphur

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.



Page 5 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029 Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Observe special regulations for aerosols!

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1000 mg/m3

© Chemical Name	Pentane		
WEL-TWA: 1800 mg/m3 (600 ppm	n) (WEL), 3000	WEL-STEL:	
mg/m3 (1000 ppm) (EU)			
Monitoring procedures:	=	Draeger - Pentane 100/a (67 24 701)	
	-	Compur - KITA-113 SB(C) (549 368)	
		DFG (D) (Loesungsmittelgemische Meth. Nr. 1), DFG (E) (S	olvent mixtures 1) - 1998,
	-	2002	
	-	NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003	
	=	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREE	ENING)) - 1996
BMGV:		Other information:	
© Chemical Name	Hydrocarbons, C	C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	



(B)

Page 6 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028 Valid from: 13.09.2023

PDF print date: 13.09.2023	
Wartungsspray weiss	
Maintenance Spray, white	
WEL-TWA: 1000 mg/m3 WEL-STEL:	
Monitoring procedures: - Compur - KITA-187 S (551 1	
BMGV:	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)
Chemical Name Titanium dioxide (in powder form containing 1 9 aerodynamic diameter <= 10 μm)	% or more of particles with
WEL-TWA: 10 mg/m3 (total inhalable dust), 4 mg/m3 WEL-STEL:	
(respirable dust)	
Monitoring procedures:	
BMGV:	Other information:
Chemical Name Butane	
WEL-TWA: 600 ppm (1450 mg/m3) WEL-STEL: 750 ppm (18	810 mg/m3)
Monitoring procedures: - Compur - KITA-221 SA (549	459)
- OSHA PV2010 (n-Butane) - 1	
BMGV:	Other information:
© Chemical Name Propane	
WEL-TWA: 1000 ppm (ACGIH) WEL-STEL:	
Monitoring procedures: - Compur - KITA-125 SA (549	954)
- OSHA PV2077 (Propane) - 1	
BMGV:	Other information:
© Chemical Name Isobutane	
WEL-TWA: 1000 ppm (EX) (ACGIH) WEL-STEL:	
Monitoring procedures: - Compur - KITA-113 SB(C) (5	
BMGV:	Other information:
Chemical Name Oil mist, mineral	,
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal WEL-STEL:	
working fluids, ACGIH)	
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33	
BMGV:	Other information:

Pentane Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
Area or application	Environmental	Effect of ficaltif	Descriptor	Value	J Oille	14010
	compartment					
	Environment - water, sporadic (intermittent) release		PNEC	880	µg/l	
	Environment - freshwater		PNEC	230	μg/l	
	Environment - marine		PNEC	230	μg/l	
	Environment - sewage treatment plant		PNEC	3600	μg/l	
	Environment - sediment, freshwater		PNEC	1,2	mg/kg dw	
	Environment - sediment, marine		PNEC	1,2	mg/kg dw	
	Environment - soil		PNEC	0,55	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	214	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	214	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	643	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3000	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	432	mg/kg bw/d	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane



B.

Page 7 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028 Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	733	mg/kg bw/d	

Dizinc pyrophosphate					1	
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,233	μg/l	
	Environment - marine		PNEC	0,023	μg/l	
	Environment - sediment,		PNEC	2560	μg/l	
	freshwater					
	Environment - sediment,		PNEC	2560	μg/l	
	marine					
	Environment - sewage		PNEC	52	μg/l	
	treatment plant					
Consumer	Human - oral	Long term, systemic	DNEL	1,93	mg/kg bw/d	
		effects				
Consumer	Human - dermal	Long term, systemic	DNEL	193	mg/kg bw/d	
		effects				
Consumer	Human - inhalation	Long term, systemic	DNEL	6,76	mg/m3	
		effects				
Workers / employees	Human - inhalation	Long term, systemic	DNEL	13,5	mg/m3	
		effects				
Workers / employees	Human - dermal	Long term, systemic	DNEL	193	mg/kg bw/d	
		effects				

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
••	Environmental		•			
	compartment					
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene



Page 8 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,51	mg/l	
	Environment - sediment, freshwater		PNEC	0,0246	mg/kg	
	Environment - sediment, marine		PNEC	0,00246	mg/kg	
	Environment - soil		PNEC	0,0193	mg/kg	
	Environment - sewage treatment plant		PNEC	0,187	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,22	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,1	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,05	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,07	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,31	mg/m3	

Zinc sulphide Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
Alea of application	Environmental	Encot on nearth	Descriptor	Value	Onn	11010
	compartment					
			PNEC	20.0	/!	
	Environment - freshwater			20,6	µg/l	
	Environment - marine		PNEC	6,1	μg/l	
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dry weight	
	Environment - sediment, marine		PNEC	56,5	mg/kg dry weight	
	Environment - soil		PNEC	35,5	mg/kg dry weight	
	Environment - sewage		PNEC	100	μg/l	
	treatment plant					
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

^{(8) =} Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 9 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,3

Permeation time (penetration time) in minutes:

>120

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties



Page 10 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029 Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss

Maintenance Spray, white

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: White Odour: Characteristic

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: n.a.

Flammability: Does not apply to aerosols.

Lower explosion limit: 1,4 Vol-%

Upper explosion limit: 10,9 Vol-%

Flash point: Does not apply to aerosols.

Auto-ignition temperature: 285 °C

There is no information available on this parameter. Decomposition temperature:

Mixture is non-soluble (in water). Does not apply to aerosols.

Solubility: Insoluble Partition coefficient n-octanol/water (log value):

Does not apply to mixtures. Vapour pressure: 2400 hPa (20°C)

Density and/or relative density: 0,64 g/ml (20°C) Relative vapour density: Does not apply to aerosols. Particle characteristics: Does not apply to aerosols.

9.2 Other information

Kinematic viscosity:

Explosives: Product is not explosive. When using: development of explosive

vapour/air mixture possible.

Oxidising liquids: No Evaporation rate: n.a. Bulk density: n.a. Solvents content: 80,7

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting.

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Wartungsspray weiss		,	,				
Maintenance Spray, white							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:						n.d.a.	
Acute toxicity, by dermal route:						n.d.a.	
Acute toxicity, by inhalation:						n.d.a.	
Skin corrosion/irritation:						n.d.a.	
Serious eye damage/irritation:						n.d.a.	
Respiratory or skin						n.d.a.	
sensitisation:							



Page 11 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Germ cell mutagenicity:		1	n.d.a.
Carcinogenicity:		1	n.d.a.
Reproductive toxicity:		1	n.d.a.
Specific target organ toxicity -		1	n.d.a.
single exposure (STOT-SE):			
Specific target organ toxicity -		1	n.d.a.
repeated exposure (STOT-RE):			
Aspiration hazard:		1	n.d.a.
Symptoms:		1	n.d.a.

Pentane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	5000	mg/kg	Mouse		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>100	mg/l/4h	Rat		
Skin corrosion/irritation:						Mild irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Mild irritant
Respiratory or skin sensitisation:						Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, vomiting,
						cramps, drowsiness,
						mucous
						membrane
						irritation

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	25,2	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:						Slightly irritant
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Specific target organ toxicity -						May cause
single exposure (STOT-SE):						drowsiness or
						dizziness.
Aspiration hazard:						Yes
Symptoms:						may cause
						headaches and
						vertigo.

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral		
					Toxicity - Up-and-Down		
					Procedure)		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	·		
Acute toxicity, by inhalation:	LC50	>6,8	mg/l/4h	Rat			



Page 12 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract)
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		(90d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		(90d)
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.

Benzenamine, N-phenyl-, react	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral			
					Toxicity)			
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute			
					Dermal Toxicity)			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Mild irritant		
					Dermal			
					Irritation/Corrosion)			
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant		
-					Irritation/Corrosion)			
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)		
sensitisation:					Sensitisation)			
Germ cell mutagenicity:					OECD 487 (In Vitro	Negative		
					Mammalian Cell			
					Micronucleus Test)			



Page 13 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Reproductive toxicity:	Rat	OECD 443 (Extended One-Generation Reproductive Toxicity Study)	Possible risk of impaired fertility.
Specific target organ toxicity - single exposure (STOT-SE):			Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Target organ(s): Thyroid, Target organ(s): liver

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat	100t mourou	110100
Germ cell mutagenicity:	2000	1000	mg///-m	Salmonella	OECD 471 (Bacterial	Negative
Com con matagornoity.				typhimurium	Reverse Mutation Test)	rioganio
Germ cell mutagenicity:				уринианан	OECD 473 (In Vitro	Negative
John John Matagomeny.					Mammalian	- rogairo
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
John Jon Malagomony.				1.10	Mammalian	lioganio
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian	Negative
,-				1.5.1	Erythrocyte	
					Micronucleus Test)	
Aspiration hazard:						No
Specific target organ toxicity -	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined	-
repeated exposure (STOT-RE),					Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Symptoms:						ataxia, breathing
						difficulties,
						drowsiness,
						unconsciousnes
						, frostbite,
						disturbed heart
						rhythm,
						headaches,
						cramps,
						intoxication,
						dizziness,
						nausea and
						vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male,
						Analogous
						conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	



Page 14 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	-
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	•

11.2. Information on other hazards

Wartungsspray weiss Maintenance Spray, white											
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes					
Endocrine disrupting properties:						Does not apply					
						to mixtures.					
Other information:						No other					
						relevant					
						information					
						available on					
						adverse effects					
						on health.					



Page 15 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: $28.08.2022 \, / \, 0028$

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene										
Toxicity / effect Endpoint Value Unit Organism Test method Notes										
Endocrine disrupting properties:						No				

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Wartungsspray weiss							
Maintenance Spray, whit							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							According to the
							recipe, contains
							no AOX.

Pentane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,87	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	9,87	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	9,99	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	9,74	mg/l	Daphnia magna		
12.2. Persistence and degradability:		8d	70	%			
12.3. Bioaccumulative potential:	Log Pow		3,39				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Goldforelle (Oncorhynchus aguabonita)
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	



Page 16 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	100	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.7. Other adverse effects:							Product floats on the water surface.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriell	U.S. EPA-600/9-	
					a subcapitata	78-018	
12.2. Persistence and							Not relevant for
degradability:							inorganic
							substances.
12.3. Bioaccumulative	BCF	42d	9,6				Not to be
potential:							expected
12.3. Bioaccumulative	BCF	14d	19-352				Oncorhynchus
potential:							mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas		
					fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	51	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC10	21d	1,69	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	Log Koc		3,8				calculated value
12.3. Bioaccumulative potential:	BCF	42d	1730		Cyprinus caprio		Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance



Page 17 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

12.6. Endocrine disrupting properties:							No
Toxicity to bacteria:	EC20	3h	~100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:	EC10	56d	259	mg/kg	Eisenia foetida	OECD 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei))	

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and							Readily
degradability:							biodegradable
12.3. Bioaccumulative							A notable
potential:							biological
							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

SECTION 13: Disposal considerations



Page 18 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

SECTION 14: Transport information

2

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: 14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

5F Classification code: I O: 1 L

Transport category:

Transport by sea (IMDG-code)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name: UN 1950 AEROSOLS (PENTANES)

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

Marine Pollutant: Yes

F-D, S-U

Transport by air (IATA)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name: UN 1950 Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.


Danger code and packing code on request.

Comply with special provisions.











(B)

Page 19 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Comply with trade association/occupational health regulations.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	ntry Nr Dangerous substances		Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

80,2 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

3, 11, 12

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.



Page 20 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

Aerosol 1, H229

Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361f Suspected of damaging fertility.

H225 Highly flammable liquid and vapour.

H351 Suspected of causing cancer by inhalation.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aguatic Chronic — Hazardous to the aguatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard

Skin Irrit. — Skin irritation

Aquatic Acute — Hazardous to the aquatic environment - acute

Carc. — Carcinogenicity

Repr. — Reproductive toxicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level



Page 21 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, $E\mu$ Cx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight



Page 22 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 13.09.2023 / 0029

Replacing version dated / version: 28.08.2022 / 0028

Valid from: 13.09.2023 PDF print date: 13.09.2023 Wartungsspray weiss Maintenance Spray, white

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.