

Page 1 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.07.2024 / 0018
Replacing version dated / version: 07.09.2022 / 0017
Valid from: 16.07.2024
PDF print date: 16.07.2024
MoS2 Leichtlauf Super Motoroil 15W-50
Super Low Friction Motor Oil MoS2 15W-50

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

MoS2 Leichtlauf Super Motoroil 15W-50
Super Low Friction Motor Oil MoS2 15W-50

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Motor oil

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Dangerous vapours heavier than air.

Product floats on the water surface.

Product can re-ignite itself.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | |
|--|-----------------------|
| Registration number (REACH) | 01-2119474889-13-XXXX |
| Index | 649-483-00-5 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 276-738-4 |
| CAS | 72623-87-1 |
| content % | 1-<10 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Asp. Tox. 1, H304 |

| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based | |
|--|-----------------------|
| Registration number (REACH) | 01-2119474878-16-XXXX |
| Index | 649-482-00-X |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 276-737-9 |
| CAS | 72623-86-0 |
| content % | 1-<10 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Asp. Tox. 1, H304 |

| Distillates (petroleum), solvent-dewaxed heavy paraffinic | |
|--|-----------------------|
| Registration number (REACH) | 01-2119471299-27-XXXX |
| Index | 649-474-00-6 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 265-169-7 |
| CAS | 64742-65-0 |
| content % | 1-<10 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Asp. Tox. 1, H304 |

| Distillates (petroleum), hydrotreated heavy paraffinic | |
|--|-----------------------|
| Registration number (REACH) | 01-2119484627-25-XXXX |
| Index | 649-467-00-8 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 265-157-1 |
| CAS | 64742-54-7 |
| content % | 1-<10 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Asp. Tox. 1, H304 |

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

Page 3 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.07.2024 / 0018
Replacing version dated / version: 07.09.2022 / 0017
Valid from: 16.07.2024
PDF print date: 16.07.2024
MoS2 Leichtlauf Super Motoroil 15W-50
Super Low Friction Motor Oil MoS2 15W-50

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes
Drying of the skin.
Dermatitis (skin inflammation)
On vapour formation:
Irritation of the respiratory tract
Ingestion:
Nausea
Vomiting
Diarrhoea

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Foam
Dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Metal oxides
Hydrogen sulphide
Oxides of sulphur
Oxides of phosphorus
Oxides of nitrogen
Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.

Page 4 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.07.2024 / 0018
Replacing version dated / version: 07.09.2022 / 0017
Valid from: 16.07.2024
PDF print date: 16.07.2024
MoS2 Leichtlauf Super Motoroil 15W-50
Super Low Friction Motor Oil MoS2 15W-50

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.
Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.
Avoid contact with eyes.
Avoid long lasting or intensive contact with skin.
Do not carry cleaning cloths soaked in product in trouser pockets.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Do not heat to temperatures close to flash point.
Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
Store product closed and only in original packing.
Under all circumstances prevent penetration into the soil.
Store at room temperature.
Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Page 5 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | | |
|---|------------------------|-----|
| WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH) | WEL-STEL: --- | --- |
| Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031) | | |
| BMGV: --- | Other information: --- | |

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|--------------------------|------------|-------|------------|------|
| | Human - oral | | PNEC | 9,33 | mg/kg feed | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 1,2 | mg/m3 | 24h |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 5,4 | mg/m3 | 8h |

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|-----------------------------|------------|-------|--------------|------|
| Consumer | Human - inhalation | Long term, local effects | DNEL | 1,2 | mg/m3 | 24h |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 0,74 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 5,58 | mg/m3 | 8h |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 0,97 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 2,73 | mg/m3 | |

Distillates (petroleum), solvent-dewaxed heavy paraffinic

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|-----------------------------|------------|-------|------------|------|
| | Environment - oral (animal feed) | | PNEC | 9,33 | mg/kg feed | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 1,19 | mg/m3 | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 0,74 | mg/kg bw/d | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 5,58 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 2,73 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 0,97 | mg/kg bw/d | |

Distillates (petroleum), hydrotreated heavy paraffinic

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|-----------------------------|------------|-------|-------|------|
| | Environment - oral (animal feed) | | PNEC | 9,33 | mg/kg | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 1,19 | mg/m3 | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 0,74 | mg/kg | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 5,58 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 0,97 | mg/kg | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 2,73 | mg/m3 | |

Distillates (petroleum), hydrotreated heavy paraffinic

Page 6 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|------------------|------------|-------|------------|------|
| | Environment - oral (animal feed) | | PNEC | 9,33 | mg/kg feed | |

Ⓒ - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:
 Protective gloves, oil resistant (EN ISO 374).
 If applicable
 Protective Neoprene® / polychloroprene gloves (EN ISO 374).
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 > 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Page 7 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state: | Liquid |
| Colour: | Black |
| Odour: | Characteristic |
| Melting point/freezing point: | There is no information available on this parameter. |
| Boiling point or initial boiling point and boiling range: | There is no information available on this parameter. |
| Flammability: | There is no information available on this parameter. |
| Lower explosion limit: | There is no information available on this parameter. |
| Upper explosion limit: | There is no information available on this parameter. |
| Flash point: | 230 °C |
| Auto-ignition temperature: | There is no information available on this parameter. |
| Decomposition temperature: | There is no information available on this parameter. |
| pH: | n.d.a. |
| Kinematic viscosity: | 140,0 mm ² /s (40°C) |
| Kinematic viscosity: | 19,2 mm ² /s (100°C) |
| Solubility: | Insoluble |
| Partition coefficient n-octanol/water (log value): | Does not apply to mixtures. |
| Vapour pressure: | There is no information available on this parameter. |
| Density and/or relative density: | 0,865 g/cm ³ |
| Relative vapour density: | There is no information available on this parameter. |
| Particle characteristics: | Does not apply to liquids. |

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Strong heat

10.5 Incompatible materials

See also section 7.

Page 8 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

Avoid contact with strong oxidizing agents.
10.6 Hazardous decomposition products

See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

MoS2 Leichtlauf Super Motoroil 15W-50 Super Low Friction Motor Oil MoS2 15W-50

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|------|----------|-------------|--------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|-------|---------|------------------------|--|--|
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >5,53 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Aerosol, Analogous conclusion |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative, Analogous conclusion Chinese hamster |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative, Analogous conclusion |
| Carcinogenicity: | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative |

Page 9 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | | | | | | |
|---|-------|------|------------|--------|--|--------------------------------|
| Carcinogenicity: | | | | Mouse | OECD 451 (Carcinogenicity Studies) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Negative |
| Reproductive toxicity: | | | | Rat | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative, Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 411 (Subchronic Dermal Toxicity - 90-day Study) | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 412 (Subacute Inhalation Toxicity - 28-Day Study) | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | 1000 | mg/kg bw/d | Rabbit | OECD 410 (Repeated Dose Dermal Toxicity - 90-Day) | Analogous conclusion |
| Aspiration hazard: | | | | | | Asp. Tox. 1 |

| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based | | | | | | |
|---|-----------------|--------------|-----------------------|------------------------|---|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >5,53 | mg/m ³ /4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Aerosol |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact), Analogous conclusion |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Mammalian | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative, Analogous conclusion, Chinese hamster |
| Carcinogenicity: | | | | Mouse | OECD 451 (Carcinogenicity Studies) | Negative, Analogous conclusion |
| Reproductive toxicity: | NOAEL | >=1000 | mg/kg/d | Rat | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative |

Page 10 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | | | | | | |
|---|-------|-------|------------|--------|--|----------------------|
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 125 | mg/kg | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | 30 | mg/kg | Rat | OECD 411 (Subchronic Dermal Toxicity - 90-day Study) | Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | ~1000 | mg/kg bw/d | Rabbit | OECD 410 (Repeated Dose Dermal Toxicity - 90-Day) | Analogous conclusion |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | nausea and vomiting. |

Distillates (petroleum), solvent-dewaxed heavy paraffinic

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|---------|------------------------|---|---|
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LD50 | >5,53 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Aerosol |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact), Analogous conclusion |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Mammalian | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative, Analogous conclusion Chinese hamster |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative, Analogous conclusion |
| Carcinogenicity: | | | | Mouse | | Female, Negative |
| Carcinogenicity: | | | | Mouse | OECD 451 (Carcinogenicity Studies) | Negative, Analogous conclusion 78 weeks, dermal |
| Reproductive toxicity: | | | | Rat | | Negative |
| Reproductive toxicity (Developmental toxicity): | | | | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | Negative, Analogous conclusion dermal |
| Reproductive toxicity (Effects on fertility): | | | | Rat | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative, Analogous conclusion oral, dermal |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | 30 | mg/kg/d | Rat | OECD 411 (Subchronic Dermal Toxicity - 90-day Study) | Analogous conclusion |

Page 11 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | | | | | | |
|---|-------|-------|------------|--------|---|---|
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | ~1000 | mg/kg bw/d | Rabbit | OECD 410 (Repeated Dose Dermal Toxicity - 90-Day) | Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 0,22 | mg/l | Rat | | Aerosol, Analogous conclusion 4 weeks |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 0,15 | mg/l | Rat | | Aerosol, Analogous conclusion 13 weeks |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | mucous membrane irritation, dizziness, nausea |

Distillates (petroleum), hydrotreated heavy paraffinic

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|---------|------------------------|---|---|
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 420 (Acute Oral toxicity - Fixe Dose Procedure) | Analogous conclusion |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | Analogous conclusion |
| Acute toxicity, by inhalation: | LC50 | >5,53 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Aerosol, Analogous conclusion |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact), Analogous conclusion |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative, Analogous conclusion Chinese hamster |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative, Analogous conclusion |
| Carcinogenicity: | | | | Mouse | OECD 451 (Carcinogenicity Studies) | Negative, Analogous conclusion 78 weeks, dermal |
| Reproductive toxicity: | | | | Rat | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative, Analogous conclusion oral |
| Reproductive toxicity (Developmental toxicity): | | | | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | Negative, Analogous conclusion dermal |

Page 12 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | | | | | | |
|---|-------|------|-------|--------|--|--|
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | LOAEL | 125 | mg/kg | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | 1000 | mg/kg | Rabbit | OECD 410 (Repeated Dose Dermal Toxicity - 90-Day) | Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 0,22 | mg/l | Rat | | Dust, Mist, Analogous conclusion 4 weeks |
| Aspiration hazard: | | | | | | Asp. Tox. 1 |
| Symptoms: | | | | | | gastrointestinal disturbances, diarrhoea |

11.2. Information on other hazards

| MoS2 Leichtlauf Super Motoroil 15W-50 Super Low Friction Motor Oil MoS2 15W-50 | | | | | | |
|---|----------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Endocrine disrupting properties: | | | | | | Does not apply to mixtures. |
| Other information: | | | | | | No other relevant information available on adverse effects on health. |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| MoS2 Leichtlauf Super Motoroil 15W-50 Super Low Friction Motor Oil MoS2 15W-50 | | | | | | | |
|---|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Endocrine disrupting properties: | | | | | | | Does not apply to mixtures. |
| 12.7. Other adverse effects: | | | | | | | No information available on other adverse effects on the environment. |
| Other information: | | | | | | | DOC-elimination degree (complexing organic substance) >= 80%/28d: No |
| Other information: | AOX | | 0 | % | | | According to the recipe, contains no AOX. |

Page 13 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | | | | | | | |
|--|-----------|-------|------------|------|---------------------------------|--|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | NOEC/NOEL | 96h | ≥ 100 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | LL50 | 96h | > 100 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EL50 | 48h | > 10000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 10 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | ≥ 100 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | EL50 | 48h | > 100 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Not readily biodegradable |
| 12.2. Persistence and degradability: | | 28d | 31 | % | activated sludge | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Analogous conclusion |
| 12.3. Bioaccumulative potential: | Log Kow | | > 6 | | | | A notable biological accumulation potential has to be expected (LogPow > 3). |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | NOEC/NOEL | 10min | $> 1,93$ | mg/l | activated sludge | | DIN 38412 |

| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based | | | | | | | |
|--|-----------|------|-------------|------|---------------------------------|--|-----------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | NOEC/NOEL | 14d | ≥ 1000 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to fish: | LL50 | 96h | > 100 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | ≥ 100 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | Analogous conclusion |
| 12.1. Toxicity to daphnia: | EL50 | 48h | > 10000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | ≥ 100 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | Analogous conclusion |
| 12.2. Persistence and degradability: | | 28d | > 60 | % | | | Readily biodegradable |

Page 14 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | | | | | | |
|--|---------|--|-----|--|--|-------------------------------------|
| 12.5. Results of PBT and vPvB assessment | | | | | | No PBT substance, No vPvB substance |
| Other information: | Log Pow | | 6,1 | | | |

Distillates (petroleum), solvent-dewaxed heavy paraffinic

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|-----------|------|-------|------|-------------------------|--|--|
| 12.1. Toxicity to fish: | LC50 | 96h | >1000 | mg/l | Salmo gairdneri | | |
| 12.1. Toxicity to fish: | LC50 | 96h | >5000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOEC/NOEL | 21d | 1000 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | Analogous conclusion |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 10 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | Analogous conclusion |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | Analogous conclusion |
| 12.1. Toxicity to algae: | EC50 | 96h | >1000 | mg/l | Scenedesmus subspicatus | | |
| 12.2. Persistence and degradability: | | 28d | 6 | % | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Analogous conclusion |
| 12.2. Persistence and degradability: | | 28d | 31 | % | activated sludge | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Not readily biodegradable (Analogous conclusion) |
| 12.3. Bioaccumulative potential: | Log Pow | | >3 | | | | Low |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC20 | 6h | >1000 | mg/l | Pseudomonas fluorescens | | |

Distillates (petroleum), hydrotreated heavy paraffinic

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|----------------------------|-----------|------|-------|------|---------------------------------|--|----------------------|
| 12.1. Toxicity to fish: | LL50 | 96h | >100 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | Analogous conclusion |
| 12.1. Toxicity to fish: | NOEC/NOEL | 28d | >1000 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 10 | mg/l | Daphnia magna | QSAR | Analogous conclusion |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | Analogous conclusion |
| 12.1. Toxicity to algae: | EC50 | 48h | >100 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |

Page 15 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | | | | | | | |
|---|-----------|-----|-------|------|-------------------------------------|--|--|
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | >=100 | mg/l | Pseudokirchneriell a subcapitata | OECD 201 (Alga, Growth Inhibition Test) | Analogous conclusion |
| 12.2. Persistence and degradability: | | 28d | 31 | % | activated sludge | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Not readily biodegradable, Analogous conclusion |
| 12.2. Persistence and degradability: | | 28d | 6 | % | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Not readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 3,9-6 | | | | High |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Other information: | AOX | | 0 | % | | | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):

Not applicable

14.4. Packing group:

Not applicable

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

Not applicable

Classification code:

Not applicable

LQ:

Not applicable

Transport category:

Not applicable

Transport by sea (IMDG-code)

Page 16 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

| | |
|-----------------------------------|----------------|
| 14.1. UN number or ID number: | Not applicable |
| 14.2. UN proper shipping name: | |
| Not applicable | |
| 14.3. Transport hazard class(es): | Not applicable |
| 14.4. Packing group: | Not applicable |
| 14.5. Environmental hazards: | Not applicable |
| Marine Pollutant: | Not applicable |
| EmS: | Not applicable |

Transport by air (IATA)

| | |
|-----------------------------------|----------------|
| 14.1. UN number or ID number: | Not applicable |
| 14.2. UN proper shipping name: | |
| Not applicable | |
| 14.3. Transport hazard class(es): | Not applicable |
| 14.4. Packing group: | Not applicable |
| 14.5. Environmental hazards: | Not applicable |

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC): < 1 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 9, 11, 12, 15, 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.
 H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

Page 17 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.07.2024 / 0018
 Replacing version dated / version: 07.09.2022 / 0017
 Valid from: 16.07.2024
 PDF print date: 16.07.2024
 MoS2 Leichtlauf Super Motoroil 15W-50
 Super Low Friction Motor Oil MoS2 15W-50

National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EµCx, Erlx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 mg/kg bw mg/kg body weight
 mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
 mg/kg dw mg/kg dry weight
 mg/kg wwt mg/kg wet weight
 n.a. not applicable

Page 18 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.07.2024 / 0018
Replacing version dated / version: 07.09.2022 / 0017
Valid from: 16.07.2024
PDF print date: 16.07.2024
MoS2 Leichtlauf Super Motoroil 15W-50
Super Low Friction Motor Oil MoS2 15W-50

n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.