

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Engine Flush

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Cleaner

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

## Danger

H319-Causes serious eye irritation. H317-May cause an allergic skin reaction. H304-May be fatal if swallowed and enters airways.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P261-Avoid breathing vapours or spray. P280-Wear protective gloves / eye protection / face protection.  
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314-Get medical advice / attention if you feel unwell.  
 P331-Do NOT induce vomiting.  
 P405-Store locked up.  
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated heavy paraffinic  
 Distillates (petroleum), solvent-dewaxed heavy paraffinic  
 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics  
 Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	
<b>Registration number (REACH)</b>	01-2119457273-39-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	918-481-9
<b>CAS</b>	---
<b>content %</b>	70-<90
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH066 Asp. Tox. 1, H304

<b>Distillates (petroleum), hydrotreated heavy paraffinic</b>	
<b>Registration number (REACH)</b>	01-2119484627-25-XXXX
<b>Index</b>	649-467-00-8
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	265-157-1
<b>CAS</b>	64742-54-7
<b>content %</b>	0-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Asp. Tox. 1, H304

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic</b>	
<b>Registration number (REACH)</b>	01-2119471299-27-XXXX
<b>Index</b>	649-474-00-6
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	265-169-7
<b>CAS</b>	64742-65-0
<b>content %</b>	0-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Asp. Tox. 1, H304

Page 3 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b>	
<b>Registration number (REACH)</b>	01-2119480132-48-XXXX
<b>Index</b>	649-469-00-9
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	265-159-2
<b>CAS</b>	64742-56-9
<b>content %</b>	0-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Asp. Tox. 1, H304

<b>Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts</b>	
<b>Registration number (REACH)</b>	01-2119948548-22-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	270-478-5
<b>CAS</b>	68442-22-8
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

<b>Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	682-816-2
<b>CAS</b>	722503-68-6
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Sens. 1B, H317

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.  
 Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."  
 Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.  
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.  
 Danger of aspiration.  
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

Page 4 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0038  
Replacing version dated / version: 01.11.2021 / 0037  
Valid from: 18.09.2022  
PDF print date: 20.02.2024  
Engine Flush

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

eyes, reddened

watering eyes

With long-term contact:

Nausea

Dizziness

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Vomiting

Danger of aspiration.

Oedema of the lungs

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

Ingestion:

Activated carbon

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

CO<sub>2</sub>

Extinction powder

Foam

Water jet spray

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Flammable vapour/air mixtures

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

## 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Do not heat to temperatures close to flash point.  
 Take measures against electrostatic charging, if appropriate.  
 Avoid contact with eyes or skin.  
 Do not carry cleaning cloths soaked in product in trouser pockets.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Solvent resistant floor  
 Do not store with oxidizing agents.  
 Protect from direct sunlight and warming.  
 Store in a well ventilated place.

## 7.3 Specific end use(s)

No information available at present.  
 Observe the instructions for good working practice and the recommendations for risk assessment.  
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---	
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c (81 03 571)	
	-	Draeger - Hydrocarbons 2/a (81 03 581)	
	-	Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Page 6 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

<b>Chemical Name</b>	Oil mist, mineral		
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---		

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m <sup>3</sup>	

Distillates (petroleum), solvent-dewaxed heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/d	

Distillates (petroleum), solvent-dewaxed light paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/day	

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	4	µg/l	
	Environment - marine		PNEC	4,6	µg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	

Page 7 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

	Environment - sediment, freshwater		PNEC	0,045	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,005	mg/kg dw	
	Environment - soil		PNEC	0,007	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	10,67	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,71	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,98	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,24	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11,4	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,05	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |  
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |  
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |  
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN ISO 374).  
 If applicable  
 Protective nitrile gloves (EN ISO 374).



Page 8 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

Minimum layer thickness in mm:  
 0,4  
 Permeation time (penetration time) in minutes:  
 >480  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 If OES or MEL is exceeded.  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Orange
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	63 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	3,462 mm <sup>2</sup> /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,808 g/cm <sup>3</sup> (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

### 9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	There is no information available on this parameter.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability



Page 9 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Open flame, ignition sources

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Engine Flush						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative

Page 10 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, mucous membrane irritation

Distillates (petroleum), hydrotreated heavy paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion 78 weeks, dermal
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion dermal
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion oral

Page 11 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

Aspiration hazard:						
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Asp. Tox. 1 Analogous conclusion
Symptoms:						gastrointestinal disturbances, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,22	mg/l	Rat		Dust, Mist, Analogous conclusion 4 weeks

Distillates (petroleum), solvent-dewaxed heavy paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion 78 weeks, dermal
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion dermal
Carcinogenicity:				Mouse		Female, Negative
Reproductive toxicity:				Rat		Negative
Reproductive toxicity (Effects on fertility):				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion oral, dermal
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	~1000	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion

Page 12 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

Aspiration hazard:						Yes
Symptoms:						mucous membrane irritation, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	30	mg/kg/d	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,22	mg/l	Rat		Aerosol, Analogous conclusion 4 weeks
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,15	mg/l	Rat		Aerosol, Analogous conclusion 13 weeks

**Distillates (petroleum), solvent-dewaxed light paraffinic**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:	NOAEL	>1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Reproductive toxicity:	NOAEL	>2000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., vomiting, nausea

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4358	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2002	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	



Page 14 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:	AOX						According to the recipe, contains no AOX.
Other information:							DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: No

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		10-2500				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymena pyriformis		
Water solubility:							Product floats on the water surface.

Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion

Page 15 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

12.1. Toxicity to algae:	EC50	48h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,9-6				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			

**Distillates (petroleum), solvent-dewaxed heavy paraffinic**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>5000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	96h	>1000	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable (Analogous conclusion)
12.3. Bioaccumulative potential:	Log Pow		>3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC20	6h	>1000	mg/l	Pseudomonas fluorescens		

**Distillates (petroleum), solvent-dewaxed light paraffinic**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------



Page 16 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	LL50	48h	>1000	mg/l	Gammarus sp.	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Inherent
12.3. Bioaccumulative potential:	Log Pow		>3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	4,5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	46	mg/l	Cyprinodon variegatus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	23	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,4	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EL50	72h	21	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	1,5	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

**Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 17 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

12.2. Persistence and degradability:								Not readily biodegradable
--------------------------------------	--	--	--	--	--	--	--	---------------------------

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable

#### Transport by sea (IMDG-code)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	Not applicable

#### Transport by air (IATA)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	Not applicable
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 88,371 %

### REGULATION (EC) No 648/2004

30 % and more

aliphatic hydrocarbons

less than 5 %

phosphates

aromatic hydrocarbons

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

National requirements/regulations on safety and health protection must be applied when using work equipment.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. — Eye irritation

Skin Sens. — Skin sensitization

Asp. Tox. — Aspiration hazard

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

## Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

Page 19 of 20  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0038  
 Replacing version dated / version: 01.11.2021 / 0037  
 Valid from: 18.09.2022  
 PDF print date: 20.02.2024  
 Engine Flush

ECHA Homepage - Information about chemicals.  
 GESTIS Substance Database (Germany).  
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
 National Lists of Occupational Exposure Limits for each country as amended.  
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, ErCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 mg/kg bw mg/kg body weight

Page 20 of 20  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0038  
Replacing version dated / version: 01.11.2021 / 0037  
Valid from: 18.09.2022  
PDF print date: 20.02.2024  
Engine Flush

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day  
mg/kg dw mg/kg dry weight  
mg/kg wwt mg/kg wet weight

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.