

Page 1 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 15.10.2014 / 0010
Valid from: 21.08.2015
PDF print date: 28.07.2017
GETRIEBE-OEL-VERLUST-STOP 50 mL
Art.: 1042

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GETRIEBE-OEL-VERLUST-STOP 50 mL

Art.: 1042

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Additives

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany

Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment.

P501-Dispose of contents / container to special waste collection point.

EUH208-Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Baseoil - unspecified	
Registration number (REACH)	---
Index	649-468-00-3 / 649-467-00-8 / 649-454-00-7 / 649-474-00-6
EINECS, ELINCS, NLP	265-158-7 / 265-157-1 / 265-090-8 / 265-169-7
CAS	64742-55-8 / 64742-54-7 / 64741-88-4 / 64742-65-0
content %	20-40
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
2-Butoxyethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475112-47-XXXX
Index	607-038-00-2
EINECS, ELINCS, NLP	203-933-3
CAS	112-07-2
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	Substance with specific conc. limit(s) acc. to REACH-registration
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	931-384-6 (REACH-IT List-No.)
CAS	---
content %	0,1-<1

Page 3 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 2, H411
(Z)-octadec-9-enylamine	
Registration number (REACH)	---
Index	612-283-00-3
EINECS, ELINCS, NLP	204-015-5
CAS	112-90-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Asp. Tox. 1, H304 STOT SE 3, H335 STOT RE 2, H373 (gastrointestinal tract, liver, immune system) Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10) Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Product removes fat.
 Dermatitis (skin inflammation)
 Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
 Extinction powder
 Foam

Unsuitable extinguishing media

Page 4 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 15.10.2014 / 0010
Valid from: 21.08.2015
PDF print date: 28.07.2017
GETRIEBE-OEL-VERLUST-STOP 50 mL
Art.: 1042

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Hot product gives off combustible vapours.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Keep away from sources of ignition - Do not smoke.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Solvent resistant floor

Store in a well ventilated place.

Protect from direct sunlight and warming.

GB

Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	2-Butoxyethyl acetate		Content %:10- <20
WEL-TWA: 20 ppm (133 mg/m3) (WEL, EU)	WEL-STEL: 50 ppm (333 mg/m3) (WEL, EU)	---	
Monitoring procedures:	- DFG (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 33-3 (2004)		
BMGV: ---	Other information: Sk (WEL)		
Chemical Name	Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---	
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

2-Butoxyethyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	4,3	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	36	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	67	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	102	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	133	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	333	mg/m3	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374)

If applicable

Protective nitrile gloves (EN 374)

Permeation time (penetration time) in minutes:

>480

Minimum layer thickness in mm:

0,4

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Blue
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	200 °C
Flash point:	66 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined

Page 7 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

Vapour density (air = 1):	Not determined
Density:	0,92 g/ml (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	partially, Soluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	642 mm ² /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Strong heat

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

GETRIEBE-OEL-VERLUST-STOP 50 mL

Art.: 1042

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>5000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>5000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.

Page 9 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

2-Butoxyethyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	28	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	37	mg/l	Daphnia pulex	DIN 38412 T.11	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriella subcapitata	ISO/DIS 8692	References
12.2. Persistence and degradability:		28d	>70	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.2. Persistence and degradability:		28d	88	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.3. Bioaccumulative potential:	Log Pow		1,51			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
Toxicity to bacteria:	EC50	17h	720	mg/l	Pseudomonas putida	DIN 38412 T.8	

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	7,4	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Pow		<0,3			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	

(Z)-octadec-9-enylamine

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	0,011	mg/l			
12.1. Toxicity to algae:	EC50	96h	0,03	mg/l			
12.2. Persistence and degradability:		28d	44-66				
12.3. Bioaccumulative potential:			2,7				0,1d

SECTION 13: Disposal considerations

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Implement substance recycling.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): ~ 72 %
 Directive 2010/75/EU (VOC): 662,4 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

Page 11 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

SECTION 16: Other information

Revised sections: 3
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Asp. Tox. — Aspiration hazard
 Acute Tox. — Acute toxicity - oral
 Acute Tox. — Acute toxicity - dermal
 Acute Tox. — Acute toxicity - inhalation
 Flam. Liq. — Flammable liquid
 Skin Sens. — Skin sensitization
 Eye Dam. — Serious eye damage
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 STOT RE — Specific target organ toxicity - repeated exposure
 Skin Corr. — Skin corrosion
 Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

Page 12 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.08.2015 / 0011
 Replacing version dated / version: 15.10.2014 / 0010
 Valid from: 21.08.2015
 PDF print date: 28.07.2017
 GETRIEBE-OEL-VERLUST-STOP 50 mL
 Art.: 1042

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemicals Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available

Page 13 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.08.2015 / 0011
Replacing version dated / version: 15.10.2014 / 0010
Valid from: 21.08.2015
PDF print date: 28.07.2017
GETRIEBE-OEL-VERLUST-STOP 50 mL
Art.: 1042

NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.