

Page 1 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 18.09.2022  
PDF print date: 19.09.2022  
Diesel Smoke Stop (C)

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Diesel Smoke Stop (C)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Additives

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

Page 2 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 18.09.2022  
 PDF print date: 19.09.2022  
 Diesel Smoke Stop (C)

H304-May be fatal if swallowed and enters airways.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting.  
 P405-Store locked up.  
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	---
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

2-ethylhexanoic acid, iron salt	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	243-169-8
CAS	19583-54-1
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315

2-ethylhexanoic acid	
Registration number (REACH)	---
Index	607-230-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	205-743-6
CAS	149-57-5
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361d

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.09.2022 / 0022

Replacing version dated / version: 01.11.2021 / 0021

Valid from: 18.09.2022

PDF print date: 19.09.2022

Diesel Smoke Stop (C)

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

##### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

##### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

##### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

##### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Headaches

Dizziness

Nausea

With long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

CO<sub>2</sub>

Dry extinguisher

Foam

##### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Aldehydes

Hydrocarbons

Toxic gases

Flammable vapour/air mixtures

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Page 4 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 18.09.2022  
PDF print date: 19.09.2022  
Diesel Smoke Stop (C)

Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid contact with eyes or skin.  
Do not carry cleaning cloths soaked in product in trouser pockets.  
Keep away from sources of ignition - Do not smoke.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Store product closed and only in original packing.  
Not to be stored in gangways or stair wells.  
Solvent resistant floor  
Do not store with oxidizing agents.  
Store in a well ventilated place.  
Protect from direct sunlight and warming.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.09.2022 / 0022

Replacing version dated / version: 01.11.2021 / 0021

Valid from: 18.09.2022

PDF print date: 19.09.2022


Diesel Smoke Stop (C)

## 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

800 mg/m<sup>3</sup>

CE	Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
WEL-TWA: 800 mg/m3		WEL-STEL: ---	---
Monitoring procedures:		<ul style="list-style-type: none"><li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li><li>- Draeger - Hydrocarbons 2/a (81 03 581)</li><li>- Compur - KITA-187 S (551 174)</li></ul>	
BMGV: ---		Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

	<b>Chemical Name</b>	Iron salts		
WEL-TWA: 1 mg/m3 (iron salts (as Fe))		WEL-STEL: 2 mg/m3 (iron salts (as Fe))		---
Monitoring procedures:		---		
BMGV: ---			Other information: ---	

2-ethylhexanoic acid						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - marine		PNEC	0,0017	mg/l	
	Environment - sediment, freshwater		PNEC	0,28	mg/kg dw	
	Environment - sediment, marine		PNEC	0,028	mg/kg dw	
	Environment - soil		PNEC	0,047	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	3,5	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	14	mg/m <sup>3</sup>	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).

(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the

date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine

(Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit

value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer

Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through

skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause

sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Page 6 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.09.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 18.09.2022  
 PDF print date: 19.09.2022  
 Diesel Smoke Stop (C)

Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN ISO 374).  
 If applicable  
 Protective Viton® / fluoroelastomer gloves (EN ISO 374).  
 Protective nitrile gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 >= 0,4  
 Permeation time (penetration time) in minutes:  
 >= 480  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 If OES or MEL is exceeded.  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Darkish, Brown
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.

Page 7 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 18.09.2022  
PDF print date: 19.09.2022  
Diesel Smoke Stop (C)

Flash point:	>63 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<7 mm <sup>2</sup> /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,7981 g/ml (15°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

## 9.2 Other information

Explosives:	Product is not explosive.
Oxidising liquids:	No
Bulk density:	n.a.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Open flame, ignition sources

Protect from humidity.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Diesel Smoke Stop (C)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics



Page 8 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 18.09.2022  
PDF print date: 19.09.2022  
Diesel Smoke Stop (C)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, mucous membrane irritation

2-ethylhexanoic acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2043	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative



Page 9 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 18.09.2022  
PDF print date: 19.09.2022  
Diesel Smoke Stop (C)

Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):		600	mg/kg	Rat		Repr. 2oral
Reproductive toxicity (Effects on fertility):						Possible
Specific target organ toxicity - single exposure (STOT-SE):						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Symptoms:						acidosis, respiratory distress, vomiting, coughing, headaches

## 11.2. Information on other hazards

Diesel Smoke Stop (C)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:						Repeated exposure may cause skin dryness or cracking.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Diesel Smoke Stop (C)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.

Page 10 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 18.09.2022  
PDF print date: 19.09.2022  
Diesel Smoke Stop (C)

12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Product floats on the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymena pyriformis		

2-ethylhexanoic acid							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL		25	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oryzias latipes	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	85,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	49,3-60,5	mg/l	Scenedesmus subspicatus	DIN 38412 T.9	
12.2. Persistence and degradability:		28d	90-100	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,7				Low
Toxicity to bacteria:	EC50	17h	112,1	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	COD		2240	mg/kg			

Page 11 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.09.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 18.09.2022  
PDF print date: 19.09.2022  
Diesel Smoke Stop (C)

Other information:	BOD		1200	mg/kg			
Other information:	Koc		140,87			OECD 106 (Adsorption/Desorption Using a Batch Equilibrium Method)	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.  
Pay attention to local and national official regulations.  
Implement substance recycling.  
E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.  
Empty container completely.  
Uncontaminated packaging can be recycled.  
Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:  
14.3. Transport hazard class(es): n.a.  
14.4. Packing group: n.a.  
Classification code: n.a.  
LQ: n.a.  
14.5. Environmental hazards: Not applicable  
Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
14.3. Transport hazard class(es): n.a.  
14.4. Packing group: n.a.  
Marine Pollutant: n.a.  
14.5. Environmental hazards: Not applicable

#### Transport by air (IATA)

14.2. UN proper shipping name:  
14.3. Transport hazard class(es): n.a.  
14.4. Packing group: n.a.  
14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.09.2022 / 0022

Replacing version dated / version: 01.11.2021 / 0021

Valid from: 18.09.2022

PDF print date: 19.09.2022

Diesel Smoke Stop (C)

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

95,294 %

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

2

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361d Suspected of damaging the unborn child.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard

Skin Irrit. — Skin irritation

Repr. — Reproductive toxicity

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, ElCx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.09.2022 / 0022

Replacing version dated / version: 01.11.2021 / 0021

Valid from: 18.09.2022

PDF print date: 19.09.2022

Diesel Smoke Stop (C)

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.