

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Pro-Line Dieselfilter Additiv

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

System cleaner for vehicle fuel units (diesel engines)

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

Page 2 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting.  
 P405-Store locked up.  
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH044-Risk of explosion if heated under confinement.  
 EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	
<b>Registration number (REACH)</b>	01-2119457273-39-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	918-481-9
<b>CAS</b>	---
<b>content %</b>	80-<100
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Asp. Tox. 1, H304

<b>2-Ethylhexylnitrate</b>	
<b>Registration number (REACH)</b>	01-2119539586-27-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	248-363-6
<b>CAS</b>	27247-96-7
<b>content %</b>	5-15
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Chronic 2, H411

<b>Hydrocarbons, C10, aromatics, &gt;1% naphthalene</b>	
<b>Registration number (REACH)</b>	01-2119463588-24-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	919-284-0
<b>CAS</b>	(64742-94-5)
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Carc. 2, H351 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Page 3 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.07.2019 / 0028  
Replacing version dated / version: 09.07.2018 / 0027  
Valid from: 18.07.2019  
PDF print date: 15.06.2021  
Pro-Line Dieselfilter Additiv

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."  
Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.  
If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting - give copious water to drink. Consult doctor immediately.  
Danger of aspiration.  
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritation of the eyes  
Product removes fat.  
Dermatitis (skin inflammation)  
Ingestion:  
Oedema of the lungs  
Lung damage  
Chemical pneumonitis (condition similar to pneumonia)  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.  
Subsequent observation for pneumonia and pulmonary oedema.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>  
Extinction powder  
Foam

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:  
Oxides of carbon  
Oxides of nitrogen  
Hydrocarbons  
Toxic pyrolysis products.  
Danger of explosion.  
Explosive vapour/air or gas/air mixtures.  
Dangerous vapours heavier than air.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire

GB

Page 4 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

Full protection, if necessary.  
 Cool container at risk with water.  
 Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.  
 Ensure sufficient supply of air.  
 Avoid inhalation, and contact with eyes or skin.  
 If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Solvent resistant floor  
 Do not store with oxidizing agents.  
 Store in a well ventilated place.  
 Protect from direct sunlight and warming.  
 Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

GB	<b>Chemical Name</b>	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:80- <100
	WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---

Ⓒ

Page 5 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)

Ⓒ Chemical Name	Hydrocarbons, C10, aromatics, >1% naphthalene	Content %:0,1-<1
WEL-TWA: 500 mg/m <sup>3</sup> (Aromatics)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: ---	

2-Ethylhexylnitrate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,8	µg/l	
	Environment - marine		PNEC	0,08	µg/l	
	Environment - sediment		PNEC	0,00074	mg/kg dw	
	Environment - soil		PNEC	0,00019 1	mg/kg dw	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,52	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,087	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,025	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	0,022	mg/cm <sup>2</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,044	mg/cm <sup>2</sup>	

Hydrocarbons, C10, aromatics, >1% naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m <sup>3</sup>	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause

sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective gloves made of polyvinyl alcohol (EN 374).

Protective Viton® / fluoroelastomer gloves (EN 374).

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0028

Replacing version dated / version: 09.07.2018 / 0027

Valid from: 18.07.2019

PDF print date: 15.06.2021

Pro-Line Dieselfilter Additiv

## 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light brown, Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	180 °C
Flash point:	63 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,7 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Upper explosive limit:	6 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,816 g/ml (15°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm <sup>2</sup> /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	No

## 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

Risk of explosion if heated under confinement.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Pro-Line Dieselfilter Additiv

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value

Page 8 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, mucous membrane irritation



Page 9 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

Other information:						Repeated exposure may cause skin dryness or cracking.
--------------------	--	--	--	--	--	---

2-Ethylhexylnitrate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:						Experiences on persons., Harmful
Acute toxicity, by inhalation:						Experiences on persons., Harmful
Acute toxicity, by inhalation:	LCLo	>4,6	mg/l/1h	Rat		Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Reproductive toxicity:	NOAEL	100	mg/kg bw/d		OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion
Symptoms:						drying of the skin., may cause headaches and vertigo., nausea, drop in blood pressure, diarrhoea, unconsciousness
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	863	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours, Analogous conclusion

Hydrocarbons, C10, aromatics, >1% naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	6318	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion

Page 10 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						drowsiness, headaches, drowsiness, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	750	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	495	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	1000	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative, Analogous conclusion

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Page 11 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

Pro-Line Dieselfilter Additiv							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Product floats on the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

2-Ethylhexylnitrate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>12,6	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	3,22	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	1,42	mg/l			

Page 12 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

12.2. Persistence and degradability:		28d	0	%		OECD 310 (Ready Biodegradability - CO <sub>2</sub> in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		1332				
12.3. Bioaccumulative potential:	Log Pow		3,74-5,24				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Log Koc		3,75			OECD 121 (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using HPLC)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	AOX		0	%			No
Water solubility:							Slight

#### Hydrocarbons, C10, aromatics, >1% naphthalene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,48	mg/l	Daphnia magna		Analogous conclusion
12.3. Bioaccumulative potential:	BCF		99-5780				High
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	58	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		2,8-6,5				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

For the substance / mixture / residual amounts

Page 13 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

EC disposal code no.:  
 The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 07 07 04 other organic solvents, washing liquids and mother liquors  
 14 06 03 other solvents and solvent mixtures  
 Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 Implement substance recycling.  
 E.g. suitable incineration plant.  
**For contaminated packing material**  
 Pay attention to local and national official regulations.  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): ~ 97,7 %

Directive 2010/75/EU (VOC): 797,2 g/l

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Page 14 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.07.2019 / 0028  
 Replacing version dated / version: 09.07.2018 / 0027  
 Valid from: 18.07.2019  
 PDF print date: 15.06.2021  
 Pro-Line Dieselfilter Additiv

Revised sections: 2  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H332 Harmful if inhaled.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Acute Tox. — Acute toxicity - oral  
 Acute Tox. — Acute toxicity - dermal  
 Acute Tox. — Acute toxicity - inhalation  
 Carc. — Carcinogenicity  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 etc. et cetera

EU	European Union
EVAL	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC (Code)	International Bulk Chemical (Code)
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
IUPAC	International Union for Pure Applied Chemistry
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
OECD	Organisation for Economic Co-operation and Development
org.	organic
PBT	persistent, bioaccumulative and toxic
PE	Polyethylene
PNEC	Predicted No Effect Concentration
ppm	parts per million
PVC	Polyvinylchloride
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No.	9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID	Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC	Substances of Very High Concern
Tel.	Telephone
UN RTDG	United Nations Recommendations on the Transport of Dangerous Goods
VOC	Volatile organic compounds
vPvB	very persistent and very bioaccumulative
wwt	wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.