

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

അ

Pro-Line JetClean Diesel-System-Reiniger

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

System cleaner for vehicle fuel units (diesel engines) Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) Hazard class Hazard category Hazard statement Asp. Tox. 1 3

Aquatic Chronic

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting. P405-Store locked up. P501. Dispesse of container to an approved waste dispessal facility.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH044-Risk of explosion if heated under confinement. EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

œ

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304
2-ethylhexyl nitrate	

Registration number (REACH)	01-2119539586-27-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	248-363-6
CAS	27247-96-7
content %	5-15
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	EUH044
	Acute Tox. 4, H302
	Acute Tox. 4, H312
	Acute Tox. 4, H332
	Aquatic Chronic 2, H411

Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	01-2119463588-24-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	919-284-0
CAS	(64742-94-5)
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Carc. 2, H351
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Naphthalene

Substance for which an EU exposure limit value applies.



Page 3 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

Registration number (REACH)	·
Index	601-052-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	202-049-5
CAS	91-20-3
content %	0,01-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Sol. 2, H228
	Acute Tox. 4, H302
	Carc. 2, H351
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting - give copious water to drink. Consult doctor immediately. Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation of the eyes Product removes fat. Dermatitis (skin inflammation) Ingestion: Oedema of the lungs Lung damage Chemical pneumonitis (condition similar to pneumonia) In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Extinction powder



Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

Foam Unsuitable extinguishing media

High volume water jet

ആ

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Hydrocarbons Toxic pyrolysis products. Danger of explosion. Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.



Page 5 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

Remove contaminated clothing and protective equipment before entering areas in which food is consumed. **7.2 Conditions for safe storage, including any incompatibilities**

Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells. Solvent resistant floor Do not store with oxidizing agents. Store in a well ventilated place. Protect from direct sunlight and warming. Store cool.

7.3 Specific end use(s)

GB

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chamical Nama	L ludra aa rhana . C		lice 20/ exemption	
Chemical Name	Hydrocarbons, C	10-C13, n-alkanes, isoalkanes, cycl	ics, <2% aromatics	
WEL-TWA: 800 mg/m3		WEL-STEL:		
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c (8	1 03 571)	
	-	Draeger - Hydrocarbons 2/a (81 03	3 581)	
	-	Compur - KITA-187 S (551 174)	,	
BMGV:			Other information: (O	EL acc. to RCP-method,
			paragraphs 84-87, EH4	-
L			paragraphs of or, En	
Chemical Name	Hydrocarbons, C	10, aromatics, >1% naphthalene		
WEL-TWA: 500 mg/m3 (Aromatics	5)	WEL-STEL:		
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c (8	1 03 571)	
	-	Draeger - Hydrocarbons 2/a (81 03	3 581)	
	-	Compur - KITA-187 S (551 174)		
BMGV:			Other information:	
			1	
Chemical Name	Naphthalene			
WEL-TWA: 500 mg/m3 (Aromatics	s) (WEL), 10 ppm	WEL-STEL:		
(50 mg/m3) (EU)				
Monitoring procedures:	-	Compur - KITA-153 U(C) (551 182	2)	
	-	NIOSH 5506 (POLYNUCLEAR AR	OMATIC HYDROCARBC	ONS by HPLC) - 1998
	-	NIOSH 5515 (POLYNUCLEAR AR		
	-	OSHA 35 (Napthalene) - 1982		
BMGV:			Other information:	
2-ethylhexyl nitrate				
	osuro routo /	Effect on health	Descriptor Value	Linit Noto

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment		DUEO		/1	
	Environment - freshwater		PNEC	0,8	µg/l	
	Environment - marine		PNEC	0,08	µg/l	
	Environment - sediment		PNEC	0,00074	mg/kg dw	
	Environment - soil		PNEC	0,00019 1	mg/kg dw	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,52	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,087	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,025	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	0,022	mg/cm2	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/day	



Page 6 of 18	
Safety data sheet according to Regulation (EC) No 1907/2006, Anne	хII
Revision date / version: 02.09.2022 / 0031	
Replacing version dated / version: 17.02.2022 / 0030	
Valid from: 02.09.2022	
PDF print date: 02.09.2022	
Pro-Line JetClean Diesel-System-Reiniger	

GB

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m3
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,044	mg/cm2

Hydrocarbons, C10, aron				-	-	
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3	

Naphthalene							
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note	
	Environment - freshwater		PNEC	0,0024	mg/l		
	Environment - marine		PNEC	0,0024	mg/l		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3		
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
 (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger Eye/face protection: Tight fitting protective goggles with side protection (EN 166). Skin protection - Hand protection: Solvent resistant protective gloves (EN ISO 374). If applicable Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0.4 Permeation time (penetration time) in minutes: > 480 Protective gloves made of polyvinyl alcohol (EN ISO 374). Protective Viton® / fluoroelastomer gloves (EN ISO 374). Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light brown, Clear
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	180 °C
Flammability:	Flammable
Lower explosion limit:	0,7 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,
	<2% aromatics)
Upper explosion limit:	6 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,
	<2% aromatics)
Flash point:	63 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<7 mm2/s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
· ·	



Page 8 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

Explosives: Oxidising liquids:

œ

0,816 g/ml (15°C) Vapours heavier than air. Does not apply to liquids.

There is no information available on this parameter.

SECTION 10: Stability and reactivity

No

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Risk of explosion if heated under confinement.

10.4 Conditions to avoid

Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Pro-Line JetClean Diesel-System-Reiniger							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value	
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value	
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours	
Skin corrosion/irritation:						n.d.a.	
Serious eye damage/irritation:						n.d.a.	
Respiratory or skin sensitisation:						n.d.a.	
Germ cell mutagenicity:						n.d.a.	
Carcinogenicity:						n.d.a.	
Reproductive toxicity:						n.d.a.	
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.	
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.	
Aspiration hazard:						n.d.a.	
Symptoms:						n.d.a.	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous				
					Toxicity)	conclusion				
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous				
					Dermal Toxicity)	conclusion				
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous				
					Inhalation Toxicity)	conclusion,				
						Vapours				
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,				
					Dermal	Analogous				
					Irritation/Corrosion)	conclusion				



Safety data sheet according to Re Revision date / version: 02.09.202 Replacing version dated / version Valid from: 02.09.2022 PDF print date: 02.09.2022	22 / 0031 : 17.02.2022 / 0030			
Pro-Line JetClean Diesel-System	-Reiniger			
Serious eye damage/irritation:			OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:			OECD 406 (Skin Sensitisation)	Not sensitizising Analogous conclusion
Germ cell mutagenicity:			OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:			OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:		Salmo typhim	nella OECD 471 (Bacterial	Negative
Carcinogenicity:			OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:			OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):			OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard: Symptoms:				Yes unconsciousnes , headaches, dizziness, mucous membrane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:						Experiences on
						persons.,
						Harmful
Acute toxicity, by inhalation:						Experiences on
						persons.,
						Harmful
Acute toxicity, by inhalation:	LCLo	>4,6	mg/l/1h	Rat		Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
					Mammalian	-
					Chromosome	
					Aberration Test)	



Page 10 of 18 Safety data sheet according to Re Revision date / version: 02.09.20 Replacing version dated / version Valid from: 02.09.2022	22 / 0031		6, Annex II			
PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System	Reiniger					
Reproductive toxicity:	NOAEL	100	mg/kg bw/d		OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	500	mg/kg bw/d	Rabbit		Negativedermal
Symptoms:						drying of the skin., may cause headaches and vertigo., nausea, drop in blood pressure, diarrhoea, unconsciousnes
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	863	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Vapours, Analogous conclusion
Hydrocarbons, C10, aromatics,	>1% nanhth:	alana				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	Toxicity) OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	6318	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50 LC50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity) OECD 403 (Acute	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4000	mg/m3	Rai	Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative



Page 11 of 18 Safety data sheet according to Re Revision date / version: 02.09.20 Replacing version dated / version Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System	22 / 0031 n: 17.02.2022		Annex II			
Reproductive toxicity (Developmental toxicity):	NOAEL	>450	mg/kg	Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 416 (Two- generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative, Analogous conclusion
Aspiration hazard: Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	750	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Yes Negative, Analogous conclusion
Symptoms:						drowsiness, headaches, drowsiness, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	495	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	1000	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Negative, Analogous conclusion
Naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route: Acute toxicity, by dermal route:	LD50 LD50	533-710 >16000	mg/kg mg/kg	Mouse Rat	OECD 401 (Acute Oral Toxicity) OECD 402 (Acute	
Acute toxicity, by inhalation:	LC50	>44	mg/l/4h	Rat	Dermal Toxicity) OECD 403 (Acute	Maximum
					Inhalation Toxicity)	achievable concentration.
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation: Respiratory or skin sensitisation:				Rabbit Guinea pig	(Draize-Test) OECD 406 (Skin Sensitisation)	Not irritant No (skin contac
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	Cech 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative



B Page 12 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

11.2. Information on other hazards

Pro-Line JetClean Diesel-System-Reiniger										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Endocrine disrupting properties:	-					Does not apply				
						to mixtures.				
Other information:						No other				
						relevant				
						information				
						available on				
						adverse effects				
						on health.				

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Other information:						Repeated				
						exposure may				
						cause skin				
						dryness or				
						cracking.				

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Pro-Line JetClean Diesel-System-Reiniger										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:							n.d.a.			
12.1. Toxicity to daphnia:							n.d.a.			
12.1. Toxicity to algae:							n.d.a.			
12.2. Persistence and							Isolate as much			
degradability:							as possible with			
							an oil separator.			
12.3. Bioaccumulative							n.d.a.			
potential:										
12.4. Mobility in soil:							n.d.a.			
12.5. Results of PBT							n.d.a.			
and vPvB assessment										
12.6. Endocrine							Does not apply			
disrupting properties:							to mixtures.			
12.7. Other adverse							No information			
effects:							available on			
							other adverse			
							effects on the			
							environment.			
Other information:							According to the			
							recipe, contains			
							no ÁOX.			

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Water solubility:							Product floats on
							the water
							surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus		
					mykiss		



Page 13 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

œ.

12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	BCF		1332				High
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>12,6	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	3,22	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	1,42	mg/l		/	
12.2. Persistence and degradability:		28d	0	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative	Log Pow		3,74-				High
potential:			5,24				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Log Koc		3,75			OECD 121 (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using HPLC)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	AOX		0	%			No
Water solubility:							Slight
Hydrocarbons, C10, aror	natice >1% non	hthalana					
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



œ							
Page 14 of 18							
Safety data sheet according	ng to Regulation	(EC) No 19	07/2006, Anr	nex II			
Revision date / version: 02			,				
Replacing version dated /	version: 17.02.20	022 / 0030					
Valid from: 02.09.2022		/					
PDF print date: 02.09.202	2						
Pro-Line JetClean Diesel-							
	e jetem rtenniger						
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,48	mg/l	Daphnia magna		Analogous
			- / -	5			conclusion
12.3. Bioaccumulative	BCF		99-5780				High
potential:							
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus		
					mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
2.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell		
, ,				U	a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell		
, 5				0	a subcapitata		
12.2. Persistence and		28d	58	%	activated sludge	OECD 301 F	Analogous
degradability:						(Ready	conclusion
5 ,						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Pow		2,8-6,5				High
potential:	5						U
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
	1	1			1	l	
Naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l	Oncorhynchus	OECD 203 (Fish,	
-				-	mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	LC50	27d	0,12	mg/l	Oncorhynchus	,	
-				Ŭ	mykiss		
12.3 Bioaccumulative	BCE		36 5-168				

	2000	210	0,12	iiig/i	mykiss		
12.3. Bioaccumulative potential:	BCF		36,5-168				Low
12.1. Toxicity to daphnia:	EC50	48h	2,16	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	>60d	0,59	mg/l	Daphnia pulex		125d
12.1. Toxicity to algae:	EC50	96h	2,96	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	>74	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.2. Persistence and degradability:		28d	0-2	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,4			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	(25°C)

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.



Page 15 of 18	
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II	
Revision date / version: 02.09.2022 / 0031	
Replacing version dated / version: 17.02.2022 / 0030	
Valid from: 02.09.2022	
PDF print date: 02.09.2022	
Pro-Line JetClean Diesel-System-Reiniger	
· · ·	_

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 07 07 04 other organic solvents, washing liquids and mother liquors 14 06 03 other solvents and solvent mixtures Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. Implement substance recycling. E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

œ

14.1. UN number or ID number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

~ 97,7 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information



Page 16 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

ആ

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H228 Flammable solid.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH044 Risk of explosion if heated under confinement.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic Acute Tox. — Acute toxicity - oral Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation Carc. — Carcinogenicity STOT SE — Specific target organ toxicity - single exposure - narcotic effects Flam. Sol. — Flammable solid Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHÁ Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)



-089				
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II				
Revision date / version: 02.09.2022 / 0031				
Replacing version dated / version: 17.02.2022 / 0030				
Valid from: 02.09.2022				
PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger				
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)				
BCF Bioconcentration factor				
BSEF The International Bromine Council				
bw body weight				
CAS Chemical Abstracts Service CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances				
CMR carcinogenic, mutagenic, reproductive toxic				
DMEL Derived Minimum Effect Level				
DNEL Derived No Effect Level DOC Dissolved organic carbon				
dw dry weight				
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance				
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)				
EC European Community				
ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect				
EEC European Economic Community				
EINECS European Inventory of Existing Commercial Chemical Substances				
ELINCS European List of Notified Chemical Substances				
EN European Norms EPA United States Environmental Protection Agency (United States of America)				
$ErCx$, $E\mu Cx$, $ErLx$ (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)				
etc. et cetera				
EU European Union				
EVAL Ethylene-vinyl alcohol copolymer				
Fax. Fax number gen. general				
gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals				
GWP Global warming potential				
Koc Adsorption coefficient of organic carbon in the soil				
Kow octanol-water partition coefficient				
IARC International Agency for Research on Cancer IATA International Air Transport Association				
IBC (Code) International Bulk Chemical (Code)				
IMDG-code International Maritime Code for Dangerous Goods				
incl. including, inclusive				
IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry				
LC50 Lethal Concentration to 50 % of a test population				
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)				
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil				
Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities				
MARPOL International Convention for the Prevention of Marine Pollution from Ships				
n.a. not applicable				
n.av. not available				
n.c. not checked				
n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA)				
NLP No-longer-Polymer				
NOEC, NOEL No Observed Effect Concentration/Level				
OECD Organisation for Economic Co-operation and Development				
org. organic OSHA Occupational Safety and Health Administration (USA)				
OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic				
PE Polyethylene				
PNEC Predicted No Effect Concentration				
ppm parts per million				
PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,				
Evaluation, Authorisation and Restriction of Chemicals)				
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List				
Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.				



Page 18 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.09.2022 / 0031 Replacing version dated / version: 17.02.2022 / 0030 Valid from: 02.09.2022 PDF print date: 02.09.2022 Pro-Line JetClean Diesel-System-Reiniger

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.