

Page 1 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ആ

Pro-Line JetClean Diesel-System-Reiniger

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

System cleaner for vehicle fuel units (diesel engines) Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

(B) LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Landspitali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland) **Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

	of the substance or mixtu ording to Regulation (EC)	
Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 17

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger



Danger

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P273-Avoid release to the environment.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH044-Risk of explosion if heated under confinement. EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10, aromatics, <1% naphthalene Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

^{n.a.} 3.2 Mixtures

01-2119457273-39-XXXX
918-481-9
75-<90
EUH066
Asp. Tox. 1, H304
ATE (oral): >5000 mg/kg
ATE (dermal): >3160 mg/kg
ATE (as inhalation): >4951 mg/m3
01-2119463583-34-XXXX
918-811-1
(64742-94-5)
1-<2,5



Page 3 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors

EUH066 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

2-ethylhexyl nitrate	
Registration number (REACH)	01-2119539586-27-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	248-363-6
CAS	27247-96-7
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH044
	EUH066
	Acute Tox. 4, H302
	Acute Tox. 4, H312
	Acute Tox. 4, H332
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	ATE (oral): 500 mg/kg
	ATE (dermal): 1100 mg/kg
	ATE (as inhalation, Aerosol): 1,5 mg/l/4h
	ATE (as inhalation, Vapours): 11 mg/l/4h

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here. The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

reddening of the skin drying of the skin. nausea vomiting Danger of aspiration.



Page 4 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

oedema of the lungs

ആ

Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Extinction powder Foam

Unsuitable extinguishing media High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling



Page 5 of 17

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

7.1.1 General recommendations

Ensure good ventilation. Keep away from sources of ignition - Do not smoke. Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Under all circumstances prevent penetration into the soil.

Do not store with oxidizing agents.

Store in a well ventilated place.

Protect from direct sunlight and warming. Store cool.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic	s, <2% aromatics	
WEL-TWA: 800 mg/m3	WEL-STEL:		
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c (81) 	03 571)	
	 Draeger - Hydrocarbons 2/a (81 03 9 	581)	
	 Compur - KITA-187 S (551 174) 		
BMGV:		Other information:	(OEL acc. to RCP-method,
		paragraphs 84-87,	EH40)
Chemical Name	Hydrocarbons, C10, aromatics, <1% naphthalene		
WEL-TWA: 500 mg/m3 (Aromatics	s) WEL-STEL:		
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c (81) 	03 571)	
	 Draeger - Hydrocarbons 2/a (81 03 9 	581)	
	- Compur - KITA-187 S (551 174)		
BMGV:		Other information:	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term	DNEL	32	mg/m3	
Consumer	Human - oral	Long term	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term	DNEL	12,5	mg/kg bw/day	



- (B)
Page 6 of 17
0
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.07.2024 / 0033
Replacing version dated / version: 03.07.2023 / 0032
Valid from: 01.07.2024
PDF print date: 01.07.2024
Pro-Line JetClean Diesel-System-Reiniger

Workers / employees	Human - inhalation	Long term	DNEL	151	mg/m3	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,8	µg/l	
	Environment - marine		PNEC	0,08	µg/l	
	Environment - soil		PNEC	0,00019 1	mg/kg dw	
	Environment - sediment, freshwater		PNEC	0,00074	mg/kg dw	
	Environment - sediment, marine		PNEC	0,00074	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,52	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,087	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,025	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	0,022	mg/cm2	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0.044	ma/cm2	

Dimethyl adipate						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - marine		PNEC	0,0018	mg/l	
	Environment - soil		PNEC	0,09	mg/kg	
	Environment - sediment,		PNEC	0,016	mg/kg	
	marine					
	Environment - sediment,		PNEC	0,16	mg/kg	
	freshwater					
	Environment - freshwater		PNEC	0,018	mg/l	
	Environment - sporadic		DNEL	0,18	mg/l	
	(intermittent) release				_	
Industrial	Human - inhalation	Long term	DNEL	8,3	mg/m3	
Consumer	Human - inhalation	Long term	DNEL	5	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - inhalation		DNEL	8,3	mg/m3	
	Environment - sediment, marine		PNEC	0,015	mg/kg	
	Environment - sediment, freshwater		PNEC	0,15	mg/kg	
	Environment - marine		PNEC	0,0031	mg/l	
	Environment - freshwater		PNEC	0,031	mg/l	
	Environment - soil		PNEC	0,113	mg/kg	
	Environment - sporadic (intermittent) release		PNEC	0,31	mg/l	

🐵 - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference



Page 7 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL))

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

ആ

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN ISO 374). If applicable Protective nitrile gloves (EN ISO 374). Protective gloves made of polyvinyl alcohol (EN ISO 374). Protective Viton® / fluoroelastomer gloves (EN ISO 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: > 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.



Page 8 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

No information available at present.

Liquid Yellow. Clear Characteristic There is no information available on this parameter. 63 °C There is no information available on this parameter. There is no information available on this parameter. n.a. <7 mm2/s (40°C) Insoluble Does not apply to mixtures. There is no information available on this parameter. 0,8308 g/ml (20°C) There is no information available on this parameter. Does not apply to liquids.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** Risk of explosion if heated under confinement. **10.4 Conditions to avoid** Heating, open flame, ignition sources Pressure increase will result in danger of bursting. **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products**

10.6 Hazardous decomposition produc

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



Page 9 of 17 Safety data sheet according to Re	egulation (FC)	No 1907/2006, Ar	nnex II			
Revision date / version: 01.07.20	24 / 0033	NO 1307/2000, AI	IIICA II			
Replacing version dated / version		/ 0032				
Valid from: 01.07.2024	. 03.07.2023	/ 0032				
PDF print date: 01.07.2024						
Pro-Line JetClean Diesel-System	-Reiniger					
Possibly more information on hea	lth effects, see	e Section 2.1 (clas	sification).			
Pro-Line JetClean Diesel-Syste	m-Reiniger	, , , , , , , , , , , , , , , , , , ,	,			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg	Ŭ.		calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value
						Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value
			_			Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:				1		n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						1
Specific target organ toxicity -				1		n.d.a.
repeated exposure (STOT-RE):						n.u.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Symptoms.						11.u.a.
Hydrocarbons, C10-C13, n-alka	nac isaalkan	oc ovaliac 20/	aromation			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>5000		Rat	OECD 401 (Acute Oral	NOLES
Acute toxicity, by oral route.	AIE	>5000	mg/kg	Rai		
Agute toxicity, by dermal routes	ATE	>3160	malka	Rabbit	Toxicity) OECD 402 (Acute	
Acute toxicity, by dermal route:	AIE	>3100	mg/kg	Rabbit		
Aguta toxicity, by inholation;	ATE	>4951		Rat	Dermal Toxicity) OECD 403 (Acute	
Acute toxicity, by inhalation:	AIE	>4951	mg/m3	Rai		
Skin corrosion/irritation:					Inhalation Toxicity)	Not irritopt
Skin conosion/imation.					OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin					OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	Analogous
						conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Carcinogenicity:					OECD 453 (Combined	Negative,
					Chronic	Analogous
					Toxicity/Carcinogenicity	conclusion
					Studies)	
Reproductive toxicity:			+		OECD 414 (Prenatal	Negative,
					Developmental Toxicity	
						Analogous
Coopilio torget error touisity					Study)	conclusion
Specific target organ toxicity -					OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):					Dose 90-Day Oral	Analogous
					Toxicity Study in	conclusion
	1	1	1	1	Rodents)	1
Aspiration hazard:						Yes



Safety data sheet according to Revision date / version: 01.07.20 Replacing version dated / version Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System	24 / 0033 n: 03.07.2023		5, Annex II			
Symptoms:						unconsciousness , headaches, dizziness, mucous membrane irritation
Hydrocarbons, C10, aromatics,	, <1% naphtha	lene				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusionoral
Reproductive toxicity (Effects on fertility):				Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative, Analogous conclusioninhala iv
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	>0,38	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Vapours, Analogous conclusion13 weeks
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	900	mg/m3	Rat	OECD 452 (Chronic Toxicity Studies)	Vapours, Analogous conclusion12 months
Aspiration hazard: Symptoms:						Yes headaches, dizziness, fatigue, nausea and vomiting.



œ						
Page 11 of 17		N- 4007/000	0 A			
Safety data sheet according to R		No 1907/2006	6, Annex II			
Revision date / version: 01.07.20		10000				
Replacing version dated / version	n: 03.07.2023	/ 0032				
Valid from: 01.07.2024						
PDF print date: 01.07.2024	_					
Pro-Line JetClean Diesel-System	n-Reiniger					
Symptoms:						drowsiness,
Cymptoms.						headaches,
						drowsiness,
						dizziness
						uizziness
2-ethylhexyl nitrate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	500	mg/kg			
Acute toxicity, by dermal route:	ATE	1100	mg/kg			
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
					,	cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	,
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
0,					Mammalian Cell Gene	U
					Mutation Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
0, 1				U U	Mammalian	U
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
,-				typhimurium	Reverse Mutation Test)	
Reproductive toxicity:	NOAEL	20	mg/kg	Rat	OECD 421	Negative, oral
			bw/d		(Reproduction/Developm	
			5 m/ G		ental Toxicity Screening	
					Test)	
Specific target organ toxicity -	NOAEL	500	mg/kg	Rabbit		Negativedermal
repeated exposure (STOT-RE),			bw/d			
dermal:			2.174			
Specific target organ toxicity -	NOAEL	863	mg/m3	Rat	OECD 413 (Subchronic	Vapours,
repeated exposure (STOT-RE),					Inhalation Toxicity - 90-	Analogous
inhalat.:					Day Study)	conclusion(90 d)
Symptoms:						headaches,
cympionio.						dizziness,
						nausea, drop in
						blood pressure,
						diarrhoea,
						unconsciousness
						, eyes, reddened
						, cycs, reduelled

11.2. Information on other hazards

Pro-Line JetClean Diesel-System-Reiniger						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.
Hydrocarbons C10-C13 n-alka	nos isoalkan	os cyclics /	2% aromatics			

nydrocarbons, c ro-c rs, n-aikanes, isoaikanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint Value	Unit	Organism	Test method	Notes		



GB							
Page 12 of 17							
Safety data sheet accordin			07/2006, An	nex II			
Revision date / version: 07	1.07.2024 / 003	33					
Replacing version dated /	version: 03.07.2	2023 / 0032					
Valid from: 01.07.2024							
PDF print date: 01.07.202	4						
Pro-Line JetClean Diesel-	System-Reinige	er					
Other information:							Repeated
							exposure may
							cause skin
							dryness or
							cracking.
							Clacking.
		SECTI	ON 12: E	Ecologia	cal informatio	n	
				•			
					(;)		
Possibly more information			ee Section 2	.1 (classifica	ation).		
Pro-Line JetClean Diese Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	Lindpoint	11110	Value	Unit	organishi	rest method	n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							
degradability.							as possible with
12.3. Bioaccumulative							an oil separator. n.d.a.
							n.a.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
							D
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.

effects:				available on other adverse
				effects on the
				environment.
Other information:				DOC-elimination
				degree(complexi
				ng organic
				substance)>=
				80%/28d: No
Other information:	AOX	0	%	According to the
				recipe, contains
				no ÁOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		10-2500				High



Page 13 of 17 Safety data sheet accordin Revision date / version: 07 Replacing version dated / Valid from: 01.07.2024 PDF print date: 01.07.202 Pro-Line JetClean Diesel-	1.07.2024 / 003 version: 03.07. 4	33 2023 / 0032		nex II			
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		
Water solubility:							Product floats of the water surface.
Hydrocarbons, C10, aro	matics <1% na	nhthalono					
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2-5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	2 - 5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	3 -10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	>1 -3	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition	

		1211		ing/i	subcapitata	Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	49,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable., Inherent
12.3. Bioaccumulative potential:	BCF		<100				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,83	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	EC50	72h	>2,53	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:	DOC	28d	0	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,24			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	High
12.3. Bioaccumulative potential:	BCF		1332				



Page 14 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

œ

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling. E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely. Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements Transport by road/by roil (ADD/DID)

Transport by road/by rail (ADR/RID)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable
Transport by sea (IMDG-code)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	Not applicable
Transport by air (IATA)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable



Page 15 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

14.4. Packing group:14.5. Environmental hazards:14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

Not applicable

Not applicable

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

97 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

Employee instruction/training in handling hazardous materials is required.

SECTION 16: Other information

Revised sections: These details refer to the product as it is delivered.

ആ

2, 3, 8, 9, 11, 12, 14, 15, 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH044 Risk of explosion if heated under confinement.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic STOT SE — Specific target organ toxicity - single exposure - narcotic effects Acute Tox. — Acute toxicity - oral Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).



Page 16 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger

Safety data sheets for the constituent substances. ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

ആ

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) Adsorbable organic halogen compounds AOX approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon for example (abbreviation of Latin 'exempli gratia'), for instance e.a. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community FFC FINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera **European Union** EU EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships



ആ Page 17 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.07.2024 / 0033 Replacing version dated / version: 03.07.2023 / 0032 Valid from: 01.07.2024 PDF print date: 01.07.2024 Pro-Line JetClean Diesel-System-Reiniger mg/kg bw mg/kg body weight mg/kg bw/d, mg/kg bw/day mg/kg body weight/day mg/kg dw mg/kg dry weight mg/kg wet weight mg/kg wwt not applicable n.a. not available n.av. n.c. not checked n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic ora. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm **PVC** Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical REACH-IT List-No. identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. Total organic carbon TOC UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.