

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Motorbike 4T 15W-50 Street

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Motor oil

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

Page 2 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Baseoil - unspecified *</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	---
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Asp. Tox. 1, H304
<b>Distillates (petroleum), hydrotreated light paraffinic</b>	
<b>Registration number (REACH)</b>	01-2119487077-29-XXXX
<b>Index</b>	649-468-00-3
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	265-158-7
<b>CAS</b>	64742-55-8
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Asp. Tox. 1, H304
<b>Bis(nonylphenyl)amine</b>	
<b>Registration number (REACH)</b>	01-2119488911-28-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	253-249-4
<b>CAS</b>	36878-20-3
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Aquatic Chronic 4, H413
<b>Specific Concentration Limits and ATE</b>	ATE (oral): >10000 mg/kg ATE (dermal): >5000 mg/kg ATE (as inhalation, Aerosol): >20

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

\* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP, REACH-IT List-No.	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:  
 Solvent

Page 3 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0008  
Replacing version dated / version: 26.05.2020 / 0007  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Motorbike 4T 15W-50 Street

Thinners

### **Eye contact**

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### **Ingestion**

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.

### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

Oil acne

On vapour formation:

Irritation of the respiratory tract

Ingestion:

Gastrointestinal disturbances

Nausea

Vomiting

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### **4.3 Indication of any immediate medical attention and special treatment needed**

n.c.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

CO<sub>2</sub>

Foam

Dry extinguisher

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

Oxides of phosphorus

Toxic gases

Flammable vapour/air mixtures

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Page 4 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

Ensure sufficient supply of air.  
 Avoid formation of oil mist.  
 Avoid contact with eyes or skin.  
 If applicable, caution - risk of slipping.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

## 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.  
 Oil binder  
 Do not wash away with water or watery cleaning agents.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Avoid formation of oil mist.  
 Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Do not heat to temperatures close to flash point.  
 Avoid contact with eyes.  
 Avoid long lasting or intensive contact with skin.  
 Do not carry cleaning cloths soaked in product in trouser pockets.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Under all circumstances prevent penetration into the soil.  
 Store at room temperature.  
 Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---	

**Distillates (petroleum), hydrotreated light paraffinic**

GB

Page 5 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	

Bis(nonylphenyl)amine						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	132000	mg/kg dw	
	Environment - sediment, marine		PNEC	13200	mg/kg dw	
	Environment - soil		DNEL	263000	mg/kg dw	
	Environment - periodic release		PNEC	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,25	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,09	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,31	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,62	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,37	mg/m3	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

Page 6 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0008  
Replacing version dated / version: 26.05.2020 / 0007  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Motorbike 4T 15W-50 Street

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.  
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. EN 14042.  
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:  
Protective gloves, oil resistant (EN ISO 374).  
If applicable  
Protective nitrile gloves (EN ISO 374).  
Minimum layer thickness in mm:  
0,4  
Permeation time (penetration time) in minutes:  
> 480  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.  
Protective PVC gloves (EN ISO 374).  
Protective Viton® / fluoroelastomer gloves (EN ISO 374).  
Protective hand cream recommended.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
Normally not necessary.  
With oil mist formation:  
Filter A2 P2 (EN 14387), code colour brown, white  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Page 7 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	230 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	140 mm <sup>2</sup> /s (40°C)
Kinematic viscosity:	18,3 mm <sup>2</sup> /s (100°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,870 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

## 9.2 Other information

Explosives:	Product is not explosive.
Oxidising liquids:	No
Bulk density:	n.a.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not to be expected

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Motorbike 4T 15W-50 Street						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.

Page 8 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Baseoil - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin sensitisation:						No (skin contact), Analogous conclusion
Symptoms:						mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

Distillates (petroleum), hydrotreated light paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion dermal
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Analogous conclusion dermal
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	<30	mg/kg bw/d	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion





Page 10 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

**Baseoil - unspecified**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

**Distillates (petroleum), hydrotreated light paraffinic**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.3. Bioaccumulative potential:							Not to be expected
12.1. Toxicity to daphnia:	EL50	48h	> 10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>6				@20°C
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Bis(nonylphenyl)amine**

Page 11 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	24	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.4. Mobility in soil:							Adsorption in ground.
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	> 100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>10	mg/l	Desmodesmus subspicatus		Analogous conclusion
12.2. Persistence and degradability:		28d	1	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>7,6				A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	BCF		1730				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Page 12 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

15 01 01 paper and cardboard packaging  
 15 01 02 plastic packaging  
 15 01 04 metallic packaging  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Classification code:

LQ:

14.5. Environmental hazards:

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine Pollutant:

14.5. Environmental hazards:

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards:

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

1-16

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Page 13 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0008  
 Replacing version dated / version: 26.05.2020 / 0007  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Motorbike 4T 15W-50 Street

Asp. Tox. — Aspiration hazard  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
 Guidelines for the preparation of safety data sheets as amended (ECHA).  
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
 Safety data sheets for the constituent substances.  
 ECHA Homepage - Information about chemicals.  
 GESTIS Substance Database (Germany).  
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
 National Lists of Occupational Exposure Limits for each country as amended.  
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association

Page 14 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0008  
Replacing version dated / version: 26.05.2020 / 0007  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Motorbike 4T 15W-50 Street

IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCILID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.