

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Bremsen-Antiquietschspray Brake Anti-Squeal Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 17.01.2024 / 0020

Replacing version dated / version: 28.08.2022 / 0019

Valid from: 17.01.2024

PDF print date: 17.01.2024

Bremsen-Antiquietschspray

Brake Anti-Squeal Spray



Danger

H315-Causes skin irritation. H318-Causes serious eye damage. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Without adequate ventilation, formation of explosive mixtures may be possible.

Calcium dihydroxide

Hydrocarbons, C6, isoalkanes, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Registration number (REACH)	01-2119484651-34-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	931-254-9
CAS	(64742-49-0)
content %	20-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	---
Index	649-467-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	265-157-1

Page 3 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

CAS	64742-54-7
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Calcium dihydroxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	215-137-3
CAS	1305-62-0
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	
Registration number (REACH)	---
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

Irritation of the respiratory tract

Coughing

Headaches

Nausea

Effects/damages the central nervous system

Page 4 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 17.01.2024 / 0020
Replacing version dated / version: 28.08.2022 / 0019
Valid from: 17.01.2024
PDF print date: 17.01.2024
Bremsen-Antiquietschspray
Brake Anti-Squeal Spray

Narcotic effect.
With long-term contact:
Dermatitis (skin inflammation)
Drying of the skin.
Other dangerous properties cannot be ruled out.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Extinction powder
Sand

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Toxic gases
Danger of bursting (explosion) when heated
Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.
Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.
Without adequate ventilation, formation of explosive mixtures may be possible.
Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.
Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

- Ensure good ventilation.
- Keep away from sources of ignition - Do not smoke.
- Take measures against electrostatic charging, if appropriate.
- Do not use on hot surfaces.
- Avoid contact with eyes or skin.
- Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
- Observe directions on label and instructions for use.
- Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

- General hygiene measures for the handling of chemicals are applicable.
- Wash hands before breaks and at end of work.
- Keep away from food, drink and animal feedingstuffs.
- Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

- Keep out of access to unauthorised individuals.
- Not to be stored in gangways or stair wells.
- Store product closed and only in original packing.
- Do not store with oxidizing agents.
- Observe special regulations for aerosols!
- Observe special storage conditions.
- Keep protected from direct sunlight and temperatures over 50°C.
- Store in a well ventilated place.

7.3 Specific end use(s)

- No information available at present.
- Observe the instructions for good working practice and the recommendations for risk assessment.
- Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

GB Chemical Name	Hydrocarbons, C6, isoalkanes, <5% n-hexane	
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

GB Chemical Name	Calcium dihydroxide	
WEL-TWA: 1 mg/m ³ (9) (WEL-TWA, EU)	WEL-STEL: 4 mg/m ³ (9) (WEL-STEL, EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission Spectrometry), Part 1-3 - 2012(Part 1), 2012(Part 2), 2004 (Part 3) - NIOSH 7020 (CALCIUM and compounds, as Ca) - 1994 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 42-4 (2004) - OSHA PV2121 (Gravimetric Determination) - 2003 	
BMGV: ---	Other information: ---	

GB Chemical Name	Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)

GB

Page 6 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

WEL-TWA: 10 mg/m3 (total inhalable dust), 4 mg/m3 (respirable dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Chemical Name	Butane	
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993	
BMGV: ---	Other information: ---	

Chemical Name	Propane	
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990	
BMGV: ---	Other information: ---	

Chemical Name	Isobutane	
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV: ---	Other information: ---	

Hydrocarbons, C6, isoalkanes, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3	

Calcium dihydroxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,49	mg/l	
	Environment - soil		PNEC	1080	mg/kg dw	
	Environment - marine		PNEC	0,32	mg/l	
	Environment - sewage treatment plant		PNEC	3	mg/l	

GB

Page 7 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

	Environment - sporadic (intermittent) release		DMEL	0,49	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/EC). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/EC). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/EC), (14) = The substance can cause sensitisation of the skin (2004/37/EC). |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

Page 8 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 >= 0,4
 Permeation time (penetration time) in minutes:
 <= 480
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 At high concentrations:
 Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 See above.

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Light grey
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	n.a.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	1,0 Vol-%
Upper explosion limit:	10,9 Vol-%
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	200 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.

Page 9 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Solubility: Insoluble
 Partition coefficient n-octanol/water (log value): Does not apply to mixtures.
 Vapour pressure: 4300 hPa (20°C)
 Density and/or relative density: 0,63 g/ml (20°C)
 Relative vapour density: Vapours heavier than air.
 Particle characteristics: Does not apply to aerosols.

9.2 Other information

Explosives: Product is not explosive. When using: development of explosive vapour/air mixture possible.
 Oxidising liquids: No
 Evaporation rate: n.a.
 Bulk density: n.a.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Heating, open flame, ignition sources
 Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Bremsen-Antiquietschspray Brake Anti-Squeal Spray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C6, isoalkanes, <5% n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

Page 10 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Acute toxicity, by inhalation:	LC50	259354	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Skin Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Reproductive toxicity:	NOAEC	10560	mg/m3	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Aspiration hazard:						Asp. Tox. 1
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion 78 weeks, dermal

Page 11 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion dermal
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion oral
Aspiration hazard:						Asp. Tox. 1
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Symptoms:						gastrointestinal disturbances, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,22	mg/l	Rat		Dust, Mist, Analogous conclusion 4 weeks

Calcium dihydroxide

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:					OECD 431 (In Vitro Skin Corrosion - Human Skin Model Test)	Non-caustic
Skin corrosion/irritation:				Rabbit		Irritant, in vivo
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						breathing difficulties, abdominal pain, drowsiness, thirst, fever, sore throat, cornea opacity, coughing, headaches, mucous membrane irritation, fatigue

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

Page 12 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract). (90d)
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		(90d)
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.

Butane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

Page 13 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Page 14 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
---	-------	--------	------	-----	--	--

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness , frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

11.2. Information on other hazards

Bremsen-Antiquietschspray Brake Anti-Squeal Spray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Bremsen-Antiquietschspray Brake Anti-Squeal Spray							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.

Page 15 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

12.7. Other adverse effects:							No information available on other adverse effects on the environment.
------------------------------	--	--	--	--	--	--	---

Hydrocarbons, C6, isoalkanes, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	4,09	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	EC50	96h	18,27	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	7,14	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	13,56	mg/l	Pseudokirchneriella subcapitata	QSAR	
12.1. Toxicity to algae:	ErL50	72h	55	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable (Analogous conclusion), Analogous conclusion
12.3. Bioaccumulative potential:	Log Kow		4				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	48h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

12.3. Bioaccumulative potential:	Log Pow		3,9-6				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			

Calcium dihydroxide

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	160	mg/l	Gambusia affinis	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	457	mg/l			marine water
12.1. Toxicity to fish:	LC50	96h	50,6	mg/l			freshwater
12.1. Toxicity to daphnia:	NOEC/NOEL	14d	32	mg/l			marine water
12.1. Toxicity to daphnia:	LC50	96h	158	mg/l			marine water
12.1. Toxicity to daphnia:	EC50	48h	49,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	184,57	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	48	mg/l			freshwater
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Calcium dihydroxide, which is sparingly soluble, presents a low mobility in most soils.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.6. Endocrine disrupting properties:							Not to be expected
12.7. Other adverse effects:							pH-value of > 12 will rapidly decrease as result of dilution and carbonation., Even though this product can be used to neutralise over-acidified water, when 1g/l is exceeded organisms in the water may be affected adversely.

Page 17 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Toxicity to bacteria:							In high concentrations the product provokes an increase in temperature and of the pH-value. It is used to sanitise sewage sludge
Other organisms:	NOEC/NOEL		2000	mg/kg dw			soil macroorganisms
Other organisms:	NOEC/NOEL		12000	mg/kg dw			soil microorganisms
Other organisms:	NOEC/NOEL	21d	1080	mg/kg			terrestrial plants

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriella subcapitata	U.S. EPA-600/9-78-018	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:	BCF	42d	9,6				Not to be expected
12.3. Bioaccumulative potential:	BCF	14d	19-352				Oncorhynchus mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C

Butane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 18 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
Classification code:	5F	



Page 19 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

LQ: 1 L
 Transport category: 2

Transport by sea (IMDG-code)

14.1. UN number or ID number: 1950
 14.2. UN proper shipping name:
 UN 1950 AEROSOLS
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable
 Marine Pollutant: Not applicable
 EmS: F-D, S-U



Transport by air (IATA)

14.1. UN number or ID number: 1950
 14.2. UN proper shipping name:
 UN 1950 Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.
 For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Page 20 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

Directive 2010/75/EU (VOC): < 84,9 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H225 Highly flammable liquid and vapour.
 H351 Suspected of causing cancer by inhalation.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation
 Eye Dam. — Serious eye damage
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Aerosol — Aerosols
 Flam. Liq. — Flammable liquid
 Asp. Tox. — Aspiration hazard
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 Carc. — Carcinogenicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

Page 21 of 22
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 17.01.2024 / 0020
 Replacing version dated / version: 28.08.2022 / 0019
 Valid from: 17.01.2024
 PDF print date: 17.01.2024
 Bremsen-Antiquietschspray
 Brake Anti-Squeal Spray

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable

Page 22 of 22
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 17.01.2024 / 0020
Replacing version dated / version: 28.08.2022 / 0019
Valid from: 17.01.2024
PDF print date: 17.01.2024
Bremsen-Antiquietschspray
Brake Anti-Squeal Spray

n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.