

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

# **Bremsfluessigkeit SL6 DOT 4**

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Hydraulic fluid
Uses advised against:
No information available at present.

## 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## 1.4 Emergency telephone number Emergency information services / official advisory body:

**Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard classHazard categoryRepr.2

Hazard statement H361d-Suspected of damaging the unborn child.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

H361d-Suspected of damaging the unborn child.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P201-Obtain special instructions before use. P280-Wear protective gloves / protective clothing / eye protection / face protection. P308+P313-IF exposed or concerned: Get medical advice / attention. P405-Store locked up. P501-Dispose of contents / container to an approved waste disposal facility.

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

#### 2.3 Other hazards

ആ

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

Polyalkylene glycols and additives

#### 3.1 Substances

## n.a. 3.2 Mixtures

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	
Registration number (REACH)	01-2119462824-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	250-418-4
CAS	30989-05-0
content %	25-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361d

01-2119531322-53-XXXX
907-996-4
1-<5
Eye Dam. 1, H318
Eye Dam. 1, H318: >=30 %
Eye Irrit. 2, H319: >=20 %
01-2119475444-34-XXXX
603-083-00-7
203-820-9
110-97-4
1-<2.5

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors Eye Irrit. 2, H319

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## **SECTION 4: First aid measures**



Page 3 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

## 4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

## Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Nitro gases Oxides of carbon Toxic gases

## **5.3 Advice for firefighters**

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Dispose of contaminated extinction water according to official regulations.

**SECTION 6: Accidental release measures** 

## 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

## 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

ആ

Avoid contact with eyes or skin.

Pregnant women should avoid contact with this product.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Keep away from combustible material.

Store at room temperature.

Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,211	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,112	mg/l	
	Environment - marine		PNEC	0,021	mg/l	
	Environment - sediment, freshwater		PNEC	0,76	mg/kg dw	
	Environment - sediment, marine		PNEC	0,076	mg/kg dw	
	Environment - soil		PNEC	0,028	mg/kg dw	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	7,2	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	4,1	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,1	mg/kg bw/d	



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

œ

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	29,1	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/d	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	0,2	mg/l	
	Environment - sporadic (intermittent) release		PNEC	1,8	mg/l	
	Environment - sewage treatment plant		PNEC	500	mg/l	
	Environment - sediment, freshwater		PNEC	6,6	mg/kg dw	
	Environment - sediment, marine		PNEC	0,66	mg/kg dw	
	Environment - soil		PNEC	0,46	mg/kg dw	
	Environment - oral (animal feed)		PNEC	111	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	12,5	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	117	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	208	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	195	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0.2777	mg/l	
	Environment - marine		PNEC	0,02777	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,777	mg/l	
	Environment - sediment, freshwater		PNEC	2,33	mg/kg dw	
	Environment - sediment, marine		PNEC	0,233	mg/kg dw	
	Environment - soil		PNEC	0,303	mg/kg dw	
	Environment - sewage treatment plant		PNEC	15000	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	3,9	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	6,3	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,3	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,4	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d	

2-(2-(2-methoxyethoxy)ethoxy)ethanol



Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	50	mg/l	
	Environment - sediment, freshwater		PNEC	36,6	mg/kg dw	
	Environment - sediment, marine		PNEC	3,66	mg/kg dw	
	Environment - soil		PNEC	1,56	mg/kg dw	
	Environment - sewage treatment plant		PNEC	200	mg/l	
	Environment - oral (animal feed)		PNEC	89	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	93	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	156	mg/m3	

#### 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

ആ

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). With short-term contact: Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0.4 Permeation time (penetration time) in minutes: 30 With long-term contact: Protective gloves in butyl rubber (EN ISO 374). Minimum layer thickness in mm: 0.7 Permeation time (penetration time) in minutes: 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).



Page 7 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Yellow Characteristic Odour: Melting point/freezing point: <-70 °C (ASTM D 1177) Boiling point or initial boiling point and boiling range: ~265 °C (ASTM D 1120) Flammability: Flammable Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. ~136 °C (ISO 2719 (Pensky-Martens, closed cup)) Flash point: Auto-ignition temperature: >300 °C (DIN 51794) Decomposition temperature: ~360 °C pH: ~8 (50 %, 20°C, ASTM D 1287) Kinematic viscosity: ~12,3 mm2/s (20°C, DIN 51562) Solubility: Mixable 20°C Does not apply to mixtures. Partition coefficient n-octanol/water (log value): Vapour pressure: ~0,27 Pa (20°C) Density and/or relative density: ~1,06 g/cm3 (20°C, DIN 51757) Relative vapour density: There is no information available on this parameter. Particle characteristics: Does not apply to liquids. 9.2 Other information Explosives: Product is not explosive. Oxidising liquids: No

## **SECTION 10: Stability and reactivity**

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
See also section 7.
Strong heat
Decomposition:
T ~ 360°C (DSC)
Protect from humidity.
Product is hygroscopic.
10.5 Incompatible materials



Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

See also section 7. None known **10.6 Hazardous decomposition products** 

See also section 5.2 No decomposition when used as directed.

œ)

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

oxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	-					n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral				
					Toxicity)				
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute				
					Dermal Toxicity)				
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant			
					Dermal				
					Irritation/Corrosion)				
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant			
					Irritation/Corrosion)				
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative			
					Reverse Mutation Test)				
Reproductive toxicity:	NOAEL	250	mg/kg	Rabbit	OECD 414 (Prenatal				
			bw/d		Developmental Toxicity				
					Study)				

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	3540	mg/kg	Rabbit		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Eye Dam. 1
Serious eye damage/irritation:		>=30	%			Eye Dam. 1
Serious eye damage/irritation:		>=20	%			Eye Irrit. 2
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					in vitro	Negative

1,1'-iminodipropan-2-ol										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Acute toxicity, by oral route:	LD50	4765	mg/kg	Rat						
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)					



Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

Acute toxicity, by dermal route:	LD50	8000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Eye Irrit. 2
					Irritation/Corrosion)	-
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	-

## 11.2. Information on other hazards

(GB)·

Bremsfluessigkeit SL6 DOT 4						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification). Bremsfluessigkeit SL6 DOT 4 Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: n.d.a. 12.1. Toxicity to algae: n.d.a. 12.2. Persistence and n.d.a. degradability: 12.3. Bioaccumulative n.d.a. potential: 12.4. Mobility in soil: n.d.a. 12.5. Results of PBT n.d.a. and vPvB assessment 12.6. Endocrine Does not apply disrupting properties: to mixtures. 12.7. Other adverse n.d.a. effects: Other information: According to the recipe, contains no ÁOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
2.2. Persistence and egradability:		10d	>70	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	
12.1. Toxicity to fish:	LC50	96h	100,3	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>211,2	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

œ

12.1. Toxicity to algae:	EC50	72h	>224,4	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2400	mg/l	Leuciscus idus	DIN 38412 T.15	Analogous
							conclusion
12.1. Toxicity to daphnia:	EC50	8h	2210	mg/l	Daphnia magna		Analogous
							conclusion
12.1. Toxicity to algae:	EC10	72h	612,5	mg/l			Analogous
							conclusion
12.2. Persistence and							Readily
degradability:							biodegradable
Toxicity to bacteria:	EC10	30min	>1995	mg/l	activated sludge	OECD 209	-
-						(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	

1,1'-iminodipropan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	94	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	277,7	mg/l	Daphnia magna	84/449/EEC C.2	
12.1. Toxicity to algae:	EC50	72h	339	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 16 01 13 brake fluids Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant. **For contaminated packing material** Pay attention to local and national official regulations. Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**



Page 11 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

#### **General statements**

14.1. UN number or ID number:	Netannliashla
	Not applicable
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	Not applicable
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for saf	e transport must be followed.
14.7. Maritime transport in bulk acco	
Non-dangerous material according to Transport Regu	JIATIONS.
SECTI	ON 15: Regulatory information
45.4. Opfoto, baskik and any income out	al no mulation all a violation, and ait is far the such stands on minteres
15.1 Safety, health and environment	al regulations/legislation specific for the substance or mixture
Observe restrictions:	
	ernity protection (national implementation of the Directive 92/85/EEC)!
Comply with trade association/occupational health re	
	guianono.

Directive 2010/75/EU (VOC):

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

9

**Revised sections:** 

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Repr. 2, H361d	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H361d Suspected of damaging the unborn child

H361d Suspected of damaging the unborn child. H318 Causes serious eye damage. H319 Causes serious eye irritation. 46,5 %



Page 12 of 13

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4

Repr. — Reproductive toxicity Eye Dam. — Serious eye damage Eye Irrit. — Eye irritation

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as

amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council bw body weight Chemical Abstracts Service CAS Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.q. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America)  $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow IARC International Agency for Research on Cancer International Air Transport Association IATA



ആ Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.11.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 21.11.2022 PDF print date: 21.11.2022 Bremsfluessigkeit SL6 DOT 4 IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million Polyvinylchloride **PVC** REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon United Nations Recommendations on the Transport of Dangerous Goods UN RTDG VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.