

Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

(GB)

Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Hydraulic fluid Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture

 Classification according to Regulation (EC)
 1272/2008 (CLP)

 Hazard class
 Hazard category
 Hazard statement

 Repr.
 2
 H361fd-Suspected of damaging fertility. Suspected of damaging the unborn child.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 14

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4



Warning

H361fd-Suspected of damaging fertility. Suspected of damaging the unborn child.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P201-Obtain special instructions before use. P280-Wear protective gloves / protective clothing / eye protection / face protection. P308+P313-IF exposed or concerned: Get medical advice / attention. P405-Store locked up. P501-Dispose of contents / container to an approved waste disposal facility.

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Polyalkylene glycols and additives

3.1 Substances

n.a. 3.2 Mixtures

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	
Registration number (REACH)	01-2119462824-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	250-418-4
CAS	30989-05-0
content %	30-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361fd

01-2119531322-53-XXXX
907-996-4
3-<10
Eye Dam. 1, H318
Eye Dam. 1, H318: >=30 %
Eye Irrit. 2, H319: >=20 %
01-2119475444-34-XXXX
603-083-00-7



Page 3 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4

Brake Fluid SL6 DOT 4

ആ

EINECS, ELINCS, NLP, REACH-IT List-No.	203-820-9
CAS	110-97-4
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Irrit. 2, H319

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Toxic gases Oxides of carbon

Oxides of nitrogen Nitro gases

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures 6.1.1 For non-emergency personnel



Page 4 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

ആ

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Pregnant women should avoid contact with this product.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Keep away from combustible material.

Store at room temperature. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate								
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note		



Page 5 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

œ.

	Environment - freshwater		PNEC	0,211	mg/l
	Environment - water, sporadic (intermittent) release		PNEC	2,112	mg/l
	Environment - marine		PNEC	0,021	mg/l
	Environment - sediment, freshwater		PNEC	0,76	mg/kg dw
	Environment - sediment, marine		PNEC	0,076	mg/kg dw
	Environment - soil		PNEC	0,028	mg/kg dw
	Environment - sewage treatment plant		PNEC	100	mg/l
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,5	mg/kg bw/d
Consumer	Human - oral	Long term, systemic effects	DNEL	1,5	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	4,2	mg/kg bw/d

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	0,2	mg/l	
	Environment - sporadic (intermittent) release		PNEC	1,8	mg/l	
	Environment - sewage treatment plant		PNEC	500	mg/l	
	Environment - sediment, freshwater		PNEC	6,6	mg/kg dw	
	Environment - sediment, marine		PNEC	0,66	mg/kg dw	
	Environment - soil		PNEC	0,46	mg/kg dw	
	Environment - oral (animal feed)		PNEC	111	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	12,5	mg/kg bw/d	
Consumer	Human - dermal Long term, system effects		DNEL	125	mg/kg bw/d	
Consumer	nsumer Human - inhalation		DNEL	117	mg/m3	
Workers / employees	rs / employees Human - dermal		DNEL	208	mg/kg bw/d	
Workers / employees	kers / employees Human - inhalation		DNEL	195	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,2777	mg/l	
	Environment - marine		PNEC	0,02777	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,777	mg/l	
	Environment - sediment, freshwater		PNEC	2,33	mg/kg dw	



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

œ

	Environment - sediment, marine		PNEC	0,233	mg/kg dw	
	Environment - soil		PNEC	0,303	mg/kg dw	
	Environment - sewage treatment plant		PNEC	15000	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	3,9	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	6,3	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,3	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,4	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	50	mg/l	
	Environment - sediment, freshwater		PNEC	36,6	mg/kg dw	
	Environment - sediment, marine		PNEC	3,66	mg/kg dw	
	Environment - soil		PNEC	1,56	mg/kg dw	
	Environment - sewage treatment plant		PNEC	200	mg/l	
	Environment - oral (animal feed)		PNEC	89	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	93	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	156	mg/m3	

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:



Page 7 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

Chemical resistant protective gloves (EN ISO 374). With short-term contact: Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: 30 With long-term contact: Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0,7

ആ

Permeation time (penetration time) in minutes: 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Gas mask filter ABEK-P3 (EN 14387), code colour brown, grey, yellow, green, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Yellow Odour: Characteristic Melting point/freezing point: <-70 °C (ASTM D 1177) Boiling point or initial boiling point and boiling range: ~265 °C (ASTM D 1120) Flammability: Flammable Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: ~136 °C (ISO 2719 (Pensky-Martens, closed cup)) Auto-ignition temperature: >300 °C (DIN 51794) Decomposition temperature: ~360 °C ~8 (50 %, 20°C, ASTM D 1287) pH: Kinematic viscosity: ~12,3 mm2/s (20°C, DIN 51562) Solubility: Mixable 20°C Partition coefficient n-octanol/water (log value): Does not apply to mixtures. Vapour pressure: ~0,27 Pa (20°C) ~1,06 g/cm3 (20°C, DIN 51757) Density and/or relative density: Relative vapour density: There is no information available on this parameter.



Page 8 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

Particle characteristics: 9.2 Other information

Explosives: Oxidising liquids:

œ

Does not apply to liquids.

Product is not explosive. No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions**

No dangerous reactions are known. **10.4 Conditions to avoid**

See also section 7. Strong heat Decomposition: T ~ 360°C (DSC) Protect from humidity. Product is hygroscopic.

10.5 Incompatible materials

See also section 7. None known

10.6 Hazardous decomposition products

See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Brake Fluid SL6 DOT 4						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)			
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)			



Page 9 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

œ

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
0 ,					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
6 ,					Mammalian	
					Chromosome	
					Aberration Test)	
Reproductive toxicity	NOAEL	250	mg/kg	Rabbit	OECD 414 (Prenatal	Positive
(Developmental toxicity):	-		5.5		Developmental Toxicity	
(Study)	
Reproductive toxicity (Effects	NOAEL	300	mg/kg	Rat	OECD 443 (Extended	Positive
on fertility):					One-Generation	
					Reproductive Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE),	I TOMEL		bw/d		Dose 90-Day Oral	
oral:			Dw/u		Toxicity Study in	
orai.					Rodents)	
	1				Nucerius)	1

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	3540	mg/kg	Rabbit		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Eye Dam. 1
Serious eye damage/irritation:		>=30	%			Eye Dam. 1
Serious eye damage/irritation:		>=20	%			Eye Irrit. 2
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					in vitro	Negative

1,1'-iminodipropan-2-ol Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4765	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	8000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

11.2. Information on other hazards

Bremsfluessigkeit SL6 DOT 4

Brake Fluid SL6 DOT 4						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.



- (GB)							
Page 10 of 14 Safety data sheet accordin Revision date / version: 12			07/2006, An	nex II			
Replacing version dated / Valid from: 12.04.2023	version: 21.11.						
PDF print date: 24.04.202 Bremsfluessigkeit SL6 DC							
Brake Fluid SL6 DOT 4							
Other information:							No other relevant
							information available on adverse effects
							on health.
		SECTI	ON 12: E	Ecologia	cal information		
Possibly more information	on environmen	ntal effects, s	ee Section 2	.1 (classific	ation).		
Bremsfluessigkeit SL6 D Brake Fluid SL6 DOT 4							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae: 12.2. Persistence and							n.d.a. n.d.a.
degradability:							11.u.a.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment 12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							According to the
							recipe, contains no AOX.
Tris[2-[2-(2-methoxyetho	vv)ethovvleth	vl] orthobor	ato				1
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and	DOC	10d	>70	%	activated sludge	OECD 301 A	Readily
degradability:			-		j	(Ready	biodegradable
						Biodegradability -	_
						DOC Die-Away	
	1.050		-			Test)	
12.1. Toxicity to fish:	LC50	96h	>222,2	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>211,2	mg/l	Daphnia magna	OECD 202	
				Ŭ		(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	>224,4	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition Test)	
Toxicity to bacteria:	EC50	30min	>1000	mg/l	activated sludge	OECD 209	
TONICITY TO DAULEHA.		5011111	-1000	ing/i		(Activated Sludge,	
						Respiration Inhibition Test	

 Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

 Toxicity / effect
 Endpoint
 Time
 Value
 Unit
 Organism
 Test method
 Notes

(Carbon and Ammonium Oxidation))



Page 11 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

œ

12.1. Toxicity to fish:	LC50	96h	2400	mg/l	Leuciscus idus	DIN 38412 T.15	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	8h	2210	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	EC10	72h	612,5	mg/l			Analogous conclusion
12.2. Persistence and degradability:							Readily biodegradable
Toxicity to bacteria:	EC10	30min	>1995	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

1,1'-iminodipropan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	277,7	mg/l	Daphnia magna	84/449/EEC C.2	
12.1. Toxicity to algae:	EC50	72h	339	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	94	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 16 01 13 brake fluids Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant. **For contaminated packing material** Pay attention to local and national official regulations.

Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:
14.2. UN proper shipping name:
Not applicable
14.3. Transport hazard class(es):
14.4. Packing group:

Not applicable

Not applicable Not applicable



Page 12 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

Not applicable 14.5. Environmental hazards: Tunnel restriction code: Not applicable Classification code: Not applicable LQ: Not applicable Transport category: Not applicable Transport by sea (IMDG-code) 14.1. UN number or ID number: Not applicable 14.2. UN proper shipping name: Not applicable 14.3. Transport hazard class(es): Not applicable 14.4. Packing group: Not applicable 14.5. Environmental hazards: Not applicable Marine Pollutant: Not applicable EmS: Not applicable Transport by air (IATA) 14.1. UN number or ID number: Not applicable 14.2. UN proper shipping name: Not applicable 14.3. Transport hazard class(es): Not applicable 14.4. Packing group: Not applicable 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

ആ

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

46,5 %

Revised sections:

2, 3, 7, 8, 11, 12, 15, 16

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Repr. 2, H361fd	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H318 Causes serious eye damage.



Page 13 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4

H319 Causes serious eye irritation.

œ

Repr. — Reproductive toxicity Eye Dam. — Serious eye damage Eye Irrit. — Eye irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

AOX	Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ational Carriage of Dangerous Goods by Road) Adsorbable organic halogen compounds approximately
	ASTM International (American Society for Testing and Materials)
ATE	Acute Toxicity Estimate
BAM	Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA	Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF BSEF	Bioconcentration factor The International Bromine Council
boer bw	body weight
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances
and mi	ixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
	Derived Minimum Effect Level
DNEL	Derived No Effect Level
dw	Dissolved organic carbon dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
	Event (a) Event (a) Event (a) Event (a) Event (a) Event (a) Even
EC	European Community
ECHA	European Chemicals Agency
	ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC	European Economic Community
EINEC	
ELINC EN	S European List of Notified Chemical Substances European Norms
EPA	United States Environmental Protection Agency (United States of America)
	$E\mu Cx$, $ErLx$ (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc.	et cetera
EU	European Union
	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general Clabelly Lermoniand System of Classification and Labelling of Chamicals
GHS GWP	Globally Harmonized System of Classification and Labelling of Chemicals Global warming potential
Koc	Adsorption coefficient of organic carbon in the soil



ദ്ര Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2023 / 0008 Replacing version dated / version: 21.11.2022 / 0007 Valid from: 12.04.2023 PDF print date: 24.04.2023 Bremsfluessigkeit SL6 DOT 4 Brake Fluid SL6 DOT 4 Kow octanol-water partition coefficient IARC International Agency for Research on Cancer ΙΑΤΑ International Air Transport Association IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code incl. including, inclusive IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.