

Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

# **Pro-Line Silikonspray**

**1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Eluent Lubricant **Uses advised against:** 

# No information available at present.

## 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number

Emergency information services / official advisory body:

**Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category
Aquatic Chronic	3
Aerosol	1
Aerosol	1

Hazard statement H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 14

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray



Danger

H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

#### <sup>n.a.</sup> 3.2 Mixtures

#### Aerosol

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	
content %	2,5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 2, H225
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person! Inhalation



Page 3 of 14

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms. If the person is unconscious, place in a stable side position and consult a doctor. Respiratory arrest - Artificial respiration apparatus necessary.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

## Eye contact

Remove contact lenses. Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Consult medical specialist.

#### Ingestion

Typically no exposure pathway. Rinse the mouth thoroughly with water. Immediate admittance to a hospital.

## 4.2 Most important symptoms and effects, both acute and delayed

Irritation of the respiratory tract Irritation of the skin. Irritation of the eyes Headaches Dizziness Effects/damages the central nervous system Coordination disorders fatigue Unconsciousness With long-term contact: Drying of the skin. Dermatitis (skin inflammation) Other dangerous properties cannot be ruled out. In certain cases the symptoms of poisoning may

#### In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

# 5.1 Extinguishing media

## Suitable extinguishing media

CO2 Sand Extinction powder Water jet spray Foam

#### Unsuitable extinguishing media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Danger of explosion by prolonged heating. Explosive vapour/air or gas/air mixtures.

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

**SECTION 6: Accidental release measures** 



Page 4 of 14

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

## 6.1 Personal precautions, protective equipment and emergency procedures

## 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### **6.2 Environmental precautions**

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. Prevent surface and ground-water infiltration, as well as ground penetration.

#### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Do not use the product in enclosed spaces.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use. Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Observe special regulations for aerosols!

Observe special regulations for aeroso Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

#### Store in a well ventilated place. 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

œ



Page 5 of 14

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

		1					
WEL-TWA: 1200 mg/m3	WEL-STEL:						
Monitoring procedures:	<ul> <li>Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> </ul>						
	- Draeger - Hydrocarbons 2/a (81 03 581)						
	<ul> <li>Compur - KITA-187 S (551 174)</li> </ul>						
BMGV:	Other information: (C	DEL acc. to RCP-method,					
	paragraphs 84-87, EH4	40)					
Chemical Name	Hydrocarbons, C3-4	Content %:					
Chemical Name WEL-TWA: 1000 ppm (ACGIH)	Hydrocarbons, C3-4 WEL-STEL: 1250 ppm (2180 mg/m3) (Liquefied	Content %:					
	WEL-STEL: 1250 ppm (2180 mg/m3) (Liquefied						
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: 1250 ppm (2180 mg/m3) (Liquefied petroleum gas (LPG))						

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics								
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note		
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d			
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3			

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes. Tight fitting protective goggles with side protection (EN 166).



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,65 Permeation time (penetration time) in minutes: > 120 Protective hand cream recommended. The breaktbrough times determined in accordance with EN 166

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. In case of emergency: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	0,9 Vol-%
Upper explosion limit:	9,5 Vol-% (Propane)
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,595 g/ml
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.
9.2 Other information	
Explosives:	Product is not explosive. Possible build up of explosive/highly
	flammable vapour/air mixture.
Oxidising liquids:	There is no information available on this parameter.
Bulk density:	n.a.



Page 7 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

Solubility(ies):

œ

Alcohols, Hydrocarbons

## **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested. Not to be expected

## 10.2 Chemical stability

Stable with proper storage and handling.

#### **10.3 Possibility of hazardous reactions**

No decomposition if used as intended.

## 10.4 Conditions to avoid

See also section 7. Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

#### **10.5 Incompatible materials**

See also section 7. Avoid contact with oxidizing agents.

#### **10.6 Hazardous decomposition products**

See also section 5.2 No decomposition when used as directed.

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Pro-Line Silikonspray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

## Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	



Page 8 of 14 Safety data sheet according to R		) No 1907/200	6, Annex II			
Revision date / version: 01.11.20 Replacing version dated / version Valid from: 01.11.2021		/ 0018				
PDF print date: 01.11.2021 Pro-Line Silikonspray						
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	cracking. Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousnes
						, heart/circulatory disorders, headaches,
						cramps, drowsiness, mucous
						membrane irritation, dizziness, nausea and
						vomiting.

Hydrocarbons, C3-4						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						malaise, nausea,
						dizziness,
						mucous
						membrane
						irritation,
						drowsiness,
						unconsciousness

# 11.2. Information on other hazards

Pro-Line Silikonspray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.



Page 9 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

Other information:

GB

		No other
		relevant
		information
		available on
		adverse effects
		on health.

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification). See section 2.

Pro-Line Silikonspray Toxicity / effect Test method Endpoint Time Value Unit Organism Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: n.d.a. 12.1. Toxicity to algae: n.d.a. 12.2. Persistence and n.d.a. degradability: 12.3. Bioaccumulative n.d.a. potential: 12.4. Mobility in soil: n.d.a. 12.5. Results of PBT n.d.a. and vPvB assessment 12.6. Endocrine Does not apply disrupting properties: to mixtures. 12.7. Other adverse No information effects: available on other adverse effects on the environment. Other information: According to the recipe, contains no ÁOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.7. Other adverse effects:							Product floats or the water surface.
12.3. Bioaccumulative potential:							Not to be expected(evapor ation)
12.1. Toxicity to fish:	NOELR	28d	0,574		Oncorhynchus mykiss		,
12.1. Toxicity to fish:	LC50	96h	3 - 10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	



- @B							
Page 10 of 14 Safety data sheet accordi	ing to Regulation	) (EC) No 19	07/2006. An	nex II			
Revision date / version: 0							
Replacing version dated /	version: 10.04.2	2019 / 0018					
Valid from: 01.11.2021							
PDF print date: 01.11.202	21						
Pro-Line Silikonspray							
12.2. Persistence and		28d	98	%		OECD 301 F	Completely
degradability:		200	00	70		(Ready	biodegradable.
						Biodegradability -	Diedegiadabiei
						Manometric	
						Respirometry Test)	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
	<b>-</b>						vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value
Hydrocarbons, C3-4							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.4. Mobility in soil:							Product is
40.0 0							slightly volatile.
12.2. Persistence and							Biodegradable
degradability: 12.3. Bioaccumulative							A notable
potential:							biological
potontial							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 02 17 waste containing silicones other than those mentioned in 07 02 16

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

## For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

## **SECTION 14: Transport information**

General statements		
14.1. UN number or ID number:	1950	
Transport by road/by rail (ADR/RID)		
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	•
Classification code:	5F	
LQ:	1 L	
14.5. Environmental hazards:	Not applicable	



®				
Page 11 of 14				
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II				
Revision date / version: 01.11.2021 / 0019				
Replacing version dated / version: 10.04.2019 / 0018				
Valid from: 01.11.2021				
PDF print date: 01.11.2021				
Pro-Line Silikonspray				
Tunnel restriction code:	D			
Transport by sea (IMDG-code)				
14.2. UN proper shipping name:				
AEROSOLS				
14.3. Transport hazard class(es):	2.1			
14.4. Packing group:	<u>.</u>			
EmS:	F-D, S-U			
Marine Pollutant:	n.a			
14.5. Environmental hazards:	Not applicable			
Transport by air (IATA)				
14.2. UN proper shipping name:				
Aerosols, flammable				
14.3. Transport hazard class(es):	2.1			
14.4. Packing group:	<u>.</u>			
14.5. Environmental hazards:	Not applicable			
14.6. Special precautions for user				
Persons employed in transporting dangerous goods must be trained.				
All persons involved in transporting must observe safety regulations.				
Precautions must be taken to prevent damage.				
14.7. Maritime transport in bulk according to IMO instruments				
Freighted as packaged goods rather than in bulk, therefore not applicable.				
Minimum amount regulations have not been taken into account.				
Danger code and packing code on request.				
Comply with special provisions.				
SECTION 15: Bogulatory information				
SECTION 15: Regulatory information				

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3b	11.1, 11.2	5000 (netto)	50000 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

91,85 %

#### **15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

Revised sections:

1-16

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):



Page 12 of 14

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Asp. Tox. — Aspiration hazard

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) Acute Toxicity Estimate ATE Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.q. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC



ആ Page 13 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances FINECS ELINCS European List of Notified Chemical Substances ΕN European Norms United States Environmental Protection Agency (United States of America) EPA Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. **IUCLID** International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wwt wet weight The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility. These statements were made by

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document



Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0019 Replacing version dated / version: 10.04.2019 / 0018 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line Silikonspray

œ

is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.