

Page 1 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# **1.1 Product identifier**

# Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

**1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

# Hydraulic oil Uses advised against:

No information available at present.

# 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAsp. Tox.1H304-May be fatal if swallowed and enters airways.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 16

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300



Danger

H304-May be fatal if swallowed and enters airways.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting. P405-Store locked up. P501-Dispose of contents / container to an approved waste disposal facility.

Distillates (petroleum), hydrotreated light naphthenic

Distillates (petroleum), solvent-dewaxed light paraffinic

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

Mineral oil raffinate Additives

# 3.1 Substances

n.a. **3.2 Mixtures** 

Distillates (petroleum), solvent-dewaxed light paraffinic	
Registration number (REACH)	01-2119480132-48-XXXX
Index	649-469-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	265-159-2
CAS	64742-56-9
content %	50-75
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light naphthenic	
Registration number (REACH)	01-2119480375-34-XXXX
Index	649-466-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	265-156-6
CAS	64742-53-6
content %	10-25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304
	· · · · · · · · · · · · · · · · · · ·
Distillates (petroleum), hydrotreated middle	
Registration number (REACH)	
Index	649-221-00-X
EINECS, ELINCS, NLP, REACH-IT List-No.	265-148-2
CAS	64742-46-7



Page 3 of 16

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

content %	<10,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and isobutyl and	

isopropyl) esters, zinc salts	
Registration number (REACH)	01-2119521201-61-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	288-917-4
CAS	85940-28-9
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Aquatic Chronic 2, H411

(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	
Registration number (REACH)	01-2119488991-20-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	203-749-3
CAS	110-25-8
content %	<0,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent

Thinners

In case of skin injury by high pressure, a risk of penetration of lubricant into the skin exists.

Immediate admittance to a hospital.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

Immediate admittance to a hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Eye contact:



Page 4 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

Temporary irritation With long-term contact: Drying of the skin. Dermatitis (skin inflammation) Oil acne On vapour formation: Irritation of the respiratory tract Ingestion: Gastrointestinal disturbances Nausea Vomiting Danger of aspiration. Oedema of the lungs Chemical pneumonitis (condition similar to pneumonia)

#### **4.3 Indication of any immediate medical attention and special treatment needed** Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

#### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

#### Suitable extinguishing media

CO2

ആ

Foam Extinction powder

#### Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition. Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications. 6.2 Environmental precautions

#### 6.2 Environmental

If leakage occurs, dam up. Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.



Page 5 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

#### If accidental entry into drainage system occurs, inform responsible authorities. 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Oil binder

Do not wash away with water or watery cleaning agents.

#### 6.4 Reference to other sections

അ

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

# 7.1 Precautions for safe handling

# 7.1.1 General recommendations

Avoid formation of oil mist. Ensure good ventilation. Keep away from sources of ignition - Do not smoke. Do not heat to temperatures close to flash point. Avoid contact with eyes. Avoid long lasting or intensive contact with skin. Do not carry cleaning cloths soaked in product in trouser pockets. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions. **7.1.2 Notes on general hygiene measures at the workplace** 

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Protect from direct sunlight and warming.

Store in a dry place.

# 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

#### SECTION 8: Exposure controls/personal protection

# 8.1 Control parameters

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment					
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	

Phosphorodithioic acid, mixed 0,0-bis(2-ethylhexyl and isobutyl and isopropyl) esters, zinc salts									
Area of application	Exposure route / Effect on health Descriptor Value Unit								
	Environmental								
	compartment								



Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

œ

	Environment - freshwater		PNEC	0,002	mg/l
	Environment - marine		PNEC	0	mg/l
	Environment - water, sporadic (intermittent) release		PNEC	0,02	mg/l
	Environment - sediment, marine		PNEC	1,93	mg/kg dry weight
	Environment - soil		PNEC	15,7	mg/kg dry weight
	Environment - sewage treatment plant		PNEC	100	mg/l
	Environment - sediment, freshwater		PNEC	19,3	mg/kg dw
Consumer	Human - oral	Long term, systemic effects	DNEL	0,19	mg/kg bw/day
Consumer	Human - dermal	Long term, systemic effects	DNEL	4,8	mg/kg bw/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,67	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,6	mg/kg bw/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,6	mg/m3

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,43	mg/l	
	Environment - marine		PNEC	0,043	mg/l	
	Environment - sporadic (intermittent) release		PNEC	13	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - oral	Short term, systemic effects	DNEL	92	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,1	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,005	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	9	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	9	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,2	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,01	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	18	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	18	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	10	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	100	mg/kg bw/d	

#### 8.2 Exposure controls

# 8.2.1 Appropriate engineering controls



Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective gloves, oil resistant (EN ISO 374). Recommended Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,35 Permeation time (penetration time) in minutes:

> 240

ആ

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

# 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Light yellow Odour: Mineral oil Melting point/freezing point: There is no information available on this parameter. Boiling point or initial boiling point and boiling range: There is no information available on this parameter. Flammability: Flammable Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: >150 °C (Cleveland, open cup)



Page 8 of 16

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

#### 9.2 Other information

Explosives: Oxidising liquids: Bulk density: There is no information available on this parameter. There is no information available on this parameter. Mixture is non-soluble (in water). 16 mm2/s (40°C) Insoluble Does not apply to mixtures. There is no information available on this parameter. <1 g/cm3 (15°C) There is no information available on this parameter. Does not apply to liquids.

Product is not explosive. No n.a.

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Heating, open flame, ignition sources **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed.

# **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

oxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Distillates (petroleum), solvent	-dewaxed ligh	nt paraffinic				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

œ

.....

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:				e annoa pig	Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
eenn een matagemeny.				typhimurium	Reverse Mutation Test)	loguito
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian	Negative
Contractigorioldy.				maininalian	Erythrocyte	Nogalivo
					Micronucleus Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
Serie cell matagementy.				Warmanan	Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	Chinese hamste
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
Gerni cell mutagenicity.				wouse	Mammalian Cell Gene	Negative
Denne ductive toxicity	NOAEL	>1000		Det	Mutation Test)	Magathia
Reproductive toxicity:	NOAEL	>1000	mg/kg	Rat	OECD 421	Negative
			bw/d		(Reproduction/Developm	
					ental Toxicity Screening	
					Test)	
Reproductive toxicity:	NOAEL	>2000	mg/kg	Rat	OECD 414 (Prenatal	
			bw/d		Developmental Toxicity	
					Study)	
Aspiration hazard:						Yes
Symptoms:						drying of the
						skin., vomiting,
						nausea

oxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Aspiration hazard:						Yes
Distillates (petroleum), hydrotr	eated middle					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



#### Page 10 of 16

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

Skin corrosion/irritation:			Repeated
			exposure may
			cause skin
			dryness or
			cracking.
Aspiration hazard:			Yes
Symptoms:			vomiting, skin
			afflictions

Phosphorodithioic acid, mixed 0,0-bis(2-ethylhexyl and isobutyl and isopropyl) esters, zinc salts							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	3000	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute		
					Dermal Toxicity)		
Skin corrosion/irritation:				Rabbit		Skin Irrit. 2	
Serious eye damage/irritation:				Rabbit		Eye Irrit. 2	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by inhalation:	LC50	1,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Symptoms:						respiratory distress, diarrhoea, cornea opacity, mucous membrane irritation

# 11.2. Information on other hazards

Zentralhydraulik-Oel 2300								
Central Hydraulic System Oil 2300								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Endocrine disrupting properties:						Does not apply to mixtures.		
Other information:						No other relevant information available on adverse effects on health.		

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

# Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300 Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.1. Toxicity to fish: 12.1. Toxicity to daphnia: 12.1. Toxicity to daphnia: 12.1. Toxicity to algae: 12.1. Toxic



Page 11 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

œ.

12.2. Persistence and degradability:	Isolate as much as possible with
	an oil separator.
12.3. Bioaccumulative potential:	n.d.a.
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Endocrine	Does not apply
disrupting properties:	to mixtures.
12.7. Other adverse	No information
effects:	available on
	other adverse
	effects on the
	environment.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales	OECD 203 (Fish,	
					promelas	Acute Toxicity	
						Test)	
2.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	LL50	48h	>1000	mg/l	Gammarus sp.	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
		701				Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
		00.1		0(		Test)	
12.2. Persistence and		28d	31	%	activated sludge	OECD 301 F	Inherent
degradability:						(Ready	
						Biodegradability - Manometric	
12.3. Bioaccumulative	Log Pow		>3			Respirometry Test)	Low
potential:	LUGFUW		>0				
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Distillates (petroleum), hydrotreated light naphthenic								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)		



Page 12 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

œ.

12.1. Toxicity to algae:	NOEC/NOEL	72h	> 100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	31	%	activated sludge	OECD 301 F	Not readily but
degradability:						(Ready	inherent
						Biodegradability -	biodegradable.,
						Manometric	Mechanical
						Respirometry Test)	precipitation
						,	possible.
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Water solubility:							Insoluble

	Distillates (petroleum), hydrotreated middle									
	Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
IΓ	12.2. Persistence and							Readily		
	degradability:							biodegradable		

Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
2.1. Toxicity to fish:	NOEC/NOEL	96h	1,8	mg/l	Oncorhynchus	OECD 203 (Fish,	Analogous
					mykiss	Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to fish:	LC50	96h	4,5	mg/l	Oncorhynchus	OECD 203 (Fish,	Analogous
					mykiss	Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	5,4	mg/l	Daphnia magna	OECD 202	Analogous
						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	<1	mg/l	Daphnia magna	OECD 202	Analogous
						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	LC50	96h	2,1	mg/l	Selenastrum	OECD 201 (Alga,	Analogous
					capricornutum	Growth Inhibition	conclusion
						Test)	
12.2. Persistence and		28d	1,5	%		OECD 301 B	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
						Test)	

Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,3	mg/l	Leuciscus idus	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to daphnia:	EC50	48h	0,1-1	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	0,43	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 13 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

œ

		1	1		1		
12.1. Toxicity to algae:	EC50	72h	6.3	mg/l	Desmodesmus	84/449/EEC C.3	
, , ,				U U	subspicatus		
10.0 D 11		00.1	05	0/	30030102103		B
12.2. Persistence and		28d	85	%		OECD 301 B	Readily
degradability:						(Ready	biodegradable
5 ,						Biodegradability -	5
						Co2 Evolution	
						Test)	
Toxicity to bacteria:	EC50	3h	1300	mg/l	activated sludge	OECD 209	
				Ŭ	5	(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Àmmonium	
						Oxidation))	
						Oxidation))	
Other information:	BOD		1840	mg/g			

# SECTION 13: Disposal considerations

# 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 01 10 mineral based non-chlorinated hydraulic oils Recommendation:

# Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling. E.g. suitable incineration plant.

# For contaminated packing material

# Pay attention to local and national official regulations.

Pay attention to local and national official regulations. 15 01 02 plastic packaging 15 01 04 metallic packaging Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

# **SECTION 14: Transport information**

General statements Transport by road/by rail (ADR/RID)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable
Transport by sea (IMDG-code)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable



Page 14 of 16

അ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

14.5. Environmental hazards: Marine Pollutant: EmS:

# Transport by air (IATA)

14.1. UN number or ID number: 14.2. UN proper shipping name: Not applicable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards:

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

# **SECTION 15: Regulatory information**

Not applicable

Not applicable Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

**Revised sections:** 

1-16

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Asp. Tox. - Aspiration hazard Skin Irrit. - Skin irritation Eye Irrit. — Eye irritation Aquatic Chronic - Hazardous to the aquatic environment - chronic Acute Tox. — Acute toxicity - inhalation Eye Dam. — Serious eye damage

Aquatic Acute - Hazardous to the aquatic environment - acute



Page 15 of 16

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council bw body weight CAS Chemical Abstracts Service Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances European Norms EN EPA United States Environmental Protection Agency (United States of America)  $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera FU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code



ആ Page 16 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 22.06.2020 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 Zentralhydraulik-Oel 2300 Central Hydraulic System Oil 2300 incl. including, inclusive IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) No-longer-Polymer NI P NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride **PVC** REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.