

Page 1 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024 Sekundenkleber

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Sekundenkleber

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Œ

Landspitali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Eye Irrit. 2 H319-Causes serious eye irritation. STOT SE 3 H335-May cause respiratory irritation.

Skin Irrit. 2 H315-Causes skin irritation.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber



H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P280-Wear protective gloves / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH202-Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

EUH208-Contains 1,4-dihydroxybenzene. May produce an allergic reaction.

Ethyl 2-cyanoacrylate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

Ethyl 2-cyanoacrylate	
Registration number (REACH)	01-2119527766-29-XXXX
Index	607-236-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	230-391-5
CAS	7085-85-0
content %	80-100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	STOT SE 3, H335
Specific Concentration Limits and ATE	STOT SE 3, H335: >=10 %

1,4-dihydroxybenzene	
Registration number (REACH)	
Index	604-005-00-4
EINECS, ELINCS, NLP, REACH-IT List-No.	204-617-8
CAS	123-31-9
content %	0,1-0,5



Page 3 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Eye Dam. 1, H318
	Skin Sens. 1, H317
	Muta. 2, H341
	Carc. 2, H351
	Aquatic Acute 1, H400 (M=10)
Specific Concentration Limits and ATE	ATE (oral): 367 mg/kg

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap. Call a doctor immediately, keep datasheet at hand

If the skin is alued:

Do not attempt to force glued areas of skin apart.

Eve contact

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting.

Call doctor immediately - have Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Respiratory distress

May cause sensitisation by inhalation.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Water jet spray

Extinction powder

Large fire:

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Toxic gases



(B)

Page 4 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

Oxides of carbon Oxides of nitrogen Cyanides

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary. Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Handle and open container with care.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

During processing:

Ambient humidity should be increased to at least 50-60% relative humidity.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with alkalis.

Do not store with acids.

Do not store with oxidizing agents.



Page 5 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024 Sekundenkleber

Protect against moisture and store closed. Protect from direct sunlight and warming. Only store at temperatures from 10°C to 22°C.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

© Chemical Name	Ethyl 2-cyanoacryla				
WEL-TWA:		WEL-STEL:	0,3 ppm (1,5 mg/r	m3)	
Monitoring procedures:		- -			
BMGV:				Other information:	
Chemical Name	1,4-dihydroxybenze	ene			
WEL-TWA: 0,5 mg/m3		WEL-STEL:			
Monitoring procedures:		-			
BMGV:				Other information:	
© Chemical Name	Silicon dioxide				
WEL-TWA: 6 mg/m3 (total inh. dus	st), 2,4 mg/m3	WEL-STEL:			
(resp. dust)					
Monitoring procedures:		-			
BMGV:				Other information:	

Ethyl 2-cyanoacrylate Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
Area or application	Environmental compartment	Effect off fleatur	Descriptor	value	Onit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	9,25	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	9,25	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	9,25	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	9,25	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	9,25	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	9,25	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	9,25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	9,25	mg/m3	

Silicon dioxide									
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note			
	Environmental								
	compartment								
	Environment - oral (animal		PNEC	60000	mg/kg feed				
	feed)								
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3				

⁻ United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

⁽EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction

^{(2004/37/}CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this



(B)

Page 6 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024 Sekundenkleber

Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE).

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU: (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

Unsuitable material:

Rubber gloves (EN ISO 374).

Protective PVC gloves (EN ISO 374).

Cotton gloves.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable



Page 7 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

450 °C

9.1 Information on basic physical and chemical properties

Physical state: Colour: Colourless Odour: Characteristic

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: >149 °C Flammability: Combustible.

Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: 80-93,4 °C (DIN 51758 (Pensky-Martens, closed cup))

Auto-ignition temperature:

Decomposition temperature: There is no information available on this parameter. pH:

Kinematic viscosity: 100-200 mPas (23°C, Dynamic viscosity) Solubility: reacts with water, Insoluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures. 1,5 hPa (25°C, DIN 51616) Vapour pressure: 1,1 g/cm3 (25°C, DIN 51757) Density and/or relative density:

Relative vapour density: There is no information available on this parameter.

Particle characteristics: Does not apply to liquids.

9.2 Other information

Explosives: Product is not explosive.

Oxidising liquids: No Solvents content: >20 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Protect from humidity.

Heating, open flame, ignition sources

Protect from frost.

10.5 Incompatible materials

Do not bring into contact with water.

Polymerisation possible

Violent reaction with:

Water

Bases Acids

Oxidizing agents

Amines

Alcohols



③B)·

Page 8 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Sekundenkleber						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse		Negative
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						STOT SE 3, H335
Aspiration hazard:						No
Symptoms:						respiratory distress, coughing, mucous membrane irritation, watering eyes

1,4-dihydroxybenzene								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	320-400	mg/kg	Rat				
Acute toxicity, by oral route.	LD30	320-400	ilig/kg	Nai		<u> </u>		



③B)·

Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

Acute toxicity, by oral route:	LD50	367	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	ATE	367	mg/kg		Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Serious eye damage/irritation:						Corrosive
Respiratory or skin						Sensitising (skin
sensitisation:						contact)
Symptoms:						respiratory
						distress,
						unconsciousness
						, vomiting,
						headaches,
						cramps, mucous
						membrane
						irritation, nausea

Silicon dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References,
						Maximum
						achievable
						concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit		Not irritant,
						Mechanical
						irritation
						possible.,
						References
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Carcinogenicity:						No indications of
						such an effect.
Reproductive toxicity						No indications of
(Developmental toxicity):						such an effect.
Symptoms:						eyes, reddened

11.2. Information on other hazards

Sekundenkleber								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Endocrine disrupting properties:						Does not apply		
						to mixtures.		
Other information:						No other		
						relevant		
						information		
						available on		
						adverse effects		
						on health.		

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Sekundenkleber							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.



Page 10 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024 Sekundenkleber

12.1. Toxicity to algae:		n.d.a.
12.2. Persistence and		n.d.a.
degradability:		
12.3. Bioaccumulative		n.d.a.
potential:		
12.4. Mobility in soil:		n.d.a.
12.5. Results of PBT		n.d.a.
and vPvB assessment		
12.6. Endocrine		Does not apply
disrupting properties:		to mixtures.
12.7. Other adverse		No information
effects:		available on
		other adverse
		effects on the
		environment.
Other information:		DOC-elimination
		degree(complexi
		ng organic
		substance)>=
		80%/28d: n.a.

Ethyl 2-cyanoacrylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative	Log Pow		1,42				Not to be
potential:							expected
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

1,4-dihydroxybenzene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,04 - 0,1	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	0,13	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	0,335	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		14d	86	%			Readily biodegradable
12.3. Bioaccumulative potential:	BCF		40				_
Toxicity to bacteria:	EC50	30min	0,038	mg/l	Photobacterium phosphoreum		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected



Page 11 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

12.5. Results of PBT				No PBT
and vPvB assessment				substance, No
				vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:
Not applicable
14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):Not applicable14.4. Packing group:Not applicable14.5. Environmental hazards:Not applicableTunnel restriction code:Not applicableClassification code:Not applicableLQ:Not applicableTransport category:Not applicable

Transport by sea (IMDG-code)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):
14.4. Packing group:
14.5. Environmental hazards:
Mot applicable
Marine Pollutant:
Not applicable
EmS:
Not applicable

Transport by air (IATA)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):
14.4. Packing group:
14.5. Environmental hazards:
Not applicable
Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.



Œ

Page 12 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024

PDF print date: 20.11.2024

Sekundenkleber

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

< 20 g/l

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

8

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

 $\hbox{ Eye Irrit.} \ -- \ \hbox{ Eye irritation}$

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Acute Tox. — Acute toxicity - oral

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

Muta. — Germ cell mutagenicity

Carc. — Carcinogenicity

Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).



Page 13 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as

amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road) Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

Acute Toxicity Estimate ATE

Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAM

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

European Community FC

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

European Economic Community EEC

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

ΕN **European Norms**

FPA United States Environmental Protection Agency (United States of America)

ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

et cetera etc.

European Union EU

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS

Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

octanol-water partition coefficient Kow

IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ **Limited Quantities**

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg body weight mg/kg bw

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight



Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 20.11.2024 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 20.11.2024 PDF print date: 20.11.2024

Sekundenkleber

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

PVC Polyvinylchloride

ppm parts per million

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.