

Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ആ

LM 48 Montagepaste

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Di-iso-octyl amino methyl tolutriazole, N-1-naphthylaniline. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients



Page 2 of 14

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

3.1 Substances

^{n.a.} 3.<u>2 Mixtures</u>

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	200-662-2
CAS	67-64-1
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Eye Irrit. 2, H319
	STOT SE 3, H336

Calcium fluoride	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119491248-30-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	232-188-7
CAS	7789-75-5
content %	<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Not required.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

With long-term contact: Product removes fat. Drying of the skin. Dermatitis (skin inflammation) Allergic reaction

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media



Page 3 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

CO2 Dry extinguisher Foam

ആ

Unsuitable extinguishing media

High volume water jet **5.2 Special hazards arising from the substance or mixture** In case of fire the following can develop: Oxides of carbon Oxides of sulphur

Hydrocarbons Toxic pyrolysis products. Hot product gives off combustible vapours.

5.3 Advice for firefighters

Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid formation of oil mist. Avoid contact with eyes or skin. Do not carry cleaning cloths soaked in product in trouser pockets. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up. Resolve leaks if this possible without risk. Prevent from entering drainage system. Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Avoid long lasting or intensive contact with skin.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing. Not to be stored in gangways or stair wells. Solvent resistant floor Do not store with oxidizing agents. Store in a well ventilated place.

Protect from direct sunlight and warming.



Page 4 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

Store in a dry place. **7.3 Specific end use(s)**

œ)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

-		
Chemical Name Acetone		Content %:1-<5
WEL-TWA: 500 ppm (1210 mg/m3) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m3) (WEL)	
Monitoring procedures: -	Draeger - Acetone 100/b (CH 22 901)	
-	Draeger - Acetone 40/a (5) (81 03 381)	
-	Compur - KITA-102 SA (548 534)	
-	Compur - KITA-102 SC (548 550)	
-	Compur - KITA-102 SD (551 109)	
	INSHT MTA/MA-031/A96 (Determination of ketones (acetor	
	methyl isobutyl ketone) in air - Charcoal tube method / Gas	chromatography) - 1996 -
-	EU project BC/CEN/ENTR/000/2002-16 card 67-1 (2004)	
	MDHS 72 (Volatile organic compounds in air – Laboratory n	
-	sorbent tubes, thermal desorption and gas chromatography NIOSH 1300 (KETONES I) - 1994) - 1993
-	NIOSH 1300 (RETONES I) - 1994 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCRE	
-	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCRE NIOSH 2555 (KETONES I) - 2003	ENING)) - 1996
-	NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EX	
_	SPECTROMETRY) - 2016	IRACINETIIR
_	OSHA 69 (Acetone) - 1988	
BMGV:	Other information:	
Chemical Name Calcium fluoride		Content %:<5
WEL-TWA: 2,5 mg/m3 (fluoride (inorganic,as F)	WEL-STEL:	
(WEL, EU)	WEE-STEE.	
Monitoring procedures:	DFG (D) (Fluorwasserstoff und Fluoride), DFG (E) (Hydroge	enfluoride and fluorides) -
	2005	
-	NIOSH 7902 (Fluorides, aerosol and gas by ISE) - 1994	
	NIOSH 7906 (PARTICULATE FLUORIDES and HYDROFLI	UORIC ACID by Ion
-	Chromatography) - 2014	
	OSHA ID-110 (Fluoride (F and HF) in workplace atmosphe	eres) - 1991 - EU project
-	BC/CEN/ENTR/000/2002-16 card 95-5 (2004)	
BMGV:	Other information:	
Chemical Name Graphite		Content %:
WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res.	WEL-STEL:	
dust)		
Monitoring procedures:		
BMGV:	Other information:	
Chemical Name Tungsten disulph	ide	Content %:
WEL-TWA: 5 mg/m3 (insoluble compounds as W)	WEL-STEL: 10 mg/m3 (insoluble compounds as W)	
Monitoring procedures:		
BMGV:	Other information:	
Image: Chemical Name Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:	
working fluids, ACGIH) Monitoring procedures: -	Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	
A		
Acetone		

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assesment factor 500



Page 5 of 14

(GB)·

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

	Environment - freshwater		PNEC	10,6	mg/l	Assesment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/kg dw	
	Environment - sediment, marine		PNEC	3,04	mg/kg dw	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assesment factor 100
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m3	Overall assesment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m3	

Distillates (petroleum), hydrotreated heavy paraffinic								
Area of application Exposure route / Effect on health Descriptor Value Unit Note								
	Environmental							
	compartment							
	Environment - oral (animal		PNEC	9,33	mg/kg feed			
	feed)							

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment Environment - freshwater		PNEC	20,6		
	Environment - marine		PNEC	6,1	μg/l μg/l	
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dry weight	
	Environment - sediment, marine		PNEC	56,5	mg/kg dry weight	
	Environment - soil		PNEC	35,5	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	100	µg/l	
Consumer Human - inhalation		Long term, systemic effects	DNEL	2,5	mg/m3	
Consumer Human - dermal		Long term, systemic effects	DNEL	83	mg/kg bw/day	
Consumer Human - oral		Long term, systemic effects	DNEL	0,83	mg/kg bw/day	
Workers / employees Human - inhalation		Long term, systemic effects	DNEL	5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	

3 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

ആ

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374). If applicable Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,4

Permeation time (penetration time) in minutes: > 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.



Page 7 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

8.2.3 Environmental exposure controls

No information available at present.

œ)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

3.1 mormation on basic physical and chemical	loperties
Physical state:	Pastelike, Liquid
Colour:	Black
Odour:	Odourless
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	101 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	No
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.
Not to be expected
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
See also section 7.
Open flame, ignition sources
10.5 Incompatible materials
Avoid contact with strong oxidizing agents.
10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.
SECTION 11: Toxicological information

11.1 Information on toxicological effects



Page 8 of 14	
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II	
Revision date / version: 28.07.2021 / 0018	
Replacing version dated / version: 26.05.2021 / 0017	
Valid from: 28.07.2021	
PDF print date: 29.07.2021	
LM 48 Montagepaste	
	_

- @B-

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Acetone	En de sint	Malua	11-21	0	To a functificated	Neter
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Repeated exposure may cause skin dryness or cracking., Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Symptoms:						unconsciousnes , vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	



B Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4250	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Symptoms:						ataxia, respiratory distress, drop in blood pressure, diarrhoea, thirst, headaches, muscle weakness, nausea and vomiting.

Graphite						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by inhalation:	NOAEC	>2000	mg/m3/4h	Rat	OECD 412 (Subacute	
					Inhalation Toxicity - 28-	
					Day Study)	
Acute toxicity, by inhalation:	LC50	>2000	mg/m3/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	Not sensitizising
sensitisation:					Sensitisation - Local	
2					Lymph Node Assay)	
Germ cell mutagenicity:				Salmonella	OECD 473 (In Vitro	Negative
				typhimurium	Mammalian	
					Chromosome	
				_	Aberration Test)	
Reproductive toxicity:	NOAEL	813	mg/kg	Rat	OECD 422 (Combined	
					Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
-					Tox. Screening Test)	
Symptoms:						breathing
						difficulties

Tungsten disulphide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>5,25	mg/l/4h	Rat		Dust

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).								
LM 48 Montagepaste								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:							n.d.a.	



B Page 10 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

12.1. Toxicity to daphnia:	n.d.a.
12.1. Toxicity to algae:	n.d.a.
12.2. Persistence and	Mechanical
degradability:	precipitation
	possible.
12.3. Bioaccumulative	n.d.a.
potential:	
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Other adverse	n.d.a.
effects:	

Acetone Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
	EC5	72h	28		Entosiphon	restmethou	NOLES
Other organisms:	ECS	/2n	28	mg/l	sulcatum		
12.1. Toxicity to fish:	EC50	96h	8300	mg/l	Lepomis		
	2000	5011	0000	ing/i	macrochirus		
12.1. Toxicity to fish:	LC50	96h	8300	mg/l	Lepomis		
	2000	0011	0000	iiig/i	macrochirus		
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus		
					mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	6100-	mg/l	Daphnia magna		
			12700	Ū			
12.1. Toxicity to daphnia:	EC50	48h	8800	mg/l	Daphnia pulex	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	8d	530	mg/l		DIN 38412 T.9	Test organism
							M. aeruginosa
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriell		
					a subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriell		
					a subcapitata		
12.2. Persistence and		28d	91	%		OECD 301 A	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						DOC Die-Away	
						Test)	
12.2. Persistence and		28d	91	%		OECD 301 B	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.2. Persistence and		30d	81-92	%		Regulation (EC)	Readily
degradability:						440/2008 C.4-E	biodegradable
						(DETERMINATIO	
						N OF 'READY'	
						BIODEGRADABILI	
						TY - CLOSED	
		ļ				BOTTLE TEST)	
12.3. Bioaccumulative	Log Pow		-0,24			OECD 107	
potential:						(Partition	
						Coefficient (n-	
						octanol/water) -	
						Shake Flask	
						Method)	



Page 11 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste 12.3. Bioaccumulative BCF 0,19 Low potential: 12.4. Mobility in soil: No adsorption in soil. 12.5. Results of PBT No PBT and vPvB assessment substance, No vPvB substance Toxicity to bacteria: EC10 30min 1000 mg/l activated sludge **OECD 209** (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) Toxicity to bacteria: BOD/COD 16h 1700 mg/l Pseudomonas putida BOD5 1760-Other information: mg/g 1900 AOX % Other information: 0 2070 Other information: COD mg/g Calcium fluoride Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.1. Toxicity to fish: LC50 660 mg/l Leuciscus idus Graphite Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.2. Persistence and Inorganic degradability: products cannot be eliminated from water through biological purification . methods. 12.1. Toxicity to fish: LC50 96h >100 OECD 203 (Fish, mg/l Brachydanio rerio Acute Toxicity Test) 12.1. Toxicity to daphnia: EC50 48h >100 mg/l Daphnia magna **OECD 202** (Daphnia sp. Acute Immobilisation Test) 12.1. Toxicity to algae: IC50 72h 100 Pseudokirchneriell OECD 201 (Alga, mg/l Growth Inhibition a subcapitata Test) Water solubility: Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

œ

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.



Page 12 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

E.g. suitable incineration plant. For contaminated packing material

ആ

Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. 15 01 02 plastic packaging 15 01 04 metallic packaging

SECTION 14: Transport information

General statements	
14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for safe trans	sport must be followed.
14.7. Transport in bulk according to Anno	•
· · ·	
Non-dangerous material according to Transport Regulations	5.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148. General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

1,252 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2, 3, 8, 11, 12, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):



Page 13 of 14

അ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Flam. Liq. — Flammable liquid Eye Irrit. — Eye irritation STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) Acute Toxicity Estimate ATF BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA BSEF The International Bromine Council bw body weight Chemical Abstracts Service CAS Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight e.g. EC for example (abbreviation of Latin 'exempli gratia'), for instance European Community ECHA European Chemicals Agency European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances ΕN **European Norms** EPA United States Environmental Protection Agency (United States of America) etc. et cetera EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a.



ആ Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 28.07.2021 / 0018 Replacing version dated / version: 26.05.2021 / 0017 Valid from: 28.07.2021 PDF print date: 29.07.2021 LM 48 Montagepaste n.av. not available not checked n.c. n.d.a. no data available OECD Organisation for Economic Co-operation and Development org. organic persistent, bioaccumulative and toxic PBT PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List **REACH-IT List-No.** Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.