

Page 1 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

# Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Cleaner

#### **Uses advised against:**

No information available at present.

# 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:** 

---

# Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
	•	LICOT III II II II

Flam. Liq. 2 H225-Highly flammable liquid and vapour.

Eye Irrit. 2 H319-Causes serious eye irritation.

Asp. Tox. 1 H304-May be fatal if swallowed and enters airways.

STOT SE 3 H336-May cause drowsiness or dizziness.

Aquatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner



#### Danger

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear eye protection / face protection.

P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10, aromatics, >1% naphthalene Hydrocarbons, C10, aromatics, <1% naphthalene

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture contains a substance with endocrine disrupting properties. The substance is named in Section 3.

#### **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

# n.a. 3.2 Mixtures

Acetone

Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	200-662-2
CAS	67-64-1
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 2, H225
	Eye Irrit. 2, H319
	STOT SE 3, H336

Substance for which an EU exposure limit value applies.

Hydrocarbons, C10, aromatics, <1% naphthalene	
Registration number (REACH)	01-2119463583-34-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-811-1
CAS	(64742-94-5)
content %	30-40



(B)

Page 3 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	919-284-0
CAS	(64742-94-5)
content %	0,1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Carc. 2, H351
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	202-049-5
CAS	91-20-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Carc. 2, H351
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Phenol, dodecyl-, branched	SVHC-substance
	Substance with endocrine disrupting properties.
Registration number (REACH)	
Index	604-092-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	310-154-3
CAS	121158-58-5
content %	0,01-<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Corr. 1C, H314
	Eye Dam. 1, H318
	Repr. 1B, H360F
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=10)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

# Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.



Page 4 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

#### Suitable extinguishing media Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Flammable vapour/air mixtures

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.



Page 5 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger
Pro-Line JetClean Diesel Intake System Cleaner

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Protect from direct sunlight and warming.

Under all circumstances prevent penetration into the soil.

Store in a well-ventilated place.

Store in a dry place.

Store cool.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 500 mg/m3

© Chemical Name Acetone		Content %:50-70
WEL-TWA: 500 ppm (1210 mg/m3) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m3) (WEL)	
Monitoring procedures:	- Draeger - Acetone 100/b (CH 22 901)	
	- Draeger - Acetone 40/a (5) (81 03 381)	
	- Compur - KITA-102 SA (548 534)	
	- Compur - KITA-102 SC (548 550)	
	- Compur - KITA-102 SD (551 109)	
	INSHT MTA/MA-031/A96 (Determination of ketones (acetone, me	thyl ethyl ketone,
	methyl isobutyl ketone) in air - Charcoal tube method / Gas chrom	atography) - 1996 -
	- EU project BC/CEN/ENTR/000/2002-16 card 67-1 (2004)	



Page 6 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger
Pro-Line JetClean Diesel Intake System Cleaner

MDHS 72 (Volatile organic compounds in air - Laboratory method using pumped solid

sorbent tubes, thermal desorption and gas chromatography) - 1993

NIOSH 1300 (KETONES I) - 1994

NIOSH 2549 (VOLATILE ÓRGANIC COMPOUNDS (SCREENING)) - 1996

NIOSH 2555 (KETONES I) - 2003 NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR

SPECTROMETRY) - 2016 OSHA 69 (Acetone) - 1988

BMGV: Other information:

	Hydrocarbons, C10, aromatics, <1% naphthalene	Content %:30-40
WEL-TWA: 500 mg/m3 (Aromatics	) WEL-STEL:	
Monitoring procedures:		
	<ul> <li>Draeger - Hydrocarbons 2/a (81 03 581)</li> </ul>	
	- Compur - KITA-187 S (551 174)	
BMGV:	Other information:	

(B)	Chemical Name  Hydrocarbons, C10, aromatics, >1% naphthalene		Content %:0,1- 2,5
W	EL-TWA: 500 mg/m3 (Aromatics	) WEL-STEL:	
M	onitoring procedures:	<ul> <li>Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> </ul>	
		<ul> <li>Draeger - Hydrocarbons 2/a (81 03 581)</li> </ul>	
		- Compur - KITA-187 S (551 174)	
BI	MGV:	Other information:	

_					
	Naphthalene				Content %:0,1-<1
WEL-TWA: 500 mg/m3 (Aromatic	s) (WEL), 10 ppm	WEL-STEL:	•		
(50 mg/m3) (EU)					
Monitoring procedures:	-	Compur - KITA-153	U(C) (551 182)		
	-	NIOSH 5506 (POLY	YNUCLEAR AROMATIC	<b>HYDROCARBONS</b>	by HPLC) - 1998
	-	NIOSH 5515 (POLY	YNUCLEAR AROMATIC	<b>HYDROCARBONS</b>	by GC) - 1994
	=	OSHA 35 (Napthale	ene) - 1982		
BMGV:			Other	nformation:	

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assesmen factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assesmen factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/kg dw	
	Environment - sediment, marine		PNEC	3,04	mg/kg dw	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assesmen factor 100
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesmen factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesmen factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m3	Overall assesmen factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	



(B)

Page 7 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Workers / employees	Human - inhalation	Short term, local	DNEL	2420	mg/m3	
		effects				
Workers / employees	Human - inhalation	Long term, systemic	DNEL	1210	mg/m3	
		effects				

Hydrocarbons, C10, aromatics, <1% naphthalene									
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Descriptor Value		Note			
Consumer	Human - dermal	Long term	DNEL	7,5	mg/kg bw/day				
Consumer	Human - inhalation	Long term	DNEL	32	mg/m3				
Consumer	Human - oral	Long term	DNEL	7,5	mg/kg bw/day				
Workers / employees	Human - dermal	Long term	DNEL	12,5	mg/kg bw/day				
Workers / employees	Human - inhalation	Long term	DNEL	151	mg/m3				

Hydrocarbons, C10, aron	natics, >1% naphthalene					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	or Value Unit		Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	2,4	μg/l	
	Environment - marine		PNEC	0,24	μg/l	
	Environment - sewage treatment plant		PNEC	2,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,0672	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,0672	mg/kg dry weight	
	Environment - soil		PNEC	0,0533	mg/kg dry weight	
	Environment - sporadic (intermittent) release		PNEC	0,02	mg/l	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	

Phenol, dodecyl-, branched						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
					•	



(B)

Page 8 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

	Environment - freshwater		PNEC	0,074	μg/l	
	Environment - marine		PNEC	0,007	μg/l	
	Environment - sediment, freshwater		PNEC	0,226	mg/kg	
	Environment - sediment, marine		PNEC	0,027	mg/kg	
	Environment - soil		PNEC	0,118	mg/kg	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - oral (animal feed)		PNEC	4	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,075	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13,26	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,79	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,075	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,26	mg/kg bw/day	
Consumer	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	166	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	44,18	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,25	mg/kg bw/day	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eve/face protection:

Tight fitting protective goggles with side protection (EN 166).



Page 9 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Minimum layer thickness in mm:

Permeation time (penetration time) in minutes:

>= 120

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

If applicable

Protective working garment, antistatic (EN1149)

Low inflammability protective clothing.

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

# 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

Liquid

Yellow, Clear

Characteristic

Flammable

<21 °C

#### 9.1 Information on basic physical and chemical properties

Physical state:

Colour: Odour:

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

Kinematic viscosity:

Vapour pressure:

Density and/or relative density: Relative vapour density: Particle characteristics:

Solubility:

Partition coefficient n-octanol/water (log value):

There is no information available on this parameter. There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

Does not apply to liquids.

Does not apply to mixtures.

0,561 mm2/s (20°C)

Not miscible

Mixture is non-soluble (in water).

#### 9.2 Other information



Page 10 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger
Pro-Line JetClean Diesel Intake System Cleaner

Explosives: Oxidising liquids:

There is no information available on this parameter. There is no information available on this parameter.

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

# 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

Heating, open flame, ignition sources Electrostatic charge

#### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

#### 10.6 Hazardous decomposition products

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Pro-Line JetClean Ansaugsyste						
Pro-Line JetClean Diesel Intake Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:		1 4.40		g	1000111001	n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the real Naphthalene content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Acetone						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		



Page 11 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Skin corrosion/irritation:				Guinea pig		Repeated
Skiii Coirosion/iintation.				Guiriea pig		exposure may
						cause skin
						dryness or
						cracking., Not
						irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Eye Irrit. 2
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
g ,					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
com con managementy.				typhimurium	Reverse Mutation Test)	1.0940
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
Germ cen matagemeny.				Warring	Mammalian	Negative
					Chromosome	
					Aberration Test)	
Donroductivo tovicity				Rat	OECD 414 (Prenatal	Negative
Reproductive toxicity				Nai		Negative
(Developmental toxicity):					Developmental Toxicity	
0					Study)	
Symptoms:						unconsciousness
						, vomiting,
						headaches,
						gastrointestinal
						disturbances,
						fatigue, mucous
						membrane
						irritation,
						dizziness,
						nausea,
						drowsiness
Specific target organ toxicity -	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	
oral:			~~		Toxicity Study in	
oran.					Rodents)	
	1				Nouthis)	

Hydrocarbons, C10, aromatics	, <1% naphtha	alene				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 479 (Genetic	Negative
					Toxicology - In Vitro	
					Sister Chromatid	
					Exchange assay in	
					Mammalian Cells)	



B.

Page 12 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Reproductive toxicity:	OECD 414 (Prenata	
	Developmental Toxic	city
	Study)	
Specific target organ toxicity -	OECD 408 (Repeate	d Negative
repeated exposure (STOT-RE):	Dose 90-Day Oral	
	Toxicity Study in	
	Rodents)	
Aspiration hazard:		Yes
Symptoms:		headaches,
		dizziness,
		fatigue, nausea
		and vomiting.
Symptoms:		drowsiness,
		headaches,
		drowsiness,
		dizziness

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	6318	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 416 (Two- generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion



Page 13 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Specific target organ toxicity -						Vapours may
single exposure (STOT-SE):						cause
						drowsiness and
						dizziness.,
						STOT SE 3,
						H336
Specific target organ toxicity -					OECD 452 (Chronic	Negative,
repeated exposure (STOT-RE):					Toxicity Studies)	Analogous
, , , , , ,					, ,	conclusion
Aspiration hazard:						Yes
Symptoms:						drowsiness,
						headaches,
						drowsiness,
						dizziness
Specific target organ toxicity -	NOAEL	750	mg/kg	Rat	OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE),					Dose 90-Day Oral	Analogous
oral:					Toxicity Study in	conclusion
					Rodents)	
Specific target organ toxicity -	NOAEL	495	mg/kg	Rat	OECD 411 (Subchronic	Negative,
repeated exposure (STOT-RE),					Dermal Toxicity - 90-day	Analogous
dermal:					Study)	conclusion
Specific target organ toxicity -	NOAEL	1000	mg/m3	Rat	OECD 413 (Subchronic	Negative,
repeated exposure (STOT-RE),					Inhalation Toxicity - 90-	Analogous
inhalat.:					Day Study)	conclusion

Naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>110	mg/l/4h	Rat		Vapours
Respiratory or skin				Guinea pig		No (skin contact)
sensitisation:						
Symptoms:						lack of appetite, ataxia, breathing difficulties, unconsciousness, diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting., sweating, Reddening, eyes, reddened

Phenol, dodecyl-, branched						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2100	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	5000	mg/kg	Rabbit		
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	_



Page 14 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger
Pro-Line JetClean Diesel Intake System Cleaner

Reproductive toxicity:	NOAEL	1,5-15	mg/kg	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	
Symptoms:						mucous membrane irritation
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	60	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

#### 11.2. Information on other hazards

Pro-Line JetClean Ansaugsyste	emreiniger										
Pro-Line JetClean Diesel Intake System Cleaner											
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes					
Endocrine disrupting properties:						Does not apply					
						to mixtures.					
Other information:						No other					
						relevant					
						information					
						available on					
						adverse effects					
						on health.					

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Acetone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other organisms:	EC5	72h	28	mg/l	Entosiphon		
_					sulcatum		
12.1. Toxicity to fish:	EC50	96h	8300	mg/l	Lepomis		
-					macrochirus		
12.1. Toxicity to fish:	LC50	96h	8300	mg/l	Lepomis		
-					macrochirus		
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus		
-					mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		



Page 15 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

12.1. Toxicity to daphnia:	EC50	48h	6100- 12700	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	8800	mg/l	Daphnia pulex	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	8d	530	mg/l		DIN 38412 T.9	Test organism: M. aeruginosa
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	91	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.2. Persistence and degradability:		30d	81-92	%		Regulation (EC) 440/2008 C.4-E (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - CLOSED BOTTLE TEST)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,24			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	
12.3. Bioaccumulative potential:	BCF		0,19			cure uy	Low
12.4. Mobility in soil: 12.5. Results of PBT and vPvB assessment							No adsorption in soil. No PBT substance, No
Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	vPvB substance
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	Pseudomonas putida		
Other information:	BOD5		1760- 1900	mg/g			
Other information: Other information:	AOX COD		2070	% mg/g			
	•	•	_		-		

Hydrocarbons, C10, aromatics, <1% naphthalene										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			



Page 16 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	1,6	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	2 - 5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	3 -10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	1 -3	mg/l		,	
12.2. Persistence and degradability:		28d	49,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable., Inherent
12.3. Bioaccumulative potential:	BCF		<100			, , ,	Low
Water solubility:							Insoluble

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,48	mg/l	Daphnia magna		Analogous conclusion
12.3. Bioaccumulative potential:	BCF		99-5780				High
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	58	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		2,8-6,5				High
12.5. Results of PBT and vPvB assessment							No PBT substance, N vPvB substa

# Naphthalene



Page 17 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l	Oncorhynchus		
					mykiss		
12.4. Mobility in soil:	Koc		240-		•		
-			1300				
12.1. Toxicity to fish:	LC50	96h	1,99	mg/l	Pimephales		Does not
-					promelas		conform with EU
					'		classification.
12.1. Toxicity to daphnia:	EC50	48h	1,6-24,1	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	>60d	0,6	mg/l	Daphnia pulex		
12.1. Toxicity to algae:	ErC50	72h	0,4	mg/l	Skeletonema		
					costatum		
12.2. Persistence and		28d	2	%			Not readily
degradability:							biodegradable
12.3. Bioaccumulative	BCF	28d	40-300				Lowfish
potential:							
Other information:	BOD5		0	%			
Other information:	COD		22	%			
Other information:	Log Pow		3,3				

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	40	mg/l	Pimephales	OECD 203 (Fish,	
-					promelas	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,037	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,004	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
<del> </del>						Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	0,15	mg/l	Desmodesmus	OECD 201 (Alga,	
					subspicatus	Growth Inhibition	
10.0 5		00.1		0/		Test)	N1 ( 17)
12.2. Persistence and		28d	25	%		OECD 301 B	Not readily
degradability:						(Ready	biodegradable
						Biodegradability - Co2 Evolution	
12.3. Bioaccumulative	Log Pow		7,1-7,14			Test)	
ootential:	Log Fow		7,1-7,14				
12.3. Bioaccumulative	BCF		794,33-				High
potential:			823				

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU) 14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material



Page 18 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

# **SECTION 14: Transport information**

#### **General statements**

14.1. UN number or ID number: 1993

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE)

14.3. Transport hazard class(es): 3 14.4. Packing group: Ш Classification code: F1

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (ACETONE, SOLVENT NAPHTHA)

14.3. Transport hazard class(es): 3 14.4. Packing group: Ш FmS: F-E, S-E Marine Pollutant:

14.5. Environmental hazards: environmentally hazardous

#### Transport by air (IATA)

14.2. UN proper shipping name: Flammable liquid, n.o.s. (ACETONE)

14.3. Transport hazard class(es): 3 14.4. Packing group: Ш

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

#### 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request. Comply with special provisions.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Phenol, dodecyl-, branched

This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):









Page 19 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

99,8 %

Observe incident regulations.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections: 1-16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H360F May damage fertility.

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid

Eye Irrit. — Eye irritation

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Carc. — Carcinogenicity



(B)

Page 20 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

Acute Tox. — Acute toxicity - oral

Aquatic Acute — Hazardous to the aquatic environment - acute

Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage Repr. — Reproductive toxicity

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil



Page 21 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 31.08.2021 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

Pro-Line JetClean Ansaugsystemreiniger Pro-Line JetClean Diesel Intake System Cleaner

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

International Maritime Code for Dangerous Goods IMDG-code

including, inclusive

**IUCLID International Uniform Chemical Information Database** IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

**Limited Quantities** LQ

**MARPOL** International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PΕ Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

**PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

Volatile organic compounds VOC

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

# These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.