

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

അ

Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

See definition of the substance or mixture.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAsp. Tox.1H304-May be fatal

H304-May be fatal if swallowed and enters airways.

2.2 Label elements Labeling according to Regulation (EC) 1272/2

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection



Danger

H304-May be fatal if swallowed and enters airways.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

01-2119457273-39-XXXX
918-481-9
80-<100
Asp. Tox. 1, H304

2-ethylhexanoic acid	
Registration number (REACH)	
Index	607-230-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	205-743-6
CAS	149-57-5
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361d

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.



Page 3 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately. Danger of aspiration. In case of vomiting, keep head low so that the stomach content does not reach the lungs. Immediate admittance to a hospital.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Product removes fat. Drying of the skin. Dermatitis (skin inflammation) Ingestion: Nausea Vomiting Danger of aspiration. Oedema of the lungs Chemical pneumonitis (condition similar to pneumonia) In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases Flammable vapour/air mixtures

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

ആ

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Avoid inhalation of the vapours. Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells. Under all circumstances prevent penetration into the soil.

Do not store with oxidizing agents.

Store in a well ventilated place.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

ആ

С	Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		Content %:80- <100				
WEL-	-TWA: 800 mg/m3	WEL-STEL:						
Monit	toring procedures:	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 						
		- Draeger - Hydrocarbons 2/a (81 03 581)						
		- Compur - KITA-187 S (551 174)						
BMG	V:	Other information: (C	DEL acc. 1	to RCP-method,				
		paragraphs 84-87, EH	paragraphs 84-87, EH40)					

2-ethylhexanoic acid						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0.017	mg/l	
	Environment - marine		PNEC	0,0017	mg/l	
	Environment - sediment, freshwater		PNEC	0,28	mg/kg dw	
	Environment - sediment, marine		PNEC	0,028	mg/kg dw	
	Environment - soil		PNEC	0,047	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	3,5	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	14	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit (15-minute reference period).

value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.



Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

ആ

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: > 480 Protective Viton® / fluoroelastomer gloves (EN 374). The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black, Brown, Red
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>63 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,7989 g/ml (15°C)
Bulk density:	n.a.



Page 7 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

Solubility(ies):

œ

Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties: Oxidising properties:

9.2 Other information Miscibility:

Fat solubility / solvent: Conductivity: Surface tension: Solvents content: Not determined Insoluble Not determined Not determined <7 mm2/s (40°C) Product is not explosive. No

Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Heating, open flame, ignition sources Electrostatic charge **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Pro-Line Dieselpartikelfilter-Sc	hutz					
Pro-Line Diesel Particulate Filte	er Protection					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						



ആ Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection Aspiration hazard: n.d.a. Symptoms: n.d.a. Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Toxicity / effect Endpoint Organism Test method Notes Value Unit OECD 401 (Acute Oral Acute toxicity, by oral route: LD50 >5000 mg/kg Rat Analogous Toxicity) conclusion LD50 >5000 OECD 402 (Acute Acute toxicity, by dermal route: mg/kg Rabbit Analogous Dermal Toxicity) conclusion LC50 Acute toxicity, by inhalation: >4951 mg/m3/4h Rat OECD 403 (Acute Analogous Inhalation Toxicity) conclusion, Vapours Skin corrosion/irritation: OECD 404 (Acute Not irritant, Dermal Analogous Irritation/Corrosion) conclusion Serious eye damage/irritation: OECD 405 (Acute Eye Not irritant, Irritation/Corrosion) Analogous conclusion Respiratory or skin OECD 406 (Skin Not sensitizising, sensitisation: Sensitisation) Analogous conclusion Germ cell mutagenicity: OECD 473 (In Vitro Negative, Mammalian Analogous Chromosome conclusion Aberration Test) OECD 474 (Mammalian Germ cell mutagenicity: Negative, Erythrocyte Analogous Micronucleus Test) conclusion Germ cell mutagenicity: Salmonella OECD 471 (Bacterial Negative Reverse Mutation Test) typhimurium Carcinogenicity: OECD 453 (Combined Negative, Analogous Chronic Toxicity/Carcinogenicity conclusion Studies) Reproductive toxicity: OECD 414 (Prenatal Negative, **Developmental Toxicity** Analogous Study) conclusion Specific target organ toxicity -OECD 408 (Repeated Negative, repeated exposure (STOT-RE): Dose 90-Day Oral Analogous Toxicity Study in conclusion Rodents) Aspiration hazard: Yes Symptoms: unconsciousness headaches. dizziness, mucous membrane irritation Other information: Repeated exposure may cause skin dryness or cracking.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2043	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	

. • •



Page 9 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.01.2019 / 0012
Replacing version dated / version: 14.11.2018 / 0011
Valid from: 29.01.2019
PDF print date: 26.07.2021
Pro-Line Dieselpartikelfilter-Schutz
Pro-Line Diesel Particulate Filter Protection

œ

Serious eye damage/irritation:			Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin			Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:				Sensitisation)	
Germ cell mutagenicity:				OECD 471 (Bacterial	Negative
				Reverse Mutation Test)	
Germ cell mutagenicity:				OECD 473 (In Vitro	Negative
				Mammalian	
				Chromosome	
				Aberration Test)	
Germ cell mutagenicity:				OECD 474 (Mammalian	Negative
				Erythrocyte	
				Micronucleus Test)	
Germ cell mutagenicity:				OECD 476 (In Vitro	Negative
				Mammalian Cell Gene	_
				Mutation Test)	
Reproductive toxicity	600	mg/kg	Rat		Repr. 2oral
(Developmental toxicity):					
Reproductive toxicity (Effects					Possible
on fertility):					
Specific target organ toxicity -					Negative
single exposure (STOT-SE):					
Specific target organ toxicity -					Negative
repeated exposure (STOT-RE):					
Symptoms:					acidosis,
					respiratory
					distress,
					vomiting,
					coughing,
					headaches

SECTION 12: Ecological information

Pro-Line Dieselpartikelfilter-Schutz										
Pro-Line Diesel Particulate Filter Protection										
Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:							n.d.a.			
12.1. Toxicity to daphnia:							n.d.a.			
12.1. Toxicity to algae:							n.d.a.			
12.2. Persistence and							n.d.a.			
degradability:										
12.3. Bioaccumulative							n.d.a.			
potential:										
12.4. Mobility in soil:							n.d.a.			
12.5. Results of PBT							n.d.a.			
and vPvB assessment										
12.6. Other adverse							n.d.a.			
effects:										

Tryulocal bolls, CTO-CTS	Trychocarbons, c to-c to, tr-aixanes, isoaixanes, cyclics, <2 / a romatics										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.5. Results of PBT							No PBT				
and vPvB assessment							substance, No				
							vPvB substance				
Water solubility:							Product floats on				
-							the water				
							surface.				
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,					
					mykiss	Acute Toxicity					
						Test)					
	•				•						



Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

(GB)·

12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

2-ethylhexanoic acid							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL		25	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oryzias latipes	OECD 203 (Fish,	
						Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	85,4	mg/l	Daphnia magna	OEĆD 202	
				0		(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	49.3-	mg/l	Scenedesmus	DIN 38412 T.9	
	2000	1211	60,5	iiig/i	subspicatus	DIN 30412 1.5	
12.2. Persistence and		28d	90-100	%	Subspicatus	OECD 301 E	Readily
degradability:		200	90-100	/0		(Ready	biodegradable
							Diouegrauable
						Biodegradability - Modified OECD	
						Screening Test)	
12.3. Bioaccumulative	Log Pow		2,7				Low
potential:							
Toxicity to bacteria:	EC50	17h	112,1	mg/l	Pseudomonas	DIN 38412 T.8	
					putida		
Other information:	COD		2240	mg/kg			
Other information:	BOD		1200	mg/kg			
Other information:	Koc		140,87			OECD 106	
						(Adsorption/Desor	
						ption Using a	
						Batch Equilibrium	
						Method)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 07 03 other fuels (including mixtures)

14 06 03 other solvents and solvent mixtures



Page 11 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant.

(GB)

For contaminated packing material

Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements			
14.1. UN number:	n.a.		
Transport by road/by rail (ADR/RID)			
14.2. UN proper shipping name:			
14.3. Transport hazard class(es):	n.a.		
14.4. Packing group:	n.a.		
Classification code:	n.a.		
LQ:	n.a.		
14.5. Environmental hazards:	Not applicable		
Tunnel restriction code:			
Transport by sea (IMDG-code)			
14.2. UN proper shipping name:			
14.3. Transport hazard class(es):	n.a.		
14.4. Packing group:	n.a.		
Marine Pollutant:	n.a		
14.5. Environmental hazards:	Not applicable		
Transport by air (IATA)			
14.2. UN proper shipping name:			
14.3. Transport hazard class(es):	n.a.		
14.4. Packing group:	n.a.		
14.5. Environmental hazards:	Not applicable		
14.6. Special precautions for user			

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

98,785 %

2, 3, 8, 11, 12, 15

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):



Page 12 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361d Suspected of damaging the unborn child. H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard Repr. — Reproductive toxicity

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) Acute Toxicity Estimate ATE BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dry weight dw e.g. for example (abbreviation of Latin 'exempli gratia'), for instance EC European Community ECHA European Chemicals Agency EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) etc. et cetera FU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) LQ Limited Quantities



ആ Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.01.2019 / 0012 Replacing version dated / version: 14.11.2018 / 0011 Valid from: 29.01.2019 PDF print date: 26.07.2021 Pro-Line Dieselpartikelfilter-Schutz Pro-Line Diesel Particulate Filter Protection International Convention for the Prevention of Marine Pollution from Ships MARPOL n.a. not applicable not available n.av. not checked n.c. no data available n.d.a. OECD Organisation for Economic Co-operation and Development ora. organic persistent, bioaccumulative and toxic PBT ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million Polyvinylchloride PVC REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.