

Page 1 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

œ

Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

	of the substance or mixtu ording to Regulation (EC)	
Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 21

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner



Danger

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking. EUH208-Contains Maleic anhydride. May produce an allergic reaction.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10, aromatics, >1% naphthalene Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	
content %	60-90
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119456620-43-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	926-141-6
CAS	
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304
Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	01-2119463588-24-XXXX



Page 3 of 21

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

919-284-0
(64742-94-5)
1-5
EUH066
Carc. 2, H351
STOT SE 3, H336
Asp. Tox. 1, H304
Aquatic Chronic 2, H411

Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	202-049-5
CAS	91-20-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Carc. 2, H351
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Maleic anhydride	
Registration number (REACH)	
Index	607-096-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	203-571-6
CAS	108-31-6
content %	<0,001
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH071
	Acute Tox. 4, H302
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
	Resp. Sens. 1, H334
	Skin Sens. 1A, H317
	STOT RE 1, H372 (respiratory system) (as inhalation)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,001 %

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here. A classification for the mixture with Carc. 2, H351 is not required as the naphthalene content in the product is < 1%. There are no other ingredients with this classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wash thoroughly with soap and water - consult doctor if necessary.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.



Page 4 of 21

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting - give copious water to drink. Consult doctor immediately. Danger of aspiration. In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Alcohol resistant foam Extinction powder Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Toxic gases Flammable vapour/air mixtures

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition. Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities. 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.



Page 5 of 21

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells.

Observe special storage conditions.

Solvent resistant floor

Do not store with oxidizing agents.

Store in a well ventilated place.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics				
WEL-TWA: 800 mg/m3	WEL-STEL:				
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571)				
	 Draeger - Hydrocarbons 2/a (81 0) 	3 581)			
	 Compur - KITA-187 S (551 174) 				
BMGV:		Other information: (O	EL acc. to RCP-method,		
		paragraphs 84-87, EH4	40)		
Chemical Name	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyc	lics, <2% aromatics			
WEL-TWA: 1200 mg/m3 (>=C7 nc	rmal and branched WEL-STEL:				
chain alkanes)					
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c (8 	1 03 571)			
	 Draeger - Hydrocarbons 2/a (81 03) 	3 581)			
	- Compur - KITA-187 S (551 174)				
BMGV:		Other information:			
Chemical Name	Hydrocarbons, C10, aromatics, >1% naphthalene				



Page 6 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

compartment

œ

WEL-STEL:		
Draeger - Hydrocarbons 0,1%/c (81	03 571)	
Draeger - Hydrocarbons 2/a (81 03	581)	
Compur - KITA-187 S (551 174)		
	Other information:	
WEL-STEL:		
Compur - KITA-153 U(C) (551 182)	1	
NIOSH 5506 (POLYNUCLEAR AR	OMATIC HYDROCARBC	NS by HPLC) - 1998
NIOSH 5515 (POLYNUCLEAR AR	OMATIC HYDROCARBC	NS by GC) - 1994
OSHA 35 (Napthalene) - 1982		
	Other information:	
9		
WEL-STEL: 3 mg/m3		
	Other information: Se	n
	Draeger - Hydrocarbons 0,1%/c (81 Draeger - Hydrocarbons 2/a (81 03 Compur - KITA-187 S (551 174) WEL-STEL: Compur - KITA-153 U(C) (551 182) NIOSH 5506 (POLYNUCLEAR ARC NIOSH 5515 (POLYNUCLEAR ARC OSHA 35 (Napthalene) - 1982 WEL-STEL: 3 mg/m3	Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) Other information: WEL-STEL: Compur - KITA-153 U(C) (551 182) NIOSH 5506 (POLYNUCLEAR AROMATIC HYDROCARBC NIOSH 5515 (POLYNUCLEAR AROMATIC HYDROCARBC OSHA 35 (Napthalene) - 1982 Other information:

Hydrocarbons, C10, arom	atics, >1% naphthalene					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3	

Naphthalene Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
Area of application	Environmental	Effect on health	Descriptor	value	Unit	Note
	compartment					
	Environment - freshwater		PNEC	2,4	µg/l	
	Environment - marine		PNEC	0,24	µg/l	
	Environment - sewage treatment plant		PNEC	2,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,0672	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,0672	mg/kg dry weight	
	Environment - soil		PNEC	0,0533	mg/kg dry weight	
	Environment - sporadic (intermittent) release		PNEC	0,02	mg/l	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	
Maleic anhydride Area of application	Exposure route /	Effect on health	DNEL	25 Value	Unit	Not
	Environmental		Descriptor	value	Unit	Note



Page 7 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

ആ

	Environment - freshwater		PNEC	0,04281	mg/l
	Environment - marine		PNEC	0,00428	mg/l
	Environment - water, sporadic (intermittent) release		PNEC	0,4281	mg/l
	Environment - sediment, freshwater		PNEC	0,334	mg/kg
	Environment - sediment, marine		PNEC	0,0334	mg/kg
	Environment - soil		PNEC	0,0415	mg/kg
	Environment - sewage treatment plant		PNEC	44,6	mg/l
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,4	mg/m3
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,8	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,4	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,8	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,04	mg/kg bw/d
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,04	mg/kg bw/d
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	0,04	mg/kg bw/d
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,04	mg/kg bw/d

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).



Page 8 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Skin protection - Hand protection: Solvent resistant protective gloves (EN ISO 374). If applicable Protective Viton® / fluoroelastomer gloves (EN ISO 374). Permeation time (penetration time) in minutes: > 480 Minimum layer thickness in mm: > 0.4

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

orr mormation on Bable physical and onon	
Physical state:	Liquid
Colour:	Light yellow
Colour:	Clear
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	>63 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<7 mm2/s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,820 g/ml (15°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
9.2 Other information	
Explosives:	There is no information available on this parameter.



Page 9 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Oxidising liquids:

œ

No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong oxidizing agents. Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).
Pro-Line Fuel Injection Cleaner

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						negative, the
						real
						Naphthalene
						content is <1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
cute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous
					Inhalation Toxicity)	conclusion,
						Vapours



Page 10 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

œ.

Skin corrosion/irritation:		OECD 404 (Acute	Not irritant,
		Dermal	Analogous
		Irritation/Corrosion)	conclusion
Serious eye damage/irritation:		OECD 405 (Acute Eye	Not irritant,
		Irritation/Corrosion)	Analogous
			conclusion
Respiratory or skin		OECD 406 (Skin	Not sensitizising,
sensitisation:		Sensitisation)	Analogous
		,	conclusion
Germ cell mutagenicity:		OECD 473 (In Vitro	Negative,
		Mammalian	Analogous
		Chromosome	conclusion
		Aberration Test)	
Germ cell mutagenicity:		OECD 474 (Mammalian	Negative,
		Erythrocyte	Analogous
		Micronucleus Test)	conclusion
Germ cell mutagenicity:	Salmonella	OECD 471 (Bacterial	Negative
	typhimurium	Reverse Mutation Test)	
Carcinogenicity:		OECD 453 (Combined	Negative,
5,		Chronic	Analogous
		Toxicity/Carcinogenicity	conclusion
		Studies)	
Reproductive toxicity:		OECD 414 (Prenatal	Negative,
· · · · · · · · · · · · · · · · · · ·		Developmental Toxicity	Analogous
		Study)	conclusion
Specific target organ toxicity -		OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):		Dose 90-Day Oral	Analogous
		Toxicity Study in	conclusion
		Rodents)	
Aspiration hazard:		Rodenio	Yes
Symptoms:			unconsciousnes
- / ··· / · ·····			, headaches,
			dizziness.
			mucous
			membrane
			irritation
			mation

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	in vivo	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion



Page 11 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

œ

	1			1		
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative,
					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Carcinogenicity:					OECD 453 (Combined	Analogous
					Chronic	conclusion,
					Toxicity/Carcinogenicity	Negative
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Analogous
					Developmental Toxicity	conclusion,
					Study)	Negative
Specific target organ toxicity -						Analogous
single exposure (STOT-SE):						conclusion, No
C						indications of
						such an effect.
Specific target organ toxicity -	NOAEL	>=1000	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE):			bw/d		Dose 90-Day Oral	
,					Toxicity Study in	
					Rodents)	
Aspiration hazard:						Yes
Symptoms:						drying of the
						skin.,
						headaches,
						fatigue,
						dizziness,
						nausea,
						diarrhoea,
						vomiting

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	6318	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion



B Page 12 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic Toxicology - In Vitro	Negative, Analogous
					Sister Chromatid Exchange assay in Mammalian Cells)	conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
Cerm cen mutagemony.				typhimurium	Reverse Mutation Test)	Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	>450	mg/kg	Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 416 (Two- generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	750	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Symptoms:						drowsiness, headaches, drowsiness, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	495	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE),	NOAEL	1000	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Negative, Analogous

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat			
Acute toxicity, by inhalation:	LC50	>110	mg/l/4h	Rat		Vapours	
Respiratory or skin				Guinea pig		No (skin contact)	
sensitisation:							



OB ______ Page 13 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Symptoms:		lack of appetite,
		ataxia, breathing
		difficulties,
		unconsciousness
		, diarrhoea,
		cornea opacity,
		headaches,
		cramps,
		gastrointestinal
		disturbances,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.,
		sweating,
		Reddening,
		eyes, reddened

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1090	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	2620	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4,35	mg/l/4h	Mouse		
Skin corrosion/irritation:				Human being		Corrosive
Skin corrosion/irritation:				Rat		Corrosive
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin				Guinea pig	OECD 406 (Skin	Sensitising (skin
sensitisation:					Sensitisation)	contact)
Respiratory or skin sensitisation:				Rat		Sensitising (inhalation)
Germ cell mutagenicity:					bacterial	References, Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	>100	mg/kg bw/d	Rat		oral
Reproductive toxicity:	NOAEC	650	mg/kg bw/d	Rat		
Reproductive toxicity:	NOAEL	55	mg/kg	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	



B Page 14 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Symptoms:						asthmatic symptoms, breathing difficulties, respiratory distress, burning of the membranes of the nose and throat, blisters, coughing, headaches, gastrointestinal disturbances, mucous membrane irritation, watering eyes, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	10	mg/kg/d	Rat	OECD 452 (Chronic Toxicity Studies)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	3,3	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Vapours

11.2. Information on other hazards

Pro-Line Fuel Injection Cleaner							
Pro-Line Gasoline System Cleaner							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Endocrine disrupting properties:						Does not apply	
						to mixtures.	
Other information:						No other	
						relevant	
						information	
						available on	
						adverse effects	
						on health.	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Other information:						Repeated		
						exposure may		
						cause skin		
						dryness or		
						cracking.		

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification). **Pro-Line Fuel Injection Cleaner** Pro-Line Gasoline System Cleaner Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: 12.1. Toxicity to algae: n.d.a. n.d.a. 12.2. Persistence and Isolate as much degradability: as possible with an oil separator. 12.3. Bioaccumulative n.d.a. potential:



Page 15 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

œ

12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Endocrine	Does not apply
disrupting properties:	to mixtures.
12.7. Other adverse	No information
effects:	available on
	other adverse
	effects on the
	environment.
Other information:	According to the
	recipe, contains
	no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No vPvB substance
Water solubility:							Product floats or
							the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

oxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:							Insoluble
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
				-	a subcapitata	Growth Inhibition	
						Test)	



OB ______ Page 16 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

12.2. Persistence and		28d	69	%	OECD 301 F	Readily
degradability:					(Ready	biodegradable
					Biodegradability -	
					Manometric	
					Respirometry Test)	
12.3. Bioaccumulative	Log Pow		6-8			High
potential:						
12.5. Results of PBT						No PBT
and vPvB assessment						substance, No
						vPvB substance

Hydrocarbons, C10, aror		1	1	1			
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,48	mg/l	Daphnia magna		Analogous
							conclusion
12.3. Bioaccumulative potential:	BCF		99-5780				High
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus		
				-	mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell		
				-	a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell		
				_	a subcapitata		
12.2. Persistence and		28d	58	%	activated sludge	OECD 301 F	Analogous
degradability:						(Ready	conclusion
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Pow		2,8-6,5				High
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l	Oncorhynchus mykiss		
12.4. Mobility in soil:	Koc		240- 1300				
12.1. Toxicity to fish:	LC50	96h	1,99	mg/l	Pimephales promelas		Does not conform with EU classification.
12.1. Toxicity to daphnia:	EC50	48h	1,6-24,1	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	>60d	0,6	mg/l	Daphnia pulex		
12.1. Toxicity to algae:	ErC50	72h	0,4	mg/l	Skeletonema costatum		
12.2. Persistence and degradability:		28d	2	%			Not readily biodegradable
12.3. Bioaccumulative potential:	BCF	28d	40-300				Lowfish
Other information:	BOD5		0	%			
Other information:	COD		22	%			
Other information:	Log Pow		3,3				

Endpoint	Time	Value	Unit	Organism	Test method	Notes
LC50	96h	75	mg/l	Oncorhynchus		EPA-660/3-75-
			_	mykiss		009
LC50	96h	75	mg/l	Lepomis		EPA-660/3-75-
			_	macrochirus		009
NOEC/NOEL	21d	10	mg/l	Daphnia magna		
	LC50 LC50	LC50 96h LC50 96h	LC50 96h 75 LC50 96h 75	LC50 96h 75 mg/l LC50 96h 75 mg/l	LC5096h75mg/lOncorhynchus mykissLC5096h75mg/lLepomis macrochirus	LC50 96h 75 mg/l Oncorhynchus mykiss LC50 96h 75 mg/l Lepomis macrochirus



Page 17 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

ആ

48h 42,81 **OECD 202** 12.1. Toxicity to daphnia: EC50 mg/l Daphnia magna (Daphnia sp. Acute Immobilisation Test) 74,32 OECD 201 (Alga, 12.1. Toxicity to algae: EC50 72h Pseudokirchneriell mg/l a subcapitata Growth Inhibition Test) EC10 72h 11,8 Pseudokirchneriell 12.1. Toxicity to algae: mg/l OECD 201 (Alga, a subcapitata Growth Inhibition Test) 12.1. Toxicity to algae: EC50 72h 29 Desmodesmus OECD 201 (Alga, mg/l subspicatus Growth Inhibition Test) 12.1. Toxicity to algae: EC10 72h 23 mg/l Desmodesmus OECD 201 (Alga. Growth Inhibition subspicatus Test) OECD 301 E 12.2. Persistence and 7d 98 Hydrolysis % degradability: (Ready Biodegradability -Modified OECD Screening Test) 12.3. Bioaccumulative -2,61 - (-Log Pow Not to be potential: 2,16) expected 12.4. Mobility in soil: Koc 1 Not to be expected 12.5. Results of PBT No PBT and vPvB assessment substance, No vPvB substance Pseudomonas EC10 18h 44.6 mg/l IUCLID Chem. Toxicity to bacteria: References putida Data Sheet (ESIS) Other information: Log Pow 1.62

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:

Not applicable



_ (GB)		
Page 18 of 21		
Safety data sheet according to Regulation (EC) No	1907/2006, Annex II	
Revision date / version: 02.03.2023 / 0027		
Replacing version dated / version: 18.09.2022 / 002	26	
Valid from: 02.03.2023		
PDF print date: 02.03.2023		
Pro-Line Fuel Injection Cleaner		
Pro-Line Gasoline System Cleaner		
14.2. UN proper shipping name:		
Not applicable		
14.3. Transport hazard class(es):	Not applicable	
14.4. Packing group:	Not applicable	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	Not applicable	
Classification code:	Not applicable	
LQ:	Not applicable	
Transport category:	Not applicable	
Transport by sea (IMDG-code)		
14.1. UN number or ID number:	Not applicable	
14.2. UN proper shipping name:		
Not applicable		
14.3. Transport hazard class(es):	Not applicable	
14.4. Packing group:	Not applicable	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	Not applicable	
Transport by air (IATA)		
14.1. UN number or ID number:	Not applicable	
14.2. UN proper shipping name:		
Not applicable		
14.3. Transport hazard class(es):	Not applicable	
14.4. Packing group:	Not applicable	
14.5. Environmental hazards:	Not applicable	
14.6. Special precautions for user		
Unless specified otherwise, general measures for sa	afe transport must be followed.	
14.7. Maritime transport in bulk acc		

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

99,64 %

Observe restrictions:

-

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

3, 11, 12 These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification i	n accordance	with regulation
(EC) No. 1272/2	008 (CLP)	-

Evaluation method used



Page 19 of 21

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H372 Causes damage to organs through prolonged or repeated exposure by inhalation.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH071 Corrosive to the respiratory tract.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic Carc. — Carcinogenicity STOT SE — Specific target organ toxicity - single exposure - narcotic effects Acute Tox. — Acute toxicity - oral Aquatic Acute — Hazardous to the aquatic environment - acute Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage Resp. Sens. — Respiratory sensitization Skin Sens. — Skin sensitization STOT RE — Specific target organ toxicity - repeated exposure

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council



ആ Page 20 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner bw body weight CAS Chemical Abstracts Service CI P Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) carcinogenic, mutagenic, reproductive toxic CMR DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community FFC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic orq. OSHA Occupational Safety and Health Administration (USA) persistent, bioaccumulative and toxic PBT Polyethylene PF PNEC Predicted No Effect Concentration ppm parts per million **PVC** Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail)



Page 21 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 02.03.2023 / 0027 Replacing version dated / version: 18.09.2022 / 0026 Valid from: 02.03.2023 PDF print date: 02.03.2023 Pro-Line Fuel Injection Cleaner Pro-Line Gasoline System Cleaner

SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $\ensuremath{\mathbb{C}}$ by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.