

Page 1 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier

# Motorsystemreiniger Diesel Diesel Engine System Cleaner

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Fuel additive

#### **Uses advised against:**

No information available at present.

## 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Asp. Tox. 1 H304-May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner





#### Danger

H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P273-Avoid release to the environment.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH044-Risk of explosion if heated under confinement.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

## n.a. **3.2 Mixtures**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	
content %	60-80
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304

2-ethylhexyl nitrate	
Registration number (REACH)	01-2119539586-27-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	248-363-6
CAS	27247-96-7
content %	10-<25



Page 3 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH044
	EUH066
	Acute Tox. 4, H302
	Acute Tox. 4, H312
	Acute Tox. 4, H332
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	ATE (oral): 500 mg/kg
	ATE (dermal): 1100 mg/kg
	ATE (as inhalation, Aerosol): 1,5 mg/l/4h
	ATE (as inhalation, Vapours): 11 mg/l/4h

2-Ethylhexanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119487289-20-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	203-234-3
CAS	104-76-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	STOT SE 3, H335
Specific Concentration Limits and ATE	ATE (as inhalation, Vapours): 11 mg/l/4h
	ATE (as inhalation, Dusts or mist): 2,7 mg/l/4h

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here. The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

## **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

## Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes



Page 4 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Product removes fat.

Dermatitis (skin inflammation)

Inaestion:

Oedema of the lungs Lung damage

Chemical pneumonitis (condition similar to pneumonia)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

## 4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media Suitable extinguishing media

CO2

Extinction powder

Foam

## Unsuitable extinguishing media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion.

Explosive vapour/air or gas/air mixtures.

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

## **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

## 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

## 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.



Page 5 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020 Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Under all circumstances prevent penetration into the soil.

Do not store with oxidizing agents.

Store in a well ventilated place.

Protect from direct sunlight and warming.

Store cool.

#### 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Ob and a library	Lludus sada sus C	40.040	00/				
© Chemical Name	Hydrocarbons, C	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics					
WEL-TWA: 800 mg/m3		WEL-STEL:					
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c (8					
	=	Draeger - Hydrocarbons 2/a (81 03	581)				
	-	Compur - KITA-187 S (551 174)					
BMGV:			Other information: (O	EL acc. to RCP-method,			
			paragraphs 84-87, EH4	10)			
○ Chemical Name	2-Ethylhexanol						
WEL-TWA: 1 ppm (5,4 mg/m3) (W	/EL-TWA, EU)	WEL-STEL:					
Monitoring procedures:	-	Draeger - Alcohol 100/a (CH 29 70	1)				
BMGV:			Other information:				

2-ethy	lhexvl	nitrate



Page 6 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019
Valid from: 14.03.2024
PDF print date: 14.03.2024
Motorsystemeiniger Diesel Diesel Engine System Cleaner

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,8	μg/l	
	Environment - marine		PNEC	0,08	μg/l	
	Environment - soil		PNEC	0,00019 1	mg/kg dw	
	Environment - sediment, freshwater		PNEC	0,00074	mg/kg dw	
	Environment - sediment, marine		PNEC	0,00074	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,52	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,087	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,025	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	0,022	mg/cm2	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,044	mg/cm2	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - marine		PNEC	0,0017	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,17	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,284	mg/kg dw	
	Environment - sediment, marine		PNEC	0,028	mg/kg dw	
	Environment - soil		PNEC	0,047	mg/kg dw	
	Environment - oral (animal feed)		PNEC	55	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,1	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	53,2	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11,4	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,3	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	26,6	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	12,8	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	23	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	53,2	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	53,2	mg/m3	



Page 7 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Workers / employees	Human - oral	Long term, systemic	DNEL	12,8	mg/m3	
		effects				

- United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this

Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

## 8.2 Exposure controls

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown



Page 8 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Clear, Amber

Odour: Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

180 °C

Flammability: Flammable

Lower explosion limit: 0,6 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,

<2% aromatics)

Upper explosion limit: 7 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,

<2% aromatics) 63 °C

Flash point:

Auto-ignition temperature:

Decomposition temperature:

There is no information available on this parameter.

There is no information available on this parameter.

pH: Mixture is non-soluble (in water).

Kinematic viscosity: <7 mm2/s (40°C)
Solubility: Insoluble

Partition coefficient n-octanol/water (log value):

Does not apply to mixtures.

Vapour pressure:

Does not apply to mixtures.

There is no information available on this parameter.

Density and/or relative density:

Relative vapour density:

Particle characteristics:

0,834 g/ml (15°C)

Vapours heavier than air.

Does not apply to liquids.

9.2 Other information

Explosives: There is no information available on this parameter.

Oxidising liquids:

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

## 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

Risk of explosion if heated under confinement.

#### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

## 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids. Avoid contact with strong alkalis.



Œ

Page 9 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

## 10.6 Hazardous decomposition products

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Motorsystemreiniger Diesel		,	,			
<b>Diesel Engine System Cleaner</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous		
					Toxicity)	conclusion		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous		
					Dermal Toxicity)	conclusion		
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous		
					Inhalation Toxicity)	conclusion,		
						Vapours		
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,		
					Dermal	Analogous		
					Irritation/Corrosion)	conclusion		
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,		
					Irritation/Corrosion)	Analogous		
						conclusion		
Respiratory or skin					OECD 406 (Skin	Not sensitizising,		
sensitisation:					Sensitisation)	Analogous		
						conclusion		
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,		
					Mammalian	Analogous		
					Chromosome	conclusion		
					Aberration Test)			
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,		
					Erythrocyte	Analogous		
					Micronucleus Test)	conclusion		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative		
				typhimurium	Reverse Mutation Test)			
Carcinogenicity:					OECD 453 (Combined	Negative,		
					Chronic	Analogous		
					Toxicity/Carcinogenicity	conclusion		
					Studies)			



Page 10 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Reproductive toxicity:	OECD 414 (Prenatal	Negative,
	Developmental Toxicity	Analogous
	Study)	conclusion
Specific target organ toxicity -	OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):	Dose 90-Day Oral	Analogous
	Toxicity Study in	conclusion
	Rodents)	
Aspiration hazard:		Yes
Symptoms:		unconsciousness
		, headaches,
		dizziness,
		mucous
		membrane
		irritation

2-ethylhexyl nitrate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	500	mg/kg			
Acute toxicity, by dermal route:	ATE	1100	mg/kg			
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Reproductive toxicity:	NOAEL	20	mg/kg	Rat	OECD 421	Negative, oral
			bw/d		(Reproduction/Developm	
					ental Toxicity Screening	
					Test)	
Specific target organ toxicity -	NOAEL	500	mg/kg	Rabbit		Negativedermal
repeated exposure (STOT-RE),			bw/d			
dermal:						
Specific target organ toxicity -	NOAEL	863	mg/m3	Rat	OECD 413 (Subchronic	Vapours,
repeated exposure (STOT-RE),					Inhalation Toxicity - 90-	Analogous
inhalat.:					Day Study)	conclusion(90 d)
Symptoms:						headaches,
						dizziness,
						nausea, drop in
						blood pressure,
						diarrhoea,
						unconsciousness
						, eyes, reddened

2-Ethylhexanol										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Acute toxicity, by oral route:	LD50	2047	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)					



Page 11 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Acute toxicity, by dermal route:	LD50	>3000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	2,7	mg/l/4h		Definal Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	>0,89-5,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Actosol
Acute toxicity, by inhalation:	ATE	11	mg/l/4h		,	Vapours
Acute toxicity, by inhalation:	ATE	2,7	mg/l/4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)literature
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	NegativeChinese hamster
Carcinogenicity:	NOAEL	750	mg/kg bw/d	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	3000	ppm	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Reproductive toxicity (Developmental toxicity):				Mouse	OECD 414 (Prenatal Developmental Toxicity Study)	Negativeoral
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract, STOT SE 3, H335
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,6384	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Vapours
Symptoms:						unconsciousness, drop in blood pressure, vomiting, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	200	mg/kg bw/d	Mouse		

## 11.2. Information on other hazards

Motorsystemreiniger Diesel						
Diesel Engine System Cleaner						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



③B)·

Page 12 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Endocrine disrupting properties:			Does not apply to mixtures.
Other information:			No other relevant information available on adverse effects on health.

Hydrocarbons, C10-C13, n	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics											
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes						
Other information:						Repeated						
						exposure may						
						cause skin						
						dryness or						
						cracking.						

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
							an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							According to the
							recipe, contains
							no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	



Page 13 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		10-2500				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		
Water solubility:							Product floats on the water surface.

2-ethylhexyl nitrate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,83	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	EC50	72h	>2,53	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:	DOC	28d	0	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,24			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	High
12.3. Bioaccumulative potential:	BCF		1332			,	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

2-Ethylhexanol										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50	96h	17,1	mg/l	Leuciscus idus	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)				
12.1. Toxicity to fish:	LC50	96h	28,2	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)				



Page 14 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

12.1. Toxicity to daphnia:	EC50	48h	39	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	EC50	72h	16,6	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	5,3	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:	COD	14d	100	%	activated sludge	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,9			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	Low
12.3. Bioaccumulative potential:	BCF		25,33				calculated value, Low
12.4. Mobility in soil:			1,42				Not to be expected
12.4. Mobility in soil:	Koc		800				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	24h	>300	mg/l	activated sludge		
Toxicity to bacteria:	EC50	3h	540	mg/l	Pseudomonas putida		
Toxicity to bacteria:	EC50	12h	> 100	mg/l	activated sludge		

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

## For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.



Page 15 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## **SECTION 14: Transport information**

#### **General statements**

## Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 3082

14.2. UN proper shipping name:

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE)

14.3. Transport hazard class(es):
9
14.4. Packing group:
III

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Classification code:

M6
LQ:

Transport category:

3

Transport by sea (IMDG-code)

14.1. UN number or ID number: 3082

14.2. UN proper shipping name:

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE)

14.3. Transport hazard class(es):
9
14.4. Packing group:
III

14.4. Packing group.

14.5. Environmental hazards:

environmentally hazardous

Marine Pollutant: Yes EmS: F-A, S-F

Transport by air (IATA)

14.1. UN number or ID number: 3082

14.2. UN proper shipping name:

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (2-ETHYLHEXYL NITRATE)

14.3. Transport hazard class(es):
9
14.4. Packing group:
III

14.5. Environmental hazards: environmentally hazardous

## 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

#### 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

_	according to storage, rianding etc.).			
	Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
			dangerous substances as	dangerous substances as
			referred to in Article 3(10) for the	referred to in Article 3(10) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
ıſ	E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.









Page 16 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 . Motorsystemreiniger Diesel Diesel Engine System Cleaner

Directive 2010/75/EU (VOC):

89 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

Revised sections:

15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH044 Risk of explosion if heated under confinement.

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation

Aquatic Acute — Hazardous to the aquatic environment - acute

Skin Irrit. — Skin irritation Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

#### **Key literature references and sources for data:**

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.



Page 17 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

## Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR

International Carriage of Dangerous Goods by Road)

Adsorbable organic halogen compounds AOX

approx. approximately

Article number Art., Art. no.

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAM

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

**BSEF** The International Bromine Council

CAS Chemical Abstracts Service

Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

for example (abbreviation of Latin 'exempli gratia'), for instance e.a.

Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EbCx, EyCx, EbLx (x = 10, 50)

EC **European Community** 

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

**FINECS** European Inventory of Existing Commercial Chemical Substances

**ELINCS** European List of Notified Chemical Substances

ΕN **Furopean Norms** 

United States Environmental Protection Agency (United States of America) **EPA** 

ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

et cetera etc.

EU **European Union** 

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

general gen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

**GWP** Global warming potential

Adsorption coefficient of organic carbon in the soil Koc

Kow octanol-water partition coefficient

International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive

**IUCLID International Uniform Chemical Information Database** 

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

**Limited Quantities** LQ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dry weight mg/kg dw mg/kg wwt mg/kg wet weight

not applicable n.a. n.av. not available



Page 18 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.03.2024 / 0020

Replacing version dated / version: 12.11.2023 / 0019

Valid from: 14.03.2024 PDF print date: 14.03.2024 Motorsystemreiniger Diesel Diesel Engine System Cleaner

n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

## Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.