

Page 1 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.09.2022 / 0018
Replacing version dated / version: 01.11.2021 / 0017
Valid from: 18.09.2022
PDF print date: 27.09.2022
Wachs-Unterbodenschutz anthrazit/schwarz
Wax Underseal, anthracite/black

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Wachs-Unterbodenschutz anthrazit/schwarz
Wax Underseal, anthracite/black

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Corrosion protection

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|-----------------|-----------------|---|
| Skin Irrit. | 2 | H315-Causes skin irritation. |
| STOT SE | 3 | H336-May cause drowsiness or dizziness. |
| Aquatic Chronic | 3 | H412-Harmful to aquatic life with long lasting effects. |
| Aerosol | 1 | H222-Extremely flammable aerosol. |
| Aerosol | 1 | H229-Pressurised container: May burst if heated. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.09.2022 / 0018

Replacing version dated / version: 01.11.2021 / 0017

Valid from: 18.09.2022

PDF print date: 27.09.2022

Wachs-Unterbodenschutz anthrazit/schwarz

Wax Underseal, anthracite/black



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P273-Avoid release to the environment. P280-Wear protective gloves.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Naphtha (petroleum), hydrotreated light

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

| | |
|---|--|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | |
| Registration number (REACH) | 01-2119463258-33-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 919-857-5 |
| CAS | --- |
| content % | 20-<30 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | EUH066 Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 |

| | |
|--|-----------------------|
| Naphtha (petroleum), hydrotreated light | |
| Registration number (REACH) | 01-2119475133-43-XXXX |
| Index | 649-328-00-1 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 265-151-9 |
| CAS | 64742-49-0 |
| content % | 10-<20 |

Page 3 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| | |
|---|--|
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
|---|--|

| | |
|---|-----------------------|
| Sulfonic acids, petroleum, sodium salts | |
| Registration number (REACH) | 01-2119527859-22-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 271-781-5 |
| CAS | 68608-26-4 |
| content % | 1-<5 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Eye Irrit. 2, H319 |

| | |
|---|---|
| Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides | |
| Registration number (REACH) | 01-2119486994-16-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 269-924-1 |
| CAS | 68391-05-9 |
| content % | 0,1-<1 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.

Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Page 4 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.09.2022 / 0018
Replacing version dated / version: 01.11.2021 / 0017
Valid from: 18.09.2022
PDF print date: 27.09.2022
Wachs-Unterbodenschutz anthrazit/schwarz
Wax Underseal, anthracite/black

Effects/damages the central nervous system
Narcotic effect.
With long-term contact:
Dermatitis (skin inflammation)
Product removes fat.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray

CO₂

Extinguishment powder

Large fire:

Water jet spray / alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

GB

Page 5 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.
 Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Keep locked away.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Do not store with oxidizing agents.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.
 Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1000 mg/m³

| Chemical Name | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | |
|--------------------------------|--|-----|--|
| WEL-TWA: 800 mg/m ³ | WEL-STEL: --- | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) | | |
| BMGV: --- | Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40) | | |

| Chemical Name | Naphtha (petroleum), hydrotreated light | | |
|--|--|-----|--|
| WEL-TWA: 1200 mg/m ³ (>=C7 normal and branched chain alkanes) | WEL-STEL: --- | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) | | |
| BMGV: --- | Other information: --- | | |

GB

GB

Page 6 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| Chemical Name | Butane | | |
|--|---|-----|--|
| WEL-TWA: 600 ppm (1450 mg/m ³) | WEL-STEL: 750 ppm (1810 mg/m ³) | --- | |
| Monitoring procedures: | - Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993 | | |
| BMGV: --- | Other information: --- | | |

| Chemical Name | Propane | | |
|---------------------------|--|-----|--|
| WEL-TWA: 1000 ppm (ACGIH) | WEL-STEL: --- | --- | |
| Monitoring procedures: | - Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990 | | |
| BMGV: --- | Other information: --- | | |

| Chemical Name | Oil mist, mineral | | |
|---|--------------------------------------|-----|--|
| WEL-TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, ACGIH) | WEL-STEL: --- | --- | |
| Monitoring procedures: | - Draeger - Oil Mist 1/a (67 33 031) | | |
| BMGV: --- | Other information: --- | | |

| Chemical Name | Isobutane | | |
|--------------------------------|-------------------------------------|-----|--|
| WEL-TWA: 1000 ppm (EX) (ACGIH) | WEL-STEL: --- | --- | |
| Monitoring procedures: | - Compur - KITA-113 SB(C) (549 368) | | |
| BMGV: --- | Other information: --- | | |

| Chemical Name | Microcrystalline paraffin wax and hydrocarbon wax | | |
|---|--|-----|--|
| WEL-TWA: 2 mg/m ³ (paraffin wax, fume) | WEL-STEL: 6 mg/m ³ (paraffin wax, fume) | --- | |
| Monitoring procedures: | --- | | |
| BMGV: --- | Other information: --- | | |

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | |
|---|--|-----------------------------|------------|-------|-------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 300 | mg/kg bw/day | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 300 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 900 | mg/m ³ | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 125 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 185 | mg/m ³ | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 125 | mg/kg bw/day | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 300 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 1500 | mg/m ³ | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 208 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 871 | mg/m ³ | |

| Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides | | | | | | |
|---|--|------------------|------------|--------|----------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,013 | mg/l | |
| | Environment - marine | | PNEC | 0,0013 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 1,2 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 8,8 | mg/kg dw | |

GB

Page 7 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| | | | | | | |
|---------------------|--|-----------------------------|------|--------|--------------|--|
| | Environment - sediment, marine | | PNEC | 0,88 | mg/kg dw | |
| | Environment - soil | | PNEC | 7 | mg/kg dw | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 0,0026 | mg/l | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 8 | mg/m3 | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 7,65 | mg/kg bw/day | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 2,3 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 27 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 12,75 | mg/kg bw/day | |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN ISO 374).
 Recommended
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 >= 0,12
 Permeation time (penetration time) in minutes:
 > 480
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Page 8 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 At high concentrations:
 Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state: | Aerosol. Active substance: liquid. |
| Colour: | Black |
| Odour: | Characteristic |
| Melting point/freezing point: | There is no information available on this parameter. |
| Boiling point or initial boiling point and boiling range: | -44,5 °C |
| Flammability: | Does not apply to aerosols. |
| Lower explosion limit: | 0,6 Vol-% |
| Upper explosion limit: | 10,9 Vol-% |
| Flash point: | Does not apply to aerosols. |
| Auto-ignition temperature: | 200 °C |
| Decomposition temperature: | There is no information available on this parameter. |
| pH: | 7 (20°C) |
| Kinematic viscosity: | 4000 mPas (20°C, Dynamic viscosity) |
| Solubility: | Insoluble |
| Partition coefficient n-octanol/water (log value): | Does not apply to mixtures. |
| Vapour pressure: | 10800 hPa (30°C) |
| Vapour pressure: | 8300 hPa (20°C) |
| Density and/or relative density: | 0,682 g/cm ³ (20°C, DIN 51757) |
| Relative vapour density: | Does not apply to aerosols. |
| Particle characteristics: | Does not apply to aerosols. |

9.2 Other information

| | |
|--------------------|---|
| Explosives: | Product is not explosive. When using: development of explosive vapour/air mixture possible. |
| Oxidising liquids: | There is no information available on this parameter. |
| Solvents content: | 74,9 % (Organic solvents) |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.09.2022 / 0018

Replacing version dated / version: 01.11.2021 / 0017

Valid from: 18.09.2022

PDF print date: 27.09.2022

Wachs-Unterbodenschutz anthrazit/schwarz

Wax Underseal, anthracite/black

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting.

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Wachs-Unterbodenschutz anthrazit/schwarz

Wax Underseal, anthracite/black

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|------|----------|-------------|--------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|-------|---------|------------------------|--|---|
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LD50 | >18,5 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Skin corrosion/irritation: | | | | | | Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |

Page 10 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| | | | | | | |
|---|-------|---------|------------|-------------|---|--|
| Germ cell mutagenicity: | | | | Human being | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Rat | OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells) | Negative, Analogous conclusion Chinese hamster |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Negative, Analogous conclusion |
| Carcinogenicity: | NOAEC | 1100 | mg/m3 | Mouse | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Female |
| Carcinogenicity: | NOAEC | >= 2200 | mg/m3 | Mouse | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Male |
| Reproductive toxicity (Effects on fertility): | NOAEL | >= 3000 | mg/kg bw/d | Rat | OECD 415 (One-Generation Reproduction Toxicity Study) | Male |
| Reproductive toxicity (Effects on fertility): | NOAEL | >= 1500 | mg/kg bw/d | Rat | OECD 415 (One-Generation Reproduction Toxicity Study) | Female |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | May cause drowsiness or dizziness., STOT SE 3, H336 |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | unconsciousness , headaches, dizziness, discoloration of the skin, vomiting, diarrhoea |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 3000 | mg/kg/d | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 1444 | ppm | Rat | OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study) | Analogous conclusion |

Naphtha (petroleum), hydrotreated light

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|----------------------------------|----------|-------|-------|----------|-------------|-------|
| Acute toxicity, by oral route: | LD50 | >6800 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >3400 | mg/kg | Rabbit | | |

Page 11 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| | | | | | | |
|----------------------------|--|--|--|--|--|--|
| Skin corrosion/irritation: | | | | | | Repeated exposure may cause skin dryness or cracking. |
| Germ cell mutagenicity: | | | | | | Negative |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting. |

Sulfonic acids, petroleum, sodium salts

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|--------------------------------|----------|-------|------|----------|-------------|------------|
| Serious eye damage/irritation: | | | | | | Eye Dam. 1 |
| Aspiration hazard: | | | | | | No |

Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|-----------|-------|------------------------|---|-----------------|
| Acute toxicity, by oral route: | LD50 | >300-2000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Corrosive |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Dam. 1 |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitising |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |

Butane

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|--------------------------------|----------|-------|---------|------------------------|--|----------|
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Human being | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Rat | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Aspiration hazard: | | | | | | No |

Page 12 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| | | | | | | |
|---|-------|--------|------|-----|--|--|
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 21,394 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Symptoms: | | | | | | ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting. |

Propane

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|--------|---------|------------------------|--|--|
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Acute toxicity, by inhalation: | LC50 | 260000 | ppmV/4h | Rat | | Gasses, Male, Analogous conclusion |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Serious eye damage/irritation: | | | | | | Not irritant |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | NOAEC | 21,641 | mg/l | | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting. |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 7,214 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | LOAEL | 21,641 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |

Isobutane

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|-------------------|----------|-------|------|----------|-------------|-------|
|-------------------|----------|-------|------|----------|-------------|-------|

GB

Page 13 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| | | | | | | |
|---|-------|--------|---------|------------------------|--|---|
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Acute toxicity, by inhalation: | LC50 | 260000 | ppmV/4h | Rat | | Gasses, Male |
| Serious eye damage/irritation: | | | | Rabbit | | Not irritant |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | unconsciousness , frostbite, headaches, cramps, dizziness, nausea and vomiting. |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 21,394 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |

Microcrystalline paraffin wax and hydrocarbon wax

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|----------------------------------|----------|-------|-------|----------|-------------|-------|
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rabbit | | |

11.2. Information on other hazards

**Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black**

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|----------------------------------|----------|-------|------|----------|-------------|---|
| Endocrine disrupting properties: | | | | | | Does not apply to mixtures. |
| Other information: | | | | | | No other relevant information available on adverse effects on health. |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

**Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black**

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|----------|-------------|---|
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Endocrine disrupting properties: | | | | | | | Does not apply to mixtures. |
| 12.7. Other adverse effects: | | | | | | | No information available on other adverse effects on the environment. |

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | | |
|---|----------|------|-------|------|---------------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| Toxicity to bacteria: | EL50 | 48h | 0,95 | mg/l | | | QSAR |
| 12.1. Toxicity to fish: | LC50 | 96h | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOELR | 28d | 0,13 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | ErC50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | EbC50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOELR | 72h | 100 | mg/l | Raphidocelis subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 80 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |
| 12.1. Toxicity to algae: | NOELR | 72h | 3 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.3. Bioaccumulative potential: | | | 5-6,7 | | | | High |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Naphtha (petroleum), hydrotreated light | | | | | | | |
|---|----------|------|-------|------|---------------|-------------|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 3 | mg/l | Daphnia magna | | |

| Sulfonic acids, petroleum, sodium salts | | | | | | | |
|--|----------|------|-------|------|----------|-------------|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.3. Bioaccumulative potential: | Log Pow | | 22,12 | | | | |

| Quaternary ammonium compounds, di-C12-18-alkyldimethyl, chlorides | | | | | | | |
|---|-----------|------|-----------|------|---------------------------------|--|-----------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 0,26 | mg/l | | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >0,1-1 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | >0,01-0,1 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 0,06 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Readily biodegradable |

Page 15 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

| Butane | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 24,11 | mg/l | | QSAR | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 14,22 | mg/l | | QSAR | |
| 12.3. Bioaccumulative potential: | Log Pow | | 2,98 | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.4. Mobility in soil: | | | | | | | Not to be expected |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Propane | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.3. Bioaccumulative potential: | Log Pow | | 2,28 | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Isobutane | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.3. Bioaccumulative potential: | | | | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.1. Toxicity to fish: | LC50 | 96h | 27,98 | mg/l | | | |
| 12.1. Toxicity to algae: | EC50 | 96h | 7,71 | mg/l | | | |
| 12.2. Persistence and degradability: | | | | | | | Readily biodegradable |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Microcrystalline paraffin wax and hydrocarbon wax | | | | | | | |
|---|----------|------|---------|------|---------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.2. Persistence and degradability: | | 28d | 31 | % | | | |
| 12.1. Toxicity to fish: | LL50 | 96h | > 100 | mg/l | Pimephales promelas | OECD 203 (Fish, Acute Toxicity Test) | Analogous conclusion |
| 12.1. Toxicity to daphnia: | EL50 | 24h | > 10000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | Analogous conclusion |
| 12.1. Toxicity to algae: | ErC50 | 24h | >10000 | mg/l | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Classification code:

5F

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.



SECTION 15: Regulatory information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| P3a | 11.1 | 150 (netto) | 500 (netto) |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

| Entry Nr | Dangerous substances | Notes to Annex I | Qualifying quantity (tonnes) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) for the application of - Upper-tier requirements |
|----------|--|------------------|---|---|
| 18 | Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas | 19 | 50 | 200 |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

77,99 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|---|
| Skin Irrit. 2, H315 | Classification according to calculation procedure. |
| STOT SE 3, H336 | Classification according to calculation procedure. |
| Aquatic Chronic 3, H412 | Classification according to calculation procedure. |
| Aerosol 1, H222 | Classification according to calculation procedure. |
| Aerosol 1, H229 | Classification based on the form or physical state. |

Page 18 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H400 Very toxic to aquatic life.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Skin Irrit. — Skin irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Aerosol — Aerosols
 Flam. Liq. — Flammable liquid
 Asp. Tox. — Aspiration hazard
 Eye Irrit. — Eye irritation
 Acute Tox. — Acute toxicity - oral
 Skin Corr. — Skin corrosion
 Eye Dam. — Serious eye damage
 Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level

Page 19 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.09.2022 / 0018
 Replacing version dated / version: 01.11.2021 / 0017
 Valid from: 18.09.2022
 PDF print date: 27.09.2022
 Wachs-Unterbodenschutz anthrazit/schwarz
 Wax Underseal, anthracite/black

DOC Dissolved organic carbon
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EµCx, Erlx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 TOC Total organic carbon
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

GB

Page 20 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.09.2022 / 0018
Replacing version dated / version: 01.11.2021 / 0017
Valid from: 18.09.2022
PDF print date: 27.09.2022
Wachs-Unterbodenschutz anthrazit/schwarz
Wax Underseal, anthracite/black

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.