

Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 25.07.2019 / 0014
Replacing version dated / version: 29.06.2018 / 0013
Valid from: 25.07.2019
PDF print date: 10.02.2021
Hohlraumversiegelung hellbraun

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Hohlraumversiegelung hellbraun

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Corrosion protection

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 9a - Coatings and paints, thinners, paint removers

PC14 - Metal surface treatment products

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC11 - Non industrial spraying

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH

Jerg-Wieland-Str. 4

89081 Ulm-Lehr

Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 29.06.2018 / 0013

Valid from: 25.07.2019

PDF print date: 10.02.2021

Hohlraumversiegelung hellbraun

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	---
EINECS, ELINCS, NLP	919-857-5 (REACH-IT List-No.)
CAS	---
content %	10-30

Page 3 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	---
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Sulfonic acids, petroleum, sodium salts	
Registration number (REACH)	01-2119527859-22-XXXX
Index	---
EINECS, ELINCS, NLP	271-781-5
CAS	68608-26-4
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319
Quaternary ammonium compounds, dicocoalkyl dimethyl, chlorides	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	263-087-6
CAS	61789-77-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Eye Dam. 1, H318

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Page 4 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 25.07.2019 / 0014
Replacing version dated / version: 29.06.2018 / 0013
Valid from: 25.07.2019
PDF print date: 10.02.2021
Hohlraumversiegelung hellbraun

Typically no exposure pathway.
Rinse the mouth thoroughly with water.
Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray
CO2
Extinction powder
Large fire:

Water jet spray / alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

GB

Page 5 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Avoid inhalation, and contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Do not store with oxidizing agents.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.
 Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:	10-30
WEL-TWA:	800 mg/m ³	WEL-STEL:	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 		
BMGV:	---	Other information:	(OEL acc. to RCP-method, paragraphs 84-87, EH40)
Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Content %:	10-20
WEL-TWA:	800 mg/m ³	WEL-STEL:	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-187 S (551 174) 		
BMGV:	---	Other information:	(OEL acc. to RCP-method, paragraphs 84-87, EH40)
Chemical Name	Oil mist, mineral	Content %:	
WEL-TWA:	5 mg/m ³ (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL:	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Oil Mist 1/a (67 33 031) 		
BMGV:	---	Other information:	---
Chemical Name	Paraffin wax, fume	Content %:	
WEL-TWA:	2 mg/m ³	WEL-STEL:	6 mg/m ³
Monitoring procedures:	---		
BMGV:	---	Other information:	---
Chemical Name	Propane	Content %:	
WEL-TWA:	1000 ppm (ACGIH)	WEL-STEL:	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990 		
BMGV:	---	Other information:	---
Chemical Name	Butane	Content %:	

CE

Page 6 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
	- OSHA PV2010 (n-Butane) - 1993	
BMGV: ---	Other information: ---	

Chemical Name	Isobutane	Content %:	
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)		
BMGV: ---	Other information: ---		

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1500	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	208	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m ³	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m ³	

CE WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause

Page 7 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 25.07.2019 / 0014
Replacing version dated / version: 29.06.2018 / 0013
Valid from: 25.07.2019
PDF print date: 10.02.2021
Hohlraumversiegelung hellbraun

sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

$\geq 0,12$

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Aerosol. Active substance: liquid.

Colour:

Brown

Page 8 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	-44 °C
Flash point:	n.a.
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	0,6 Vol-%
Upper explosive limit:	10,9 Vol-% (When using: development of explosive vapour/air mixture possible.)
Vapour pressure:	10800 hPa (30°C)
Vapour pressure:	8300 hPa (20°C)
Vapour density (air = 1):	Not determined
Density:	0,70442 g/cm ³ (20°C, DIN 51757)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	>200 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	3750 mPas (20°C, Active substance)
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	76,6 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Hohlraumversiegelung hellbraun						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.

Page 9 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Aspiration hazard:						Yes
Symptoms:						unconsciousness , headaches, dizziness, discoloration of the skin, vomiting, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Not to be expected

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours

Page 10 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Analogous conclusion, No (inhalation and skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:						Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract).

Sulfonic acids, petroleum, sodium salts

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Serious eye damage/irritation:						Eye Dam. 1
Aspiration hazard:						No

Propane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Page 12 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.3. Bioaccumulative potential:			5-6,7				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EL50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	81	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion, Readily biodegradable

GB

Page 13 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

12.1. Toxicity to algae:	EL50	72h	30-100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Sulfonic acids, petroleum, sodium salts							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.3. Bioaccumulative potential:	Log Pow		22,12				

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

Page 14 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 16 05 04 gases in pressure containers (including halons) containing hazardous substances
 08 01 11 waste paint and varnish containing organic solvents or other hazardous substances
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Take full aerosol cans to problem waste collection.
 Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.
 Recommendation:
 Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Classification code:

5F

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

D



Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

14.5. Environmental hazards:

Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

GB

Page 15 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 80,81 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 8
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Page 16 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 25.07.2019 / 0014
 Replacing version dated / version: 29.06.2018 / 0013
 Valid from: 25.07.2019
 PDF print date: 10.02.2021
 Hohlraumversiegelung hellbraun

H400 Very toxic to aquatic life.
 H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Aerosol — Aerosols
 Flam. Liq. — Flammable liquid
 Asp. Tox. — Aspiration hazard
 Eye Irrit. — Eye irritation
 Acute Tox. — Acute toxicity - oral
 Skin Corr. — Skin corrosion
 Aquatic Acute — Hazardous to the aquatic environment - acute
 Eye Dam. — Serious eye damage

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable

Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 29.06.2018 / 0013

Valid from: 25.07.2019

PDF print date: 10.02.2021

Hohlraumversiegelung hellbraun

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.