

Page 1 of 25
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 28.11.2024 / 0027
Replacing version dated / version: 04.03.2024 / 0026
Valid from: 28.11.2024
PDF print date: 28.11.2024
Unterbodenschutz Bitumen schwarz
Underseal Bitumen, black

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Unterbodenschutz Bitumen schwarz
Underseal Bitumen, black

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Corrosion protection

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.11.2024 / 0027

Replacing version dated / version: 04.03.2024 / 0026

Valid from: 28.11.2024

PDF print date: 28.11.2024

Unterbodenschutz Bitumen schwarz

Underseal Bitumen, black

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Acetone

Naphtha (petroleum), hydrotreated light

Hydrocarbons, C9, aromatics

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	---
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Page 3 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Naphtha (petroleum), hydrotreated light	
Registration number (REACH)	01-2119475133-43-XXXX
Index	649-328-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	265-151-9
CAS	64742-49-0
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	200-662-2
CAS	67-64-1
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Hydrocarbons, C9, aromatics	
Registration number (REACH)	01-2119455851-35-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-668-5
CAS	(64742-95-6)
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Effects/damages the central nervous system

Narcotic effect.

With long-term contact:

Dermatitis (skin inflammation)

Product removes fat.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray

CO₂

Extinction powder

Large fire:

Water jet spray / alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Fume

Oxides of nitrogen

Toxic gases

Danger of bursting (explosion) when heated

Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

GB

Page 5 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Leave the danger zone if possible, use existing emergency plans if necessary.
 Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent from entering drainage system.
 Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid breathing vapours or spray.
 Avoid contact with eyes or skin.
 Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Do not store with flammable or self-igniting materials.
 Protect from direct sunlight and warming.
 Store in a well ventilated place.
 Store cool.

7.3 Specific end use(s)

No information available at present.
 Observe the instructions for good working practice and the recommendations for risk assessment.
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1200 mg/m³

GB	Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
WEL-TWA:	1200 mg/m ³	WEL-STEL: ---

GB

Page 6 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---		Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)

Chemical Name	Naphtha (petroleum), hydrotreated light	
WEL-TWA: 1200 mg/m3 (>=C7 normal and branched chain alkanes)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---		Other information: ---

Chemical Name	Acetone	
WEL-TWA: 500 ppm (1210 mg/m3) (WEL-TWA, EU)	WEL-STEL: 1500 ppm (3620 mg/m3) (WEL-STEL)	---
Monitoring procedures:	- Draeger - Acetone 100/b (CH 22 901) - Draeger - Acetone 40/a (5) (81 03 381) - Compur - KITA-102 SA (548 534) - Compur - KITA-102 SC (548 550) - Compur - KITA-102 SD (551 109) - INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - - EU project BC/CEN/ENTR/000/2002-16 card 67-1 (2004) - MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993 - NIOSH 1300 (KETONES I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - NIOSH 2555 (KETONES I) - 2003 - NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 - OSHA 69 (Acetone) - 1988	
BMGV: ---		Other information: ---

Chemical Name	Hydrocarbons, C9, aromatics	
WEL-TWA: 500 mg/m3 (Aromatics)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---		Other information: ---

Chemical Name	Butane	
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993	
BMGV: ---		Other information: ---

Chemical Name	Propane	
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990	
BMGV: ---		Other information: ---

Chemical Name	Isobutane	
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV: ---		Other information: ---

Chemical Name	Asphalt	
WEL-TWA: 5 mg/m3 (Asphalt, petroleum fumes)	WEL-STEL: 10 mg/m3 (Asphalt, petroleum fumes)	---
Monitoring procedures:	---	
BMGV: ---		Other information: ---

Chemical Name	Calcium carbonate	
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---
Monitoring procedures:	---	

BMGV: ---

Other information: ---

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	

Acetone

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assessment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assessment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/kg dw	
	Environment - sediment, marine		PNEC	3,04	mg/kg dw	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assessment factor 100
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m ³	Overall assessment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m ³	

Hydrocarbons, C9, aromatics

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	

GB

Page 8 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m3	

Asphalt						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, local effects	DNEL	0,6	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	2,9	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN ISO 374).
 Recommended
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 >= 0,12
 Permeation time (penetration time) in minutes:

Page 9 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

>= 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 Filter A P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid. 20°C
Colour:	Black
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	-44,5 °C
Flammability:	Does not apply to aerosols.
Lower explosion limit:	0,6 Vol-%
Upper explosion limit:	13 Vol-%
Flash point:	<0 °C (DIN 53213 (Pensky-Martens, closed cup))
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<=20,5 mm ² /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	800 hPa (50°C)
Density and/or relative density:	0,76 g/cm ³ (20°C, DIN 51757)
Density and/or relative density:	1,09 g/ml (Active substance)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

Explosives:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Solvents content:	67,6 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Page 10 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting.

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Unterbodenschutz Bitumen schwarz Underseal Bitumen, black

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Human being	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:	NOAEL	9000	ppm		OECD 416 (Two-generation Reproduction Toxicity Study)	Negative

Page 11 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	5,8	mg/l		OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Naphtha (petroleum), hydrotreated light

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>6800	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3400	mg/kg	Rabbit		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Germ cell mutagenicity:						Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Acetone

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5800-7190	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising

Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Carcinogenicity:				Mouse		Negative, References
Reproductive toxicity (Developmental toxicity):	NOAEC	2200	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336, May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Symptoms:						unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness

Hydrocarbons, C9, aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>6,193	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative

Page 13 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:						Negative
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H335, STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative
Aspiration hazard:						Yes
Symptoms:						respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousness, fever, ear noises, drying of the skin.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No

Page 15 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.

Asphalt						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	> 94,4	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative Chinese hamster
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	> 2000	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	

12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	3-10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	4,6-10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	LC50	72h	10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		4-5,7				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Naphtha (petroleum), hydrotreated light

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	LC50	48h	3	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EL50	48h	4,5	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	77,05	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable

Acetone

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		

12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	8300	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	EC50	96h	8300	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	8800	mg/l	Daphnia pulex	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	8d	530	mg/l		DIN 38412 T.9	Test organism: M. aeruginosa
12.2. Persistence and degradability:		30d	81-92	%		Regulation (EC) 440/2008 C.4-E (DETERMINATION OF 'READY' BIODEGRADABILITY - CLOSED BOTTLE TEST)	Readily biodegradable
12.2. Persistence and degradability:		28d	91	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,24			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.3. Bioaccumulative potential:	BCF		3				Low
12.4. Mobility in soil:							No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	Pseudomonas putida		
Other organisms:	EC5	72h	28	mg/l	Entosiphon sulcatum		

Other information:	BOD5		1760-1900	mg/g		
Other information:	AOX		0	%		
Other information:	COD		2070-2100	mg/g		

Hydrocarbons, C9, aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	9,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	3,2	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	54-56	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.2. Persistence and degradability:		28d	78	%	activated sludge	OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	78	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		3,7 - 4,5				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	10min	>99	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Asphalt							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	> 1000	mg/l	Oncorhynchus mykiss	QSAR	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	>= 1000	mg/l	Oncorhynchus mykiss	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>= 1000	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	LL50	48h	> 1000	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	> 1000	mg/l	Pseudokirchneriella subcapitata	QSAR	Analogous conclusion
12.2. Persistence and degradability:							Not biodegradable
12.3. Bioaccumulative potential:	Log Kow		>6				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 21 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.6. Endocrine disrupting properties:							Not to be expected
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:

1950

Page 22 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

14.2. UN proper shipping name:
 UN 1950 AEROSOLS
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: environmentally hazardous
 Tunnel restriction code: D
 Classification code: 5F
 LQ: 1 L
 Transport category: 2



Transport by sea (IMDG-code)

14.1. UN number or ID number: 1950
 14.2. UN proper shipping name:
 UN 1950 AEROSOLS
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: environmentally hazardous
 Marine Pollutant: Yes
 EmS: F-D, S-U



Transport by air (IATA)

14.1. UN number or ID number: 1950
 14.2. UN proper shipping name:
 UN 1950 Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.
 For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

GB

Page 23 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.11.2024 / 0027
 Replacing version dated / version: 04.03.2024 / 0026
 Valid from: 28.11.2024
 PDF print date: 28.11.2024
 Unterbodenschutz Bitumen schwarz
 Underseal Bitumen, black

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 71,33 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 14
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. — Eye irritation
 Skin Irrit. — Skin irritation
 Asp. Tox. — Aspiration hazard
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Aerosol — Aerosols
 Flam. Liq. — Flammable liquid
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.11.2024 / 0027

Replacing version dated / version: 04.03.2024 / 0026

Valid from: 28.11.2024

PDF print date: 28.11.2024

Unterbodenschutz Bitumen schwarz

Underseal Bitumen, black

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

Page 25 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.11.2024 / 0027

Replacing version dated / version: 04.03.2024 / 0026

Valid from: 28.11.2024

PDF print date: 28.11.2024

Unterbodenschutz Bitumen schwarz

Underseal Bitumen, black

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log K_{oc} Logarithm of adsorption coefficient of organic carbon in the soil

Log K_{ow}, Log P_{ow} Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight

mg/kg wwt mg/kg wet weight

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.