

Page 1 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz Underseal, black

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Unterbodenschutz schwarz Underseal, black

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Corrosion protection

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Flam. Liq. 2 H225-Highly flammable liquid and vapour.

Skin Irrit. 2 H315-Causes skin irritation.

STOT SE 3 H336-May cause drowsiness or dizziness.

Aguatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black



H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P243-Take action to prevent static discharges. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Ethyl acetate

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

OIZ IIIIACA OO	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119475515-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	927-510-4
CAS	
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Asp. Tox. 1, H304
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Aguatic Chronic 2, H411

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	
content %	10-<25



Page 3 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz Underseal, black

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225	
	Asp. Tox. 1, H304	
	Skin Irrit, 2, H315	

Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aguatic Chronic 2, H411

Ethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475103-46-XXXX
Index	607-022-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	205-500-4
CAS	141-78-6
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Eye Irrit. 2, H319
	STOT SE 3, H336

Hydrocarbons, C9, aromatics	
Registration number (REACH)	01-2119455851-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-668-5
CAS	64742-95-6
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H335
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.



Page 4 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black

Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Headaches

Dizziness

Nausea

Unconsciousness

Irritation of the respiratory tract

Product removes fat.

Dermatitis (skin inflammation)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Extinction powder

Sand

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep unprotected persons away.

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.



(B)

Page 5 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz Underseal, black

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

If applicable, suction measures at the workstation or on the processing machine necessary.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Keep away from food, drink and animal feedingstuffs.

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Store cool.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			Content %:10- <25
WEL-TWA: 800 mg/m3	WEL-STEL:			
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c (81 	03 571)		
	- Draeger - Hydrocarbons 2/a (81 03	581)		
	- Compur - KITA-187 S (551 174)			
BMGV:		Other information: (O	EL acc. t	o RCP-method,
		paragraphs 84-87, EH	40)	
Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics,	<5% n-hexane		Content %:10- <25
WEL-TWA: 600 mg/m3	WEL-STEL:			
Monitoring procedures:	- Compur - KITA-187 S (551 174)		•	
BMGV:		Other information: (O paragraphs 84-87, EH4		o RCP-method,
Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			Content %:5-<10



(GB) Page 6 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024 Replacing version dated / version: 12.02.2019 / 0023 Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz Underseal, black WEL-TWA: 1200 mg/m3 WEL-STEL: ---Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40) BMGV: ---© Chemical Name Ethyl acetate Content %:3-<5 WEL-TWA: 200 ppm (734 mg/m3) (WEL, EU) WEL-STEL: 400 ppm (1468 mg/m3) (WEL, EU) ---Draeger - Ethyl Acetate 200/a (CH 20 201) Monitoring procedures: Compur - KITA-111 SA (549 160) Compur - KITA-111 U(C) (549 178) DFG Meth. Nr. 1 (D) (Loesungsmittelgemische 2), DFG (E) (Solvent mixtures 2) - 1993, DFG Meth. Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 DFG Meth. Nr. 6 (D) (Loesungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 2014, 2002 NIOSH 1457 (ETHYL ACETATE) - 1994 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 BMGV: ---Other information: Hydrocarbons, C9, aromatics © Chemical Name Content %:3-<5 WEL-TWA: 500 mg/m3 (Aromatics) WEL-STEL: Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---Other information: ---Calcium carbonate Content %: WEL-STEL: ---WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust) Monitoring procedures: BMGV: Other information: ---

© Chemical Name Quartz		Content %:			
WEL-TWA: 0,1 mg/m3 (silica, respirable, crystalline)	WEL-STEL:				
Monitoring procedures:	INSHT MTA/MA-036/A00 (Determination of Quartz in Air - I	Membrane Filter Method/			
-	Xray Diffraction) - 2000, 2004				
	MDHS 101/2 (Crystalline silica in respirable airborne dust -	Direct on-filter analysis by			
	infrared spectroscopy and X-ray diffraction) - 2015 - EU proj	ject			
- BC/CEN/ENTR/000/2002-16 card 52-1 (2004)					
	NIOSH 7500 (Crystalline Silica, by XRD (filter redeposition))) - 2003 - EU project			
-	BC/CEN/ENTR/000/2002-16 card 52-6 (2004)				
-	NIOSH 7601 (SILICA, CRYSTALLINE, by VIS) - 2003				
-	NIOSH 7602 (Crystalline Silica, by IR (KBr pellet)) - 2003				
-	NIOSH 7603 (QUARTZ in coal mine dust, by IR (redeposition)				
-	OSHA ID-142 (Quartz and Cristobalite in Workplace Atmosp	oheres) - 2016			
BMGV:	Other information:				

Hydrocarbons, C7, n-alka	nes, isoalkanes, cyclics					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	447	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	149	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2085	mg/m3	



Page 7 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Hydrocarbons, C6-C7, n-a	alkanes, isoalkanes, cyclics,	<5% n-hexane				
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

Ethyl acetate Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
7 a oa o appiloation	Environmental	Zilost on libaian	2000p.o.	Tuiuo	0	11010
	compartment					
	Environment - freshwater		PNEC	0,24	mg/l	
	Environment - marine		PNEC	0,024	mg/l	
	Environment - water,		PNEC	1,65	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sediment,		PNEC	1,15	mg/kg	
	freshwater					
	Environment - sediment,		PNEC	0,115	mg/kg	
	marine					
	Environment - soil		PNEC	0,148	mg/kg	
	Environment - sewage		PNEC	650	mg/l	
	treatment plant					
	Environment - oral (animal		PNEC	200	mg/kg	
	feed)					
Consumer	Human - oral	Long term, systemic	DNEL	4,5	mg/kg	
		effects				
Consumer	Human - dermal	Long term, systemic	DNEL	37	mg/kg	
		effects				
Consumer	Human - inhalation	Long term, systemic	DNEL	367	mg/m3	
		effects				
Consumer	Human - inhalation	Long term, local effects	DNEL	367	mg/m3	
Consumer	Human - inhalation	Short term, systemic	DNEL	734	mg/m3	
		effects				



Page 8 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black

Consumer	Human - inhalation	Short term, local effects	DNEL	734	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	63	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	734	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	734	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1468	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1468	mg/m3	

Hydrocarbons, C9, arom					1	1
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m3	

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment					
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.



Page 9 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective Viton® / fluoroelastomer gloves (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

>= 0,12

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Liquid Black

Odour: Characteristic
Odour threshold: Not determined
pH-value: Not determined



Page 10 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black

Melting point/freezing point:

Initial boiling point and boiling range: 94-99 °C

Flash point: Evaporation rate:

Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure:

Vapour density (air = 1):

Density: Bulk density: Solubility(ies): Water solubility:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Auto-ignition temperature:

Decomposition temperature: Viscosity:

Viscosity:

Explosive properties:

Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension:

Solvents content:

Not determined

-7 °C (DIN 53213 (Pensky-Martens, closed cup))

Not determined

n.a. 0,6 Vol-% 7 Vol-% 60 hPa (20°C) Not determined

1,04 g/cm3 (20°C, DIN 51757)

n.a.

Not determined Insoluble Not determined No

>200 °C (Ignition temperature)

Not determined 690 mPas (20°C) >20,5 mm2/s (40°C)

Product is not explosive. When using: development of explosive

vapour/air mixture possible.

Not determined Not determined

> Not determined Not determined

50,8 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Unterbodenschutz schwarz						
Underseal, black						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.



Page 11 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal,	b	lack	
------------	---	------	--

Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

Hydrocarbons, C7, n-alkanes,	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral	Analogous		
					Toxicity)	conclusion		
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat	OECD 402 (Acute	Analogous		
					Dermal Toxicity)	conclusion		
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Analogous		
					Inhalation Toxicity)	conclusion		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Irritant		
					Dermal			
					Irritation/Corrosion)			
Serious eye damage/irritation:				Rabbit		Not irritant		
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)		
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative		
Commodit matagementy.					Mammalian Cell Gene	rioganio		
					Mutation Test)			
Carcinogenicity:					- matation rooty	Negative		
Reproductive toxicity:	NOAEL	9000	ppm	Rat	OECD 416 (Two-	Negative		
			FF		generation	i i i gami i		
					Reproduction Toxicity			
					Study)			
Aspiration hazard:					3,	Yes		
Symptoms:						diarrhoea,		
•						headaches,		
						dizziness,		
						nausea and		
						vomiting.		
Symptoms:						drowsiness,		
						unconsciousness		
						heart/circulatory		
						disorders,		
						headaches,		
						cramps,		
						drowsiness,		
						mucous		
						membrane		
						irritation,		
						dizziness.		
						nausea and		
						vomiting.,		
						diarrhoea		
		_1				diaminoca		

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)		



Page 12 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute	
Obia a a maraila a firmita ti a ma				D-bbit	Inhalation Toxicity)	Olaira Jamit O
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Skin Irrit. 2
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Mild irritant
					Irritation/Corrosion)	(Analogous
						conclusion)
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Carcinogenicity:					,	Negative
Reproductive toxicity:					OECD 414 (Prenatal	Analogous
•					Developmental Toxicity	conclusion,
					Study)	Negative
Specific target organ toxicity -					,	STOT SE 3,
single exposure (STOT-SE):						H336
Specific target organ toxicity -						Negative
repeated exposure (STOT-RE):						
Aspiration hazard:						Yes
Symptoms:						drowsiness,
Cymptomo.						unconsciousness
						unconsciousness
						heart/circulatory
						disorders.
						headaches.
						cramps,
						drowsiness,
						mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.
Specific target organ toxicity -						Not irritant
single exposure (STOT-SE),						(respiratory tract)
inhalative:						

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	



Page 13 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte	Negative
					Micronucleus Test)	
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Negative
Aspiration hazard:					•	Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Ethyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4934	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>20000	mg/kg	Rabbit	TOXICITY)	
Acute toxicity, by inhalation:	LC0	29,3	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:		24	h	Rabbit		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						No



Page 14 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Symptoms:			_			lack of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, cornea opacity, coughing, headaches, gastrointestinal disturbances, intoxication, drowsiness, mucous membrane irritation, dizziness, salivation, nausea and vomiting., fatigue
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	Regulation (EC) 440/2008 B.26 (SUB- CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,002	mg/kg	Rat	Regulation (EC) 440/2008 B.29 (SUB-CHRONIC INHALATION TOXICITY STUDY 90-DAY REPEATED (RODENTS))	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	> 6,193	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative



Page 15 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Germ cell mutagenicity:	OECD 476 (In Vitro Negative Mammalian Cell Gene Mutation Test)
Germ cell mutagenicity:	OECD 479 (Genetic Negative Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)
Germ cell mutagenicity:	Salmonella OECD 471 (Bacterial Negative, typhimurium Reverse Mutation Test) Analogous conclusion
Carcinogenicity:	Negative
Reproductive toxicity:	Rat OECD 421 Negative, (Reproduction/Developm Analogous ental Toxicity Screening conclusion Test)
Reproductive toxicity:	OECD 414 (Prenatal Negative Developmental Toxicity Study)
Reproductive toxicity:	OECD 416 (Two- generation Reproduction Toxicity Study)
Specific target organ toxicity - single exposure (STOT-SE):	STOT SE 3, H335, STOT S 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):	OECD 408 (Repeated Negative Dose 90-Day Oral Toxicity Study in Rodents)
Specific target organ toxicity - repeated exposure (STOT-RE):	OECD 452 (Chronic Negative Toxicity Studies)
Aspiration hazard:	Yes
Symptoms:	respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousne , fever, ear noises, drying

Calcium carbonate	Calcium carbonate								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral				
					toxicity - Fixe Dose				
					Procedure)				
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute				
					Dermal Toxicity)				
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute				
					Inhalation Toxicity)				
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant			
					Dermal				
					Irritation/Corrosion)				
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant			
_					Irritation/Corrosion)				



③B)·

Page 16 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black

Respiratory or skin				Mouse	OECD 429 (Skin	No (skin contact)
sensitisation:					Sensitisation - Local Lymph Node Assay)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
Germ cen mutagemony.					Reverse Mutation Test)	ivegalive
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	

Quartz										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Symptoms:						respiratory				
						distress,				
						coughing,				
						mucous				
						membrane				
						irritation				

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Unterbodenschutz schw	arz										
Underseal, black											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to fish:							n.d.a.				
12.1. Toxicity to daphnia:							n.d.a.				
12.1. Toxicity to algae:							n.d.a.				
12.2. Persistence and							n.d.a.				
degradability:											
12.3. Bioaccumulative							n.d.a.				
potential:											
12.4. Mobility in soil:							n.d.a.				
12.5. Results of PBT							n.d.a.				
and vPvB assessment											
12.6. Other adverse							n.d.a.				
effects:											



Page 17 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Other information:				DOC-elimination degree(complexi ng organic substance)>= 80%/28d: n.a.
Other information:	AOX	0	%	According to the recipe, contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13,4	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>13,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	1,53	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to daphnia:	NOELR	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	10 - 30	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	10	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	ErL50	72h	10-30	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	6,3	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Water solubility:			2,6	mg/l		- sp	25°C

Hydrocarbons, C6-C7, n-	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.3. Bioaccumulative potential:							Concentration in organisms possible.				
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna						
12.1. Toxicity to daphnia:	LOEC/LOEL	21d	0,32	mg/l	Daphnia magna						
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss						
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri						
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)					
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OEĆD 203 (Fish, Acute Toxicity Test)					
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)					
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna						
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)					



Page 18 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

12.2. Persistence and degradability:		28d	81	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	BCF		242-253				
12.4. Mobility in soil:							Adsorption in ground., Product is slightly volatile.
Other information:	AOX		0	%			

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.6. Other adverse effects:							Product floats on the water
12.3. Bioaccumulative							surface. Not to be
potential:							expected(evapor ation)
12.1. Toxicity to fish:	NOELR	28d	0,574		Oncorhynchus mykiss		,
12.1. Toxicity to fish:	LC50	96h	3 - 10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchneriell a subcapitata	OEĆD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Completely biodegradable.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC10	18h	2900	mg/l	Pseudomonas putida		
12.1. Toxicity to fish:	LC50	48h	333	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	NOEC/NOEL	32d	>9,65	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	230	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	610	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,4	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	



Page 19 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

12.1. Toxicity to daphnia:	EC50	48h	165	mg/l			Daphnia cucullata
12.1. Toxicity to algae:	EC50	48h	5600	mg/l	Desmodesmus subspicatus	DIN 38412 T.9	Cucullata
12.1. Toxicity to algae:	NOEC/NOEL	96h	2000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	48h	3300	mg/l	Scenedesmus subspicatus	,	
12.2. Persistence and degradability:		20d	79	%	·	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF	72h	30			,	(Fish)
12.3. Bioaccumulative potential:	Log Kow		0,68			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	Bioaccumulation is unlikely (LogPow < 1).25 °C
12.4. Mobility in soil:	H (Henry)		0,00012	atm*m3/m ol		,	
12.4. Mobility in soil:	Koc		3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	2900	mg/l	Escherichia coli		
Toxicity to bacteria:	EC50	15min	5870	mg/l	Photobacterium phosphoreum		

Hydrocarbons, C9, arom							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,2	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	3,2	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	54-56	%		OECD 301 B	
degradability:						(Ready	
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.2. Persistence and		28d	78	%		OECD 301 E	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	_
						Modified OECD	
						Screening Test)	



Page 20 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

12.2. Persistence and degradability:		28d	78	%	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)
12.3. Bioaccumulative potential:	Log Pow		3,7 - 4,5		Treepinementy Teety
12.5. Results of PBT and vPvB assessment					No PBT substance, No vPvB substance

Calcium carbonate Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	value	O I III	Oncorhynchus	OECD 203 (Fish,	No observation
12.1. TOXICITY TO HSH.	LC30	9011			mykiss	Acute Toxicity	with saturated
					IIIykiss		solution of test
						Test)	
10.1 T ::: 1 L :	F050	401			D 1 .	0505.000	material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202	No observation
						(Daphnia sp.	with saturated
						Acute	solution of test
						Immobilisation	material.
						Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus	OECD 201 (Alga,	
					subspicatus	Growth Inhibition	
						Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	14	mg/l	Desmodesmus	OECD 201 (Alga,	
3 3 3 3 3 3					subspicatus	Growth Inhibition	
					- Cubopicatus	Test)	
12.2. Persistence and						. 550)	Not relevant for
degradability:							inorganic
aogradability.							substances.
12.3. Bioaccumulative			+	+			Not to be
potential:							expected
12.4. Mobility in soil:							-
12.5. Results of PBT							n.a. No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209	
						(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Àmmonium	
						Oxidation))	
Toxicity to bacteria:	NOEC/NOEL	3h	1000	mg/l	activated sludge	OECD 209	
,						(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208	Glycine max
Other organisms.	EC30	Z10	>1000	mg/kg dw			Glycine max
						(Terrestrial Plants,	
Other	F050	04-1	4000			Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208	Lycopersicon
						(Terrestrial Plants,	esculentum
			1			Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208	Avena sativa
						(Terrestrial Plants,	
						Growth Test)	
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208	Glycine max
-						(Terrestrial Plants,	
		1	1	1	I .	Growth Test)	I .



Page 21 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black

Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	NOEC/NOEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Water solubility:			0,0166	g/l		OECD 105 (Water Solubility)	20°C

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and							Not relevant for
degradability:							inorganic
							substances.
12.3. Bioaccumulative							Not to be
potential:							expected
12.4. Mobility in soil:							Low
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 wastes from MFSU and removal of paint and varnish

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging



Page 22 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz Underseal, black

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: 1139

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
UN 1139 COATING SOLUTION
14.3. Transport hazard class(es):
14.4. Packing group:
Classification code:
LQ:
5 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

COATING SOLUTION (NAPHTHA (PETROLEUM))

14.3. Transport hazard class(es):

14.4. Packing group:

II

EmS:

F-E, S-E

Marine Pollutant:

Yes

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Coating solution

14.3. Transport hazard class(es):

3
14.4. Packing group:

II

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P5c		5000	50000
E2		200	500









Page 23 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz Underseal, black

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 50,82 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 7, 8, 15, 16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid

Skin Irrit. — Skin irritation STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Asp. Tox. — Aspiration hazard

Eye Irrit. — Eye irritation

 ${\tt STOT\ SE-Specific\ target\ organ\ toxicity-single\ exposure-respiratory\ tract\ irritation}$

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

Adsorbable organic halogen compounds AOX

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)



Page 24 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz

Underseal, black

Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA

BSEF The International Bromine Council

body weight hw

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level

dry weight dw

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC **European Community** ECHA European Chemicals Agency EEC **European Economic Community**

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

ΕN European Norms

EPA United States Environmental Protection Agency (United States of America)

et cetera etc. FU **European Union**

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number general aen.

Globally Harmonized System of Classification and Labelling of Chemicals GHS

GWP Global warming potential

IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Limited Quantities LQ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

organic org. **PBT**

persistent, bioaccumulative and toxic

PΕ Polyethylene

PNEC Predicted No Effect Concentration

parts per million mag Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

very persistent and very bioaccumulative

wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.



③B)·

Page 25 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.06.2020 / 0024

Replacing version dated / version: 12.02.2019 / 0023

Valid from: 25.06.2020 PDF print date: 23.07.2021 Unterbodenschutz schwarz Underseal, black

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.