

Page 1 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Seilfett Cable Grease

œ

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Corrosion protection

Underfloor protection

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0, 1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.



Page 2 of 11

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

Mineral oil raffinate

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	(64742-48-9)
content %	40-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Additives

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the eyes With long-term contact: Drying of the skin. Dermatitis (skin inflammation) On vapour formation: Irritant to mucosa of the nose and throat drowsiness drowsiness Headaches Nausea Vomiting



Page 3 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

Dizziness

Narcotic effect.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

ആ

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Oil binder

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours. Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Avoid long lasting or intensive contact with skin. Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.



Page 4 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

Observe directions on label and instructions for use. 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents. Under all circumstances prevent penetration into the soil.

7.3 Specific end use(s)

ആ

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10	0-C13, n-alkane	s, isoalkanes, cycli	cs, <2% aromatics		Content %:40-50
WEL-TWA: 800 mg/m3		WEL-STEL:				
Monitoring procedures:	- [Draeger - Hydro	carbons 0,1%/c (81	1 03 571)		
	- [Draeger - Hydro	carbons 2/a (81 03	581)		
			187 S (551 174)	,		
BMGV:				Other information: (C	EL acc. to	o RCP-method,
				paragraphs 84-87, EH4	40)	
Chemical Name	Paraffin wax, fume					Content %:
WEL-TWA: 2 mg/m3		WEL-STEL:	6 mg/m3			
Monitoring procedures:	-					
BMGV:				Other information:		
Chemical Name	Oil mist, mineral					Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL:				
working fluids, ACGIH)						
Monitoring procedures:	- [Draeger - Oil Mis	st 1/a (67 33 031)			
BMGV:				Other information:		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.



Page 5 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

ആ

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). Recommended Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,7 Permeation time (penetration time) in minutes: > 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Liquid, Viscous Darkish, Brown Characteristic Not determined n.a. Not determined ~160 °C >=61 °C (ISO 2719 (Pensky-Martens, closed cup)) Not determined



B Page 6 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties:

Oxidising properties: 9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: n.a. 0,6 Vol-% 7 Vol-% Not determined Not determined 0,85 g/ml (15°C) n.a. Not determined Insoluble Not determined >200 °C (Ignition temperature) Not determined >20,5 mm2/s (40°C) Product is not explosive. When using: development of explosive vapour/air mixture possible. No

Not determined Not determined Not determined ~44 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Heating, open flame, ignition sources **10.5 Incompatible materials** See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.



Page 7 of 11 Safety data sheet according to Re Revision date / version: 12.07.20 Replacing version dated / version Valid from: 12.07.2018 PDF print date: 26.07.2021	18 / 0011		, Annex II			
Seilfett						
Cable Grease						
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.
Hydrocarbons, C10-C13, n-alka						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						No indications o such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications o such an effect., Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousnes , headaches, dizziness

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification). Seilfett

- @B-

Cable Grease							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.



Page 8 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

(GB)·

12.2. Persistence and degradability:	Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:	n.d.a.
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Other adverse	n.d.a.
effects:	
Other information:	According to the recipe, contains no AOX.

Hydrocarbons, C10-C13,	, n-alkanes, iso	oalkanes, cy	vclics, <2% a	romatics			
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,1	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				
12.4. Mobility in soil:	Log Koc		>3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Other adverse effects:							Product floats on the water surface.
Water solubility:			~10	mg/l			Slight

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

12 01 12 spent waxes and fats

Recommendation:



Page 9 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant.

œ

For contaminated packing material

Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

14.1. UN number:	
	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards: Tunnel restriction code:	Not applicable
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
Non-dangerous material according to Transport Por	o Annex II of MARPOL and the IBC Code
Non-dangerous material according to Transport Reg	gulations.
SECT	gulations. FION 15: Regulatory information tal regulations/legislation specific for the substance or mixture nicals are applicable.
SECT 15.1 Safety, health and environmen Observe restrictions:	gulations. FION 15: Regulatory information tal regulations/legislation specific for the substance or mixture
SECT 15.1 Safety, health and environmen Observe restrictions: General hygiene measures for the handling of chem	gulations. FION 15: Regulatory information tal regulations/legislation specific for the substance or mixture nicals are applicable. ~ 44 %
SECT 15.1 Safety, health and environmen Observe restrictions: General hygiene measures for the handling of chem Directive 2010/75/EU (VOC): 15.2 Chemical safety assessment A chemical safety assessment is not provided for m	gulations. FION 15: Regulatory information tal regulations/legislation specific for the substance or mixture nicals are applicable. ~ 44 %
SECT 15.1 Safety, health and environmen Observe restrictions: General hygiene measures for the handling of chem Directive 2010/75/EU (VOC): 15.2 Chemical safety assessment A chemical safety assessment is not provided for m SE	gulations. TION 15: Regulatory information tal regulations/legislation specific for the substance or mixture hicals are applicable. ~ 44 % ixtures. ECTION 16: Other information
SECT 15.1 Safety, health and environmen Observe restrictions: General hygiene measures for the handling of chem Directive 2010/75/EU (VOC): 15.2 Chemical safety assessment A chemical safety assessment is not provided for m	gulations. FION 15: Regulatory information tal regulations/legislation specific for the substance or mixture nicals are applicable. ~ 44 % ixtures.



Page 10 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

ദ്ര

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council bw body weight CAS Chemical Abstracts Service CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) carcinogenic, mutagenic, reproductive toxic CMR DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN **European Norms** United States Environmental Protection Agency (United States of America) EPA etc. et cetera EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number aen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) LQ Limited Quantities International Convention for the Prevention of Marine Pollution from Ships MARPOL not applicable n.a. not available n.av. n.c. not checked n.d.a. no data available OECD Organisation for Economic Co-operation and Development org. organic PBT persistent, bioaccumulative and toxic PΕ Polyethylene PNEC Predicted No Effect Concentration



Page 11 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0011 Replacing version dated / version: 26.03.2018 / 0010 Valid from: 12.07.2018 PDF print date: 26.07.2021 Seilfett Cable Grease

parts per million ppm

œ

PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List **REACH-IT List-No.** Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.