

Page 1 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Liquimate 8200 MS Polymer schwarz

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive sealant

അ

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Landspitali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland) **Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Trimethoxyvinylsilane, Reaction mass of: bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl-1,2,2,6,6-pentamethyl-4-piperidyl sebacate, N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).



Page 2 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

^{n.a.} 3.2 Mixtures

Tains of here we develop the

œ

N-(3-(trimethoxysilyl)propyl)ethylenediamine	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No. 217-164-6	
CAS 1760-24-3	
content % 0,25-<1	
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors Acute Tox. 4, H332	
Eye Dam. 1, H318	
Skin Sens. 1B, H317	
STOT SE 3, H335	
STOT RE 2, H373	
Aquatic Chronic 3, H412	
Specific Concentration Limits and ATE ATE (as inhalation, Dusts or mist): 1,49 mg/l/	4h
ATE (as inhalation, Vapours): 11 mg/l/4h	

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	014-049-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	220-449-8
CAS	2768-02-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	Acute Tox. 4, H332
	Skin Sens. 1B, H317
Specific Concentration Limits and ATE	ATE (as inhalation, Dusts or mist): 1,5 mg/l/4h
	ATE (as inhalation, Vapours): 16,8 mg/l/4h

Reaction mass of: bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and	
methyl-1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Registration number (REACH)	01-2119491304-40-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	915-687-0
CAS	1065336-91-5
content %	0,025-<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1A, H317
	Repr. 2, H361f
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!



Page 3 of 20

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Sensitive individuals:

Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂ Extinction powder Water jet spray Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Calcium oxide Oxides of carbon Fume Silicon dioxide Methanol Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin. 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.



Page 4 of 20

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

6.2 Environmental precautions

If leakage occurs, dam up. Resolve leaks if this possible without risk. Prevent from entering drainage system. Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Protect from frost. Protect from direct sunlight and warming. Store in a well ventilated place. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The methanol listed below can arise	upon contact with wa	ater.		
Chemical Name	Silicon dioxide			
WEL-TWA: 6 mg/m3 (total inh. dus	st), 2,4 mg/m3	WEL-STEL:		
(resp. dust)				
Monitoring procedures:		-		
BMGV:			Other information:	
Chemical Name	Diisononyl phthalat	2		
	Disononyi primalati			
WEL-TWA: 5 mg/m3		WEL-STEL:		
Monitoring procedures:		-		
BMGV:			Other information:	
Chemical Name	Calcium carbonate			
WEL-TWA: 4 mg/m3 (respirable du	ust), 10 mg/m3	WEL-STEL:		
(total inhalable dust)				
Monitoring procedures:		-		
BMGV:			Other information:	
Chemical Name	general dust limit			
WEL-TWA: 10 mg/m3 (inhal. dust)	0	WEL-STEL:		
dust)	, – mg/mo (respir.			
uusij				



œ) Page 5 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Monitoring procedures:

BMGV: ---

Other information: ---

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental compartment					
	Environment - freshwater		PNEC	0,4	mg/l	Assessmer t factor: 50
	Environment - marine		PNEC	0,04	mg/l	Assessmen t factor: 500
	Environment - water, sporadic (intermittent) release		PNEC	1,21	mg/l	
	Environment - sewage treatment plant		PNEC	6,6	mg/l	
	Environment - sediment, freshwater		PNEC	0,29	mg/kg dw	
	Environment - sediment, marine		PNEC	0,15	mg/kg dw	
	Environment - soil		PNEC	0,048	mg/kg dw	
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,63	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	6,8	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,63	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,91	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	27,6	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m3	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,002	mg/l	
	Environment - marine		PNEC	0,00022	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,009	mg/l	
	Environment - sediment, freshwater		PNEC	1,05	mg/kg	
	Environment - sediment, marine		PNEC	0,11	mg/kg	
	Environment - soil		PNEC	0,21	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	1,25	mg/kg	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,25	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,87	mg/m3	



Page 6 of 20

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Consumer	Human - oral	Long term, systemic effects	DNEL	0,5	mg/kg	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	2,5	mg/kg	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	2,35	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3,35	mg/m3	

Silicon dioxide						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - oral (animal		PNEC	60000	mg/kg feed	
	feed)					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

Diisononyl phthalate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	ue Unit	Note
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral (animal feed)		PNEC	150	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	51,72	mg/m3	

Calcium carbonate Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental compartment					
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	6,1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

(GB) - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference

period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)). (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits



Page 7 of 20

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

(Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL))

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes. Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Protective gloves in butyl rubber (EN ISO 374). Minimum layer thickness in mm: 0.5

Permeation time (penetration time) in minutes: 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Normal protective working garments

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.



Page 8 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

8.2.3 Environmental exposure controls

No information available at present.

ആ

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

Explosives:

Oxidizing solids:

Paste, solid. Black Characteristic There is no information available on this parameter. n.a. Not combustible. Does not apply to solids. There is no information available on this parameter. Mixture is non-soluble (in water). There is no information available on this parameter. Not miscible Does not apply to mixtures. There is no information available on this parameter. 1.61 a/cm3 (20°C) Does not apply to solids. There is no information available on this parameter.

Product is not explosive.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Protect from humidity.

10.5 Incompatible materials

Avoid contact with oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

In case of contact with water: Developement of: Methanol

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.



B)						
Page 9 of 20						
Safety data sheet according to R	egulation (EC)	No 1907/2006.	Annex II (last a	mended by Reau	lation (EU) 2020/878)	
Revision date / version: 20.11.20				inenaca zy riega		
Replacing version dated / versior		/ 0016				
Valid from: 20.11.2024		,				
PDF print date: 20.11.2024						
Liquimate 8200 MS Polymer sch	warz					
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
N-(3-(trimethoxysilyl)propyl)eth			11	Ormeria	Test mothers	Note -
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2413	mg/kg	Rat	OECD 401 (Acute Oral	
Acute toxicity, by dermal route:	LD50	> 2000	malka	Rat	Toxicity) OECD 402 (Acute	
Acute toxicity, by dermarroute.	LD50	> 2000	mg/kg	Rai		
Acute toxicity, by inhalation:	LC50	1,49-2,44	mg/l/4h	Rat	Dermal Toxicity) OECD 403 (Acute	Aerosol
Acute toxicity, by initialation.	LC30	1,49-2,44	111g/1/411	Rai	Inhalation Toxicity)	Aerosor
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,49	mg/l/4h			Dusts or mist
Skin corrosion/irritation:		1,40	iiig/i/-iii	Rabbit	OECD 404 (Acute	Not irritant
				Rabbit	Dermal	Not initiant
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Eye Dam. 1
conous eye damago, matom					Irritation/Corrosion)	Lyo Danii T
Respiratory or skin				Guinea pig	OECD 406 (Skin	Skin Sens, 1B
sensitisation:				0	Sensitisation)	
Respiratory or skin				Mouse	OECD 429 (Śkin	Skin Sens. 1B
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	Chinese hamste
					Mutation Test)	
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Reproductive toxicity:	NOAEL	>= 500	mg/kg	Rat	OECD 422 (Combined	
					Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Specific target organ toxicity -	NOAEC	0,015	mg/l/6h/d	Rat	OECD 413 (Subchronic	
repeated exposure (STOT-RE),					Inhalation Toxicity - 90-	
inhalat.:					Day Study)	
Trimothown involution						
Trimethoxyvinylsilane	Endneint	Value	Unit	Organiam	Toot mothed	Notes
Toxicity / effect Acute toxicity, by oral route:	Endpoint LD50	7120	Unit	Organism Rat	OECD 401 (Acute Oral	110162
Acute toxicity, by order toute.	LD30	1120	mg/kg	INAL	Toxicity)	
Acute toxicity, by dermal route:	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute	
, touto toxioity, by donnal route.	2200	0200	lg/ikg		Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute	Vapours
is the testion, by mindlation.					Inhalation Toxicity)	
Acute toxicity, by inhalation:	ATE	16,8	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Dusts or mist
Skin corrosion/irritation:	-	,-		Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
	1	1		1	Irritation/Corrosion)	1

Irritation/Corrosion)



Repr. 2, Analogous conclusion

Page 10 of 20						
Safety data sheet according to R	egulation (EC)	No 1907/2006	6, Annex II (last	amended by Regu	Ilation (EU) 2020/878)	
Revision date / version: 20.11.20	24 / 0017		, - (
Replacing version dated / versior	n: 31.07.2023	/ 0016				
Valid from: 20.11.2024						
PDF print date: 20.11.2024						
Liquimate 8200 MS Polymer sch	warz					
Respiratory or skin				Guinea pig	OECD 406 (Skin	Skin Sens. 1B
sensitisation:				Ounica pig	Sensitisation)	OKIT OCTIS. TD
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
Common analysis and the second s					Mammalian Cell Gene	Chinese hamster
					Mutation Test)	
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo	Negative
					Mammalian Alkaline	
<u> </u>					Comet Assay)	NL C
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	typhimurium Rat	Reverse Mutation Test) OECD 422 (Combined	Negative
Reproductive toxicity.	NOAEL	1000	mg/kg	Rai	Repeated Dose Tox.	Negalive
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Reproductive toxicity	NOAEL	>= 75	mg/kg	Rabbit	OECD 414 (Prenatal	Negative
(Developmental toxicity):					Developmental Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	62,5	mg/kg	Rat	OECD 408 (Repeated	Target organ(s):
repeated exposure (STOT-RE),					Dose 90-Day Oral	bladder
oral:					Toxicity Study in	
					Rodents)	
Specific target organ toxicity -	LOAEL	0,58	mg/l	Rat	OECD 413 (Subchronic	Vapours
repeated exposure (STOT-RE), inhalat.:					Inhalation Toxicity - 90- Day Study)	
Symptoms:					Day Study)	drowsiness,
cymptoms.						dizziness,
						nausea,
						abdominal pain,
						breathing
						difficulties, visual
						disturbances
Reaction mass of: bis(1,2,2,6,6	-pentamethyl	-4-piperidyl)se		ethyl-1,2,2,6,6-pe	ntamethyl-4-piperidyl sebac	
Toxicity / effect	Endpoint		Unit		Test method	Notes
Acute toxicity, by oral route:	LD50	3230	mg/kg	Rat	OECD 423 (Acute Oral	
					Toxicity - Acute Toxic	
Acute toxicity, by dermal route:	LD50	>3170	mg/kg	Rat	Class Method) OECD 402 (Acute	
Acute toxicity, by definial route.	LDJU	>3170	iiig/kg	Nai	Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
				Rabbit	Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Sensitising (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
A					Mutation Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative
					Erythrocyte	
	1	1	1	1	Micronucleus Test)	1

Silicon dioxide Test method OECD 401 (Acute Oral Toxicity / effect Endpoint Value Unit Organism Notes Acute toxicity, by oral route: LD50 >5000 mg/kg Rat Analogous Toxicity) conclusion

Reproductive toxicity:



Page 11 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References,
			-			Maximum
						achievable
						concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit		Not irritant,
						Mechanical
						irritation
						possible.,
						References
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Carcinogenicity:						No indications of
						such an effect.
Reproductive toxicity						No indications of
(Developmental toxicity):						such an effect.
Symptoms:						eyes, reddened

Diisononyl phthalate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4h	Rat	Limit-Test	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	Regulation (EC)	No (skin contact)
sensitisation:					440/2008 B.6 (SKIN	
					SENSITISATION)	
Germ cell mutagenicity:					(Ames-Test)	Negative
Symptoms:						diarrhoea,
						nausea and
						vomiting.

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral	
					toxicity - Fixe Dose	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin contact)
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	



B Page 12 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian	Negative
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	- 5
					Mutation Test)	
Carcinogenicity:						No indications of
						such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg	Rat	OECD 422 (Combined	
			bw/d		Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Specific target organ toxicity -						No indications of
single exposure (STOT-SE):						such an effect.
Specific target organ toxicity -						No indications of
repeated exposure (STOT-RE):						such an effect.
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),			bw/d		Repeated Dose Tox.	
oral:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Specific target organ toxicity -	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic	
repeated exposure (STOT-RE),					Inhalation Toxicity - 90-	
inhalat.:					Day Study)	
Aspiration hazard:						No

11.2. Information on other hazards

Liquimate 8200 MS Polymer sch	nwarz					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Liquimate 8200 MS Poly	mer schwarz						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.



Bevision date / version: 20.11.2024 / 0017 Replacing version date / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	597	mg/l	Brachydanio rerio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to daphnia:	EC50	48h	81	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	8,8	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	DOC	28d	39	%	activated sludge	Regulation (EC) 440/2008 C.4-A (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - DOC DIE- AWAY TEST)	Not readily biodegradable
12.3. Bioaccumulative potential:							Low
12.4. Mobility in soil:							Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	25	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other organisms:	NOEC/NOEL	14d	>= 1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	168,7	mg/l	Daphnia magna	Regulation (EC)	
						440/2008 C.2	
						(DAPHNIA SP.	
						ACUTE	
						IMMOBILISATION	
						TEST)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	28,1	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum	OECD 201 (Alga,	
					capricornutum	Growth Inhibition	
						Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	25	mg/l	Selenastrum		
					capricornutum		
12.2. Persistence and	BOD	28d	51	%		OECD 301 F	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Kow		1,1				Not to be
potential:							expected 20 °C
							QSAR
12.4. Mobility in soil:							Slight



B Page 14 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	5h	1000	mg/l	Pseudomonas putida		
Toxicity to bacteria:	EC50	3h	>2500	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,97	mg/l	Lepomis	OECD 203 (Fish,	
					macrochirus	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	LC50	96h	7,9	mg/l	Oncorhynchus	OECD 203 (Fish,	
-				-	mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	24h	20	mg/l	Daphnia magna	OECD 202	
, ,				0		(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211	
	HOLO, HOLL	2.0	·	ing/i	Dapinia magna	(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1,68	mg/l	Desmodesmus	OECD 201 (Alga,	
12.1. TOXICITY TO algae.	EC30	1211	1,00	mg/i	subspicatus	Growth Inhibition	
					subspicatus	Test)	
12.2. Persistence and	DOC	28d	38	%		OECD 301 F	
	DOC	280	38	%	activated sludge		
degradability:						(Ready	
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative							A notable
potential:							biological
							accumulation
							potential is not t
							be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	IC50	3h	>100	mg/l		OECD 209	
,		-		3		(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



B Page 15 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

12.1. Toxicity to algae:	EL50	72h	>10000	mg/l	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:						Abiotically degradable.
12.3. Bioaccumulative potential:						Not to be expected
12.4. Mobility in soil:						Not to be expected
12.5. Results of PBT and vPvB assessment						No PBT substance, No vPvB substance

Diisononyl phthalate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>102	mg/l	Brachydanio rerio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>=74	mg/l	Daphnia magna	84/449/EEC C.2	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	88	mg/l	Scenedesmus subspicatus		
12.1. Toxicity to algae:	EC50	72h	>88	mg/l	Scenedesmus subspicatus	84/449/EEC C.3	
12.2. Persistence and degradability:		28d	81	%	activated sludge	Regulation (EC) 440/2008 C.4-C (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - CO2 EVOLUTION TEST)	Readily biodegradable
12.2. Persistence and degradability:		28d	80-90	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		8,8-9,7			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	Analogous conclusion
12.3. Bioaccumulative potential:	BCF	14d	<3				Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,00000 149	atm*m3/m ol			
Toxicity to bacteria:	EC50	30min	>83,9	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	56d	>982,4	mg/kg	Eisenia foetida		
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
.							
Calcium carbonate		1	-				
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 16 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz 12.1. Toxicity to fish: LC50 96h Oncorhynchus OECD 203 (Fish, No observation Acute Toxicity with saturated mykiss Test) solution of test material. EC50 48h **OECD 202** 12.1. Toxicity to daphnia: Daphnia magna No observation (Daphnia sp. with saturated Acute solution of test Immobilisation material. Test) 72h >14 Desmodesmus OECD 201 (Alga, 12.1. Toxicity to algae: EC50 mg/l Growth Inhibition subspicatus Test) 12.1. Toxicity to algae: NOEC/NOEL 72h 14 Desmodesmus OECD 201 (Alga, mg/l subspicatus Growth Inhibition Test) 12.2. Persistence and Not relevant for degradability: inorganic substances. 12.3. Bioaccumulative Not to be potential: expected 12.4. Mobility in soil: n.a. No PBT 12.5. Results of PBT and vPvB assessment substance, No vPvB substance Toxicity to bacteria: EC50 3h >1000 mg/l activated sludge **OECD 209** (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) Toxicity to bacteria: NOEC/NOEL 3h 1000 mg/l activated sludge **OECD 209** (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) EC50 Other organisms: 21d >1000 mg/kg dw **OECD 208** Glycine max (Terrestrial Plants, Growth Test) Other organisms: EC50 21d >1000 mg/kg dw **OECD 208** Lycopersicon (Terrestrial Plants, esculentum Growth Test) Other organisms: EC50 21d >1000 **OECD 208** Avena sativa mg/kg dw (Terrestrial Plants, Growth Test) **OECD 208** Other organisms: NOEC/NOEL 21d 1000 Glycine max mg/kg dw (Terrestrial Plants, Growth Test) NOEC/NOEL 1000 Other organisms: 21d mg/kg dw **OECD 208** Lycopersicon (Terrestrial Plants, esculentum Growth Test) NOEC/NOEL 21d 1000 Other organisms: mg/kg dw **OECD 208** Avena sativa (Terrestrial Plants. Growth Test) Other organisms: EC50 14d >1000 Eisenia foetida **OECD 207** mg/kg dw (Earthworm, Acute Toxicity Tests) NOEC/NOEL 1000 **OECD 207** Other organisms: 14d mg/kg dw Eisenia foetida (Earthworm, Acute Toxicity Tests)

ആ



Page 17 of 20

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

Other organisms:	EC50	28d	>1000	mg/kg dw	OECD 216 (Soil	
					Microorganisms -	
					Nitrogen	
					Transformation	
					Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw	OECD 216 (Soil	
-					Microorganisms -	
					Nitrogen	
					Transformation	
					Test)	
Water solubility:			0,0166	g/l	OECD 105 (Water	20°C
-					Solubility)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

08 04 11 adhesive and sealant sludges containing organic solvents or other hazardous substances

08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable
Classification code:	Not applicable
LQ:	Not applicable
Transport category:	Not applicable
Transport by sea (IMDG-code)	
14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	Not applicable
Transport by air (IATA)	



Page 18 of 20

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

14.1. UN number or ID number:14.2. UN proper shipping name:Not applicable14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards:

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

Not applicable

Not applicable

Not applicable

Not applicable

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

0.01 %

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

8

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H361f Suspected of damaging fertility. H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H332 Harmful if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. Acute Tox. — Acute toxicity - inhalation Eye Dam. — Serious eye damage Skin Sens. — Skin sensitization STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation STOT RE — Specific target organ toxicity - repeated exposure Aquatic Chronic - Hazardous to the aquatic environment - chronic Flam. Liq. — Flammable liquid Repr. — Reproductive toxicity

Aquatic Acute - Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances.



Page 19 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016

ആ

Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany). German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** The International Bromine Council BSEF CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon for example (abbreviation of Latin 'exempli gratia'), for instance e.q. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS European List of Notified Chemical Substances ELINCS EN European Norms United States Environmental Protection Agency (United States of America) EPA $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. general aen. GHS Globally Harmonized System of Classification and Labelling of Chemicals Global warming potential GWP Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association International Bulk Chemical (Code) IBC (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships mg/kg bw mg/kg body weight



ആ Page 20 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 20.11.2024 / 0017 Replacing version dated / version: 31.07.2023 / 0016 Valid from: 20.11.2024 PDF print date: 20.11.2024 Liquimate 8200 MS Polymer schwarz mg/kg bw/d, mg/kg bw/day mg/kg body weight/day mg/kg dry weight mg/kg dw mg/kg wwt mg/kg wet weight not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NI P No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical REACH-IT List-No. identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone тос Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.