

Page 1 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Liquimate 8200 MS Polymer weiss

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive sealant

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

#### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

#### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Trimethoxyvinylsilane, Reaction mass of: bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl-1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl-1,2,2,6,6-pentamethyl-4-piperidyllysebacate and methyl-4-piperidyllysebacate and methyl-4-piperidyll piperidyl sebacate, N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

EUH212-Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024  $\,$  / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

## n.a. 3.2 Mixtures

Titanium dioxide (in powder form containing 1 % or more of particles	
with aerodynamic diameter <= 10 μm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

N-(3-(trimethoxysilyl)propyl)ethylenediamine	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	217-164-6
CAS	1760-24-3
content %	0,25-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332
	Eye Dam. 1, H318
	Skin Sens. 1B, H317
	STOT SE 3, H335
	STOT RE 2, H373
	Aquatic Chronic 3, H412
Specific Concentration Limits and ATE	ATE (as inhalation, Dusts or mist): 1,49 mg/l/4h
	ATE (as inhalation, Vapours): 11 mg/l/4h

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	014-049-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	220-449-8
CAS	2768-02-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	Acute Tox. 4, H332
	Skin Sens. 1B, H317
Specific Concentration Limits and ATE	ATE (as inhalation, Dusts or mist): 1,5 mg/l/4h
	ATE (as inhalation, Vapours): 16,8 mg/l/4h

Reaction mass of: bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl-1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Registration number (REACH)	01-2119491304-40-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	915-687-0
CAS	1065336-91-5
content %	0,025-<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1A, H317
	Repr. 2, H361f
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.



(B)

Page 3 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

Allergic reaction possible.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media Suitable extinguishing media

CO2

Extinction powder

Water jet spray

Alcohol resistant foam

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Calcium oxide

Oxides of carbon

Fume

Silicon dioxide

Methanol

Toxic gases

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

## 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.



Page 4 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

#### 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect from frost.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

The methanol listed below can arise upon contact with water.

® Chamical Name	Titanium dioxide (ir	n powder form containing 1 % or me	ore of particles with	
Chemical Name	aerodynamic diame		•	
WEL-TWA: 10 mg/m3 (total inhala	ble dust), 4 mg/m3	WEL-STEL:		
(respirable dust)				
Monitoring procedures:				
BMGV:			Other information:	
Chemical Name	Silicon dioxide			
WEL-TWA: 6 mg/m3 (total inh. dus	st), 2,4 mg/m3	WEL-STEL:		
(resp. dust)				
Monitoring procedures:				
BMGV:			Other information:	
Chemical Name	Diisononyl phthalat	e		



Page 5 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

WEL-TWA: 5 mg/m3		WEL-STEL:		
Monitoring procedures:		-		
BMGV:			Other information:	
Chemical Name	Calcium carbonate			
WEL-TWA: 4 mg/m3 (respirable du	st), 10 mg/m3	WEL-STEL:		
(total inhalable dust)				
Monitoring procedures:		-		
BMGV:			Other information:	
Chemical Name	general dust limit			
WEL-TWA: 10 mg/m3 (inhal. dust),	4 mg/m3 (respir.	WEL-STEL:		
dust)				
Monitoring procedures:		-		
BMGV:			Other information:	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water,		PNEC	0,193	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sewage		PNEC	100	mg/l	
	treatment plant					
	Environment - sediment,		PNEC	1000	mg/kg dw	
	freshwater					
	Environment - sediment,		PNEC	100	mg/kg dw	
	marine					
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal		PNEC	1667	mg/kg feed	
	feed)					
Consumer	Human - oral	Long term, systemic	DNEL	700	mg/kg bw/d	
		effects				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	Für entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - marine		PNEC	0,04	mg/l	Für entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entspreche ndes Silantriol (Hydrolysprodukt) ermittelt.



Page 6 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

	Environment - sewage		PNEC	6,6	mg/l	Für
	treatment plant					entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
	Environment - soil		PNEC	0,06	mg/kg dw	Für entspreche ndes Silantriol (Hydrolyspr odukt) ermittelt.
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,63	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	6,8	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,63	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,91	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	27,6	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0.002	mg/l	
	Environment - marine		PNEC	0,00022	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,009	mg/l	
	Environment - sediment, freshwater		PNEC	1,05	mg/kg	
	Environment - sediment,		PNEC	0,11	mg/kg	
	Environment - soil		PNEC	0,21	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	1,25	mg/kg	



③B)·

Page 7 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Consumer	Human - oral	Short term, systemic effects	DNEL	1,25	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,87	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,5	mg/kg	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	2,5	mg/kg	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	2,35	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3,35	mg/m3	

Silicon dioxide						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - oral (animal		PNEC	60000	mg/kg feed	
	feed)					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

Diisononyl phthalate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral (animal feed)		PNEC	150	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m3	

Calcium carbonate										
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note				
	Environment - sewage treatment plant		PNEC	100	mg/l					
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day					
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3					
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3					
Consumer	Human - oral	Short term, systemic effects	DNEL	6,1	mg/kg bw/day					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3					
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3					

<sup>-</sup> United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).



(B)

Page 8 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a binomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits

(Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0.5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Normal protective working garments

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.



Page 9 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Paste, Solid Colour: White

Odour: Characteristic

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

Flammability: There is no information available on this parameter. Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter.

Flash point: Does not apply to solids.

Auto-ignition temperature: There is no information available on this parameter. Decomposition temperature: There is no information available on this parameter.

pH: Mixture is non-soluble (in water).

Kinematic viscosity: There is no information available on this parameter. Not miscible

Solubility: Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 1,62 g/cm3 (20°C)

Relative vapour density: There is no information available on this parameter. Particle characteristics: There is no information available on this parameter.

9.2 Other information

**Explosives:** Product is not explosive.

Oxidizing solids: Nο

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

Protect from humidity.

#### 10.5 Incompatible materials

Avoid contact with strong acids.

Avoid contact with strong oxidizing agents.

#### 10.6 Hazardous decomposition products

In case of contact with water:

Developement of:

Methanol

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Liquimate 8200 MS Polymer weise

Elquiniate 0200 Mo 1 Olynici weiss									
Toxicity / effect E	ndpoint '	Value	Unit	Organism	Test method	Notes			



(B)

Page 10 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Acute toxicity, by oral route:	n.d.a.
Acute toxicity, by dermal route:	n.d.a.
Acute toxicity, by inhalation:	n.d.a.
Skin corrosion/irritation:	n.d.a.
Serious eye damage/irritation:	n.d.a.
Respiratory or skin	n.d.a.
sensitisation:	
Germ cell mutagenicity:	n.d.a.
Carcinogenicity:	n.d.a.
Reproductive toxicity:	n.d.a.
Specific target organ toxicity -	n.d.a.
single exposure (STOT-SE):	
Specific target organ toxicity -	n.d.a.
repeated exposure (STOT-RE):	
Aspiration hazard:	n.d.a.
Symptoms:	n.d.a.

Titanium dioxide (in powder for Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	Hotes
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract)
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		(90d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		(90d)



Page 11 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Symptoms:			mucous
			membrane
			irritation,
			coughing,
			respiratory
			distress, drying
			of the skin.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2413	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	1,49-2,44	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,49	mg/l/4h			Dusts or mist
Skin corrosion/irritation:		,		Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1B
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				,	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative Chinese hamste
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:	NOAEL	>= 500	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,015	mg/l/6h/d	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	ATE	16,8	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1B



(B)

Page 12 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene Mutation Test)	Chinese hamster
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo	Negative
					Mammalian Alkaline	
					Comet Assay)	
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined	Negative
					Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Reproductive toxicity	NOAEL	>= 75	mg/kg	Rabbit	OECD 414 (Prenatal	Negative
(Developmental toxicity):					Developmental Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	62,5	mg/kg	Rat	OECD 408 (Repeated	Target organ(s):
repeated exposure (STOT-RE),					Dose 90-Day Oral	bladder
oral:					Toxicity Study in	
					Rodents)	
Specific target organ toxicity -	LOAEL	0,58	mg/l	Rat	OECD 413 (Subchronic	Vapours
repeated exposure (STOT-RE),					Inhalation Toxicity - 90-	
inhalat.:					Day Study)	
Symptoms:						drowsiness,
						dizziness,
						nausea,
						abdominal pain,
						breathing
						difficulties, visual
						disturbances

Reaction mass of: bis(1,2,2,6,6	-pentamethyl-	4-piperidyl)s	ebacate and me	ethyl-1,2,2,6,6-pe	ntamethyl-4-piperidyl sebac	cate
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3230	mg/kg	Rat	OECD 423 (Acute Oral	
					Toxicity - Acute Toxic	
					Class Method)	
Acute toxicity, by dermal route:	LD50	>3170	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Sensitising (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Reproductive toxicity:						Repr. 2,
						Analogous
						conclusion

Silicon dioxide									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous			
					Toxicity)	conclusion			
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References			



Page 13 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References,
						Maximum
						achievable
						concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit		Not irritant,
						Mechanical
						irritation
						possible.,
						References
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Carcinogenicity:						No indications of
						such an effect.
Reproductive toxicity						No indications of
(Developmental toxicity):						such an effect.
Symptoms:						eyes, reddened

Diisononyl phthalate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4h	Rat	Limit-Test	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
· · · · ·					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	Regulation (EC)	No (skin contact)
sensitisation:					440/2008 B.6 (SKIN	
					SENSITISATION)	
Germ cell mutagenicity:					(Ames-Test)	Negative
Symptoms:						diarrhoea,
						nausea and
						vomiting.

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral	
					toxicity - Fixe Dose	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
• •					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
• • •					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
, ,					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin contact)
sensitisation:					Sensitisation - Local	,
					Lymph Node Assay)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	



③B)·

Page 14 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	

#### 11.2. Information on other hazards

Liquimate 8200 MS Polymer we	Liquimate 8200 MS Polymer weiss										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes					
Endocrine disrupting properties:						Does not apply					
						to mixtures.					
Other information:						No other					
						relevant					
						information					
						available on					
						adverse effects					
						on health.					

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)										
Toxicity / effect Endpoint Time Value Unit Organism Test method Notes										



Page 15 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
l de la companya de						Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriell	U.S. EPA-600/9-	
					a subcapitata	78-018	
12.2. Persistence and							Not relevant for
degradability:							inorganic
							substances.
12.3. Bioaccumulative	BCF	42d	9,6				Not to be
potential:							expected
12.3. Bioaccumulative	BCF	14d	19-352				Oncorhynchus
potential:							mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
l							vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas		
l					fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:	DOC	28d	39	%	activated sludge	Regulation (EC) 440/2008 C.4-A (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - DOC DIE- AWAY TEST)	Not readily biodegradable
12.3. Bioaccumulative potential:							Low
12.1. Toxicity to fish:	LC50	96h	597	mg/l	Brachydanio rerio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to daphnia:	EC50	48h	81	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	8,8	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC10	16h	25	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other organisms:	NOEC/NOEL	14d	>= 1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:							Slight

Trimethoxyvinylsilane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 16 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity	
12.1. Toxicity to daphnia:	EC50	48h	168,7	mg/l	Daphnia magna	Test) Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	25	mg/l	Selenastrum capricornutum		
12.2. Persistence and degradability:	BOD	28d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		1,1				Not to be expected 20 °C, QSAR
12.4. Mobility in soil:							Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	5h	1000	mg/l	Pseudomonas putida		
Toxicity to bacteria:	EC50	3h	>2500	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,97	mg/l	Lepomis	OECD 203 (Fish,	
-					macrochirus	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	LC50	96h	7,9	mg/l	Oncorhynchus	OECD 203 (Fish,	
•					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	24h	20	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1,68	mg/l	Desmodesmus	OECD 201 (Alga,	
					subspicatus	Growth Inhibition	
						Test)	
12.2. Persistence and	DOC	28d	38	%	activated sludge	OECD 301 F	
degradability:						(Ready	
						Biodegradability -	
						Manometric	
		1				Respirometry Test)	



Page 17 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

12.3. Bioaccumulative						A notable
potential:						biological
						accumulation
						potential is not to
						be expected
						(LogPow 1-3).
12.5. Results of PBT						No PBT
and vPvB assessment						substance, No
						vPvB substance
Toxicity to bacteria:	IC50	3h	>100	mg/l	OECD 209	
					(Activated Sludge,	
					Respiration	
					Inhibition Test	
					(Carbon and	
					Àmmonium	
					Oxidation))	

Silicon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:						,	Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Diisononyl phthalate								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	>102	mg/l	Brachydanio rerio	92/69/EC		
12.1. Toxicity to daphnia:	EC50	48h	>=74	mg/l	Daphnia magna	84/449/EEC C.2		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=100	mg/l	Daphnia magna	OECD 202		
						(Daphnia sp.		
						Acute		
						Immobilisation		
						Test)		
12.1. Toxicity to algae:	NOEC/NOEL	72h	88	mg/l	Scenedesmus			
					subspicatus			
12.1. Toxicity to algae:	EC50	72h	>88	mg/l	Scenedesmus	84/449/EEC C.3		
					subspicatus			
12.2. Persistence and		28d	81	%	activated sludge	Regulation (EC)	Readily	
degradability:						440/2008 C.4-C	biodegradable	
						(DETERMINATIO		
						N OF 'READY'		
						BIODEGRADABILI		
						TY - CO2		
						EVOLUTION		
						TEST)		



Page 18 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018 Valid from: 04.03.2024

PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

12.3. Bioaccumulative potential:	Log Kow		8,8-9,7			OECD 117 (Partition Coefficient (noctanol/water) - HPLC method)	Analogous conclusion
12.3. Bioaccumulative potential:	BCF	14d	<3			,	Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,00000 149	atm*m3/m ol			
Toxicity to bacteria:	EC50	30min	>83,9	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	56d	>982,4	mg/kg	Eisenia foetida		
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Calcium carbonate Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	value	Unit	Oncorhynchus	OECD 203 (Fish,	No observation
12.1. Toxiony to non.	2030	3011			mykiss	Acute Toxicity	with saturated
					IIIykioo	Test)	solution of test
						1001)	material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202	No observation
12.11. Toxiony to daprima.	2000	1011			Daprilla magna	(Daphnia sp.	with saturated
						Acute	solution of test
						Immobilisation	material.
						Test)	a.o.i.a.ii
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus	OECD 201 (Alga,	
in the state of the digues.		1			subspicatus	Growth Inhibition	
					- Casopicatus	Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	14	mg/l	Desmodesmus	OECD 201 (Alga,	
3 3 3 3 3 3					subspicatus	Growth Inhibition	
						Test)	
12.2. Persistence and						,	Not relevant for
degradability:							inorganic
,							substances.
12.3. Bioaccumulative							Not to be
potential:							expected
12.4. Mobility in soil:							n.a.
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209	
						(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
<del></del>	NOEC/NOEL	3h	1000		a ativata al alvel	Oxidation)) OECD 209	
Toxicity to bacteria:	INUEU/NUEL	SII	1000	mg/l	activated sludge		
						(Activated Sludge, Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	
		1				Oxidation))	



Page 19 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208	Glycine max
						(Terrestrial Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208	Lycopersicon
						(Terrestrial Plants,	esculentum
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208	Avena sativa
						(Terrestrial Plants,	
						Growth Test)	
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208	Glycine max
_						(Terrestrial Plants,	
						Growth Test)	
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208	Lycopersicon
<u> </u>						(Terrestrial Plants,	esculentum
						Growth Test)	
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208	Avena sativa
· ·						(Terrestrial Plants,	
						Growth Test)	
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207	
· ·						(Earthworm,	
						Acute Toxicity	
						Tests)	
Other organisms:	NOEC/NOEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207	
· ·						(Earthworm,	
						Acute Toxicity	
						Tests)	
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil	
· ·						Microorganisms -	
						Nitrogen	
						Transformation	
						Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw		OECD 216 (Soil	
				3 3		Microorganisms -	
						Nitrogen	
						Transformation	
						Test)	
Water solubility:			0,0166	g/l		OECD 105 (Water	20°C
	1	1	1 2,2:20	J		Solubility)	ı

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

08 04 11 adhesive and sealant sludges containing organic solvents or other hazardous substances

08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.



Page 20 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

#### **SECTION 14: Transport information**

#### **General statements**

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards:

14.6. Environmental hazards:

14.7. Not applicable

14.8. Environmental hazards:

15. Not applicable

16. Not applicable

17. Not applicable

18. Not applicable

19. Not applicable

Transport by sea (IMDG-code)

14.1. UN number or ID number:

Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):Not applicable14.4. Packing group:Not applicable14.5. Environmental hazards:Not applicableMarine Pollutant:Not applicableEmS:Not applicable

Transport by air (IATA)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):Not applicable14.4. Packing group:Not applicable14.5. Environmental hazards:Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0,01 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.



Page 21 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

H361f Suspected of damaging fertility.

H226 Flammable liquid and vapour.

H351 Suspected of causing cancer by inhalation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Carc. — Carcinogenicity

Acute Tox. — Acute toxicity - inhalation

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation STOT RE — Specific target organ toxicity - repeated exposure

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Flam. Liq. — Flammable liquid

Repr. — Reproductive toxicity

Aquatic Acute — Hazardous to the aquatic environment - acute

#### **Key literature references and sources for data:**

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHÁ Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAM

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

carcinogenic, mutagenic, reproductive toxic CMR

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50)Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

European Community FC

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect



Page 22 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

**European Economic Community** 

European Inventory of Existing Commercial Chemical Substances **EINECS** 

**ELINCS** European List of Notified Chemical Substances

FΝ European Norms

**EPA** United States Environmental Protection Agency (United States of America)

ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

et cetera etc. European Union EU

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number general gen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

Global warming potential **GWP** 

Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive

**IUCLID International Uniform Chemical Information Database** IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient

**Limited Quantities** LQ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg body weight mg/kg bw

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dry weight mg/kg dw mg/kg wet weight mg/kg wwt

not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NI P No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PΕ Polyethylene

PNEC Predicted No Effect Concentration

parts per million ppm Polyvinylchloride PVC

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.



③B)·

Page 23 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0019

Replacing version dated / version: 12.07.2023 / 0018

Valid from: 04.03.2024 PDF print date: 08.03.2024 Liquimate 8200 MS Polymer weiss

No responsibility.

## These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.