

Page 1 of 21
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 27.09.2024 / 0016
Replacing version dated / version: 04.03.2024 / 0015
Valid from: 27.09.2024
PDF print date: 27.09.2024
Silikondichtmasse schwarz
Silicone Sealing Compound, black

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Silikondichtmasse schwarz
Silicone Sealing Compound, black

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Silicone sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	3	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

Warning

H412-Harmful to aquatic life with long lasting effects. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251-Do not pierce or burn, even after use. P273-Avoid release to the environment.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH208-Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.

13,2 % by mass of the contents are flammable.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

O,O',O''-(methylsilyldiylne)trioxime-2-pentanone	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	484-460-1
CAS	37859-55-5
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1234 mg/kg
2-pentanone, O,O',O''-(ethenylsilyldiylne)trioxime	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	700-810-0
CAS	58190-62-8
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1000 mg/kg
Decamethylcyclopentasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119511367-43-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	208-764-9
CAS	541-02-6
content %	0,25-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 4, H413
Dodecamethylcyclohexasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119517435-42-XXXX

Page 3 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	208-762-8
CAS	540-97-6
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	---

3-aminopropyltriethoxysilane	
Registration number (REACH)	01-2119480479-24-XXXX
Index	612-108-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	213-048-4
CAS	919-30-2
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Specific Concentration Limits and ATE	ATE (oral): 1457 mg/kg

Octamethylcyclotetrasiloxane	
	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119529238-36-XXXX
Index	014-018-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	209-136-7
CAS	556-67-2
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.
 Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:
 Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 27.09.2024 / 0016

Replacing version dated / version: 04.03.2024 / 0015

Valid from: 27.09.2024

PDF print date: 27.09.2024

Silikondichtmasse schwarz

Silicone Sealing Compound, black

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Foam

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of nitrogen

Silicon dioxide

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Page 5 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Do not store with oxidizing agents.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect against moisture and store closed.

Keep protected from direct sunlight and temperatures over 50°C.

Recommended storage temperature:

0 - 30°C

Observe special regulations for aerosols!

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Silicon dioxide - amorphous	
WEL-TWA: 6 mg/m ³ (total inh. dust), 2,4 mg/m ³ (resp. dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

2-pentanone, O,O',O''-(ethenylsilyldiyl)trioxime						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,103	mg/l	
	Environment - marine		PNEC	0,0103	mg/l	
	Environment - sediment, freshwater		PNEC	0,586	mg/kg dw	
	Environment - sediment, marine		PNEC	0,059	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2,22	mg/l	
	Environment - soil		PNEC	0,04555	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,057	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,033	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,033	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,229	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,065	mg/kg bw/d	

Dodecamethylcyclohexasiloxane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sediment, freshwater		PNEC	13,5	mg/kg dw	
	Environment - sediment, marine		PNEC	1,35	mg/kg dw	
	Environment - soil		PNEC	3,336	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - oral (animal feed)		PNEC	66,7	mg/kg	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	1,5	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,3	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,1	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	11	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1,22	mg/m ³	

Decamethylcyclopentasiloxane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - sediment, freshwater		PNEC	2,4	mg/kg	
	Environment - sediment, marine		PNEC	0,24	mg/kg	
	Environment - soil		PNEC	1,1	mg/kg	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,3	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	4,3	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,3	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	4,3	mg/m ³	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	97,3	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	24,2	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	97,3	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	24,2	mg/m ³	

3-aminopropyltriethoxysilane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,5	mg/l	Assessment factor: 50
	Environment - marine		PNEC	0,05	mg/l	Assessment factor: 500
	Environment - sporadic (intermittent) release		PNEC	2,05	mg/l	
	Environment - sediment, freshwater		PNEC	1,8	mg/kg dw	
	Environment - soil		PNEC	0,069	mg/kg dw	
	Environment - sewage treatment plant		PNEC	0,81	mg/l	Assessment factor: 10
	Environment - sediment, marine		PNEC	0,18	mg/kg dw	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1	mg/kg bw/d	
Consumer	Human - dermal	Short term, systemic effects	DNEL	5	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,4	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	3,5	mg/m ³	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	8,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	59	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	14	mg/m ³	

Octamethylcyclotetrasiloxane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1,5	µg/l	
	Environment - marine		PNEC	0,15	µg/l	
	Environment - sediment, freshwater		PNEC	3	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,3	mg/kg dry weight	
	Environment - soil		PNEC	0,54	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - oral (animal feed)		PNEC	41	mg/kg feed	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	13	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,7	mg/kg bw/day	

Page 8 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

Consumer	Human - oral	Short term, systemic effects	DNEL	3,7	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	73	mg/m3	

Silicon dioxide - amorphous						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 With danger of contact with eyes.
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:

Page 9 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

> 0,1
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid The propellant is not released when used in accordance with the regulations.
Colour:	Black
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	There is no information available on this parameter.
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Not miscible
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,01 g/cm ³ (Active substance)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Protect from humidity.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Water

Bases

Alcohols

Oxidizing agents

Acids

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Silikondichtmasse schwarz

Silicone Sealing Compound, black

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

O,O',O''-(methylsilylidyne)trioxime-2-pentanone

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1234	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by oral route:	ATE	1234	mg/kg			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative

Reproductive toxicity:	NOAEL	200	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
------------------------	-------	-----	---------------	-----	---	--

2-pentanone, O,O',O''-(ethenylsilylidine)trioxime

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1000	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	1000	mg/kg			

Decamethylcyclopentasiloxane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	8,67	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Respiratory or skin sensitisation:				Mouse	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Rat	OECD 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells In Vivo)	Negative

Dodecamethylcyclohexasiloxane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,15	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

3-aminopropyltriethoxysilane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1457	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	ATE	1457	mg/kg			
Acute toxicity, by dermal route:	LD50	4076	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>7,35	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	>16	ppm/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Female
Acute toxicity, by inhalation:	LC50	>5	ppm/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Male
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	100	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	200	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	(90d)
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	84	mg/kg	Rabbit		(9d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,147	mg/l	Rat		(19d)
Symptoms:						respiratory distress, burning of the membranes of the nose and throat, coughing, mucous membrane irritation
Symptoms:						eyes, reddened, watering eyes

Octamethylcyclotetrasiloxane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>4800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Male
Acute toxicity, by dermal route:	LD50	>2375	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	36	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol

12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

O,O',O''-(methylsilylidyn)trioxime-2-pentanone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>113	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	113	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	113	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	>113	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	56	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	LOEC/LOEL	72h	36	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.3. Bioaccumulative potential:	Log Pow		1,25			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	

Decamethylcyclopentasiloxane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>16	µg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to fish:	NOEC/NOEL	>60d	>14	µg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>15	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water-solubility value.

12.1. Toxicity to daphnia:	EC50	48h	>2,9	µg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	EC50	96h	>12	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.
12.2. Persistence and degradability:		28d	0,14	%		OECD 310 (Ready Biodegradability - CO ₂ in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		8,023				
12.3. Bioaccumulative potential:	BCF		7060				
Toxicity to bacteria:	EC50	3h	>2000	mg/l	activated sludge		

Docecamethylcyclohexasiloxane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LD50	49d	>4,4	µg/l	Pimephales promelas		
12.1. Toxicity to fish:	NOEC/NOEL	>60d	>=14	µg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	90d
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>4,6	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>2	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>= 2	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	4,47	%		OECD 310 (Ready Biodegradability - CO ₂ in sealed vessels (Headspace Test))	Not readily biodegradable CO ₂ evolution
12.3. Bioaccumulative potential:	Log Pow		8,87-9,45				
12.3. Bioaccumulative potential:	BCF	49d	1160			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.5. Results of PBT and vPvB assessment							vPvB-substance, PBT-substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Water solubility:			5	µg/l			25°C

3-aminopropyltriethoxysilane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

12.1. Toxicity to fish:	LC50	96h	>934	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	311	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	1,3	mg/l	Scenedesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:	DOC	28d	67	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,4		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected
12.3. Bioaccumulative potential:	Log Pow		1,7				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	6h	13	mg/l	Pseudomonas putida		
Water solubility:							Insoluble

Octamethylcyclotetrasiloxane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>500	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	NOEC/NOEL	>60d	4,4	µg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	>0,015	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,0079	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC10	96h	0,022	mg/l			
12.2. Persistence and degradability:			3,7	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	29d
12.3. Bioaccumulative potential:	Log Pow		6,98				
12.3. Bioaccumulative potential:	BCF	28d	12400		Pimephales promelas		
12.5. Results of PBT and vPvB assessment							PBT-substance, vPvB-substance
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge		

Silicon dioxide - amorphous

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 17 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	30d	34223	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>10000	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	IC50	72h	440	mg/l	Pseudokirchneriella subcapitata	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	60	mg/l	Pseudokirchneriella subcapitata	IUCLID Chem. Data Sheet (ESIS)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 02 17 waste containing silicones other than those mentioned in 07 02 16

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.


Recycling

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.2	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	E	
Classification code:	5A	
LQ:	1 L	
Transport category:	3	

Transport by sea (IMDG-code)

14.1. UN number or ID number:	1950
14.2. UN proper shipping name:	
UN 1950 AEROSOLS	



GB

Page 18 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 27.09.2024 / 0016
 Replacing version dated / version: 04.03.2024 / 0015
 Valid from: 27.09.2024
 PDF print date: 27.09.2024
 Silikondichtmasse schwarz
 Silicone Sealing Compound, black

14.3. Transport hazard class(es): 2.2
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable
 Marine Pollutant: Not applicable
 EmS: F-D, S-U

Transport by air (IATA)

14.1. UN number or ID number: 1950
 14.2. UN proper shipping name: UN 1950 Aerosols, non-flammable
 14.3. Transport hazard class(es): 2.2
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Regulation (EC) No 1907/2006, Annex XVII
 Dodecamethylcyclohexasiloxane
 Decamethylcyclopentasiloxane
 Octamethylcyclotetrasiloxane
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
25	Oxygen		200	2000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 6,07 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 15, 16
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 27.09.2024 / 0016

Replacing version dated / version: 04.03.2024 / 0015

Valid from: 27.09.2024

PDF print date: 27.09.2024

Silikondichtmasse schwarz

Silicone Sealing Compound, black

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 3, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H361f Suspected of damaging fertility.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Acute Tox. — Acute toxicity - oral

Eye Irrit. — Eye irritation

Skin Corr. — Skin corrosion

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

Repr. — Reproductive toxicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, Eblx (x = 10, 50)	Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC	European Community
ECHA	European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)	Effect Concentration/Level for x % effect
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ErCx, EµCx, Erlx (x = 10, 50)	Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc.	et cetera
EU	European Union
EVAL	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
Koc	Adsorption coefficient of organic carbon in the soil
Kow	octanol-water partition coefficient
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC (Code)	International Bulk Chemical (Code)
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
IUPAC	International Union for Pure Applied Chemistry
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc	Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow	Logarithm of octanol-water partition coefficient
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw	mg/kg body weight
mg/kg bw/d, mg/kg bw/day	mg/kg body weight/day
mg/kg dw	mg/kg dry weight
mg/kg wwt	mg/kg wet weight
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute for Occupational Safety and Health (USA)
NLP	No-longer-Polymer
NOEC, NOEL	No Observed Effect Concentration/Level
OECD	Organisation for Economic Co-operation and Development
org.	organic
OSHA	Occupational Safety and Health Administration (USA)
PBT	persistent, bioaccumulative and toxic
PE	Polyethylene
PNEC	Predicted No Effect Concentration
ppm	parts per million
PVC	Polyvinylchloride
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No.	6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID	Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC	Substances of Very High Concern
Tel.	Telephone
TOC	Total organic carbon
UN RTDG	United Nations Recommendations on the Transport of Dangerous Goods
VOC	Volatile organic compounds

Page 21 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 27.09.2024 / 0016

Replacing version dated / version: 04.03.2024 / 0015

Valid from: 27.09.2024

PDF print date: 27.09.2024

Silikondichtmasse schwarz

Silicone Sealing Compound, black

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.