

Page 1 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 14.10.2021 / 0006  
Replacing version dated / version: 29.01.2020 / 0005  
Valid from: 14.10.2021  
PDF print date: 15.10.2021  
Top Tec MTF 5100 75W

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Top Tec MTF 5100 75W**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Gear lubricant

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)  
+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment.

P501-Dispose of contents / container to an approved waste disposal facility.

#### 2.3 Other hazards

Page 2 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic</b>	
<b>Registration number (REACH)</b>	01-2119471299-27-XXXX
<b>Index</b>	649-474-00-6
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	265-169-7
<b>CAS</b>	64742-65-0
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Asp. Tox. 1, H304

<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines</b>	
<b>Registration number (REACH)</b>	01-2119473797-19-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	627-034-4
<b>CAS</b>	1213789-63-9
<b>content %</b>	0,025-<0,25
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 (gastrointestinal tract, liver, immune system) (oral) Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Page 3 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 14.10.2021 / 0006  
Replacing version dated / version: 29.01.2020 / 0005  
Valid from: 14.10.2021  
PDF print date: 15.10.2021  
Top Tec MTF 5100 75W

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

CO<sub>2</sub>  
Foam  
Dry extinguisher  
Water mist

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Toxic gases

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

#### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

### **6.2 Environmental precautions**

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
Fill the absorbed material into lockable containers.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0006

Replacing version dated / version: 29.01.2020 / 0005

Valid from: 14.10.2021

PDF print date: 15.10.2021

Top Tec MTF 5100 75W

### 7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store at room temperature.

Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---	

Distillates (petroleum), solvent-dewaxed heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m <sup>3</sup>	

C16-18-(even numbered, saturated and unsaturated)-alkylamines						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,26	µg/l	
	Environment - marine		PNEC	0,026	µg/l	
	Environment - sediment, freshwater		PNEC	3,76	mg/kg dw	
	Environment - sediment, marine		PNEC	0,376	mg/kg dw	
	Environment - soil		PNEC	10	mg/kg dw	
	Environment - sewage treatment plant		PNEC	550	µg/l	

GB

Page 5 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

	Environment - water, sporadic (intermittent) release		PNEC	1,6	µg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,04	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,09	mg/kg	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:  
 Protective gloves, oil resistant (EN ISO 374).  
 If applicable  
 Protective nitrile gloves (EN ISO 374).  
 Protective gloves made of polyvinyl alcohol (EN ISO 374).  
 Protective Viton® / fluoroelastomer gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 >= 0,5  
 Permeation time (penetration time) in minutes:  
 >= 480  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Page 6 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

**Skin protection - Other:**  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

**Respiratory protection:**  
 Normally not necessary.  
 With oil mist formation:  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

**Thermal hazards:**  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Flash point:	224 °C
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
pH-value:	Not determined
Viscosity:	33,1 mm <sup>2</sup> /s (40°C)
Viscosity:	6 mm <sup>2</sup> /s (100°C)
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Vapour pressure:	Not determined
Density:	0,855 g/ml
Vapour density (air = 1):	Not determined
Evaporation rate:	Not determined
Bulk density:	n.a.
Solubility(ies):	Not determined
Explosive properties:	Not determined
Oxidising properties:	Not determined

### 9.2 Other information

Miscibility:	Not determined
Conductivity:	Not determined
Fat solubility / solvent:	Not determined
Solvents content:	Not determined
Surface tension:	Not determined

## SECTION 10: Stability and reactivity

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Strong heat

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Top Tec MTF 5100 75W						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), solvent-dewaxed heavy paraffinic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion



Page 8 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse		Female, Negative
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion 78 weeks, dermal
Reproductive toxicity:				Rat		Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion dermal
Reproductive toxicity (Effects on fertility):				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion oral, dermal
Aspiration hazard:						Yes
Symptoms:						mucous membrane irritation, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	~1000	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	30	mg/kg/d	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,22	mg/l	Rat		Aerosol, Analogous conclusion 4 weeks
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,15	mg/l	Rat		Aerosol, Analogous conclusion 13 weeks

**C16-18-(even numbered, saturated and unsaturated)-alkylamines**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1689	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LD50	>0,099	ppmV/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion



Page 9 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity (Effects on fertility):	NOAEL	12,5	mg/kg	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract, STOT SE 3, H335
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3,25	mg/kg/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	Target organ(s): gastrointestinal tract, liver, immune system

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Top Tec MTF 5100 75W							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Distillates (petroleum), solvent-dewaxed heavy paraffinic							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>5000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	96h	>1000	mg/l	Scenedesmus subspicatus		

Page 10 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable (Analogous conclusion)
12.3. Bioaccumulative potential:	Log Pow		>3				Low
Toxicity to bacteria:	EC20	6h	>1000	mg/l	Pseudomonas fluorescens		

**C16-18-(even numbered, saturated and unsaturated)-alkylamines**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	0,06	mg/l	Pimephales promelas		EPA OPPTS 850.1085
12.1. Toxicity to daphnia:	EL50	48h	0,011	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,46	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	96h	0,04	mg/l	Selenastrum capricornutum		
12.2. Persistence and degradability:		28d	66	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
Toxicity to bacteria:	EL50	3h	32	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 Observe regulations for disposal of old oil/waste.  
 E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.  
 Empty container completely.  
 Untampered packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

Page 11 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

2, 3, 8, 11, 12, 15

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H302 Harmful if swallowed.

Page 12 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 14.10.2021 / 0006  
 Replacing version dated / version: 29.01.2020 / 0005  
 Valid from: 14.10.2021  
 PDF print date: 15.10.2021  
 Top Tec MTF 5100 75W

H304 May be fatal if swallowed and enters airways.  
 H314 Causes severe skin burns and eye damage.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Asp. Tox. — Aspiration hazard  
 Acute Tox. — Acute toxicity - oral  
 Skin Corr. — Skin corrosion  
 Eye Dam. — Serious eye damage  
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation  
 STOT RE — Specific target organ toxicity - repeated exposure  
 Aquatic Acute — Hazardous to the aquatic environment - acute

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods

Page 13 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 14.10.2021 / 0006  
Replacing version dated / version: 29.01.2020 / 0005  
Valid from: 14.10.2021  
PDF print date: 15.10.2021  
Top Tec MTF 5100 75W

incl. including, inclusive  
IUCLD International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log K<sub>oc</sub> Logarithm of adsorption coefficient of organic carbon in the soil  
Log K<sub>ow</sub>, Log P<sub>ow</sub> Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.