

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Frostschutz fuer Druckluftbremsen

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Anti-freeze

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.08.2022 / 0011

Replacing version dated / version: 04.01.2022 / 0010

Valid from: 29.08.2022

PDF print date: 27.09.2022

Frostschutz fuer Druckluftbremsen



Danger

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal plant.

Propan-2-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Propan-2-ol	
Registration number (REACH)	---
Index	603-117-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	200-661-7
CAS	67-63-0
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Morpholine	
Registration number (REACH)	Substance for which an EU exposure limit value applies.
Index	01-2119496057-30-XXXX
EINECS, ELINCS, NLP, REACH-IT List-No.	613-028-00-9
CAS	203-815-1
CAS	110-91-8
content %	1-<3

Page 3 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.08.2022 / 0011
Replacing version dated / version: 04.01.2022 / 0010
Valid from: 29.08.2022
PDF print date: 27.09.2022
Frostschutz fuer Druckluftbremsen

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors

Flam. Liq. 3, H226
Acute Tox. 3, H311
Acute Tox. 3, H331
Acute Tox. 4, H302
Skin Corr. 1A, H314
Eye Dam. 1, H318
Repr. 2, H361fd

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures**4.1 Description of first aid measures**

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

At high concentrations:

Irritation of the respiratory tract
Dizziness
Headaches
Coordination disorders
Effects/damages the central nervous system
Narcotic effect.

With long-term contact:

Drying of the skin.
Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Indications for the physician:

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Page 4 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.08.2022 / 0011
Replacing version dated / version: 04.01.2022 / 0010
Valid from: 29.08.2022
PDF print date: 27.09.2022
Frostschutz fuer Druckluftbremsen

Toxic gases
Danger of bursting (explosion) when heated
Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Take measures against electrostatic charging, if appropriate.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Observe special storage conditions.

GB

Page 5 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Do not store with flammable or self-igniting materials.
 Solvent resistant floor
 Do not store with oxidizing agents.
 Do not store with acids.
 Protect from direct sunlight and warming.
 Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Propan-2-ol		
WEL-TWA: 400 ppm (999 mg/m3)	WEL-STEL: 500 ppm (1250 mg/m3)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Alcohol 25/a i-Propanol (81 01 631) - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - DFG (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - NIOSH 1400 (ALCOHOLS I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - Draeger - Alcohol 100/a (CH 29 701) 		
BMGV: ---	Other information: ---		
Chemical Name	Morpholine		
WEL-TWA: 10 ppm (36 mg/m3) (WEL, EU)	WEL-STEL: 20 ppm (72 mg/m3) (WEL, EU)	---	
Monitoring procedures:	---		
BMGV: ---	Other information: Sk		

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg dw	
	Environment - sediment, marine		PNEC	552	mg/kg dw	
	Environment - soil		PNEC	28	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
	Environment - oral (animal feed)		PNEC	160	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	319	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	89	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	888	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	500	mg/m3	

Morpholine

Page 6 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,163	mg/l	
	Environment - marine		PNEC	0,0163	mg/l	
	Environment - sediment, freshwater		PNEC	1,83	mg/kg dw	
	Environment - sediment, marine		PNEC	0,183	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	0,45	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - soil		PNEC	0,269	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,84	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	36	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 With long-term contact:
 Protective gloves made of butyl (EN ISO 374).
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 > 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Page 7 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Clear
Colour:	Colourless
Odour:	Alcoholic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	<100 °C
Flammability:	Flammable
Lower explosion limit:	2 Vol-% (20°C)
Upper explosion limit:	There is no information available on this parameter.
Flash point:	12 °C
Auto-ignition temperature:	No
Decomposition temperature:	There is no information available on this parameter.
pH:	There is no information available on this parameter.
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Mixable
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,798 g/ml (15°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	No

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.
 The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.
 Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.
 No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7.
 Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.
 Avoid contact with strong oxidizing agents.
 Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.
 See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Frostschutz fuer Druckluftbremsen						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	12800-13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	> 25	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	46600	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative

Page 9 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	5000	ppm	Rat		Vapours (OECD 451)

Morpholine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1910	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	500	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	References
Acute toxicity, by inhalation:	LC50	8	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Corrosive, Skin Corr. 1A
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Corrosive, Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium		Negative

11.2. Information on other hazards

Frostschutz fuer Druckluftbremsen						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Page 10 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Possibly more information on environmental effects, see Section 2.1 (classification).

Frostschutz fuer Druckluftbremsen							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	BCF		3,2				Low
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Slight
12.4. Mobility in soil:	Koc		1,1				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Toxicity to bacteria:	EC10	16h	1050	mg/l	Pseudomonas putida		
Other organisms:	IC50	3d	2104	mg/l	Lactuca sativa		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

Page 11 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Morpholine							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:	BCF	42d	<2,8		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oryzias latipes	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	45	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	References
12.1. Toxicity to daphnia:	EC10	21d	8,134	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	64,6	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC20	30min	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:							No adsorption in soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Do not dispose of with household waste.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number or ID number:

2924

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ISOPROPYL ALCOHOL,MORPHOLINE)
 14.3. Transport hazard class(es): 3(8)
 14.4. Packing group: II
 Classification code: FC
 LQ: 1 L
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code: D/E



Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ISOPROPYL ALCOHOL,MORPHOLINE)
 14.3. Transport hazard class(es): 3(8)
 14.4. Packing group: II
 EmS: F-E, S-C
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:
 Flammable liquid, corrosive, n.o.s. (ISOPROPYL ALCOHOL,MORPHOLINE)
 14.3. Transport hazard class(es): 3(8)
 14.4. Packing group: II
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 100 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Page 13 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.08.2022 / 0011
 Replacing version dated / version: 04.01.2022 / 0010
 Valid from: 29.08.2022
 PDF print date: 27.09.2022
 Frostschutz fuer Druckluftbremsen

Revised sections: 8
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.
 H225 Highly flammable liquid and vapour.
 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
 H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H311 Toxic in contact with skin.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H336 May cause drowsiness or dizziness.

Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation
 Skin Irrit. — Skin irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Acute Tox. — Acute toxicity - dermal
 Acute Tox. — Acute toxicity - inhalation
 Acute Tox. — Acute toxicity - oral
 Skin Corr. — Skin corrosion
 Eye Dam. — Serious eye damage
 Repr. — Reproductive toxicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately

Art., Art. no.	Article number
ASTM	ASTM International (American Society for Testing and Materials)
ATE	Acute Toxicity Estimate
BAM	Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA	Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF	Bioconcentration factor
BSEF	The International Bromine Council
bw	body weight
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, Eblx (x = 10, 50)	Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC	European Community
ECHA	European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)	Effect Concentration/Level for x % effect
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ErCx, EµCx, Erlx (x = 10, 50)	Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc.	et cetera
EU	European Union
EVAL	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
Koc	Adsorption coefficient of organic carbon in the soil
Kow	octanol-water partition coefficient
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC (Code)	International Bulk Chemical (Code)
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
IUPAC	International Union for Pure Applied Chemistry
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc	Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow	Logarithm of octanol-water partition coefficient
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute for Occupational Safety and Health (USA)
NLP	No-longer-Polymer
NOEC, NOEL	No Observed Effect Concentration/Level
OECD	Organisation for Economic Co-operation and Development
org.	organic
OSHA	Occupational Safety and Health Administration (USA)
PBT	persistent, bioaccumulative and toxic
PE	Polyethylene
PNEC	Predicted No Effect Concentration
ppm	parts per million
PVC	Polyvinylchloride

Page 15 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.08.2022 / 0011
Replacing version dated / version: 04.01.2022 / 0010
Valid from: 29.08.2022
PDF print date: 27.09.2022
Frostschutz fuer Druckluftbremsen

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.