

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Marine Diesel Protect

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Biocide

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)
+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Acute Tox.	4	H302-Harmful if swallowed.
Eye Dam.	1	H318-Causes serious eye damage.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Repr.	2	H361d-Suspected of damaging the unborn child.
Aquatic Acute	1	H400-Very toxic to aquatic life.
Aquatic Chronic	1	H410-Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect



Danger

H332-Harmful if inhaled. H302-Harmful if swallowed. H318-Causes serious eye damage. H317-May cause an allergic skin reaction. H304-May be fatal if swallowed and enters airways. H361d-Suspected of damaging the unborn child. H410-Very toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P201-Obtain special instructions before use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.
 P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313-IF exposed or concerned: Get medical advice / attention. P331-Do NOT induce vomiting.
 P405-Store locked up.
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH044-Risk of explosion if heated under confinement.
 EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
 Methyl salicylate
 2-ethylhexyl nitrate
 1,2-benzisothiazol-3(2H)-one

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	---
content %	40-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

2-ethylhexyl nitrate	
Registration number (REACH)	01-2119539586-27-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	248-363-6
CAS	27247-96-7

Page 3 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

content %	25-<30
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH044 EUH066 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	ATE (oral): 500 mg/kg ATE (dermal): 1100 mg/kg ATE (as inhalation, Aerosol): 1,5 mg/l/4h ATE (as inhalation, Vapours): 11 mg/l/4h

Methyl salicylate	
Registration number (REACH)	01-2119515671-44-XXXX
Index	607-749-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	204-317-7
CAS	119-36-8
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 2, H361d Aquatic Chronic 3, H412
Specific Concentration Limits and ATE	ATE (oral): 890 mg/kg

Ethanediol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119456816-28-XXXX
Index	603-027-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-473-3
CAS	107-21-1
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 STOT RE 2, H373 (kidneys) (oral)
Specific Concentration Limits and ATE	ATE (oral): 1600 mg/kg

1,2-benzisothiazol-3(2H)-one	
Registration number (REACH)	01-2120761540-60-XXXX
Index	613-088-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	220-120-9
CAS	2634-33-5
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 2, H330 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: $\geq 0,036\%$ ATE (oral): 450 mg/kg ATE (as inhalation, Dusts or mist): 0,21 mg/l/4h ATE (as inhalation, Vapours): 0,5 mg/l/4h

2-Ethylhexanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119487289-20-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	203-234-3
CAS	104-76-7
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Page 4 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Specific Concentration Limits and ATE	ATE (as inhalation, Vapours): 11 mg/l/4h ATE (as inhalation, Dusts or mist): 2,7 mg/l/4h
--	---

Alcohols, C16-18 and C18-unsatd., ethoxylated	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	68920-66-1
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Aquatic Chronic 2, H411

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	265-157-1
CAS	64742-54-7
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.
 If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.
 Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."
 Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.
 Protect uninjured eye.
 Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting. Consult doctor immediately.
 Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Ingestion:

Nausea
 Vomiting
 Danger of aspiration.
 Oedema of the lungs

Page 5 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.08.2024 / 0015
Replacing version dated / version: 04.03.2024 / 0014
Valid from: 01.08.2024
PDF print date: 01.08.2024
Marine Diesel Protect

Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO₂/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

Danger of bursting (explosion) when heated

Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Resolve leaks if this possible without risk.

If leakage occurs, dam up.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

GB

Page 6 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Ensure good ventilation.
 Keep away from sources of ignition - Do not smoke.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.
 Pregnant women should avoid contact with this product.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Under all circumstances prevent penetration into the soil.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.
 Store in a dry place.

7.3 Specific end use(s)

No information available at present.
 Observe the instructions for good working practice and the recommendations for risk assessment.
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Chemical Name	Ethanediol		
WEL-TWA: 10 mg/m ³ (particulate), 52 mg/m ³ (vapour) (WEL-TWA), 20 ppm (52 mg/m ³) (EU)	WEL-STEL: 104 mg/m ³ (vapour) (WEL-STEL), 40 ppm (104 mg/m ³) (EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Ethylene Glycol 10 (5) (81 01 351) - Compur - KITA-232 SA (502 342) - Compur - KITA-232 SB (550 267) - NIOSH 5500 (ETHYLENE GLYCOL) - 1993 - NIOSH 5523 (GLYCOLS) - 1996 - OSHA PV2024 (Ethylene glycol) - 1999 - EU project BC/CEN/ENTR/000/2002-16 card - 11-2 (2004) 		
BMGV: ---	Other information: Sk (particulate, vapour)		

Chemical Name	2-Ethylhexanol		
WEL-TWA: 1 ppm (5,4 mg/m ³) (WEL-TWA, EU)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Alcohol 100/a (CH 29 701)		
BMGV: ---	Other information: ---		

Chemical Name	Oil mist, mineral		
WEL-TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---		

Page 7 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

2-ethylhexyl nitrate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,8	µg/l	
	Environment - marine		PNEC	0,08	µg/l	
	Environment - soil		PNEC	0,00019 1	mg/kg dw	
	Environment - sediment, freshwater		PNEC	0,00074	mg/kg dw	
	Environment - sediment, marine		PNEC	0,00074	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,52	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,087	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,025	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	0,022	mg/cm2	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,044	mg/cm2	

Methyl salicylate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	20	µg/l	
	Environment - marine		PNEC	2	µg/l	
	Environment - sewage treatment plant		PNEC	140	mg/l	
	Environment - soil		PNEC	0,35	mg/kg dw	
	Environment - sediment, freshwater		PNEC	0,52	mg/kg dw	
	Environment - sediment, marine		PNEC	0,052	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	4	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	213	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	3	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1	mg/kg bw/day	
Consumer	Human - oral	Short term, local effects	DNEL	5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	17,5	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	285	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	6	mg/kg bw/day	

Ethanediol

Page 8 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sediment		PNEC	20,9	mg/kg	
	Environment - soil		PNEC	1,53	mg/kg	
	Environment - sewage treatment plant		PNEC	199,5	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	37	mg/kg dry weight	
	Environment - sediment, marine		PNEC	3,7	mg/kg dry weight	
Consumer	Human - inhalation	Long term, local effects	DNEL	7	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	53	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	35	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	106	mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,00403	mg/l	
	Environment - marine		PNEC	0,000403	mg/l	
	Environment - sediment, freshwater		PNEC	0,0499	mg/kg dw	
	Environment - sediment, marine		PNEC	0,00499	mg/kg dw	
	Environment - soil		PNEC	3	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1,03	mg/l	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,966	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,81	mg/m ³	

2-Ethylhexanol

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - marine		PNEC	0,0017	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,17	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,284	mg/kg dw	
	Environment - sediment, marine		PNEC	0,028	mg/kg dw	
	Environment - soil		PNEC	0,047	mg/kg dw	
	Environment - oral (animal feed)		PNEC	55	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,1	mg/kg body weight/day	

Page 9 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Consumer	Human - inhalation	Short term, local effects	DNEL	53,2	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11,4	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,3	mg/m ³	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	26,6	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	12,8	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	23	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	53,2	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	53,2	mg/m ³	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	12,8	mg/m ³	

Distillates (petroleum), hydrotreated heavy paraffinic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m ³	

Ⓒ - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.

Page 10 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN ISO 374).
 If applicable
 Protective Neoprene® / polychloroprene gloves (EN ISO 374).
 Protective nitrile gloves (EN ISO 374).
 Protective gloves made of fluorocarbon rubber (EN ISO 374).
 Minimum layer thickness in mm:
 0,5
 Permeation time (penetration time) in minutes:
 > 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 Filter A P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	63 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<=20,5 mm ² /s (40°C)
Kinematic viscosity:	<7 mm ² /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.

Page 11 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Density and/or relative density: 0,905 g/cm³ (20°C)
 Relative vapour density: There is no information available on this parameter.
 Particle characteristics: Does not apply to liquids.

9.2 Other information

Explosives: Product is not explosive.
 Oxidising liquids: No

SECTION 10: Stability and reactivity

10.1 Reactivity

Risk of explosion if heated under confinement.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Marine Diesel Protect						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1402	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	11,32	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	3,07	mg/l/4h			calculated value, Aerosol, Mist
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4951	mg/m ³	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion

Page 12 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizing, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, mucous membrane irritation

2-ethylhexyl nitrate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	500	mg/kg			
Acute toxicity, by dermal route:	ATE	1100	mg/kg			
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	20	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, oral

Page 13 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	500	mg/kg bw/d	Rabbit		Negative dermal
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	863	mg/m ³	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours, Analogous conclusion(90 d)
Symptoms:						headaches, dizziness, nausea, drop in blood pressure, diarrhoea, unconsciousness, eyes, reddened

Methyl salicylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	890	mg/kg			
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 491 (Short-time Exposure ... Chemicals Causing Eye Dam., Chem. Not Requir. Eye Dam. or Irrit.)	Eye Dam. 1
Symptoms:						acidosis, respiratory distress, annoyance, blisters, heart/circulatory disorders, coughing, cramps, stomach pain, intoxication, mucous membrane irritation, pain in chest, sweats, dizziness, visual disturbances, nausea and vomiting.

Ethanediol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1600	mg/kg	Human being		
Acute toxicity, by oral route:	ATE	1600	mg/kg			
Acute toxicity, by dermal route:	LD50	9530	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>2,5	mg/l/6h	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Human being	(Patch-Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	in vivo	Negative
Carcinogenicity:	NOAEL	1500	mg/kg	Mouse		Male, Negative oral, 2 a
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat		Negative

Page 14 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Reproductive toxicity (Developmental toxicity):	NOAEL	250	mg/kg bw/d	Rat		Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	150	mg/kg bw/d		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	STOT RE 2, Target organ(s): kidneys
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	150	mg/kg bw/d	Rat	OECD 452 (Chronic Toxicity Studies)	STOT RE 2, Target organ(s): kidneys
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>2200 - <4400	mg/kg bw/d	Dog		Negative
Symptoms:						ataxia, breathing difficulties, unconsciousness, cramps, fatigue

1,2-benzisothiazol-3(2H)-one

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1020	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	450	mg/kg			
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	0,4	mg/l/4h	Rat		Aerosol
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	0,21	mg/l/4h		OECD 403 (Acute Inhalation Toxicity)	Dusts or mist
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Sensitising (skin contact)

2-Ethylhexanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	2,7	mg/l/4h			Aerosol
Acute toxicity, by inhalation:	LC50	>0,89-5,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	2,7	mg/l/4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact) literature
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative Chinese hamster
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:	NOAEL	750	mg/kg bw/d	Mouse	OECD 451 (Carcinogenicity Studies)	Negative, oral
Reproductive toxicity:	NOAEL	3000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, oral
Reproductive toxicity (Developmental toxicity):				Mouse	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, oral

Page 15 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	200	mg/kg bw/d	Mouse		
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,6384	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours
Symptoms:						unconsciousness, drop in blood pressure, vomiting, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea

Alcohols, C16-18 and C18-unsatd., ethoxylated

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Rat	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion

Page 16 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative Chinese hamster
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion 78 weeks, dermal
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion oral
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion dermal
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	<30	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	~1000	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOEC	~220	mg/m3	Rat	OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	Analogous conclusion, Aerosol
Symptoms:						coughing, respiratory distress, nausea and vomiting, diarrhoea

11.2. Information on other hazards

Marine Diesel Protect						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Page 17 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:						Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Marine Diesel Protect							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree (complexing organic substance) \geq 80%/28d: No

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		10-2500				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Page 18 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		
Water solubility:							Product floats on the water surface.

2-ethylhexyl nitrate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,83	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>2,53	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:	DOC	28d	0	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,24			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	High
12.3. Bioaccumulative potential:	BCF		1332				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Methyl salicylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	19,8	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	870	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	28	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	27	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,79	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	

Page 19 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

12.2. Persistence and degradability:	DOC	28d	98,4	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,5				
12.4. Mobility in soil:	Log Koc		2,346				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	16h	380	mg/l	Pseudomonas putida		

Ethanediol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales promelas	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to fish:	NOEC/NOEL	7d	15380	mg/l	Pimephales promelas	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	NOEC/NOEL		8590	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	NOEC/NOEL	7d	8590	mg/l	Ceriodaphnia spec.	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	EC50	96h	6500-13000	mg/l	Pseudokirchneriella subcapitata	U.S. EPA ECOTOX Database	
12.2. Persistence and degradability:		10d	90-100	%	activated sludge	OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	56	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.3. Bioaccumulative potential:	Log Pow		-1,36				Not to be expected
12.4. Mobility in soil:	Log Koc		0-1				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	16h	>10000	mg/l	Pseudomonas putida	IUCLID Chem. Data Sheet (ESIS)	
Toxicity to bacteria:	EC20	30min	>1995	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other information:	BOD5		0,78	g/g			IUCLID

1,2-benzisothiazol-3(2H)-one							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2,18	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	2,94	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 20 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

12.1. Toxicity to algae:	ErC50	24h	0,1087	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	ErC10	24h	0,0268	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:					activated sludge	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		6,95			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
Toxicity to bacteria:	EC50	3h	13	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

2-Ethylhexanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	17,1	mg/l	Leuciscus idus	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to fish:	LC50	96h	28,2	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	39	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	EC50	72h	16,6	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	5,3	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:	COD	14d	100	%	activated sludge	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,9			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	Low
12.3. Bioaccumulative potential:	BCF		25,33				calculated value, Low

Page 21 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

12.4. Mobility in soil:							Not to be expected
12.4. Mobility in soil:	Koc		800				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	24h	>300	mg/l	activated sludge		
Toxicity to bacteria:	EC50	3h	540	mg/l	Pseudomonas putida		
Toxicity to bacteria:	EC50	12h	> 100	mg/l	activated sludge		

Alcohols, C16-18 and C18-unsatd., ethoxylated							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	108	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	51	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	>60	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable

Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EL50	21d	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EL50	48h	10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	LL50	72h	>100	mg/l			
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

Page 22 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be
 allocated under certain circumstances. (2014/955/EU)

13 07 03 other fuels (including mixtures)

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.



Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.



SECTION 14: Transport information

General statements



Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	3082	
14.2. UN proper shipping name:		
	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)	
14.3. Transport hazard class(es):	9	 
14.4. Packing group:	III	
14.5. Environmental hazards:	environmentally hazardous	
Tunnel restriction code:	-	
Classification code:	M6	
LQ:	5 L	
Transport category:	3	

Transport by sea (IMDG-code)

14.1. UN number or ID number:	3082	
14.2. UN proper shipping name:		
	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ETHYLHEXYL NITRATE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)	
14.3. Transport hazard class(es):	9	 
14.4. Packing group:	III	
14.5. Environmental hazards:	environmentally hazardous	
Marine Pollutant:	Yes	
EmS:	F-A, S-F	

Transport by air (IATA)

14.1. UN number or ID number:	3082	
14.2. UN proper shipping name:		
	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (2-ETHYLHEXYL NITRATE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)	
14.3. Transport hazard class(es):	9	 
14.4. Packing group:	III	
14.5. Environmental hazards:	environmentally hazardous	

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Page 23 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E1		100	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 83,82 %

Observe Regulation (EU) No 528/2012 concerning the placing of biocidal products on the market.

Additional data acc. to Art. 69 (2), Regulation (EU) No 528/2012 (Biocide products):

The identity of every active substance and its concentration in metric units:

1,2-benzisothiazol-3(2H)-one

3,2 g/100 g

The uses:

Preservation

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 3, 11, 12

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Acute Tox. 4, H302	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Repr. 2, H361d	Classification according to calculation procedure.
Aquatic Acute 1, H400	Classification according to calculation procedure.
Aquatic Chronic 1, H410	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H330 Fatal if inhaled.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Page 24 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

H317 May cause an allergic skin reaction.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH044 Risk of explosion if heated under confinement.

Acute Tox. — Acute toxicity - inhalation
 Acute Tox. — Acute toxicity - oral
 Eye Dam. — Serious eye damage
 Skin Sens. — Skin sensitization
 Asp. Tox. — Aspiration hazard
 Repr. — Reproductive toxicity
 Aquatic Acute — Hazardous to the aquatic environment - acute
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Acute Tox. — Acute toxicity - dermal
 STOT RE — Specific target organ toxicity - repeated exposure
 Skin Irrit. — Skin irritation
 Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level

Page 25 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.08.2024 / 0015
 Replacing version dated / version: 04.03.2024 / 0014
 Valid from: 01.08.2024
 PDF print date: 01.08.2024
 Marine Diesel Protect

DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 mg/kg bw mg/kg body weight
 mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
 mg/kg dw mg/kg dry weight
 mg/kg wwt mg/kg wet weight
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 TOC Total organic carbon

Page 26 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.08.2024 / 0015
Replacing version dated / version: 04.03.2024 / 0014
Valid from: 01.08.2024
PDF print date: 01.08.2024
Marine Diesel Protect

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.