

Page 1 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Diesel Russ-Stop Diesel Smoke Stop

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Asp. Tox. 1 H304-May be fatal if swallowed and enters airways.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Danger

H304-May be fatal if swallowed and enters airways.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox 1 H304

2-ethylhexanoic acid, iron salt	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	243-169-8
CAS	19583-54-1
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315

2-ethylhexanoic acid	
Registration number (REACH)	
Index	607-230-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	205-743-6
CAS	149-57-5
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Repr. 2, H361d

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here. Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."



Page 3 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Headaches

Dizziness

Nausea

With long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Danger of aspiration.

Lung damage

Oedema of the lungs

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO₂

Dry extinguisher

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.



Œ

Page 4 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Solvent resistant floor

Store in a well ventilated place.

Protect from direct sunlight and warming.

Suitable container:

Steel

Stainless steel (alloy steel)

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection



③B)·

Page 5 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons	s, C10-C13, n-alkanes, isoalka	Content %:80- <100				
WEL-TWA: 800 mg/m3		WEL-STEL:					
Monitoring procedures:		 Draeger - Hydrocarbons (0,1%/c (81 03 571)				
	- Draeger - Hydrocarbons 2/a (81 03 581)						
		- Compur - KITA-187 S (55	i1 174)				
BMGV:			Other information: (O	EL acc. 1	to RCP-method,		
			paragraphs 84-87, EH	10)			
Chemical Name	Iron salts				Content %:		
M/EL TM/A: 1 mg/m2 (iron colto	(ac Ea))	WELSTEL: 2 mg/m2	(iron colta (oc Eo))				

Chemical Name	Iron salts	Content %:
WEL-TWA: 1 mg/m3 (iron salts (as	Fe)) WEL-STEL: 2 mg/m3 (iron salts (as Fe))	
Monitoring procedures:		
BMGV:	Other information:	

2-ethylhexanoic acid	Evenesius varita /	Effect on bealth	Descriptor	Value	I I m !4	Nata
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - marine		PNEC	0,0017	mg/l	
	Environment - sediment, freshwater		PNEC	0,28	mg/kg dw	
	Environment - sediment, marine		PNEC	0,028	mg/kg dw	
	Environment - soil		PNEC	0,047	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	3,5	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	14	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

^{(8) =} Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

^{(13) =} The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).



Page 6 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacture.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Liquia

Colour:

Darkish, Brown Characteristic

Odour: Melting point/freezing point:

There is no information available on this parameter.



Page 7 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

pH: Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

Explosives: Oxidising liquids: Bulk density:

There is no information available on this parameter.

Flammable

There is no information available on this parameter. There is no information available on this parameter.

>63 °C

There is no information available on this parameter. There is no information available on this parameter.

Mixture is non-soluble (in water).

<7 mm2/s (40°C)

Insoluble

Does not apply to mixtures.

There is no information available on this parameter.

0,7937 g/ml (15°C)

There is no information available on this parameter.

Does not apply to liquids.

Product is not explosive.

n.a.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Open flame, ignition sources

Protect from humidity.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.



Page 8 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Hydrocarbons, C10-C13, n-alka				ı		
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
<i>,,</i> ,					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous
riodic toxiony, by initialation.	2000	74001	1119/1110/-111	rtat	Inhalation Toxicity)	conclusion,
					initial autori Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant.
Skin corrosion/irritation.						
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin					OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	Analogous
					,	conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
, , , , , , , , , , , , , , , , , , ,					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	Corroradion
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
Germ cen matagemony.					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Composition and initial				Salmonella		
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	NI d
Carcinogenicity:					OECD 453 (Combined	Negative,
					Chronic	Analogous
					Toxicity/Carcinogenicity	conclusion
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative,
					Developmental Toxicity	Analogous
					Study)	conclusion
Specific target organ toxicity -					OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):					Dose 90-Day Oral	Analogous
					Toxicity Study in	conclusion
					Rodents)	
Aspiration hazard:					1.0000,	Yes
Symptoms:						unconsciousnes
Cymptomo.						, headaches,
						dizziness,
						mucous
						membrane
						irritation

2-ethylhexanoic acid							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	2043	mg/kg	Rat	OECD 401 (Acute Oral		
					Toxicity)		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute		
					Dermal Toxicity)		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant	
					Dermal		
					Irritation/Corrosion)		
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant	
					Irritation/Corrosion)		
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)	
sensitisation:					Sensitisation)		
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative	
					Reverse Mutation Test)		



Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Germ cell mutagenicity:				OECD 473 (In Vitro	Negative
				Mammalian	
				Chromosome	
				Aberration Test)	
Germ cell mutagenicity:				OECD 474 (Mammalian	Negative
				Erythrocyte	
				Micronucleus Test)	
Germ cell mutagenicity:				OECD 476 (In Vitro	Negative
,				Mammalian Cell Gene	
				Mutation Test)	
Reproductive toxicity	600	mg/kg	Rat		Repr. 2oral
(Developmental toxicity):					
Reproductive toxicity (Effects					Possible
on fertility):					
Specific target organ toxicity -					Negative
single exposure (STOT-SE):					
Specific target organ toxicity -					Negative
repeated exposure (STOT-RE):					
Symptoms:					acidosis,
					respiratory
					distress,
					vomiting,
					coughing,
					headaches

11.2. Information on other hazards

Diesel Russ-Stop Diesel Smoke Stop						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Other information:						Repeated	
						exposure may	
						cause skin	
						dryness or	
						cracking.	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Diesel Russ-Stop							
Diesel Smoke Stop							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Mechanical
degradability:							precipitation
							possible.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.



Page 10 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

12.5. Results of PBT and vPvB assessment	n.d.a.
12.6. Endocrine disrupting properties:	Does not apply to mixtures.
12.7. Other adverse effects:	No information available on other adverse effects on the environment.
Other information:	According to the recipe, contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT	-						No PBT
and vPvB assessment							substance, No vPvB substance
Water solubility:							Product floats or the water surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen pyriformis		

2-ethylhexanoic acid Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	Time	25	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oryzias latipes	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	85,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	49,3- 60,5	mg/l	Scenedesmus subspicatus	DIN 38412 T.9	
12.2. Persistence and degradability:		28d	90-100	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable



Page 11 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

12.3. Bioaccumulative potential:	Log Pow		2,7				Low
Toxicity to bacteria:	EC50	17h	112,1	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	COD		2240	mg/kg			
Other information:	BOD		1200	mg/kg			
Other information:	Koc		140,87			OECD 106 (Adsorption/Desor ption Using a Batch Equilibrium Method)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

n.a

General statements

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): 14.4. Packing group: n.a. Classification code: n.a. LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name: 14.3. Transport hazard class(es): n.a. 14.4. Packing group:

Marine Pollutant: 14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments



Page 12 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1-16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Asp. Tox. 1, H304	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361d Suspected of damaging the unborn child.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard Skin Irrit. — Skin irritation Repr. — Reproductive toxicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number



Page 13 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

ncl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride



Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021 PDF print date: 01.11.2021 Diesel Russ-Stop Diesel Smoke Stop

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Telephone Tel.

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.