

ദ

Page 1 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Special Tec AA 5W-40 Diesel

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.10.2021 $\,$ / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	276-738-4
CAS	72623-87-1
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	265-157-1
CAS	64742-54-7
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

1-decene, trimers, hydrogenated	
Registration number (REACH)	01-2119493949-12-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	500-393-3
CAS	157707-86-3
content %	1-10
Classification according to Regulation (FC) 1272/2008 (CLP). M-factors	Asp. Tox. 1. H304

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP, REACH-IT List-No.	265-158-7
CAS	64742-55-8
content %	0,5-5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP, REACH-	Registration number (REACH)	EACH) Chemical name					
IT List-No.							
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic					
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic					
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic					
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic					

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures



Œ

Page 3 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004
Replacing version dated / version: 27.05.2020

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

reddening of the skin

Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Foam

Dry extinguisher

Water mist

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.



Page 4 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:	
working fluids, ACGIH)		
Monitoring procedures: - I	Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based							
Area of application	Area of application Exposure route / Effect on health Descriptor Value Unit Note						
	Environmental						
	compartment						
	Human - oral		PNEC	9,33	mg/kg feed		
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h	



Page 5 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Distillates (petroleum), hydrotreated heavy paraffinic							
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note	
	Environmental						
	compartment						
	Environment - oral (animal		PNEC	9,33	mg/kg feed		
	feed)						
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3		
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3		

Baseoil - unspecified						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	9,33	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,6	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	

Area of application	ydrotreated light paraffinic Exposure route /	Effect on health	Descriptor	Value	Unit	Note
• •	Environmental		•			
	compartment					
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	

Distillates (petroleum), hydrotreated heavy paraffinic								
Area of application	Exposure route /	Exposure route / Effect on health Descriptor Value Unit Note						
	Environmental							
	compartment							
	Environment - oral (animal		PNEC	9,33	mg/kg feed			
	feed)							

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

^{(8) =} Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

^{(13) =} The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).



Page 6 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004 Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Protective gloves, oil resistant (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Protective gloves made of polyvinyl alcohol (EN ISO 374).

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0,5

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties



Page 7 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

Physical state:

Colour:

Odour:

Odour threshold:

Melting point/freezing point:

Liquid

Brown

Characteristic

Not determined

Not determined

Melting point/freezing point:

Initial boiling point and boiling range:

Not determined

Not determined

Not determined

n.a.

Flammability (solid, gas): n.a.
Lower explosive limit: Not determined

Upper explosive limit:

Flash point:

Auto-ignition temperature:

Decomposition temperature:

Devomposition temperature:

Not determined

Not determined

Not determined

Not determined

pH-value:
Viscosity:
V

Partition coefficient (n-octanol/water):

Vapour pressure:

Density:

Vapour density (air = 1):

Evaporation rate:

Not determined

Not determined

Not determined

Not determined

Bulk density: n.a.

Solubility(ies): Not determined

Explosive properties: Product is not explosive.

Oxidising properties:

9.2 Other information

Miscibility:

Conductivity:

Not determined

Fat solubility / solvent:

Not determined

Not determined

Not determined

Solvents content:

Not determined

Surface tension:

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Strong heat

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Special Tec AA 5W-40 Diesel						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.



Page 8 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
riodic texicity, by crail route.	LDOO	20000	mg/kg	- rui	Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
Acute toxicity, by definal route.	LD30	>3000	mg/kg	Rabbit	Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	
Acute toxicity, by illinatation.	LC30	>5,55	1119/1/411	Nat	Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
Skiri corrosion/irritation.				Kabbit	Dermal	
					Irritation/Corrosion)	Repeated exposure may
					imation/Corrosion)	cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
Serious eye damage/imiation.				Kabbit		Not imiant
Daniertani analda				0	Irritation/Corrosion)	NI= (=lala====+)
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	NI d
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Carcinogenicity:					OECD 451	Negative
					(Carcinogenicity Studies)	
Carcinogenicity:					OECD 453 (Combined	Negative
					Chronic	
					Toxicity/Carcinogenicity	
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative
					Developmental Toxicity	_
					Study)	
Reproductive toxicity:					OECD 421	Negative
					(Reproduction/Developm	•
					ental Toxicity Screening	
					Test)	
Specific target organ toxicity -					OECD 408 (Repeated	Negative
repeated exposure (STOT-RE):					Dose 90-Day Oral	5
, (2.2.7.2).					Toxicity Study in	
					Rodents)	
Specific target organ toxicity -		1			OECD 410 (Repeated	Negative
repeated exposure (STOT-RE):					Dose Dermal Toxicity -	1 10 galivo
ropodito oxpoduro (OTOT INE).					90-Day)	



Page 9 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Specific target organ toxicity -		OECD 411 (Subchronic	Negative
repeated exposure (STOT-RE):		Dermal Toxicity - 90-day	
		Study)	
Specific target organ toxicity -		OECD 412 (Subacute	Negative
repeated exposure (STOT-RE):		Inhalation Toxicity - 28-	
		Day Study)	
Aspiration hazard:			Asp. Tox. 1

Distillates (petroleum), hydrotr Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
Acute toxicity, by oral route.	LDSO	20000	mg/kg	Ital	Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
Acute toxicity, by definal route.	LD30	>2000	IIIg/kg	Rabbit	Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol,
Acute toxicity, by irinalation.	LCSU	>5,55	1119/1/411	Kal	Inhalation Toxicity)	,
					innaiation roxicity)	Analogous
Older and a final to the con-				D-b-i4	OFOD 404 (A suits	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
0				D-b-b-it	Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	NegativeChinese
					Mammalian	hamster
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
					,	conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative,
,					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro	Negative,
,-					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Carcinogenicity:				Mouse	OECD 451	Negative,
Caroniogornony.				Modoo	(Carcinogenicity Studies)	Analogous
					(Caroniagornally Cladico)	conclusion78
						weeks, dermal
Reproductive toxicity:				Rat	OECD 421	Negative,
reproductive toxicity.				Ital	(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusionoral
					Test)	Conclusionoral
Reproductive toxicity	1			Rat	OECD 414 (Prenatal	Negative,
(Developmental toxicity):				ı ı ı ı	Developmental Toxicity	Analogous
(Dovelopinemai toxicity).					Study)	conclusionderma
Symptoms:	-				Jiduy)	coughing,
Symptoms.						
						respiratory
						distress, nausea
						and vomiting.,
0	1045	405	n	D-4	0500 400 (5	diarrhoea
Specific target organ toxicity -	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose 90-Day Oral	conclusion
oral:					Toxicity Study in	
					Rodents)	
Specific target organ toxicity -	NOAEL	30	mg/kg	Rat	OECD 411 (Subchronic	Analogous
repeated exposure (STOT-RE),					Dermal Toxicity - 90-day	conclusion
dermal:				1	Study)	



Page 10 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Specific target organ toxicity -	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose Dermal Toxicity -	conclusion
inhalat.:					90-Day)	

1-decene, trimers, hydrogenate	ed					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising

Baseoil - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin						Not sensitizising,
sensitisation:						Analogous
						conclusion
Aspiration hazard:						Yes
Symptoms:						mucous
						membrane
						irritation

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol,
					Inhalation Toxicity)	Analogous
						conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
, ,					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
					,	Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian `	Analogous
					Chromosome	conclusionChines
					Aberration Test)	e hamster
Carcinogenicity:				Mouse	OECD 451	Negative,
					(Carcinogenicity Studies)	Analogous
						conclusiondermal
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 421	Analogous
-			bw/d		(Reproduction/Developm	conclusiondermal
					ental Toxicity Screening	
					Test)	



Page 11 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative,
(Developmental toxicity):					Developmental Toxicity	Analogous
					Study)	conclusion
Aspiration hazard:						Yes
Specific target organ toxicity -	NOAEL	125	mg/kg	Rat	OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	conclusion
oral:					Toxicity Study in	
					Rodents)	
Specific target organ toxicity -	NOAEL	<30	mg/kg	Rat	OECD 411 (Subchronic	Analogous
repeated exposure (STOT-RE),			bw/d		Dermal Toxicity - 90-day	conclusion
dermal:					Study)	
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose Dermal Toxicity -	conclusion
dermal:					90-Day)	
Specific target organ toxicity -	NOAEL	0,05	mg/l	Rat	OECD 412 (Subacute	Aerosol,
repeated exposure (STOT-RE),					Inhalation Toxicity - 28-	Analogous
inhalat.:					Day Study)	conclusion
Specific target organ toxicity -	NOAEL	0,15	mg/l	Rat		Aerosol,
repeated exposure (STOT-RE),						Analogous
inhalat.:						conclusion13
						weeks

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Special Tec AA 5W-40 D	iesel						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>=100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	



Page 12 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

12.2. Persistence and degradability:		28d	46	%	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Kow		>6		1 555,	A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment						No PBT substance, No vPvB substance
Toxicity to bacteria:	NOEC/NOEL	10min	>1,93	mg/l	DIN 38412 T.8	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	LL50	96h	>10000	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	,	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.5. Results of PBT and vPvB assessment						, , , , , , , ,	No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	125	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Mysidopsis bahia	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Selenastrum	OECD 201 (Alga,	
					capricornutum	Growth Inhibition	
						Test)	



Page 13 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

12.2. Persistence and degradability:						Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		>10			
12.5. Results of PBT and vPvB assessment						No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	1000	mg/l	activated sludge	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

Distillates (petroleum), h				T			
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.3. Bioaccumulative potential:							Not to be expected
12.1. Toxicity to daphnia:	EL50	48h	> 10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OEĆD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>6			, , ,	@20°C
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods



Page 14 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Observe regulations for disposal of old oil/waste.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name: 14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Classification code: n.a. IO. n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information



Œ

Page 15 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

Revised sections:

2, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

Effect Concentration/Level for x % effect

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances
EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods



Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 14.10.2021 / 0004

Replacing version dated / version: 27.05.2020 / 0003

Valid from: 14.10.2021 PDF print date: 14.10.2021 Special Tec AA 5W-40 Diesel

including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

Limited Quantities LQ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable not available n.av. n.c. not checked n.d.a. no data available NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

Polyethylene ΡF

PNEC Predicted No Effect Concentration

parts per million ppm PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

Volatile organic compounds VOC

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.