

Page 1 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Special Tec AA 5W-40 Diesel

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances



Page 2 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

n.a. 3.2 Mixtures

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	276-738-4
CAS	72623-87-1
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	265-157-1
CAS	64742-54-7
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

1-decene, trimers, hydrogenated	
Registration number (REACH)	01-2119493949-12-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	500-393-3
CAS	157707-86-3
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP, REACH-	Registration number (REACH)	Chemical name
IT List-No.		
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.



(B)

Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007 Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals: reddening of the skin Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2 Foam

Dry extinguisher

Water mist

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.



Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

© Chemical Name Oil mist, mineral		
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:	
working fluids, ACGIH)		
Monitoring procedures: -	Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based									
Area of application	Exposure route / Effect on health Descriptor Value Unit Note								
	Environmental								
	compartment								
	Human - oral		PNEC	9,33	mg/kg feed				
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h			

Distillates (petroleum), hydrotreated heavy paraffinic								
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note		
	Environmental							
	compartment							
	Environment - oral (animal		PNEC	9,33	mg/kg feed			
	feed)							
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3			



(B)

Page 5 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Baseoil - unspecified								
Area of application	Exposure route / Environmental compartment	Environmental Environmental		Value	Unit	Note		
	Environment - oral (animal feed)		PNEC	9,33	mg/kg			
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3			
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3			

Distillates (petroleum), hydrotreated heavy paraffinic									
Area of application	Exposure route /	Exposure route / Effect on health Descriptor Value Unit Note							
	Environmental								
	compartment								
	Environment - oral (animal		PNEC	9,33	mg/kg feed				
	feed)								

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Protective gloves, oil resistant (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Protective gloves made of polyvinyl alcohol (EN ISO 374).

Protective Viton® / fluoroelastomer gloves (EN ISO 374).



Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Minimum layer thickness in mm:

>=0.5

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Brown Odour:

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: There is no information available on this parameter.

Flammability: Flammable

Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: 220 °C

Auto-ignition temperature: There is no information available on this parameter. Decomposition temperature: There is no information available on this parameter.

Mixture is non-soluble (in water).

86 mm2/s (40°C) 14,5 mm2/s (100°C)

Insoluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 0,855 g/ml

Relative vapour density: There is no information available on this parameter.

Particle characteristics: Does not apply to liquids.

9.2 Other information

Explosives: Product is not explosive.

Oxidising liquids:

SECTION 10: Stability and reactivity

10.1 Reactivity

Kinematic viscosity:

Kinematic viscosity:

Solubility:



Page 7 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

The product has not been tested. **10.2 Chemical stability**

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Strong heat

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Special Tec AA 5W-40 Diesel						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion Chinese hamster



(B)

Page 8 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Germ cell mutagenicity:	Mouse	OECD 476 (In Vitro	Negative,
Certif Cell Hidlagerilony.	Wiodoc	Mammalian Cell Gene	Analogous
		Mutation Test)	conclusion
Germ cell mutagenicity:	Mouse	OECD 474 (Mammalian	Negative,
defin centricitagementy.	Wiodae	Erythrocyte	Analogous
		Micronucleus Test)	conclusion
Carcinogenicity:		OECD 453 (Combined	Negative
Carcinogenicity.		Chronic	Negative
		Toxicity/Carcinogenicity	
		Studies)	
Carcinogenicity:	Mouse	OECD 451	Negative,
Carcinogenicity.	Mouse	(Carcinogenicity Studies)	Analogous
		(Carcinogenicity Studies)	conclusion
Reproductive toxicity:		OECD 414 (Prenatal	Negative
Reproductive toxicity.		Developmental Toxicity	ivegative
		Study)	
Deproductive toxicity		OECD 421	Monotivo
Reproductive toxicity:		(Reproduction/Developm	Negative
		` '	
		ental Toxicity Screening Test)	
Denne dustine terripitus	Det	OECD 421	Nagativa
Reproductive toxicity:	Rat		Negative,
		(Reproduction/Developm	Analogous
		ental Toxicity Screening	conclusion
On a siffic to annot a name to visite		Test) OECD 453 (Combined	NI
Specific target organ toxicity -			Negative
repeated exposure (STOT-RE):		Chronic	
		Toxicity/Carcinogenicity	
0 15 4 4 1 1 1		Studies)	NI C
Specific target organ toxicity -		OECD 408 (Repeated	Negative
repeated exposure (STOT-RE):		Dose 90-Day Oral	
		Toxicity Study in	
0 15 4 4 1 1 1		Rodents)	NI e
Specific target organ toxicity -		OECD 410 (Repeated	Negative
repeated exposure (STOT-RE):		Dose Dermal Toxicity -	
0 17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		90-Day)	
Specific target organ toxicity -		OECD 411 (Subchronic	Negative
repeated exposure (STOT-RE):		Dermal Toxicity - 90-day	
0 7 1		Study)	NI C
Specific target organ toxicity -		OECD 412 (Subacute	Negative
repeated exposure (STOT-RE):		Inhalation Toxicity - 28-	
		Day Study)	
Aspiration hazard:			Asp. Tox. 1

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol,
					Inhalation Toxicity)	Analogous
						conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion



Page 9 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Germ cell mutagenicity:					OECD 473 (In Vitro	NegativeChinese
					Mammalian	hamster
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative,
					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro	Negative,
					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Carcinogenicity:				Mouse	OECD 451	Negative,
					(Carcinogenicity Studies)	Analogous
						conclusion78
						weeks, dermal
Reproductive toxicity:				Rat	OECD 421	Negative,
					(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusionoral
					Test)	
Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative,
(Developmental toxicity):					Developmental Toxicity	Analogous
, , , , , , , , , , , , , , , , , , , ,					Study)	conclusiondermal
Specific target organ toxicity -	NOAEL	~1000	mg/kg	Rabbit	OECD 410 (Repeated	Analogous
repeated exposure (STOT-RE),			bw/d		Dose Dermal Toxicity -	conclusion
dermal:					90-Day)	
Specific target organ toxicity -	NOAEL	<30	mg/kg	Rat	OECD 411 (Subchronic	Analogous
repeated exposure (STOT-RE),					Dermal Toxicity - 90-day	conclusion
dermal:					Study)	
Specific target organ toxicity -	NOEC	~220	mg/m3	Rat	OECD 412 (Subacute	Analogous
repeated exposure (STOT-RE),					Inhalation Toxicity - 28-	conclusion,
inhalat.:					Day Study)	Aerosol
Symptoms:						coughing,
•						respiratory
						distress, nausea
						and vomiting.,
						diarrhoea
Specific target organ toxicity -	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose 90-Day Oral	conclusion
oral:					Toxicity Study in	
					Rodents)	

1-decene, trimers, hydrogenate	ed					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,2	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Aspiration hazard:						Asp. Tox. 1

Baseoil - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 10 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Respiratory or skin			Not sensitizising,
sensitisation:			Analogous
			conclusion
Aspiration hazard:			Yes
Symptoms:			mucous
			membrane
			irritation

11.2. Information on other hazards

Special Tec AA 5W-40 Diesel	Special Tec AA 5W-40 Diesel								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Endocrine disrupting properties:						Does not apply			
						to mixtures.			
Other information:						No other			
						relevant			
						information			
						available on			
						adverse effects			
						on health.			

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Special Tec AA 5W-40 Di	iesel						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
1							other adverse
1							effects on the
							environment.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
Toxicity to bacteria:	NOEC/NOEL	10min	> 1,93	mg/l	activated sludge		DIN 38412		
12.1. Toxicity to fish:	NOEC/NOEL	96h	>=100	mg/l	Pimephales	OECD 203 (Fish,			
					promelas	Acute Toxicity			
						Test)			
12.1. Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales	OECD 203 (Fish,			
					promelas	Acute Toxicity			
						Test)			
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202			
						(Daphnia sp.			
						Acute			
						Immobilisation			
						Test)			
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211			
						(Daphnia magna			
						Reproduction Test)			



Page 11 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and						OECD 301 B	Not readily
degradability:						(Ready	biodegradable
,						Biodegradability -	
						Co2 Evolution	
						Test)	
12.2. Persistence and		28d	46	%		OECD 301 B	
degradability:						(Ready	
1 29 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2						Biodegradability -	
						Co2 Evolution	
						Test)	
12.3. Bioaccumulative	Log Kow		>6			,	A notable
potential:							biological
'							accumulation
							potential has to
							be expected
							(LogPow > 3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Distillates (petroleum), h	ydrotreated hea	vy paraffi	nic				
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	LL50	96h	>10000	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

1-decene, trimers, hydrogenated								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)		



Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

12.1. Toxicity to daphnia:	NOELR	21d	125	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Mysidopsis bahia	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Selenastrum	OECD 201 (Alga,	
					capricornutum	Growth Inhibition	
						Test)	
12.2. Persistence and							Not readily
degradability:							biodegradable
12.3. Bioaccumulative	Log Pow		>10				
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	EC50	3h	1000	mg/l	activated sludge		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Observe regulations for disposal of old oil/waste.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number:

Not applicable

Transport by road/by rail (ADR/RID)



Page 13 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:
Classification code:
LQ:
Not applicable
LQ:
Not applicable
14.5. Environmental hazards:
Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group: Not applicable

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: Not applicable14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 3, 8, 11, 12

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.



®

Page 14 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, $E\mu Cx$, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)



Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.10.2022 / 0007

Replacing version dated / version: 29.03.2022 / 0006

Valid from: 25.10.2022 PDF print date: 26.10.2022 Special Tec AA 5W-40 Diesel

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.